

Week:03-01

Q1) Problem Statement:

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false.

Example: If 698 and 768 are given, program should print true as they both end with 8.

Sample Input 1

25 53

Sample Output 1

false

Sample Input 2

27 77

Sample Output 2

true

Status

Finished

Started

Monday, 23 December 2024, 5:33 PM

Completed

Monday, 4 November 2024, 2:10 PM

Duration

49 days 3 hours

Question 1

Correct

Marked out of 3.00

Flag question

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int num1,num2;
5     scanf("%d %d",&num1,&num2);
6     int lastdigit1 = num1%10;
7     int lastdigit2 = num2%10;
8     if(lastdigit1 == lastdigit2)
9     {
10        printf("true");
11    }
12    else{
13        printf("false");
14    }
15    return 0;
16 }
```

|   | Input | Expected | Got   |   |
|---|-------|----------|-------|---|
| ✓ | 25 53 | false    | false | ✓ |
| ✓ | 27 77 | true     | true  | ✓ |

Passed all tests! ✓

Q2) Problem Statement:

In this challenge, we're getting started with conditional statements.

Task

Given an integer, n, perform the following conditional actions:

If  $n$  is odd, print Weird

If  $n$  is even and in the inclusive range of 2 to 5, print Not Weird

If  $n$  is even and in the inclusive range of 6 to 20, print Weird

If  $n$  is even and greater than 20, print Not Weird

Complete the stub code provided in your editor to print whether or not  $n$  is weird.

## Input Format

A single line containing a positive integer,  $n$ .

## Constraints

$1 < n < 100$

## Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

## Sample Input 0

3

## Sample Output 0

Weird

Question 2  
Correct  
Marked out of 5.00  
1/1 flag question

### Objective

In this challenge, we're getting started with conditional statements.

### Task

Given an integer,  $n$ , perform the following conditional actions:

- If  $n$  is odd, print Weird
- If  $n$  is even and in the inclusive range of 2 to 5, print *Not Weird*
- If  $n$  is even and in the inclusive range of 6 to 20, print *Weird*
- If  $n$  is even and greater than 20, print *Not Weird*

Complete the stub code provided in your editor to print whether or not  $n$  is weird.

### Input Format

A single line containing a positive integer,  $n$ .

### Constraints

- $1 \leq n \leq 100$

### Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

### Sample Input 0

3

### Sample Output 0

Weird

### Sample Input 1

24

### Sample Output 1

Not Weird

### Explanation

Sample Case 0:  $n = 3$   
 $n$  is odd and odd numbers are weird, so we print *Weird*.

Sample Case 1:  $n = 24$   
 $n > 20$  and  $n$  is even, so it isn't weird. Thus, we print *Not Weird*.

```

1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     if(n%2!=0)
7     {
8         printf("Weird");
9     }
10    else
11    {
12        if(n>=2 && n<=5)
13        {
14            printf("Not Weird");
15        }
16        else if(n>=6 && n<=20)
17        {
18            printf("Not Weird");
19        }
20        else if(n>20)
21        {
22            printf("Not Weird");
23        }
24    }
25 }

```

OUTPUT:

|   | Input | Expected  | Got       |   |
|---|-------|-----------|-----------|---|
| ✓ | 3     | Weird     | Weird     | ✓ |
| ✓ | 24    | Not Weird | Not Weird | ✓ |

Passed all tests! ✓

### Q3) Problem Statement:

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third.

For example, 3, 5 and 4 form a Pythagorean triple, since  $3^2 + 4^2 = 25 = 5^2$

You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters.

#### Sample Input 1

3

5

4

#### Sample Output 1

Yes

Question 3

Correct

Marked out of 7.00

Flag question

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since  $3^2 + 4^2 = 25 = 5^2$ . You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
6     if((a*a+b*b==c*c)|| (a*a+c*c==b*b) || (b*b+c*c==a*a))
7         printf("yes");
8     else
9         printf("no");
10    return 0;
11 }
```

OUTPUT:

|   | Input       | Expected | Got |   |
|---|-------------|----------|-----|---|
| ✓ | 3<br>5<br>4 | yes      | yes | ✓ |
| ✓ | 5<br>8<br>2 | no       | no  | ✓ |

Passed all tests! ✓

## Week:03-02

### Q1) Problem Statement:

Write a program that determines the name of a shape from its number of sides. Read the number of sides from the user and then report the appropriate name as part of a meaningful message. Your program should support shapes with anywhere from 3 up to (and including) 10 sides. If a number of sides outside of this range is entered then your program should display an appropriate error message.

#### Sample Input 1

3

#### Sample Output 1

Triangle

#### Sample Input 2

7

#### Sample Output 2

Heptagon

#### Sample Input 3

11

#### Sample Output 3

The number of sides is not supported.

|           |                                     |
|-----------|-------------------------------------|
| Status    | Finished                            |
| Started   | Monday, 23 December 2024, 5:33 PM   |
| Completed | Wednesday, 6 November 2024, 6:06 PM |
| Duration  | 46 days 23 hours                    |

Question 1

Correct

Marked out of 3.00

Flag question

Write a program that determines the name of a shape from its number of sides. Read the number of sides from the user and then report the appropriate name as part of a meaningful message. Your program should support shapes with anywhere from 3 up to (and including) 10 sides. If a number of sides outside of this range is entered then your program should display an appropriate error message.

Sample Input 1

3

Sample Output 1

Triangle

Sample Input 2

7

Sample Output 2

Heptagon

Sample Input 3

11

Sample Output 3

The number of sides is not supported.

```

1 #include<stdio.h>
2 int main()
3 {
4     int sides;
5     scanf("%d",&sides);
6     switch(sides)
7     {
8         case 3:
9             printf("Triangle\n");
10            break;
11         case 4:
12            printf("Quadrilateral\n");
13            break;
14         case 5:
15            printf("Pentagon\n");
16            break;
17         case 6:
18            printf("Hexagon\n");
19            break;
20         case 7:
21            printf("Heptagon\n");
22            break;
23         case 8:
24            printf("Octagon\n");
25            break;
26         case 9:
27            printf("Nonagon\n");
28            break;
29         case 10:
30            printf("Decagon\n");
31            break;
32         default:
33            printf("The number of sides is not supported.\n");
34            break;
35     }
36     return 0;
37 }

```

OUTPUT:

|   | Input | Expected                              | Got                                   |   |
|---|-------|---------------------------------------|---------------------------------------|---|
| ✓ | 3     | Triangle                              | Triangle                              | ✓ |
| ✓ | 7     | Heptagon                              | Heptagon                              | ✓ |
| ✓ | 11    | The number of sides is not supported. | The number of sides is not supported. | ✓ |

Passed all tests! ✓

## Q2) Problem Statement:

The Chinese zodiac assigns animals to years in a 12-year cycle. One 12-year cycle is shown in the table below. The pattern repeats from there, with 2012 being another year of the Dragon, and 1999 being another year of the Hare.

Year    Animal

2000    Dragon

2001    Snake

2002    Horse

2003    Sheep

2004    Monkey

2005    Rooster

2006    Dog

2007    Pig

2008    Rat

2009    Ox

2010 Tiger

2011 Hare

Write a program that reads a year from the user and displays the animal associated with that year. Your program should work correctly for any year greater than or equal to zero, not just the ones listed in the table.

Sample Input 1

2004

Sample Output 1

Monkey

Sample Input 2

2010

Sample Output 2

Tiger

Question 2

Correct

Marked out of 5.00

Flag question

The Chinese zodiac assigns animals to years in a 12-year cycle. One 12-year cycle is shown in the table below. The pattern repeats from there, with 2012 being another year of the Dragon, and 1999 being another year of the Hare.

| Year | Animal  |
|------|---------|
| 2000 | Dragon  |
| 2001 | Snake   |
| 2002 | Horse   |
| 2003 | Sheep   |
| 2004 | Monkey  |
| 2005 | Rooster |
| 2006 | Dog     |
| 2007 | Pig     |
| 2008 | Rat     |
| 2009 | Ox      |
| 2010 | Tiger   |
| 2011 | Hare    |

Write a program that reads a year from the user and displays the animal associated with that year. Your program should work correctly for any year greater than or equal to zero, not just the ones listed in the table.

Sample Input 1

2004

Sample Output 1

Monkey

Sample Input 2

2010

Sample Output 2

Tiger

```
1 #include<stdio.h>
2 int main()
3 {
4     int year;
5     const char*animals[]={
6         "Dragons","Snake","Horse","Sheep","Monkey","Rooster",
7         "Dog","Pig","Rat","Ox","Tiger","Hare"
8     };
9     scanf("%d",&year);
10    int index = (year-2000)%12;
11    if(index<0)
12    {
13        index+=12;
14    }
15    printf("%s\n",animals[index]);
16    return 0;
17 }
18 }
```

OUTPUT:

|   | Input | Expected | Got    |   |
|---|-------|----------|--------|---|
| ✓ | 2004  | Monkey   | Monkey | ✓ |
| ✓ | 2010  | Tiger    | Tiger  | ✓ |

Passed all tests! ✓

### Q3) Problem Statement:

Positions on a chess board are identified by a letter and a number. The letter identifies the column, while the number identifies the row,

Write a program that reads a position from the user. Use an if statement to determine if the column begins with a black square or a white square. Then use modular arithmetic to report the color of the square in that row. For example, if the user enters a1 then your program should report that the square is black. If the user enters d5 then your program should report that the square is white. Your program may assume that a valid position will always be entered. It does not need to perform any error checking.

#### Sample Input 1

A 1

#### Sample Output 1

The square is black.

#### Sample Input 2


D 5

#### Sample Output 2

The square is white.

Question 3  
Correct  
Marked out of  
7.00  
[Flag question](#)

Positions on a chess board are identified by a letter and a number. The letter identifies the column, while the number identifies the row, as shown below:



Write a program that reads a position from the user. Use an if statement to determine if the column begins with a black square or a white square. Then use modular arithmetic to report the color of the square in that row. For example, if the user enters a1 then your program should report that the square is black. If the user enters d5 then your program should report that the square is white. Your program may assume that a valid position will always be entered. It does not need to perform any error checking.

Sample Input 1

a 1

Sample Output 1

The square is black.

Sample Input 2

d 5

Sample Output 2

The square is white.



```

1 #include<stdio.h>
2 int main()
3 {
4     char column;
5     int row;
6     scanf("%c%d",&column,&row);
7     int columnindex = column-'a';
8     if((columnindex+row)%2==0)
9     {
10         printf("The square is white.\n");
11     }
12     else
13     {
14         printf("The square is black.\n");
15     }
16     return 0;
17 }

```

OUTPUT:

|   | Input | Expected             | Got                  |   |
|---|-------|----------------------|----------------------|---|
| ✓ | a 1   | The square is black. | The square is black. | ✓ |
| ✓ | d 5   | The square is white. | The square is white. | ✓ |

Passed all tests! ✓

## Week:03-03

### Q1) Problem Statement:

Some data sets specify dates using the year and day of year rather than the year, month, and day of month. The day of year (DOY) is the sequential day number starting with day 1 on January 1st.

There are two calendars - one for normal years with 365 days, and one for leap years with 366 days. Leap years are divisible by 4. Centuries, Cent like 1900, are not leap years unless they are divisible by 400. So, 2000 was a leap year.

To find the day of year number for a standard date, scan down the Jan column to find the day of month, then scan across to the appropriate month column and read the day of year number. Reverse the process to find the standard date for a given day of year. Write a program to print the Day of Year of a given date, month and year

### Sample Input 1

18

6

2020

### Sample Output 1

170

|                  |                                     |
|------------------|-------------------------------------|
| <b>Status</b>    | Finished                            |
| <b>Started</b>   | Monday, 23 December 2024, 5:33 PM   |
| <b>Completed</b> | Thursday, 28 November 2024, 9:55 PM |
| <b>Duration</b>  | 24 days 19 hours                    |

Question 1

Correct

Marked out of 3.00

Flag question

Some data sets specify dates using the year and day of year rather than the year, month, and day of month. The day of year (DOY) is the sequential day number starting with day 1 on January 1st.

There are two calendars - one for normal years with 365 days, and one for leap years with 366 days. Leap years are divisible by 4. Centuries, like 1900, are not leap years unless they are divisible by 400. So, 2000 was a leap year.

To find the day of year number for a standard date, scan down the Jan column to find the day of month, then scan across to the appropriate month column and read the day of year number. Reverse the process to find the standard date for a given day of year.

Write a program to print the Day of Year of a given date, month and year.

Sample Input 1

18

6

2020

Sample Output 1

170

```

1 #include<stdio.h>
2 #include<stdbool.h>
3 bool isleapyear(int year)
4 {
5     if(year%400==0)
6     {
7         return true;
8     }
9     else if(year%100==0)
10    {
11        return false;
12    }
13    else if(year%4==0)
14    {
15        return true;
16    }
17    return false;
18 }
19 int dayofyear(int day,int month,int year)
20 {
21     int daysinmonth[ ] =
22     {31,28,31,30,31,30,31,31,30,31,30,31};
23     int day = 0;
24     if(isleapyear(year))
25     {
26         daysinmonth[1]=29;
27     }
28     for(int i=0;i<month-1;i++)
29     {
30         day+=daysinmonth[i];
31     }
32     day+=day;
33     return day;
34 }
35 int main()
36 {
37     int day,month,year;
38     scanf("%d%d%d",&day,&month,&year);
39     printf("%d\n",dayofyear(day,month,year));
40     return 0;
41 }

```

OUTPUT:

|   | Input           | Expected | Got |   |
|---|-----------------|----------|-----|---|
| ✓ | 18<br>6<br>2020 | 170      | 170 | ✓ |

Passed all tests! ✓

## Q2) Problem Statement:

Suppandi is trying to take pan in the local village math qua. In the first round, he is asked about shapes and areas. Suppandi, is confused, he was never any good at math. And also, he is bad at remembering the names of shapes. Instead, you will be helping him calculate the area of shapes.

- When he says rectangle, he is actually referring to a square.
- When he says square, he is actually referring to a triangle.
- When he says triangle, he is referring to a rectangle
- And when he is confused, he just says something random. At this point, all you can do is say 0.
- Help Suppandi by printing the correct answer in an integer.

### Input Format

- Name of shape (always in upper case R -> Rectangle, S--> Square, T->Triangle)
- Length of 1 side
- Length of other side

Note: In case of triangle, you can consider the sides as height and length of base

### Output Format

- Print the area of the shape.

## Sample Input 1

T

10

20

## Sample Output 1

200

Question 2  
Correct  
Marked out of  
5.00  
Flag question

Suppandi is trying to take part in the local village math quiz. In the first round, he is asked about shapes and areas. Suppandi, is confused, he was never any good at math. And also, he is bad at remembering the names of shapes. Instead, you will be helping him calculate the area of shapes.

- When he says rectangle he is actually referring to a square.
- When he says square, he is actually referring to a triangle.
- When he says triangle he is referring to a rectangle
- And when he is confused, he just says something random. At this point, all you can do is say 0.

Help Suppandi by printing the correct answer in an integer.

Input Format

- Name of shape (always in upper case R à Rectangle, S à Square, T à Triangle)
- Length of 1 side
- Length of other side

Note: In case of triangle, you can consider the sides as height and length of base

Output Format

- Print the area of the shape.

Sample Input 1

T  
10  
20

Sample Output 1

200

```
1 #include<stdio.h>
2 int calculatearea(char shape,int length1,int length2)
3 {
4     int area =0;
5     switch(shape)
6     {
7         case 'R':
8             area=length1*length2;
9             break;
10        case 'S':
11            area=(length1*length2)/2;
12            break;
13        case 'T':
14            area=length1*length2;
15            break;
16        default:
17            area=0;
18            break;
19    }
20    return area;
21 }
22 int main()
23 {
24     char shape;
25     int length1,length2;
26     scanf("%c",&shape);
27     scanf("%d%d",&length1,&length2);
28     int area=calculatearea(shape,length1,length2);
29     printf("%d\n",area);
30 }
```

OUTPUT:

|   | Input         | Expected | Got  |   |
|---|---------------|----------|------|---|
| ✓ | T<br>10<br>20 | 200      | 200  | ✓ |
| ✓ | S<br>30<br>40 | 600      | 600  | ✓ |
| ✓ | B<br>2<br>11  | 0        | 0    | ✓ |
| ✓ | R<br>10<br>30 | 300      | 300  | ✓ |
| ✓ | S<br>40<br>50 | 1000     | 1000 | ✓ |

Passed all tests! ✓

### Q3) Problem Statement:

superday he arrives there. They to his home planet. It is very important for him to know which dy week with the fou. They don't follow a 10-day following days: hitney follow

Day      Number Name of Day

- |    |           |
|----|-----------|
| 1  | sunday    |
| 2  | monday    |
| 3  | tuesday   |
| 4  | wednesday |
| 5  | thursday  |
| 6  | friday    |
| 7  | Saturday  |
| 8  | kryptoday |
| 9  | coluday   |
| 10 | daxamday  |

Here are the rules of the calendar:

- The calendar starts with Sunday always.
- It has only 296 days. After the 296th day, it goes back to Sunday.

You begin your journey on a Sunday and will reach after n. You have to tell on which day you will arrive when you reach there.

Input format:

Contain a number n ( $0 < n$ )

Output format:

Print the name of the day you are arriving on

Sample Input

7

Sample Output

Kryptonday

Sample Input

1

Sample Output

Monday

Question 3

Correct

Marked out of 7.00

Flag question

Superman is planning a journey to his home planet. It is very important for him to know which day he arrives there. They don't follow the 7-day week like us. Instead, they follow a 10-day week with the following days: Day Number Name of Day 1 Sunday 2 Monday 3 Tuesday 4 Wednesday 5 Thursday 6 Friday 7 Saturday 8 Kryptonday 9 Coluday 10 Daxamday Here are the rules of the calendar: • The calendar starts with Sunday always. • It has only 296 days. After the 296th day, it goes back to Sunday. You begin your journey on a Sunday and will reach after n. You have to tell on which day you will arrive when you reach there.

Input format: •

Contain a number n (0 < n)

Output format: Print the name of the day you are arriving on

Example Input

7

Example Output

Kryptonday

Example Input

1

Example Output Monday

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     const char* days[] = {"Sunday"
5     "Monday", "Tuesday", "Wednesday", "Thursday", "Friday", "Saturday", "Kryptonday", "Clouday", "Daxamday"};
6     int n;
7     scanf("%d", &n);
8     n=n%296;
9     int arrival_day=n%10;
10    printf("%s\n", days[arrival_day]);
11    return 0;
12 }
```

OUTPUT:

|   | Input | Expected   | Got        |   |
|---|-------|------------|------------|---|
| ✓ | 7     | Kryptonday | Kryptonday | ✓ |
| ✓ | 1     | Monday     | Monday     | ✓ |

Passed all tests! ✓

