

```

#include <iostream>
#include <fstream>
#include <string>
#include <sstream>
#include <iomanip>

using namespace std;

void calculation(string name, string rollno, float q1, float q2, float q3, float
q4,
                float a1, float a2, float m, float f, float p);

float convertStringToInt(string str);

int main(int argc, char** argv)
{
    ifstream f;

    f.open("C:\\Users\\iftik\\Downloads\\CP - CP.csv", ios::in);

    if (!f.is_open())
    {
        cout << "Failed to open file.\n";
        return 1;
    }

    cout << left;

    string line;

    // Skip first two lines of CSV
    getline(f, line);
    getline(f, line);

    cout << setw(24) << "Students Name"
         << setw(10) << "Roll No"
         << setw(10) << "Quiz 1"
         << setw(10) << "Quiz 2"
         << setw(10) << "Quiz 3"
         << setw(10) << "Quiz 4"
         << setw(10) << "Ass 1"
         << setw(10) << "Ass 2"
         << setw(10) << "Mid"
         << setw(10) << "Final"
         << setw(10) << "Project"
         << setw(12) << "Total"
         << endl;

    while (getline(f, line))
    {

```

```

    stringstream lr(line);

    string ar[11];

    // CORRECTED: for instead of br
    for (int i = 0; i < 11; i++)
    {
        getline(lr, ar[i], ',');
    }

    calculation(
        ar[0],
        ar[1],
        convertStringToInt(ar[2]),
        convertStringToInt(ar[3]),
        convertStringToInt(ar[4]),
        convertStringToInt(ar[5]),
        convertStringToInt(ar[6]),
        convertStringToInt(ar[7]),
        convertStringToInt(ar[8]),
        convertStringToInt(ar[9]),
        convertStringToInt(ar[10])
    );

    cout << endl;
}

f.close();

return 0;
}

void calculation(string name, string rollno, float q1, float q2, float q3,
                float q4, float a1, float a2, float m, float f, float p)
{
    cout << endl;

    // Use float instead of int
    float total =
        (((q1 + q2 + q3 + q4) / 40.0) * 10.0)
        + (((a1 + a2) / 10.0) * 5.0)
        + ((m / 50.0) * 30.0)
        + ((f / 100.0) * 45.0)
        + ((p / 40.0) * 10.0);

    cout << setw(26) << name
        << setw(10) << rollno
        << setw(10) << q1
        << setw(10) << q2
        << setw(10) << q3

```

```
<< setw(10) << q4
<< setw(10) << a1
<< setw(10) << a2
<< setw(10) << m
<< setw(10) << f
<< setw(10) << p
<< setw(15) << total
<< endl;
```

```
cout <<
```

```
"
_____"
_____";
}
```

```
// Convert String To Float
float convertStringToInt(string str)
{
    float num;

    stringstream ss(str);
    ss >> num;

    return num;
}
```