

OptKnock Tutorial

Author: Sebastián N. Mendoza, Center for Mathematical Modeling, University of Chile.
snmendoz@uc.cl

Reviewer(s): Thomas Pfau, Sylvian Arreckx, Laurent Heirendt, Ronan Fleming, John Sauls

INTRODUCTION:

In this tutorial we will run optKnock. For a detailed description of the procedure, please see [1]. Briefly, the problem is to find a set of reactions of size "numDel" such that when these reactions are deleted from the network, the mutant created will produce a particular target of interest in a higher rate than the wild-type strain.

For example, imagine that we would like to increase the production of succinate or lactate in Escherichia coli. Which are the knock-outs needed to increase the production of these products? We will approach these problems in this tutorial.

MATERIALS

EQUIPMENT

1. MATLAB
2. A solver for Mixed Integer Linear Programming (MILP) problems. For example, Gurobi.

EQUIPMENT SETUP

Use changeCobraSolver to choose the solver for MILP problems.

PROCEDURE

The procedure consists on the following steps

- 1) Define constraints.
- 2) Define a set of reactions to search knockouts. Only reactions in this set will be deleted.
- 3) Define the number of reactions to be deleted, the target reaction and some constraints to be accomplish.
- 4) Run optKnock.

TIMING: This task should take from a few seconds to a few hours depending on the size of your reconstruction.

We verify that cobratoolbox has been initialized and that the solver has been set.

```
global TUTORIAL_INIT_CB;  
if ~isempty(TUTORIAL_INIT_CB) && TUTORIAL_INIT_CB==1  
    initCobraToolbox  
end
```

```
changeCobraSolver('gurobi','all');
```

```
> Gurobi interface added to MATLAB path.  
> Solver for LP problems has been set to gurobi.  
  
> Gurobi interface added to MATLAB path.  
> Solver for MILP problems has been set to gurobi.  
  
> Gurobi interface added to MATLAB path.  
> Solver for QP problems has been set to gurobi.  
  
> Gurobi interface added to MATLAB path.  
> Solver for MIQP problems has been set to gurobi.  
> Solver gurobi not supported for problems of type NLP. No solver set for this problemtype
```

```
fullPath = which('tutorial_optKnock');  
folder = fileparts(fullPath);  
currentDirectory = pwd;  
cd(folder);
```

We load the model of E. coli [2].

```
model = readCbModel('iJ01366.mat')
```

```
model =  
    rxns: {2583×1 cell}  
    mets: {1805×1 cell}  
    S: [1805×2583 double]  
    lb: [2583×1 double]  
    ub: [2583×1 double]  
    c: [2583×1 double]  
    rxnNames: {2583×1 cell}  
    subSystems: {2583×1 cell}  
    grRules: {2583×1 cell}  
    metNames: {1805×1 cell}  
    metFormulas: {1805×1 cell}  
    genes: {1367×1 cell}  
    description: 'iJ01366.mat'  
    rxnGeneMat: [2583×1367 double]  
    csense: [1805×1 char]  
    b: [1805×1 double]  
    osense: -1  
    rules: {2583×1 cell}
```

```
biomass = 'BIOMASS_Ec_iJ01366_core_53p95M';
```

Warning: A value of class "com.mathworks.mde.cmdwin.XCmdWndView" was indexed with no subscripts specified. Currently the result of this operation is the indexed value itself, but in a future release, it will be an error.

Warning: A value of class "com.mathworks.mde.cmdwin.XCmdWndView" was indexed with no subscripts specified. Currently the result of this operation is the indexed value itself, but in a future release, it will be an error.

We define the maximum number of solutions to find

```
threshold = 5;
```

First, we define the set for reactions which could be deleted from the network. Reactions not in this list are not going to be deleted.

```
selectedRxnList = {'GLCabcpp'; 'GLCptspp'; 'HEX1'; 'PGI'; 'PFK'; 'FBA'; 'TPI'; 'GAPD'; ...  
                  'PGK'; 'PGM'; 'ENO'; 'PYK'; 'LDH_D'; 'PFL'; 'ALCD2x'; 'PTAr'; 'ACKr'; ...  
                  'G6PDH2r'; 'PGL'; 'GND'; 'RPI'; 'RPE'; 'TKT1'; 'TALA'; 'TKT2'; 'FUM'; ...  
                  'FRD2'; 'SUCOAS'; 'AKGDH'; 'ACONTa'; 'ACONTb'; 'ICDHyr'; 'CS'; 'MDH'; ...  
                  'MDH2'; 'MDH3'; 'ACALD'};
```

Then, we define some constraints

```
% prespecified amount of glucose uptake 10 mmol/grDW*hr  
model = changeRxnBounds(model, 'EX_glc_D_e', -10, 'b');  
  
% Unconstrained uptake routes for inorganic phosphate, sulfate and  
% ammonia  
model = changeRxnBounds(model, 'EX_o2_e', 0, 'l');  
model = changeRxnBounds(model, 'EX_pi_e', -1000, 'l');  
model = changeRxnBounds(model, 'EX_so4_e', -1000, 'l');  
model = changeRxnBounds(model, 'EX_nh4_e', -1000, 'l');  
  
% The optimization step could opt for or against the phosphotransferase  
% system, glucokinase, or both mechanisms for the uptake of glucose  
model = changeRxnBounds(model, 'GLCabcpp', -1000, 'l');  
model = changeRxnBounds(model, 'GLCptspp', -1000, 'l');  
model = changeRxnBounds(model, 'GLCabcpp', 1000, 'u');  
model = changeRxnBounds(model, 'GLCptspp', 1000, 'u');  
model = changeRxnBounds(model, 'GLCt2pp', 0, 'b');  
  
% Secretion routes for acetate, carbon dioxide, ethanol, formate, lactate  
% and succinate are enabled  
model = changeRxnBounds(model, 'EX_ac_e', 1000, 'u');  
model = changeRxnBounds(model, 'EX_co2_e', 1000, 'u');  
model = changeRxnBounds(model, 'EX_etoh_e', 1000, 'u');  
model = changeRxnBounds(model, 'EX_for_e', 1000, 'u');  
model = changeRxnBounds(model, 'EX_lac_D_e', 1000, 'u');  
model = changeRxnBounds(model, 'EX_succ_e', 1000, 'u');
```

Then, we calculate the production of metabolites before running optKnock.

```
% determine succinate production and growth rate before optimization  
fbaWT = optimizeCbModel(model);  
succFluxWT = fbaWT.x(strcmp(model.rxns, 'EX_succ_e'));  
etohFluxWT = fbaWT.x(strcmp(model.rxns, 'EX_etoh_e'));  
formFluxWT = fbaWT.x(strcmp(model.rxns, 'EX_for_e'));  
lactFluxWT = fbaWT.x(strcmp(model.rxns, 'EX_lac_D_e'));  
acetFluxWT = fbaWT.x(strcmp(model.rxns, 'EX_ac_e'));  
growthRateWT = fbaWT.f;  
fprintf('The production of succinate before optimization is %.1f \n', succFluxWT);
```

The production of succinate before optimization is 0.1

```
fprintf('The growth rate before optimization is %.1f \n', growthRateWT);
```

The growth rate before optimization is 0.2

```
fprintf(['The production of other products such as ethanol, formate, lactate and'...
'acetate are %.1f, %.1f, %.1f and %.1f, respectively. \n'], ...
etohFluxWT, formFluxWT, lactFluxWT, acetFluxWT);
```

The production of other products such as ethanol, formate, lactate and acetate are 8.1, 17.3, 0.0 and 8.2

I) SUCCINATE OVERPRODUCTION

EXAMPLE 1: finding optKnock reactions sets of size 2 for increasing production of succinate

```
fprintf('\n...EXAMPLE 1: Finding optKnock sets of size 2 or less...\n\n')
```

...EXAMPLE 1: Finding optKnock sets of size 2 or less...

```
% Set optKnock options
% The exchange of succinate will be the objective of the outer problem
options = struct('targetRxn', 'EX_succ_e', 'numDel', 2);
% We will impose that biomass be at least 50% of the biomass of wild-type
constrOpt = struct('rxnList', {{biomass}}, 'values', 0.5*fbaWT.f, 'sense', 'G');
% We will try to find 10 optKnock sets of a maximum length of 2
previousSolutions = cell(10, 1);
contPreviousSolutions = 1;
nIter = 1;
while nIter < threshold
    fprintf('...Performing optKnock analysis...\n')
    if isempty(previousSolutions{1})
        optKnockSol = OptKnock(model, selectedRxnList, options, constrOpt);
    else
        optKnockSol = OptKnock(model, selectedRxnList, options, constrOpt, previousSolutions,
    end

    % determine succinate production and growth rate after optimization
    succFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_succ_e'));
    growthRateM1 = optKnockSol.fluxes(strcmp(model.rxns, biomass));
    etohFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_etoh_e'));
    formFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_for_e'));
    lactFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_lac_D_e'));
    acetFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_ac_e'));
    setM1 = optKnockSol.rxnList;

    if ~isempty(setM1)
        previousSolutions{contPreviousSolutions} = setM1;
        contPreviousSolutions = contPreviousSolutions + 1;
        %printing results
        fprintf('optKnock found a optKnock set of large %d composed by ', length(setM1));
        for j = 1:length(setM1)
            if j == 1
                fprintf('%s', setM1{j});
            elseif j == length(setM1)
                fprintf(' and %s', setM1{j});
            else
                fprintf(', %s', setM1{j});
            end
        end
        fprintf('\n');
        fprintf('The production of succinate after optimization is %.2f \n', succFluxM1);
        fprintf('The growth rate after optimization is %.2f \n', growthRateM1);
        fprintf(['The production of other products such as ethanol, formate, lactate and acetate are %.1f, %.1f, %.1f and %.1f, respectively. \n'], etohFluxM1, formFluxM1, lactFluxM1, acetFluxM1);
    end
    nIter = nIter + 1;
end
```

```

        '%.1f, %.1f, %.1f and %.1f, respectively. \n'], etohFluxM1, formFluxM1, lactF
fprintf('...Performing coupling analysis...\n');
[type, maxGrowth, maxProd, minProd] = analyzeOptKnock(model, setM1, 'EX_succ_e');
fprintf('The solution is of type: %s\n', type);
fprintf('The maximun growth rate given the optKnock set is %.2f\n', maxGrowth);
fprintf(['The maximun and minimun production of succinate given the optKnock set is '
        '%.2f and %.2f, respectively \n\n'], minProd, maxProd);
if strcmp(type, 'growth coupled')
    singleProductionEnvelope(model, setM1, 'EX_succ_e', biomass, 'savePlot', 1, 'showP
        'fileName', ['succ_ex1_' num2str(nIter)], 'outputFolder',
end,
else
    if nIter == 1
        fprintf('optKnock was not able to found an optKnock set\n');
    else
        fprintf('optKnock was not able to found additional optKnock sets\n');
    end
    break;
end
nIter = nIter + 1;
end

```

...Performing optKnock analysis...

optKnock found a optKnock set of large 2 composed by

PFL

and RPI

The production of succinate after optimization is 2.75

The growth rate after optimization is 0.14

The production of other products such as ethanol, formate, lactate and acetate are 9.4, 0.0, -0.0 and 0.0

...Performing coupling analysis...

The solution is of type: growth coupled non unique

The maximun growth rate given the optKnock set is 0.12

The maximun and minimun production of succinate given the optKnock set is 0.04 and 2.31, respectively

...Performing optKnock analysis...

MILP problem with 8398 constraints 63 integer variables and 8370 continuous variables

Optimize a model with 8398 rows, 8370 columns and 34671 nonzeros

Variable types: 8307 continuous, 63 integer (63 binary)

Coefficient statistics:

Matrix range [2e-06, 1e+03]

Objective range [1e+00, 1e+00]

Bounds range [1e+00, 1e+03]

RHS range [1e-02, 1e+03]

Presolve removed 5079 rows and 3321 columns

Presolve time: 0.09s

Presolved: 3319 rows, 5049 columns, 21617 nonzeros

Variable types: 5012 continuous, 37 integer (37 binary)

Root relaxation: objective 1.230321e+01, 4944 iterations, 0.64 seconds

Nodes		Current Node			Objective Bounds			Work	
Expl	Unexpl	Obj	Depth	IntInf	Incumbent	BestBd	Gap	It/Node	Time
	0	0	12.30321	0	2	-	12.30321	-	1s
H	0	0				0.0915893	12.30321	-	1s
	0	0	12.30321	0	2	0.09159	12.30321	-	1s
	0	2	12.30321	0	2	0.09159	12.30321	-	1s
*	79	63		25		0.2411614	12.30321	5002%	60.1
*	90	70		24		0.2411614	12.30321	5002%	59.3
*	175	78		21		0.2856919	12.30321	4206%	58.0
*	193	81		26		0.2864668	12.30321	4195%	54.6
*	194	81		26		0.2864668	12.30321	4195%	54.3

*	240	104	21	1.2019176	12.29845	923%	55.5	2s
*	291	87	19	1.4425937	12.28821	752%	58.5	2s
*	303	65	19	1.6792803	12.27798	631%	60.7	3s

Explored 379 nodes (35252 simplex iterations) in 3.71 seconds
Thread count was 8 (of 8 available processors)

Solution count 9: 1.67928 1.44259 1.20192 ... 0.0915893
Pool objective bound 1.67928

Optimal solution found (tolerance 1.00e-12)
Best objective 1.679280339834e+00, best bound 1.679280339834e+00, gap 0.0000%

optKnock found a optKnock set of large 2 composed by

PFL

and TKT2

The production of succinate after optimization is 1.68

The growth rate after optimization is 0.22

The production of other products such as ethanol, formate, lactate and acetate are 14.9, 0.0, 0.0 and -0.0

...Performing coupling analysis...

The solution is of type: growth coupled non unique

The maximum growth rate given the optKnock set is 0.18

The maximum and minimum production of succinate given the optKnock set is 0.06 and 1.41, respectively

...Performing optKnock analysis...

MILP problem with 8399 constraints 63 integer variables and 8370 continuous variables

Optimize a model with 8399 rows, 8370 columns and 34674 nonzeros

Variable types: 8307 continuous, 63 integer (63 binary)

Coefficient statistics:

Matrix range [2e-06, 1e+03]

Objective range [1e+00, 1e+00]

Bounds range [1e+00, 1e+03]

RHS range [1e-02, 1e+03]

Presolve removed 5079 rows and 3321 columns

Presolve time: 0.10s

Presolved: 3320 rows, 5049 columns, 21619 nonzeros

Variable types: 5012 continuous, 37 integer (37 binary)

Root relaxation: objective 1.230321e+01, 5180 iterations, 0.69 seconds

Nodes		Current Node			Objective Bounds		Gap	Work	
Expl	Unexpl	Obj	Depth	IntInf	Incumbent	BestBd		It/Node	Time
	0	0	12.30321	0	2	-	12.30321	-	1s
H	0	0				0.0915893	12.30321	-	1s
	0	0	12.30321	0	2	0.09159	12.30321	-	1s
	0	2	12.30321	0	2	0.09159	12.30321	-	1s
*	174	80		16		0.2864668	12.30321	4195%	53.5
*	245	91		21		1.2019176	12.30321	924%	57.3
*	258	86		22		1.2019176	12.29845	923%	61.1
*	291	53		21		1.4425937	12.27798	751%	68.9

Explored 373 nodes (33379 simplex iterations) in 3.60 seconds
Thread count was 8 (of 8 available processors)

Solution count 5: 1.44259 1.20192 1.20192 ... 0.0915893
Pool objective bound 1.44259

Optimal solution found (tolerance 1.00e-12)
Best objective 1.442593733917e+00, best bound 1.442593733917e+00, gap 0.0000%

optKnock found a optKnock set of large 2 composed by

PFL

and RPE

The production of succinate after optimization is 1.44

The growth rate after optimization is 0.22
 The production of other products such as ethanol, formate, lactate and acetate are 0.0, 0.0, 15.2 and 0.0
 ...Performing coupling analysis...
 The solution is of type: growth coupled non unique
 The maximum growth rate given the optKnock set is 0.18
 The maximum and minimum production of succinate given the optKnock set is 0.06 and 1.22, respectively
 ...Performing optKnock analysis...

MILP problem with 8400 constraints 63 integer variables and 8370 continuous variables
 Optimize a model with 8400 rows, 8370 columns and 34677 nonzeros
 Variable types: 8307 continuous, 63 integer (63 binary)
 Coefficient statistics:
 Matrix range [2e-06, 1e+03]
 Objective range [1e+00, 1e+00]
 Bounds range [1e+00, 1e+03]
 RHS range [1e-02, 1e+03]
 Presolve removed 5079 rows and 3321 columns
 Presolve time: 0.09s
 Presolved: 3321 rows, 5049 columns, 21621 nonzeros
 Variable types: 5012 continuous, 37 integer (37 binary)

Root relaxation: objective 1.230321e+01, 4774 iterations, 0.63 seconds

Nodes			Current Node			Objective Bounds			Work	
Expl	Unexpl		Obj	Depth	IntInf	Incumbent	BestBd	Gap	It/Node	Time
H	0	0	12.30321	0	2	-	12.30321	-	-	1s
	0	0				0.0915893	12.30321	-	-	1s
	0	0	12.30321	0	2	0.09159	12.30321	-	-	1s
	0	2	12.30321	0	2	0.09159	12.30321	-	-	1s
*	82	63		25		0.2411614	12.30321	5002%	40.6	1s
*	94	71		17		0.2864668	12.30321	4195%	41.6	1s
*	291	75		21		1.2019176	12.29845	923%	55.8	3s

Explored 390 nodes (32387 simplex iterations) in 3.94 seconds
 Thread count was 8 (of 8 available processors)

Solution count 4: 1.20192 0.286467 0.241161 0.0915893
 Pool objective bound 1.20192

Optimal solution found (tolerance 1.00e-12)
 Warning: max constraint violation (3.1562e-09) exceeds tolerance
 Best objective 1.201917633447e+00, best bound 1.201917633447e+00, gap 0.0000%

optKnock found a optKnock set of large 2 composed by
 PFL
 and TALA

The production of succinate after optimization is 1.20
 The growth rate after optimization is 0.22
 The production of other products such as ethanol, formate, lactate and acetate are 15.4, 0.0, -0.0 and 0.0
 ...Performing coupling analysis...
 The solution is of type: growth coupled non unique
 The maximum growth rate given the optKnock set is 0.19
 The maximum and minimum production of succinate given the optKnock set is 0.06 and 1.01, respectively

TROUBLESHOOTING 1: "The algorithm takes a long time to find a solution"

TROUBLESHOOTING 2: "The algorithm finds a set of knockouts too big"

TROUBLESHOOTING 3: "The algorithm found a solution that is not useful for me"

EXAMPLE 2: finding optKnock reactions sets of size 3 for increasing production of succinate

```
fprintf('\n...EXAMPLE 1: Finding optKnock sets of size 3...\n\n')
```

```
...EXAMPLE 1: Finding optKnock sets of size 3...
```

```
% Set optKnock options
% The exchange of succinate will be the objective of the outer problem
options = struct('targetRxn', 'EX_succ_e', 'numDel', 3);
% We will impose that biomass be at least 50% of the biomass of wild-type
constrOpt = struct('rxnList', {{biomass}}, 'values', 0.5*fbawT.f, 'sense', 'G');
% We will try to find 10 optKnock sets of a maximum length of 3
nIter = 1;
while nIter < threshold
    fprintf('...Performing optKnock analysis...')
    if isempty(previousSolutions{1})
        optKnockSol = OptKnock(model, selectedRxnList, options, constrOpt);
    else
        optKnockSol = OptKnock(model, selectedRxnList, options, constrOpt, previousSolutions);
    end

    % determine succinate production and growth rate after optimization
    succFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_succ_e'));
    growthRateM1 = optKnockSol.fluxes(strcmp(model.rxns, biomass));
    etohFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_etoh_e'));
    formFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_for_e'));
    lactFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_lac_D_e'));
    acetFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_ac_e'));
    setM1 = optKnockSol.rxnList;

    if ~isempty(setM1)
        previousSolutions{contPreviousSolutions} = setM1;
        contPreviousSolutions=contPreviousSolutions + 1;
        %printing results
        fprintf('optKnock found a optKnock set of large %d composed by ',length(setM1));
        for j = 1:length(setM1)
            if j == 1
                fprintf('%s',setM1{j});
            elseif j == length(setM1)
                fprintf(' and %s',setM1{j});
            else
                fprintf(', %s',setM1{j});
            end
        end
        fprintf('\n');
        fprintf('The production of succinate after optimization is %.2f \n', succFluxM1);
        fprintf('The growth rate after optimization is %.2f \n', growthRateM1);
        fprintf(['The production of other products such as ethanol, formate, lactate and acetate\n',
            '%.1f, %.1f, %.1f and %.1f, respectively. \n'], etohFluxM1, formFluxM1, lactFluxM1, acetFluxM1);
        fprintf('...Performing coupling analysis...\n');
        [type, maxGrowth, maxProd, minProd] = analyzeOptKnock(model, setM1, 'EX_succ_e');
        fprintf('The solution is of type: %s\n', type);
        fprintf('The maximum growth rate given the optKnock set is %.2f\n', maxGrowth);
        fprintf(['The maximum and minimum production of succinate given the optKnock set is\n',
            '%.2f and %.2f, respectively \n\n'], minProd, maxProd);
        if strcmp(type,'growth coupled')
```



```

        singleProductionEnvelope(model, setM1, 'EX_succ_e', biomass, 'savePlot', 1, 'showP
        'fileName', ['succ_ex2_' num2str(nIter)], 'outputFolder',
    end
else
    if nIter == 1
        fprintf('optKnock was not able to found an optKnock set\n');
    else
        fprintf('optKnock was not able to found additional optKnock sets\n');
    end
    break;
end
nIter = nIter + 1;
end

```

...Performing optKnock analysis...

optKnock found a optKnock set of large 3 composed by
ALCD2x
, LDH_D
and PFL

The production of succinate after optimization is 8.81

The growth rate after optimization is 0.15

The production of other products such as ethanol, formate, lactate and acetate are 0.0, 0.0, -0.0 and 1.

...Performing coupling analysis...

The solution is of type: growth coupled

The maximum growth rate given the optKnock set is 0.11

The maximum and minimum production of succinate given the optKnock set is 9.11 and 9.11, respectively

...Performing optKnock analysis...

optKnock found a optKnock set of large 3 composed by
ACALD
, LDH_D
and PFL

The production of succinate after optimization is 8.81

The growth rate after optimization is 0.15

The production of other products such as ethanol, formate, lactate and acetate are 0.0, 0.0, -0.0 and 4.

...Performing coupling analysis...

The solution is of type: growth coupled non unique

The maximum growth rate given the optKnock set is 0.11

The maximum and minimum production of succinate given the optKnock set is 4.23 and 9.11, respectively

...Performing optKnock analysis...

optKnock found a optKnock set of large 2 composed by
PFL
and TKT1

The production of succinate after optimization is 1.20

The growth rate after optimization is 0.22

The production of other products such as ethanol, formate, lactate and acetate are 0.0, 0.0, 15.4 and 0.

...Performing coupling analysis...

The solution is of type: growth coupled non unique

The maximum growth rate given the optKnock set is 0.19

The maximum and minimum production of succinate given the optKnock set is 0.06 and 1.01, respectively

...Performing optKnock analysis...

optKnock found a optKnock set of large 3 composed by
ACALD
, ALCD2x
and PFL

The production of succinate after optimization is 0.95


The growth rate after optimization is 0.22

The production of other products such as ethanol, formate, lactate and acetate are 0.0, 0.0, 15.7 and -0.01, respectively
...Performing coupling analysis...

The solution is of type: growth coupled non unique

The maximum growth rate given the optKnock set is 0.19

The maximum and minimum production of succinate given the optKnock set is 0.06 and 0.80, respectively



II) LACTATE OVERPRODUCTION

EXAMPLE 1: finding optKnock reactions sets of size 3 for increasing production of lactate

```
fprintf('\n...EXAMPLE 1: Finding optKnock sets of size 3...\n\n')
```

```
...EXAMPLE 1: Finding optKnock sets of size 3...
```

```
% Set optKnock options
% The exchange of lactate will be the objective of the outer problem
options = struct('targetRxn', 'EX_lac_D_e', 'numDel', 3);
% We will impose that biomass be at least 50% of the biomass of wild-type
constrOpt = struct('rxnList', {{biomass}}, 'values', 0.5*fbaWT.f, 'sense', 'G');
% We will try to find 10 optKnock sets of a maximum length of 6
previousSolutions = cell(100, 1);
contPreviousSolutions = 1;
nIter = 1;
while nIter < threshold
    fprintf('...Performing optKnock analysis...')
```

```

if isempty(previousSolutions{1})
    optKnockSol = OptKnock(model, selectedRxnList, options, constrOpt);
else
    optKnockSol = OptKnock(model, selectedRxnList, options, constrOpt, previousSolutions);
end

% determine lactate production and growth rate after optimization
lactFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_lac_D_e'));
growthRateM1 = optKnockSol.fluxes(strcmp(model.rxns, biomass));
etohFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_etoh_e'));
formFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_for_e'));
succFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_succ_e'));
acetFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_ac_e'));
setM1 = optKnockSol.rxnList;

if ~isempty(setM1)
    previousSolutions{contPreviousSolutions} = setM1;
    contPreviousSolutions=contPreviousSolutions + 1;
    %printing results
    fprintf('optKnock found a optKnock set of large %d composed by ',length(setM1));
    for j = 1:length(setM1)
        if j == 1
            fprintf('%s', setM1{j});
        elseif j == length(setM1)
            fprintf(' and %s', setM1{j});
        else
            fprintf(', %s', setM1{j});
        end
    end
    fprintf('\n');
    fprintf('The production of lactate after optimization is %.2f \n', lactFluxM1);
    fprintf('The growth rate after optimization is %.2f \n', growthRateM1);
    fprintf(['The production of other products such as ethanol, formate, succinate and acetate\n',
            '%.1f, %.1f, %.1f and %.1f, respectively. \n'], etohFluxM1, formFluxM1, succFluxM1, acetFluxM1);
    fprintf('...Performing coupling analysis...\n');
    [type, maxGrowth, maxProd, minProd] = analyzeOptKnock(model, setM1, 'EX_lac_D_e');
    fprintf('The solution is of type: %s\n', type);
    fprintf('The maximun growth rate given the optKnock set is %.2f\n', maxGrowth);
    fprintf(['The maximun and minimun production of lactate given the optKnock set is ' ...
            '%.2f and %.2f, respectively \n\n'], minProd, maxProd);
    singleProductionEnvelope(model, setM1, 'EX_lac_D_e', biomass, 'savePlot', 1, 'showPlot', 1,
        'fileName', ['lact_ex1_' num2str(nIter)], 'outputFolder', 'Output');
else
    if nIter == 1
        fprintf('optKnock was not able to found an optKnock set\n');
    else
        fprintf('optKnock was not able to found additional optKnock sets\n');
    end
    break;
end
nIter = nIter + 1;
end

```

...Performing optKnock analysis...

optKnock found a optKnock set of large 3 composed by

GLCabcpp

, PFL

and PGI

The production of lactate after optimization is 18.13

The growth rate after optimization is 0.12

The production of other products such as ethanol, formate, succinate and acetate are 0.0, 0.0, 0.0 and 0.0

...Performing coupling analysis...

The solution is of type: non unique

The maximum growth rate given the optKnock set is 0.08

The maximum and minimum production of lactate given the optKnock set is 0.00 and 18.72, respectively

...Performing optKnock analysis...

optKnock found a optKnock set of large 2 composed by

PFL

and PGI

The production of lactate after optimization is 18.13

The growth rate after optimization is 0.12

The production of other products such as ethanol, formate, succinate and acetate are 0.0, 0.0, 0.0 and 0.0

...Performing coupling analysis...

The solution is of type: non unique

The maximum growth rate given the optKnock set is 0.08

The maximum and minimum production of lactate given the optKnock set is 0.00 and 18.72, respectively

...Performing optKnock analysis...

optKnock found a optKnock set of large 3 composed by

GND

, PGI

and PTAr

The production of lactate after optimization is 18.01

The growth rate after optimization is 0.12

The production of other products such as ethanol, formate, succinate and acetate are 0.0, 0.6, 0.0 and 0.0

...Performing coupling analysis...

The solution is of type: non unique

The maximum growth rate given the optKnock set is 0.09

The maximum and minimum production of lactate given the optKnock set is 0.00 and 18.64, respectively

...Performing optKnock analysis...

optKnock found a optKnock set of large 3 composed by

ACKr

, GND

and PGI

The production of lactate after optimization is 18.01

The growth rate after optimization is 0.12



The production of other products such as ethanol, formate, succinate and acetate are 0.0, 0.6, 0.0 and 0.0



...Performing coupling analysis...

The solution is of type: non unique

The maximum growth rate given the optKnock set is 0.09

The maximum and minimum production of lactate given the optKnock set is 0.00 and 18.64, respectively





EXAMPLE 2: finding optKnock reactions sets of size 6 for increasing production of lactate

```
fprintf('...EXAMPLE 3: Finding optKnock sets of size 6...\n')
```

```
...EXAMPLE 3: Finding optKnock sets of size 6...
```

```
% Set optKnock options
% The exchange of lactate will be the objective of the outer problem
options = struct('targetRxn', 'EX_lac_D_e', 'numDel', 6);
% We will impose that biomass be at least 50% of the biomass of wild-type
constrOpt = struct('rxnList', {{biomass}}, 'values', 0.5*fbaWT.f, 'sense', 'G');
% We will try to find 10 optKnock sets of a maximum length of 2
nIter = 1;
while nIter < threshold
    fprintf('...Performing optKnock analysis...')
    if isempty(previousSolutions{1})
        optKnockSol = OptKnock(model, selectedRxnList, options, constrOpt);
    else
        optKnockSol = OptKnock(model, selectedRxnList, options, constrOpt, previousSolutions);
    end

    % determine lactate production and growth rate after optimization
    lactFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_lac_D_e'));
    growthRateM1 = optKnockSol.fluxes(strcmp(model.rxns, biomass));
    etohFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_etoh_e'));
    formFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_for_e'));
    succFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_succ_e'));
    acetFluxM1 = optKnockSol.fluxes(strcmp(model.rxns, 'EX_ac_e'));
    setM1 = optKnockSol.rxnList;

    if ~isempty(setM1)
        previousSolutions{contPreviousSolutions} = setM1;
        contPreviousSolutions = contPreviousSolutions + 1;
        %printing results
        fprintf('optKnock found a optKnock set of large %d composed by ', length(setM1));
        for j = 1:length(setM1)
            if j == 1
                fprintf('%s', setM1{j});
            elseif j == length(setM1)
                fprintf(' and %s', setM1{j});
            else
                fprintf(', %s', setM1{j});
            end
        end
        fprintf('\n');
        fprintf('The production of lactate after optimization is %.2f \n', lactFluxM1);
        fprintf('The growth rate after optimization is %.2f \n', growthRateM1);
        fprintf(['The production of other products such as ethanol, formate, succinate and acetate\n',
            '%.1f, %.1f, %.1f and %.1f, respectively. \n'], etohFluxM1, formFluxM1, succFluxM1, acetFluxM1);
        fprintf('...Performing coupling analysis...\n');
        [type, maxGrowth, maxProd, minProd] = analyzeOptKnock(model, setM1, 'EX_lac_D_e');
        fprintf('The solution is of type: %s\n', type);
        fprintf('The maximum growth rate given the optKnock set is %.2f\n', maxGrowth);
        fprintf(['The maximum and minimum production of lactate given the optKnock set is ' ..
            '%.2f and %.2f, respectively \n\n'], minProd, maxProd);
    end
    nIter = nIter + 1;
end
```

```

        singleProductionEnvelope(model, setM1, 'EX_lac_D_e', biomass, 'savePlot', 1, 'showPlot',
                                'fileName', ['lact_ex2_' num2str(nIter)], 'outputFolder', 'OptKnock');
    else
        if nIter == 1
            fprintf('optKnock was not able to found an optKnock set\n');
        else
            fprintf('optKnock was not able to found additional optKnock sets\n');
        end
        break;
    end
    nIter = nIter + 1;
end

```

...Performing optKnock analysis...

optKnock found a optKnock set of large 4 composed by

HEX1

, PGI

, PTAr

and TKT1

The production of lactate after optimization is 17.99

The growth rate after optimization is 0.12

The production of other products such as ethanol, formate, succinate and acetate are 0.0, 0.7, 0.0 and 0.0

...Performing coupling analysis...

The solution is of type: non unique

The maximun growth rate given the optKnock set is 0.09

The maximun and minimun production of lactate given the optKnock set is 0.00 and 18.62, respectively

...Performing optKnock analysis...

optKnock found a optKnock set of large 5 composed by

GLCabcpp

, PGI

, PTAr

, PYK

and TKT1

The production of lactate after optimization is 17.99

The growth rate after optimization is 0.12

The production of other products such as ethanol, formate, succinate and acetate are 0.0, 0.7, 0.0 and 0.0

...Performing coupling analysis...

The solution is of type: non unique

The maximun growth rate given the optKnock set is 0.09

The maximun and minimun production of lactate given the optKnock set is 0.00 and 18.62, respectively

...Performing optKnock analysis...

optKnock found a optKnock set of large 4 composed by

GLCabcpp

, PGI

, PTAr

and TKT1

The production of lactate after optimization is 17.99

The growth rate after optimization is 0.12

The production of other products such as ethanol, formate, succinate and acetate are 0.0, 0.7, 0.0 and 0.0

...Performing coupling analysis...

The solution is of type: non unique

The maximun growth rate given the optKnock set is 0.09

The maximun and minimun production of lactate given the optKnock set is 0.00 and 18.62, respectively

...Performing optKnock analysis...

optKnock found a optKnock set of large 6 composed by
ACKr
, ALCD2x
, GLCabcpp
, PGI
, PYK
and TKT1

The production of lactate after optimization is 17.99


The growth rate after optimization is 0.12



The production of other products such as ethanol, formate, succinate and acetate are 0.0, 0.7, 0.0 and 0.0
...Performing coupling analysis...


The solution is of type: growth coupled non unique

The maximum growth rate given the optKnock set is 0.09

The maximum and minimum production of lactate given the optKnock set is 10.38 and 18.62, respectively







```
cd(currentDirectory);
```

TIMING

1. Example 1 ~ 1-2 minutes
2. Example 2 ~ 1-2 minutes
3. Example 3 ~ 1-2 minutes
4. Example 4 ~ 1-2 minutes
5. Example 5 ~ 1-2 minutes
6. Example 6 ~ 1-2 minutes

TROUBLESHOOTING

- 1) If the algorithm takes a long time to find a solution, it is possible that the search space is too large. You can reduce the search space using a smaller set of reactions in the input variable "selectedRxnList."
- 2) The default number of deletions used by optKnock is 5. If the algorithm is returning more deletions than what you want, you can change the number of deletions using the input variable "numDel."
- 3) optKnock could find a solution that it is not useful for you. For example, you may think that a solution is very obvious or that it breaks some important biological constraints. If optKnock found a solution that you don't want to find, use the input variable "prevSolutions" to prevent that solution to be found.

ANTICIPATED RESULTS

The optKnock algorithm will find sets of reactions that, when removed from the model, will improve the production of succinate and lactate respectively. In this tutorial, once optKnock finds a solution, then the

type of solution is determined (if the product is coupled with biomass formation or not). Some of the sets will generate a coupled solution, i.e., the production rate will increase as biomass formation increases. For these kind of reactions a plot will be generated using the function `singleProductionEnvelope` and will be saved in the folder `tutoriales/optKnock/optKnockResults`

When you find a solution with OptKnock, you should always verify the minimum and maximum production rate using the function `analyzeOptKnock`.

References

- [1] Burgard, A. P., Pharkya, P. & Maranas, C. D. (2003). OptKnock: A Bilevel Programming Framework for Identifying Gene Knockout Strategies for Microbial Strain Optimization. *Biotechnology and Bioengineering*, 84(6), 647–657. <http://doi.org/10.1002/bit.10803>.
- [2] Orth, J. D., Conrad, T. M., Na, J., Lerman, J. A., Nam, H., Feist, A. M., & Palsson, B. Ø. (2011). A comprehensive *genome* - scale reconstruction of *Escherichia coli* metabolism—2011. *Molecular systems biology*, 7(1), 535.