


# Example use of functions listed in the Standard operating procedure for metabolic reconstruction.

**Author(s):** Ines Thiele, LCSB, University of Luxembourg.

**Reviewer(s):** Catherine Clancy, LCSB, University of Luxembourg.

## INTRODUCTION

This tutorial has been adapted and expanded from the protocol for generating metabolic network reconstruction [1].



*This tutorial will illustrate the example input for The COBRA Toolbox functions applied in the steps 38 to 96 of the protocol workflow, using the *E. coli* core reconstruction [2] as the model of choice.*

*When Matlab/Toolbox commands are following by a ‘;’ the output is not printed. Omitting the ‘;’ invokes printing of the variable content.*

## EQUIPMENT SETUP

### Step 38. Initialize The COBRA Toolbox.

Initialize The COBRA Toolbox using the `initCobraToolbox` function.

```
initCobraToolbox
```

## Setting the optimization solver.

This tutorial will be run with a 'glpk' package, which is a linear programming ('LP') solver. The 'glpk' package does not require additional installation and configuration.

```
solverName = 'glpk';  
solverType = 'LP';  
changeCobraSolver(solverName, solverType);
```

However, for the analysis of large models, such as Recon 3, it is not recommended to use the 'glpk' package but rather an industrial strength solver, such as the 'gurobi' package. For detailed information, refer to The COBRA Toolbox [solver installation guide](#).

A solver package may offer different types of optimization programmes to solve a problem. The above example used a LP optimization, other types of optimization programmes include; mixed-integer linear programming ('MILP'), quadratic programming ('QP'), and mixed-integer quadratic programming ('MIQP').

```
warning off MATLAB:subscripting:noSubscriptsSpecified
```


## PROCEDURE

### Step 39. Load reconstruction into Matlab.

The metabolic network reconstruction, containing a reaction and metabolite list, is contained by the file 'Ecoli\_core\_model.mat'.

```
load('Ecoli_core_model.mat');  
modelEcore = model; % TODO model does not load into workspace a 'modelEcore' but as 'model'.
```

The reconstruction is contained in the resulting model structure.



The figure above shows the data contained in the different structure fields. We will use this model structure for all consequent computation if not noted differently.

Use the command `open` to view the model structure in Matlab.

```
open modelEcore
```

The content of the structure can be assessed as follows:

- You wish to see the abbreviation of the 8th metabolite in the model:

```
modelEcore.mets{8}
```

```
ans = acald[c]
```

- You wish to see the abbreviation of the 1st reaction in the model:

```
modelEcore.rxns{1}
```

```
ans = ACALD
```

- You wish to see the entry of the stoichiometric matrix of the 1st reaction (column) and 8th metabolite (row):

```
modelEcore.S(8,1)
```

```
ans =  
    (1,1)      -1
```

- Print the reaction formula:

```
printRxnFormula(modelEcore,modelEcore.rxns(1))
```

```
ACALD acald[c] + coa[c] + nad[c] <=> accoa[c] + h[c] + nadh[c]  
ans =  
    'acald[c] + coa[c] + nad[c] <=> accoa[c] + h[c] + nadh[c] '
```

- You want to change the lower bound (lb) of the 5th reaction to 10 mmol/gDW/h (without using any COBRA Toolbox functions):

```
modelEcore.lb(5) = 10
```

```
modelEcore =  
    rxns: {95x1 cell}  
    mets: {72x1 cell}  
    S: [72x95 double]  
    rev: [95x1 double]  
    lb: [95x1 double]  
    ub: [95x1 double]  
    c: [95x1 double]  
    rules: {95x1 cell}  
    genes: {137x1 cell}
```

```

rxnGeneMat: [95x137 double]
grRules: {95x1 cell}
subSystems: {95x1 cell}
rxnNames: {95x1 cell}
metNames: {72x1 cell}
metFormulas: {72x1 cell}
b: [72x1 double]
description: 'Ecoli_core_model'

```

- You want to add a field to the model structure.

A note:

```
modelEcore.newField = 'ABC – a note'
```

```

modelEcore =
    rxns: {95x1 cell}
    mets: {72x1 cell}
    S: [72x95 double]
    rev: [95x1 double]
    lb: [95x1 double]
    ub: [95x1 double]
    c: [95x1 double]
    rules: {95x1 cell}
    genes: {137x1 cell}
    rxnGeneMat: [95x137 double]
    grRules: {95x1 cell}
    subSystems: {95x1 cell}
    rxnNames: {95x1 cell}
    metNames: {72x1 cell}
    metFormulas: {72x1 cell}
    b: [72x1 double]
    description: 'Ecoli_core_model'
    newField: 'ABC – a note'

```

An array B = [1 2 3]

```

B = [1 2 3];
modelEcore.newField = B

```

```

modelEcore =
    rxns: {95x1 cell}
    mets: {72x1 cell}
    S: [72x95 double]
    rev: [95x1 double]
    lb: [95x1 double]
    ub: [95x1 double]
    c: [95x1 double]
    rules: {95x1 cell}
    genes: {137x1 cell}
    rxnGeneMat: [95x137 double]
    grRules: {95x1 cell}
    subSystems: {95x1 cell}
    rxnNames: {95x1 cell}
    metNames: {72x1 cell}
    metFormulas: {72x1 cell}
    b: [72x1 double]
    description: 'Ecoli_core_model'
    newField: [1 2 3]

```

- Create a list of strings:

```
ListStrings = {'A' 'B' 'C'}
```

```
ListStrings =  
    'A'    'B'    'C'
```

- Create a list of numbers:

```
ListNumbers = [1 2 3]
```

```
ListNumbers =  
    1    2    3
```

- Transpose a list:

```
ListTranspose = ListNumbers'
```

```
ListTranspose =  
    1  
    2  
    3
```

- Find the index of a reaction, e.g., 'ATPM', in the model


```
rxnList='ATPM';  
rxnID = findRxnIDs(modelEcore, rxnList)
```

```
rxnID = 11
```

## Step 40. Verify S matrix.

Remember that in the S matrix the rows and the columns correspond to the metabolites and the reactions of the model, respectively. The number of non-zero entries in the S matrix is visualized graphically below using a spy image.

```
spy(modelEcore.S)
```



To put this number into perspective, we can calculate the percentage of non-zero entries of S.


```
[a,b] = size(modelEcore.S);
nz = nnz(modelEcore.S);
Perc_nz = nz*100/(a*b)
```

```
Perc_nz = 5.2632
```


- Many large scale models have less than 1% of non-zero entries in the S matrix.
- Looking at the S matrix is a quick way to see whether there is something obviously wrong with the model and the S matrix.

Here are two further examples of S matrices visualized using a spy image:

E. coli - AF1260 [3]



### *Geobacter sulfurreducans* [4]



Consider to also use the tutorial on 'Numerical properties of a reconstruction' to investigate the properties of the S matrix.

### Step 41. Set objective function.

We will set the biomass reaction (Biomass\_Ecoli\_core\_w\_GAM) of the *E. coli* core model as objective function:

```
modelEcore = changeObjective(modelEcore, 'Biomass_Ecoli_core_w_GAM');
```

If you wish to check which reaction(s) make up the objective function and its components, use the following function:

```
objectiveAbbr = checkObjective(modelEcore)
```

```
summaryT =
  Coefficient    Metabolite    metID    Reaction    RxnID
-----
-1.496          3pg[c]         3      Biomass_Ecoli_core_w_GAM    13
-3.7478         accoa[c]        10     Biomass_Ecoli_core_w_GAM    13
59.81           adp[c]          13     Biomass_Ecoli_core_w_GAM    13
4.1182          akg[c]          14     Biomass_Ecoli_core_w_GAM    13
-59.81          atp[c]          17     Biomass_Ecoli_core_w_GAM    13
3.7478          coa[c]          21     Biomass_Ecoli_core_w_GAM    13
-0.361          e4p[c]          23     Biomass_Ecoli_core_w_GAM    13
-0.0709         f6p[c]          26     Biomass_Ecoli_core_w_GAM    13
-0.129          g3p[c]          33     Biomass_Ecoli_core_w_GAM    13
-0.205          g6p[c]          34     Biomass_Ecoli_core_w_GAM    13
-0.2557         gln-L[c]        36     Biomass_Ecoli_core_w_GAM    13
-4.9414         glu-L[c]        38     Biomass_Ecoli_core_w_GAM    13
-59.81          h2o[c]          41     Biomass_Ecoli_core_w_GAM    13
59.81           h[c]            43     Biomass_Ecoli_core_w_GAM    13
-3.547          nad[c]          50     Biomass_Ecoli_core_w_GAM    13
3.547           nadh[c]         51     Biomass_Ecoli_core_w_GAM    13
13.028          nadp[c]         52     Biomass_Ecoli_core_w_GAM    13
-13.028         nadph[c]        53     Biomass_Ecoli_core_w_GAM    13
-1.7867         oaa[c]          58     Biomass_Ecoli_core_w_GAM    13
-0.5191         pep[c]          59     Biomass_Ecoli_core_w_GAM    13
59.81           pi[c]           60     Biomass_Ecoli_core_w_GAM    13
-2.8328         pyr[c]          62     Biomass_Ecoli_core_w_GAM    13
-0.8977         r5p[c]          66     Biomass_Ecoli_core_w_GAM    13
```

```
objectiveAbbr =
  'Biomass_Ecoli_core_w_GAM'
```

## Step 42. Set simulation constraints.

A first step when using and debugging a model should be to identify the constraints that have been applied.

```
minInf = -1000;
maxInf = 1000;
printConstraints(modelEcore, minInf,maxInf)
```

```
MinConstraints:
ACONTb 10
ATPM 8.39
EX_glc(e) -10
maxConstraints:
```

- As you can see, only three reactions are constrained in this model. The glucose exchange reaction (EX\_glc(e)), the aconitase reaction (ACONTb) and the ATP non-growth associated maintenance reaction (ATPM). Note that in all three cases, a lower bound has been set only but no upper bound.
- The 'minInf' and 'maxInf' were set to -1000 and 1000, respectively, as these values represent the infinity of the E. coli core model. Other models may have different infinities.
- Note also that the `printConstraints` function returns only those constraints that are greater than -1000 but are smaller than 1000.

To know which medium constraints are applied to the model, we can use the following function:



```
printUptakeBound(modelEcore);
```

```
EX_co2(e) -1000
EX_glc(e) -10
EX_h(e) -1000
EX_h2o(e) -1000
EX_nh4(e) -1000
EX_o2(e) -1000
EX_pi(e) -1000
```

- As you can see, the model is set to a minimal medium with the presence of oxygen.

Let's assume that you would like to set the lower bound of the ATP maintenance reaction ('ATPM') to 8.39 mmol/gDW/h:

```
modelEcore = changeRxnBounds(modelEcore, 'ATPM', 8.39, 'l');
```

and the upper bound of the 'ATPM' reaction to 8.39 mmol/gDW/h:

```
modelEcore = changeRxnBounds(modelEcore, 'ATPM', 8.39, 'u');
```

To change both the lower and upper bound in the same command use:

```
modelEcore = changeRxnBounds(modelEcore, 'ATPM', 8.39, 'b');
```

Let's assume that you would like to set the lower bound of the 'ATPM' reaction to 8.39 mmol/gDW/h and the ATP synthetase ('ATPS4r') to an upper bound of 100 mmol/gDW/h:

```
modelEcore = changeRxnBounds(modelEcore, 'ATPM', 8.39, 'l' );
modelEcore = changeRxnBounds(modelEcore, 'ATPS4r', 100, 'u');
```

The set constraints can be checked using the following function:

```
printConstraints(modelEcore, -1000, 1000)
```

```
MinConstraints:
ACONTb 10
ATPM 8.39
EX_glc(e) -10
maxConstraints:
ATPM 8.39
ATPS4r 100
```

## Steps 43 - 44. Test if network is mass- and charge balanced.

Check mass- and charge balance for the entire network of the model:

```
[massImbalance, imBalancedMass, imBalancedCharge, imBalancedRxnBool, Elements, missingFormulae]
```

## Step 45. Identify metabolic dead-ends

Detect deadend metabolites:

```
outputMets = detectDeadEnds(modelEcore)
```

```
outputMets =  
    30  
    32  
    37  
    49
```

Print the corresponding metabolite names:

```
DeadEnds = modelEcore.mets(outputMets)
```

```
DeadEnds =  
    'fru[e]'  
    'fum[e]'  
    'gln-L[e]'  
    'mal-L[e]'
```

- These metabolites are only produced or consumed in the network and the associated reactions are blocked reactions.

Identify associated reactions:

```
[rxnList, rxnFormulaList] = findRxnsFromMets(modelEcore, DeadEnds)
```

```
rxnList =  
    'EX_fru(e)'  
    'EX_fum(e)'  
    'EX_gln_L(e)'  
    'EX_mal_L(e)'  
    'FRUpts2'  
    'FUMt2_2'  
    'GLNabc'  
    'MALt2_2'  
  
rxnFormulaList =  
    'fru[e] -> '  
    'fum[e] -> '  
    'gln-L[e] -> '  
    'mal-L[e] -> '  
    'fru[e] + pep[c] -> f6p[c] + pyr[c] '  
    'fum[e] + 2 h[e] -> fum[c] + 2 h[c] '  
    'atp[c] + gln-L[e] + h2o[c] -> adp[c] + gln-L[c] + h[c] + pi[c] '  
    '2 h[e] + mal-L[e] -> 2 h[c] + mal-L[c] '
```

- As you can see, these metabolites have each two reactions associated. Why are they then detected as deadend metabolites?

Let's have a look at the lower and upper bounds of these reactions:

```
modelEcore.lb(find(ismember(modelEcore.rxns,rxnList)))
```

```
ans =  
    0
```

```
0
0
0
0
0
0
0
```

```
modelEcore.ub(find(ismember(modelEcore.rxns,rxnList)))
```

```
ans =
```

```
1000
1000
1000
1000
1000
1000
1000
1000
1000
1000
```

- In this particular case, these four metabolites are deadend metabolites as the associated exchange reactions are set to lb=0 (i.e., no uptake is permitted). As we are interested in dead-end metabolites that are generally only consumed or produced by the network, irrespective of the applied constraints, we will set the lower bound of all exchange reaction to -1000 and the upper bound to 1000.

```
modelEcore_New = modelEcore;
modelEcore_New.lb(strmatch('EX_',modelEcore_New.rxns)) = -1000;
modelEcore_New.ub(strmatch('EX_',modelEcore_New.rxns)) = 1000;
```

Now we repeat the identification of deadend metabolites:

```
outputMets = detectDeadEnds(modelEcore_New)
```

```
outputMets =
```

```
0x1 empty double column vector
```

```
DeadEnds = modelEcore_New.mets(outputMets)
```

```
DeadEnds =
```

```
0x1 empty cell array
```

```
[rxnList, rxnFormulaList] = findRxnsFromMets(modelEcore_New, DeadEnds)
```

```
rxnList =
```

```
0x1 empty cell array
```

```
rxnFormulaList =
```

```
0x0 empty cell array
```

- And indeed no deadend metabolites remain. This example also illustrates how such issues can be fixed - one option is to revert the directionality of the associated reactions.
- Note that changing the directionality must be carefully evaluated in each case, to ensure that the resulting model is biologically accurate. For instance, changing the directionality of the 'FRUpts\_2'

reaction would have not been biologically meaningful, as the Phosphotransferase system is known to be unidirectional under physiologically relevant conditions.

## Steps 46 - 49. Refer to 'gap analysis' tutorial.

## Step 50. Set exchange constraints for a simulation condition.

The Cobra Toolbox function, `changeRxnBounds`, is used to set constraints on a reaction which is demonstrated in step 67 of this tutorial.

## Steps 51 - 59. Test for stoichiometrically balanced cycles (SBCs).

SBCs or Type III pathways, are formed by internal network reactions and can carry fluxes despite closed exchange reactions (closed system). Therefore, use the following `testForTypeIIIPathways` function:

- The indices of the exchange reactions ('EX\_') are input as a list.
- The output filename can be specified with 'test', it receives automatically the extension '.expa'. The filename is optional, the default name is: 'ModelTestTypeIII'

```
listExch = strmatch('EX_', modelEcore.rxns);
try
    testForTypeIIIPathways(modelEcore, listExch, 'test');
catch ME
    getReport(ME)
end
```

```
ans =
Error using fprintf
Function is not defined for sparse inputs.

Error in convertModelToEX (line 54)
    fprintf(fid, '%i\t%s\t', model.S(reactionPlace(j), i), model.mets{reactionPlace(j)});

Error in testForTypeIIIPathways (line 48)
convertModelToEX(model, strcat(filename, '.expa'), rxnzero, model.rxns(ListExch));

Error in LiveEditorEvaluationHelper (line 52)
    testForTypeIIIPathways(modelEcore, listExch, 'test');

Error in matlab.internal.editor.Evaluator/evalFile

Error in matlab.internal.editor.Evaluator/evaluateFile

Error in matlab.internal.editor.Evaluator/evaluateCode

Error in matlab.internal.editor.RegionEvaluator/evaluateRegions

Error in matlab.internal.editor.evaluateRegions

Error in matlab.internal.editor.EvaluationOutputsService.evalRegions
```

- This error message is returned from X3.exe since there are no SBCs in the E. coli core network.

## Steps 60 - 66. Test if biomass precursors can be produced in standard medium

**%TODO steps 64 to 66 are not referenced in this section.**

**60.** Obtain a list of biomass components:

```
BiomassComponents = modelEcore.mets(find(modelEcore.S(:,strmatch('Biomass',modelEcore.rxns))))
```

```
BiomassComponents =
    '3pg[c]'
    'accoa[c]'
    'adp[c]'
    'akg[c]'
    'atp[c]'
    'coa[c]'
    'e4p[c]'
    'f6p[c]'
    'g3p[c]'
    'g6p[c]'
    'gln-L[c]'
    'glu-L[c]'
    'h2o[c]'
    'h[c]'
    'nad[c]'
    'nadh[c]'
    'nadp[c]'
    'nadph[c]'
    'oaa[c]'
    'pep[c]'
    'pi[c]'
    'pyr[c]'
    'r5p[c]'
```

**61.** Add a demand function for each biomass precursor:

```
[modelEcore_NEW ,rxnNames] = addDemandReaction(modelEcore, BiomassComponents);
```

```
DM_3pg[c] 3pg[c] ->
DM_accoa[c] accoa[c] ->
DM_adp[c] adp[c] ->
DM_akg[c] akg[c] ->
DM_atp[c] atp[c] ->
DM_coa[c] coa[c] ->
DM_e4p[c] e4p[c] ->
DM_f6p[c] f6p[c] ->
DM_g3p[c] g3p[c] ->
DM_g6p[c] g6p[c] ->
DM_gln-L[c] gln-L[c] ->
DM_glu-L[c] glu-L[c] ->
DM_h2o[c] h2o[c] ->
DM_h[c] h[c] ->
DM_nad[c] nad[c] ->
DM_nadh[c] nadh[c] ->
DM_nadp[c] nadp[c] ->
```

```

DM_nadph[c] nadph[c] ->
DM_oaa[c] oaa[c] ->
DM_pep[c] pep[c] ->
DM_pi[c] pi[c] ->
DM_pyr[c] pyr[c] ->
DM_r5p[c] r5p[c] ->

```

For each biomass component *i*, perform the following test:

```
for i = 1 : length(BiomassComponents)
```

**62.** Change objective function to the demand function:

```
modelEcore_NEW = changeObjective(modelEcore_NEW, rxnNames(i));
```

**63.** Maximize ('max') for new objective function (Demand function)

```
FBAsolution = optimizeCbModel (modelEcore_NEW, 'max');
```

- FBAsolution is a structure containing the result of the optimization. FBAsolution.f gives the maximal value of the objective reaction (i.e., 'DM\_pep[c]'), which is greater than 0 mmol/gDW/h. This means that our *E. colicore* model can produce pep[c].
- Store each solution in a vector:

```

BiomassComponentsValue(i,1) = FBAsolution.f;
end

```

- Print each BiomassComponent and the corresponding value:

```
[BiomassComponents num2cell(BiomassComponentsValue)]
```

```

ans =
    '3pg[c]'      [ 10.0000]
    'accoa[c]'    [ 1.7764e-15]
    'adp[c]'      [-3.5527e-15]
    'akg[c]'      [ 10.0000]
    'atp[c]'      [ 0]
    'coa[c]'      [ 0]
    'e4p[c]'      [ 7.5000]
    'f6p[c]'      [ 5]
    'g3p[c]'      [ 10.0000]
    'g6p[c]'      [ 5.0000]
    'gln-L[c]'    [ 10.0000]
    'glu-L[c]'    [ 10.0000]
    'h2o[c]'      [ 1000]
    'h[c]'        [ 1000]
    'nad[c]'      [-7.1054e-15]
    'nadh[c]'     [ 7.1054e-15]
    'nadp[c]'     [ 0]
    'nadph[c]'    [ 0]
    'oaa[c]'      [ 10.0000]
    'pep[c]'      [ 10.0000]
    'pi[c]'       [ 1000]
    'pyr[c]'      [ 10.0000]
    'r5p[c]'      [ 6.0000]

```

- As we can see, not all biomass components (or rather their corresponding demand reaction) can have a non-zero flux. Why is that?
- Just to remember us, the model constraints are:

```
printConstraints(modelEcore_NEW, -1000,1000)
```

```
MinConstraints:
ACONTb 10
ATPM 8.39
EX_glc(e) -10
maxConstraints:
ATPM 8.39
ATPS4r 100
```

- Note that only those constraints will be printed that are smaller greater than -1000 and smaller than 1000.
- Let's revisit how the biomass reaction is formulated in this model:

```
modelEcore = changeObjective(modelEcore,modelEcore.rxns(strmatch('Biomass',modelEcore.rxns)));
[objectiveAbbr] = checkObjective(modelEcore)
```

```
summaryT =
Coefficient    Metabolite    metID    Reaction    RxnID
-----
-1.496         3pg[c]        3        Biomass_Ecoli_core_w_GAM    13
-3.7478        accoa[c]      10        Biomass_Ecoli_core_w_GAM    13
59.81          adp[c]        13        Biomass_Ecoli_core_w_GAM    13
4.1182         akg[c]        14        Biomass_Ecoli_core_w_GAM    13
-59.81         atp[c]        17        Biomass_Ecoli_core_w_GAM    13
3.7478         coa[c]        21        Biomass_Ecoli_core_w_GAM    13
-0.361         e4p[c]        23        Biomass_Ecoli_core_w_GAM    13
-0.0709        f6p[c]        26        Biomass_Ecoli_core_w_GAM    13
-0.129         g3p[c]        33        Biomass_Ecoli_core_w_GAM    13
-0.205         g6p[c]        34        Biomass_Ecoli_core_w_GAM    13
-0.2557        gln-L[c]      36        Biomass_Ecoli_core_w_GAM    13
-4.9414        glu-L[c]      38        Biomass_Ecoli_core_w_GAM    13
-59.81         h2o[c]        41        Biomass_Ecoli_core_w_GAM    13
59.81          h[c]          43        Biomass_Ecoli_core_w_GAM    13
-3.547         nad[c]        50        Biomass_Ecoli_core_w_GAM    13
3.547          nadh[c]       51        Biomass_Ecoli_core_w_GAM    13
13.028         nadp[c]       52        Biomass_Ecoli_core_w_GAM    13
-13.028        nadph[c]      53        Biomass_Ecoli_core_w_GAM    13
-1.7867        oaa[c]        58        Biomass_Ecoli_core_w_GAM    13
-0.5191        pep[c]        59        Biomass_Ecoli_core_w_GAM    13
59.81          pi[c]         60        Biomass_Ecoli_core_w_GAM    13
-2.8328        pyr[c]        62        Biomass_Ecoli_core_w_GAM    13
-0.8977        r5p[c]        66        Biomass_Ecoli_core_w_GAM    13
```

```
objectiveAbbr =
'Biomass_Ecoli_core_w_GAM'
```

- As you can see, there are numerous metabolites that have a positive coefficient in the biomass equation, meaning that they are produced by the biomass reaction and thus we need to test whether these metabolites can be removed, rather than produced by the model. Hence, we need to add sink reactions (rather than demand reactions) and minimize them:

- Let's get all biomass components with a positive coefficient in the biomass reaction:

```
BiomassComponentsPos = modelEcore.mets(find(modelEcore.S(:,strmatch('Biomass',modelEcore.rxns))
```

```
BiomassComponentsPos =
    'adp[c]'
    'akg[c]'
    'coa[c]'
    'h[c]'
    'nadh[c]'
    'nadp[c]'
    'pi[c]'
```

```
BiomassComponentsNeg = modelEcore.mets(find(modelEcore.S(:,strmatch('Biomass',modelEcore.rxns))
```

```
BiomassComponentsNeg =
    '3pg[c]'
    'accoa[c]'
    'atp[c]'
    'e4p[c]'
    'f6p[c]'
    'g3p[c]'
    'g6p[c]'
    'gln-L[c]'
    'glu-L[c]'
    'h2o[c]'
    'nad[c]'
    'nadph[c]'
    'oaa[c]'
    'pep[c]'
    'pyr[c]'
    'r5p[c]'
```

```
[modelEcore_NEW] = addSinkReactions(modelEcore, BiomassComponentsPos);
```

```
sink_adp[c] adp[c] <=>
sink_akg[c] akg[c] <=>
sink_coa[c] coa[c] <=>
sink_h[c] h[c] <=>
sink_nadh[c] nadh[c] <=>
sink_nadp[c] nadp[c] <=>
sink_pi[c] pi[c] <=>
```

```
[modelEcore_NEW ,rxnNames] = addDemandReaction(modelEcore_NEW, BiomassComponentsNeg);
```

```
DM_3pg[c] 3pg[c] ->
DM_accoa[c] accoa[c] ->
DM_atp[c] atp[c] ->
DM_e4p[c] e4p[c] ->
DM_f6p[c] f6p[c] ->
DM_g3p[c] g3p[c] ->
DM_g6p[c] g6p[c] ->
DM_gln-L[c] gln-L[c] ->
DM_glu-L[c] glu-L[c] ->
DM_h2o[c] h2o[c] ->
DM_nad[c] nad[c] ->
DM_nadph[c] nadph[c] ->
```



```
DM_oaa[c] oaa[c] ->
DM_pep[c] pep[c] ->
DM_pyr[c] pyr[c] ->
DM_r5p[c] r5p[c] ->
```

- Note that we added both the sink and the demand reactions to the model simultaneously. The reason for this is that metabolites such as coa and accoa, or nadh and nad, are not produced or consumed in this model but only recycled. Hence, for obtaining a non-zero flux for any of the associated sink or demand reactions one needs to add the reaction pair. In larger networks (than the E. coli core model) this will be less of a problem as they capture the biosynthetic pathways for these metabolites.

Now lets repeat the analysis (note that we minimize the objective):

```
for i = 1 : length(BiomassComponentsPos)
    modelEcore_NEW = changeObjective(modelEcore_NEW, strcat('sink_',BiomassComponentsPos(i)));
    FBAolution = optimizeCbModel (modelEcore_NEW,'min');
    BiomassComponentsValuePos(i,1) = FBAolution.f;
end
[BiomassComponentsPos num2cell(BiomassComponentsValuePos)]
```

```
ans =
    'adp[c]'      [ -1000]
    'akg[c]'      [ -1000]
    'coa[c]'      [-663.3333]
    'h[c]'        [ -1000]
    'nadh[c]'     [ -1000]
    'nadp[c]'     [ -1000]
    'pi[c]'       [ -1000]
```

- All these metabolites can be removed by the model.
- We repeat the same analysis for all negative biomass components.

Now lets repeat the analysis (note that we maximize the objective):

```
for i = 1 : length(BiomassComponentsNeg)
    modelEcore_NEW = changeObjective(modelEcore_NEW, strcat('DM_',BiomassComponentsNeg(i)));
    FBAolution = optimizeCbModel (modelEcore_NEW,'max');
    BiomassComponentsValueNeg(i,1) = FBAolution.f;
end
[BiomassComponentsNeg num2cell(BiomassComponentsValueNeg)]
```

```
ans =
    '3pg[c]'      [ 555.8050]
    'accoa[c]'    [ 663.3333]
    'atp[c]'      [1.0000e+03]
    'e4p[c]'      [ 280.4025]
    'f6p[c]'      [ 186.9350]
    'g3p[c]'      [ 370.5367]
    'g6p[c]'      [ 186.9350]
    'gln-L[c]'    [ 500]
    'glu-L[c]'    [1.0000e+03]
    'h2o[c]'      [ 1000]
    'nad[c]'      [1.0000e+03]
    'nadph[c]'    [ 1000]
    'oaa[c]'      [ 990.1464]
    'pep[c]'      [ 555.8050]
    'pyr[c]'      [ 992.5000]
    'r5p[c]'      [ 224.3220]
```

- All these biomass precursors can be produced by the model. Hence a non-zero, positive flux through the biomass reaction should be possible:

```
FBAsolution = optimizeCbModel(modelEcore, 'max');  
FBAsolution.f
```

```
ans = 0.7082
```

FBAsolution.x contains the flux value for each reaction in the network. To view the flux values use:

```
printFluxVector(modelEcore, FBAsolution.x, 'true')
```

```
ACONTa 10  
ACONTb 10  
AKGDH 9.23588  
ATPM 8.39  
ATPS4r 28.2124  
Biomass_Ecoli_core_w_GAM 0.708235  
CO2t -29.8607  
CS 10  
CYTBD 58.0838  
ENO 17.0578  
EX_co2(e) 29.8607  
EX_glc(e) -10  
EX_h(e) 14.2072  
EX_h2o(e) 35.0198  
EX_nh4(e) -3.86187  
EX_o2(e) -29.0419  
EX_pi(e) -2.60539  
FBA 9.29552  
FORt2 127.234  
FORti 127.234  
FUM 9.23588  
GAPD 18.1173  
GLCpts 10  
GLNS 0.181096  
GLUDy -3.68077  
H2Ot -35.0198  
ICDHyr 10  
MDH 9.23588  
NADH16 48.8479  
NH4t 3.86187  
O2t 29.0419  
PDH 12.6543  
PFK 9.29552  
PGI 9.85481  
PGK -18.1173  
PGM -17.0578  
PIt2r 2.60539  
PPC 2.02952  
PYK 4.66061  
RPE -0.50908  
RPI -0.50908  
SUCDi 9.23588  
SUCOAS -9.23588  
TALA -0.126703  
THD2 2.90759  
TKT1 -0.126703  
TKT2 -0.382376  
TPI 9.29552
```

- To see which network reactions participate in the optimal solution. Keep in mind that there may be more than one optimal solution (so-called alternate optimal solutions, which have the same optimal value for the objective function but the internal flux distribution may be different) .
- Compare this solution with a sparse FBA solution, which returns an optimal flux distribution with the least number of active model reactions. Note that the underlying algorithm is an approximation to the exact sparsest solution and also that there may be alternative optimal solutions with equal numbers of active reactions.

```
FBAsolution = optimizeCbModel(modelEcore, 'max', 'zero');
FBAsolution.f
```

```
ans = 0.7082
```

```
printFluxVector(modelEcore, FBAsolution.x, 'true')
```

```
ACONTa 10
ACONTb 10
AKGDH 3.69917
ATPM 8.39
ATPS4r 31.7196
Biomass_Ecoli_core_w_GAM 0.708235
CO2t -11.6696
CS 10
CYTBD 39.8928
ENO 17.0578
EX_co2(e) 11.6696
EX_for(e) 18.191
EX_glc(e) -10
EX_h(e) 32.3982
EX_h2o(e) 16.8287
EX_nh4(e) -3.86187
EX_o2(e) -19.9464
EX_pi(e) -2.60539
FBA 9.29552
FORti 18.191
FUM 9.23588
GAPD 18.1173
GLCpts 10
GLNS 0.181096
GLUDy -3.68077
H2Ot -16.8287
ICDHyr 4.46328
ICL 5.53672
MALS 5.53672
MDH 11.2654
ME2 3.5072
NADH16 30.6569
NH4t 3.86187
O2t 19.9464
PFK 9.29552
PFL 18.191
PGI 9.85481
PGK -18.1173
PGM -17.0578
PIt2r 2.60539
PYK 6.69013
RPE -0.50908
RPI -0.50908
SUCDi 9.23588
SUCOAS -3.69917
TALA -0.126703
THD2 4.93711
```

TKT1 -0.126703  
TKT2 -0.382376  
TPI 9.29552

---

## Steps 67 - 70. Test if model can produce known secretion products.

### 67. Collect a list of known secretion products and medium conditions.

For this example, acetate secretion ('EX\_ac(e)') was chosen and let's require that secretion flux is at least 2 mmol/gDW/h (i.e. the lower bound is constrained to 2).

```
modelEcore_New = changeRxnBounds(modelEcore, 'EX_ac(e)', 2, 'l');
```

### 68. Set the constraints to the desired medium condition (e.g., minimal medium + carbon source). For changing the constraints use the following function:

```
modelEcore_New = changeRxnBounds(modelEcore, {'EX_glc(e)' 'EX_o2(e)'}, [-10 -18.5], 'l');
```

- If the model is required to grow in addition to producing the by-product, set the lower bound of the biomass reaction to the corresponding value required for growth.

**Note:** If the model is required to grow in addition to producing the by-product, set the lower bound of the biomass reaction to the corresponding value required for growth. We determine the value based on the following FBA solution.

- Optimize for growth:

```
modelEcore_New = changeObjective(modelEcore_New, 'Biomass_Ecoli_core_w_GAM');  
FBA_solution = optimizeCbModel(modelEcore_New, 'max')
```

```
FBA_solution =  
    full: [95x1 double]  
    obj: 0.6411  
    rcost: [95x1 double]  
    dual: [72x1 double]  
    solver: 'glpk'  
    algorithm: 'default'  
    stat: 1  
    origStat: 5  
    time: 0.0165  
    basis: []  
        x: [95x1 double]  
        f: 0.6411  
        y: [72x1 double]  
        w: [95x1 double]  
        v: [95x1 double]
```

- Set the lower bound of the biomass reaction to the value of the FBA solution:


```
modelEcore_New = changeRxnBounds(modelEcore_New, 'Biomass_Ecoli_core_w_GAM', 0.64, 'l');
```

- Note that the maximally possible biomass reaction flux decreased substantially, with these additional constraints.

69. Change the objective function to the exchange reaction of your secretion product (i.e., acetate):

```
modelEcore_New = changeObjective(modelEcore_New, 'EX_ac(e)');
```

70. Maximize ('max') for the new objective function (as a secretion is expected to have a positive flux value, see Figure ):



```
FBAsolution = optimizeCbModel (modelEcore_New, 'max')
```

```
FBAsolution =
  full: [95x1 double]
  obj: 0.0448
  rcost: [95x1 double]
  dual: [72x1 double]
  solver: 'glpk'
  algorithm: 'default'
  stat: 1
  origStat: 5
  time: 0.0103
  basis: []
```

```
x: [95×1 double]
f: 0.0448
y: [72×1 double]
w: [95×1 double]
v: [95×1 double]
```

- It seems that the model can produce 3.5x mmol/gDW/h of acetate with the following constraints:

```
printConstraints(modelEcore_New, -1000,1000)
```

```
MinConstraints:
ACONTb 10
ATPM 8.39
Biomass_Ecoli_core_w_GAM 0.64
EX_glc(e) -10
EX_o2(e) -18.5
maxConstraints:
ATPM 8.39
ATPS4r 100
```

### ***Steps 71 - 75. Test if model can produce a certain ratio of two secretion products.***

Acetate and Formate secretion are the two secretion products used in this example.

**71.** Set the constraints to the desired medium condition (e.g., minimal medium + carbon source). As shown above in step 68.

**72.** Let's verify that both metabolites can be secreted independently. Repeat steps 69 and 70.

```
modelEcoreAc = changeObjective(modelEcore, 'EX_ac(e)');
FBAsolution = optimizeCbModel(modelEcoreAc, 'max')
```

```
FBAsolution =
    full: [95×1 double]
    obj: 10.0000
    rcost: [95×1 double]
    dual: [72×1 double]
    solver: 'glpk'
    algorithm: 'default'
    stat: 1
    origStat: 5
    time: 0.0098
    basis: []
    x: [95×1 double]
    f: 10.0000
    y: [72×1 double]
    w: [95×1 double]
    v: [95×1 double]
```

```
modelEcoreFor = changeObjective(modelEcore, 'EX_for(e)');
FBAsolution = optimizeCbModel(modelEcoreFor, 'max')
```

```
FBAsolution =
    full: [95×1 double]
    obj: 40
```

```

rcost: [95x1 double]
dual: [72x1 double]
solver: 'glpk'
algorithm: 'default'
stat: 1
origStat: 5
time: 0.0082
basis: []
x: [95x1 double]
f: 40
y: [72x1 double]
w: [95x1 double]
v: [95x1 double]

```

**73.** Add a row to the S matrix to couple the by-product secretion reactions:

```
modelEcore_NEW = addRatioReaction(modelEcore, {'EX_ac(e)' 'EX_for(e)'}, [1 1]);
```

- Acetate and Formate secretion are coupled to a ratio of 1:1.

Also, let's require that the acetate secretion flux is at least 1 mmol/gDW/h (i.e. the lower bound is constrained to 1).

```
modelEcore_NEW = changeRxnBounds(modelEcore_NEW, 'EX_ac(e)', 1, 'l');
```

**Note:** If the model is required to grow in addition to producing the by-product, set the lower bound of the biomass reaction to the corresponding value required for growth. We determine the value based on the following FBA solution.

- Optimize for growth:

```
modelEcore_NEW = changeObjective(modelEcore_NEW, 'Biomass_Ecoli_core_w_GAM');
FBA_solution = optimizeCbModel(modelEcore_NEW, 'max')
```

```

FBA_solution =
    full: [95x1 double]
    obj: 0.6374
    rcost: [95x1 double]
    dual: [73x1 double]
    solver: 'glpk'
    algorithm: 'default'
    stat: 1
    origStat: 5
    time: 0.0090
    basis: []
    x: [95x1 double]
    f: 0.6374
    y: [73x1 double]
    w: [95x1 double]
    v: [95x1 double]

```

- Note that the maximally possible biomass reaction flux decreased due to the additional constraints.
- Set the lower bound of the biomass reaction to the value of the FBA solution:

```
modelEcore_NEW = changeRxnBounds(modelEcore_NEW, 'Biomass_Ecoli_core_w_GAM',0.63,'l');
```

What is the flux through the two secretion reactions:

```
FBAsolution.x(find(ismember(modelEcore_NEW.rxns,'EX_for(e)')))
```

```
ans = 1
```

```
FBAsolution.x(find(ismember(modelEcore_NEW.rxns,'EX_ac(e)')))
```

```
ans = 1
```

- Keep in mind that the `optimizeCbModel` only returns one of the possible flux distributions with maximal biomass yield.

**74.** Change the objective function to the exchange reaction of one of your secretion products:

```
modelEcore_NEW = changeObjective(modelEcore_NEW, 'EX_ac(e)');
```

**75.** Maximize for the new objective function (as a secretion is expected to have a positive flux value):

```
FBAsolution = optimizeCbModel (modelEcore_NEW,'max')
```

```
FBAsolution =  
    full: [95x1 double]  
    obj: 1.1047  
    rcost: [95x1 double]  
    dual: [73x1 double]  
    solver: 'glpk'  
    algorithm: 'default'  
    stat: 1  
    origStat: 5  
    time: 0.0120  
    basis: []  
    x: [95x1 double]  
    f: 1.1047  
    y: [73x1 double]  
    w: [95x1 double]  
    v: [95x1 double]
```

- Check that the second secretion product can be produced in the defined ratio:

```
FBAsolution.x(find(ismember(modelEcore_NEW.rxns,'EX_for(e)')))
```

```
ans = 1.1047
```

**Steps 76 - 77. Check for blocked reactions.**

**76.** Change simulation conditions to rich medium or open all exchange reactions.



- Identify the exchange reactions and set the reaction values to  $-\infty$  (e.g.,  $-1,000$ ) and  $+\infty$  (e.g.,  $+1,000$ ):

```
ExR = modelEcore.rxns(strmatch('EX_',modelEcore.rxns));
modelEcore_Open = changeRxnBounds(modelEcore, ExR , -1000,'l');
modelEcore_Open = changeRxnBounds(modelEcore_Open, ExR, 1000,'u');
```

- Verify the constraints on the model:

```
printConstraints(modelEcore_Open, -1000,1000)
```

```
MinConstraints:
ACONTb 10
ATPM 8.39
maxConstraints:
ATPM 8.39
ATPS4r 100
```

```
printUptakeBound(modelEcore_Open);
```

```
EX_ac(e) -1000
EX_acald(e) -1000
EX_akg(e) -1000
EX_co2(e) -1000
EX_etoh(e) -1000
EX_for(e) -1000
EX_fru(e) -1000
EX_fum(e) -1000
EX_glc(e) -1000
EX_gln_L(e) -1000
EX_glu_L(e) -1000
EX_h(e) -1000
EX_h2o(e) -1000
EX_lac_D(e) -1000
EX_mal_L(e) -1000
EX_nh4(e) -1000
EX_o2(e) -1000
EX_pi(e) -1000
EX_pyr(e) -1000
EX_succ(e) -1000
```

**77.** Run analysis for blocked reactions. The `findBlockedReaction` function returns a list of blocked reactions ('BlockedReactions').

```
BlockedReactions = findBlockedReaction(modelEcore_Open)
```

```
BlockedReactions =
{''}
```

- The answer is an empty array since the *E. coli* core network has no blocked reactions.
- If the model contains blocked reactions, please refer to the tutorial for 'gap filling' on how to proceed.

## Steps 79 - 80. Compute single gene deletion phenotypes


79. Use The Cobra Toolbox function, `singleGeneDeletion`, to simulate gene deletion:

```
[grRatio,grRateK0,grRateWT, hasEffect] = singleGeneDeletion (modelEcore);
```

- The variable 'hasEffect' is returned, and an entry of 1 in the vector indicate that a gene deletion had an affect on the objective function (here, growth rate).

Let's visualize hasEffect:

```
bar(sort(hasEffect, 'descend'))  
xlabel('Model genes (rank ordered)');  
ylabel('Lethality (1 = lethal, 0 = no effect)')
```



How many genes are in my model?

```
length(modelEcore.genes)
```

```
ans = 137
```

How many genes have an effect and which ones?

```
length(find(hasEffect))
```

```
ans = 71
```

Which gene deletions had an affect?

```
modelEcore.genes(find(hasEffect))
```

```
ans =  
'b0114'  
'b0115'  
'b0116'  
'b0474'  
'b0720'  
'b0721'  
'b0722'  
'b0723'  
'b0724'  
'b0726'  
'b0727'  
'b0728'  
'b0729'  
'b0767'  
'b0809'  
'b0810'  
'b0811'  
'b1136'  
'b1479'  
'b1602'  
'b1603'  
'b1702'  
'b1761'  
'b1779'  
'b1817'  
'b1818'  
'b1819'  
'b1852'  
'b2029'  
'b2276'  
'b2277'  
'b2278'  
'b2279'  
'b2280'  
'b2281'  
'b2282'  
'b2283'  
'b2284'  
'b2285'  
'b2286'  
'b2287'  
'b2288'  
'b2415'  
'b2416'  
'b2463'  
'b2587'  
'b2779'  
'b2926'  
'b3212'  
'b3213'  
'b3236'  
'b3403'  
'b3528'  
'b3731'  
'b3732'  
'b3733'  
'b3734'  
'b3735'  
'b3736'  
'b3737'
```

```
'b3738'  
'b3919'  
'b3956'  
'b4015'  
'b4025'  
'b4077'  
'b4151'  
'b4152'  
'b4153'  
'b4154'  
's0001'
```

---

Which gene deletions are lethal?

- We define all growth rates lower than 0.0001 1/hr as no growth.

```
tol = 1e-3;  
LethalGenes = modelEcore.genes(find(grRateK0 < tol))
```

```
LethalGenes =  
    'b0721'  
    'b0722'  
    'b0723'  
    'b0724'  
    'b1136'  
    'b3919'
```


```
length(LethalGenes)
```

```
ans = 6
```

- Plot the effect of gene deletions on growth rate:

Some entries in 'grRateKO' maybe NaN. This is because the model is infeasible for those knockouts due to the lower bound on the 'ATPM'. We will replace those instances by zero.

```
grRateK0(isnan(grRateK0)) = 0;  
  
bar(sort(grRateK0, 'descend'));  
xlabel('Model genes (rank ordered)');  
ylabel('Growth rate (1/hr)')
```



**80.** Compare with experimental data.

- Are those genes known to be lethal in the organism (in vivo)?

*%TODO Steps 81 - 87 ?*

**Steps 88 - 89. Test if the model grows too fast.**

When optimization results for a biomass reaction in different medium conditions are compared with experimental data, one can evaluate if the model grows too fast. Analysis of modeling constraints, reduced cost and single gene deletion, are helpful in the evaluation of growth conditions.

**88.** Determine the reduced cost associated with network reactions when optimizing for an objective function:

```
FBAsolution = optimizeCbModel(modelEcore, 'max', false)
```

```
FBAsolution =
    full: [95x1 double]
    obj: 0.7082
    rcost: [95x1 double]
    dual: [72x1 double]
    solver: 'glpk'
    algorithm: 'default'
    stat: 1
    origStat: 5
```

```

time: 0.0176
basis: []
x: [95x1 double]
f: 0.7082
y: [72x1 double]
w: [95x1 double]
v: [95x1 double]

```

- FBA solution.y contains the shadow price for each metabolite and FBA solution.w contains the reduced cost for each network reaction.

Shadow price:  $\pi_i = - \frac{\partial Z}{\partial b_i} \left[ \frac{\partial \text{growth}}{\partial \text{nutrient}} \right]$

↑  
+ or -

1.  $\pi_i = 0$  ; not a governing constraint

2.  $\pi_i < 0$  ; more 'i' the higher Z becomes

3.  $\pi_i > 0$  ; more 'i' the lower Z becomes

Reduced cost:  $\rho_i = \frac{\partial Z}{\partial v_i}$

Amount by which the objective function will change with  
the flux level through an internal flux that is not in the basis  
solution

- We find the reduced cost particularly informative to identify constraints that limit the maximal value of the objective function.
- Note that by definition the reduced cost has a negative sign. Meaning that a reaction A with a reduced cost of 35 would lead to an increase in the objective value by 35 if the flux through this reaction would be increased by 1 flux unit.

Print those reactions that have the smallest reduced cost associated:

```

[a,b] = sort(FBA solution.w, 'descend');
modelEcore.rxn(b(1:10))

```

```

ans =
'EX_fru(e)'
'EX_glc(e)'
'ACONTb'
'EX_ac(e)'
'EX_ald(e)'
'EX_eto(e)'
'EX_fum(e)'
'EX_lac_D(e)'
'EX_pyr(e)'
'EX_succ(e)'

```

```
a(1:10)
```

```
ans =  
    0.1416  
    0.1416  
    0.0708  
    0.0708  
    0.0708  
    0.0708  
    0.0708  
    0.0708  
    0.0708  
    0.0708
```

- Generally, we are looking for exchange reactions that may be limiting the objective value (e.g., growth yield) as those ones are easy to adjust *in silico* (and *in vitro*).
- The uptake of glucose is limiting and the associated reduced cost is 0.1416, i.e., if we were to increase the flux through this reaction by 1 unit we would increase the objective by 0.1416.
- Let's test this by repeating step 88 with an increase to the flux through EX\_glc(e) by one unit.

**89.** Beforehand we proceed, let's verify the constraints are set as intended:

```
printConstraints(modelEcore, -1000, 1000);
```

```
MinConstraints:  
ACONTb 10  
ATPM 8.39  
EX_glc(e) -10  
maxConstraints:  
ATPM 8.39  
ATPS4r 100
```

```
printUptakeBound(modelEcore);
```

```
EX_co2(e) -1000  
EX_glc(e) -10  
EX_h(e) -1000  
EX_h2o(e) -1000  
EX_nh4(e) -1000  
EX_o2(e) -1000  
EX_pi(e) -1000
```

Increase the flux through EX\_glc(e) by one unit (keep in mind that uptake is defined as a negative flux through exchange reactions):

```
modelEcore_New = changeRxnBounds(modelEcore, 'EX_glc(e)', -11, 'l');  
FBAsolution = optimizeCbModel(modelEcore_New, 'max', false)
```

```
FBAsolution =  
    full: [95×1 double]  
    obj: 0.8499  
    rcost: [95×1 double]  
    dual: [72×1 double]  
    solver: 'glpk'
```

```

algorithm: 'default'
stat: 1
origStat: 5
time: 0.0101
basis: []
x: [95×1 double]
f: 0.8499
y: [72×1 double]
w: [95×1 double]
v: [95×1 double]

```


- And indeed the biomass flux rate increased accordingly.
- For more systematic analysis of the effect of reduced costs and limiting variable, please also refer to the tutorial on robustness and phase plane analysis.

### 93. Use single-reaction deletion to identify single reactions that may enable the model to grow too fast.

```
[grRatio,grRateK0,grRateWT] = singleRxnDeletion(modelEcore);
```

- Which gene deletion would lead to a lower growth rate?

```
plot(grRateK0)
```





## 94. Reduced cost.

The reduced cost analysis can be used to identify those reactions that can reduce the growth rate (positive cost value). Reduced cost demonstrated as as part of step 89.

## 95. Print Matlab model content.

- Add a field if missing:

```
if ~isfield(modelEcore, 'osense')
    modelEcore.osense = -1;
end
if ~isfield(modelEcore, 'csense')
    modelEcore.csense(1:length(modelEcore.mets),1) = 'E';
end
```

- Write a SBML file:

```
writeCbModel(modelEcore,'sbml', 'EColiCore.xml')
```

Document written

```
ans =
    constraint: [1x0 struct]
functionDefinition: [1x0 struct]
    event: [1x0 struct]
    rule: [1x0 struct]
    unitDefinition: [1x1 struct]
initialAssignment: [1x0 struct]
    SBML_level: 3
    SBML_version: 1
    annotation: ''
    areaUnits: ''
    avogadro_symbol: ''
    conversionFactor: ''
    delay_symbol: ''
    extentUnits: ''
fbc_activeObjective: 'obj'
    fbc_version: 2
        id: 'COBRAModel'
    lengthUnits: ''
    metaid: 'COBRAModel'
    name: ''
    notes: ''
    sboTerm: -1
    substanceUnits: ''
    timeUnits: ''
    time_symbol: ''
    typecode: 'SBML_MODEL'
    volumeUnits: ''
    species: [1x72 struct]
    compartment: [1x2 struct]
    parameter: [1x7 struct]
    reaction: [1x95 struct]
    fbc_fluxBound: [1x2 struct]
fbc_geneProduct: [1x137 struct]
    fbc_objective: [1x1 struct]
    namespaces: [1x2 struct]
    fbc_strict: 1
```

---

## TIMING

The tutorial runs as given in a few seconds to minutes. However, if you use this tutorial for debugging and generating your own model, please consider the timing of the steps, as they have been given in the original protocol [1].

The timing of the entire reconstruction process depends on the properties of the target organism (prokaryote vs. eukaryote, genome size), the quality of the genome annotation, and the availability of experimental data.

The timing listed below represents an average and can be used to plan the different stages.

Step 1 - 4 (Stage 1, draft reconstruction): days to a week.

Step 5 (Stage 1, collection of experimental data): ongoing throughout the reconstruction process

Step 6 - 23 (Stage 2, reconstruction refinement): months to a year (if debugging and gap filling is done along the way)

Step 24 - 32 (Stage 2, biomass determination): days to weeks, depending on data availability

Step 34 - 36 (Stage 2, biomass determination): days to a week.

Step 37 (Stage 2, growth requirements): days to weeks, depending on data availability

Step 38 - 42 (Stage 3, conversion): days to a week.

Step 43 - 94 (Stage 4, network evaluation/debugging): week to months.

Step 95 - 96 (Data assembly): days to weeks, depending how much and in which format data was collected.

## TROUBLESHOOTING

As given in original protocol [1].

Step 38 See installation instructions of the COBRA Toolbox for details on how to install and setup Matlab, SBML and COBRA Toolbox.

Step 51 Make sure that you are working in the directory where the X3.exe script was copied to. The .expa file produced by the function must be in the same directory as X3.exe.

## ANTICIPATED RESULTS

As given in original protocol [1].

This protocol will result in a reconstruction that covers most of the known metabolic information of the target organism and represents a knowledge database. This reconstruction can be used as a resource for information (query tool), high-throughput data mapping (context for content), and a starting point for mathematical models.

## References

[1] Thiele Nat Protoc

[2] EcoSal

[3] iAF1260

*Geobacter sulfurreducans* [4]