

genetic Minimal Cut Sets - gMCS

Authors: Iñigo Apaolaza, University of Navarra, TECNUN School of Engineering, Spain

Luis V. Valcarcel, University of Navarra, TECNUN School of Engineering, Spain

Francisco J. Planes, University of Navarra, TECNUN School of Engineering, Spain

Reviewer(s):

INTRODUCTION

Minimal Cut Sets (MCSs) are minimal sets of reaction knockouts which deprive a network from accomplishing a given metabolic task¹. On the other hand, genetic Minimal Cut Sets (gMCSs) consist of minimal sets of genes whose simultaneous inhibition would render the functioning of a given metabolic task impossible². Therefore, the concepts of MCSs and gMCSs are equivalent but at different levels: at the reaction level for the former and at the gene level for the latter.

MCSs are not directly converted into feasible knockout strategies at a gene level due to the fact that the Gene-Protein-Reaction (GPR) rules, typically provided in genome-scale metabolic reconstructions, are not one-to-one. Certainly, we can find impractical reaction knockouts because they are catalyzed by enzymes involving several genes, which increase the cost of the intervention. On the other hand, the resulting gene knockout interventions from MCSs may provoke undesired metabolic effects, as we may have reactions (included in a particular MCS) catalyzed by an enzyme that additionally participate in other relevant reactions (not included in the MCS under consideration). This fact is further discussed in Apaolaza et al., 2017 (a)², (b)³.

Moreover, state-of-the-art methods which calculate combined gene intervention strategies are based on combinatorial approaches and, as a consequence, are not viable for seeking for high order therapeutic strategies in large metabolic networks. This tutorial aims also to demonstrate that the calculation gMCSs involving a large number of genes is viable with the function provided.

EQUIPMENT SETUP

Initialize The Cobra Toolbox and select the solver (~25 sec)

If necessary, initialise the Cobra Toolbox:

```
initCobraToolbox
```



```
> Checking if git is installed ... Done.
> Checking if the repository is tracked using git ... Done.
> Checking if curl is installed ... Done.
> Checking if remote can be reached ... Done.
> Initializing and updating submodules (this may take a while)... Done.
> Adding all the files of The COBRA Toolbox ... Done.
> Define CB map output... set to sug.
> TranslateSBML is installed and working properly.
> Configuring solver environment variables ...
- [----] ILOG_CPLEX_PATH: C:\Program Files\IBM\ILOG\CPLEX_Studio128\cplex\matlab\win64
- [----] GUROBI_PATH: -> set this path manually after installing the solver ( see instructions )
- [----] TOMLAB_PATH: -> set this path manually after installing the solver ( see instructions )
- [----] MOSEK_PATH: -> set this path manually after installing the solver ( see instructions )
Done.
> Checking available solvers and solver interfaces ... Done.
> Setting default solvers ... Done.
> Saving the MATLAB path ... Done.
- The MATLAB path was saved in the default location.
```

> Summary of available solvers and solver interfaces

Support	LP	MILP	QP	MIQP	NLP	
gurobi	active		0	0	0	-
ibm_cplex	active	1	1	1	-	-
tomlab_cplex	active	0	0	0	0	-
glpk	active	1	1	-	-	-
mosek	active	0	-	0	-	-
matlab	active	1	-	-	-	1
cplex_direct	active	0	0	0	0	-
dqqMinos	active	0	-	-	-	-
pdco	active	1	-	1	-	-
quadMinos	active	0	-	-	-	-
qpnp	passive	-	-	1	-	-
tomlab_unopt	passive	-	-	-	-	0
gurobi_mex	legacy	0	0	0	0	-
lindo_old	legacy	0	-	-	-	-
lindo_legacy	legacy	0	-	-	-	-
lp_solve	legacy	1	-	-	-	-
opti	legacy	0	0	0	0	0
Total	-	5	2	3	0	1

+ Legend: - = not applicable, 0 = solver not compatible or not installed, 1 = solver installed.

```
> You can solve LP problems using: 'ibm_cplex' - 'glpk' - 'matlab' - 'pdco' - 'lp_solve'
> You can solve MILP problems using: 'ibm_cplex' - 'glpk'
> You can solve QP problems using: 'ibm_cplex' - 'pdco' - 'qpnp'
> You can solve MIQP problems using:
> You can solve NLP problems using: 'matlab'
```

```
> Checking for available updates ...
--> You cannot update your fork using updateCobraToolbox(). [06067a @ gmcs_v3].
Please use the MATLAB.devTools (https://github.com/spencobra/MATLAB\_devTools).
```

Note that the approaches to search for MCS and gMCS problems are based on Mixed Integer Linear Programming (MILP). The solver selected will be Cplex.

```
changeCobraSolver('ibm_cplex', 'all');
```

```

> IBM ILOG CPLEX interface added to MATLAB path.
> The solver compatibility is not tested with MATLAB R2017a.
> Solver for LP problems has been set to ibm_cplex.

> IBM ILOG CPLEX interface added to MATLAB path.
> The solver compatibility is not tested with MATLAB R2017a.
> Solver for QP problems has been set to ibm_cplex.
> Solver ibm_cplex not supported for problems of type MINQP. No solver set for this problemtype
> Solver ibm_cplex not supported for problems of type NLP. Currently used: matlab


```

PROCEDURE

This tutorial will be divided in two different parts. First, a toy example will be used to illustrate the difference between MCSs and gMCSs and, second, gMCSs will be calculated for Recon2.v04 metabolic model⁴.

1. Toy example (~5 sec)

The toy example under study is presented below:



First, we are going to load the MAT-file which contains the metabolic network in the toy example.

```
load('gMCStoyExample.mat');
```

As different metabolic models in COBRA format, it contains the following fields: *S*, *ub*, *lb*, *rxns*, *metS*, *genes*, *rules*, *grRules*, *rxnGeneMat* and *c*.

```
rxns = model.rxns
```

```

rxns =
    'r1'
    'r2'
    'r3'
    'r4'
    'r5'
    'r6'
    'rBio'

```

```
grRules = model.grRules
```

```

grRules =
    '{g1}'
    '{g2}'
    '{g2} or {g3}'
    '{g4}'
    '{g5} and {g6}'
    '{g5}'
    ''

```

We can observe that all reactions and genes have a one-to-one relationship except for *r3* and *r5*, which have rules containing 2 different genes and an "or" and an "and" relationship, respectively. On the other hand, *g2* and *g5* take part in two different reactions each. The existence of non-trivial relationships between genes and reactions are the cause of not obtaining the same solutions with MCSs and gMCSs.

We aim to calculate MCSs which will render the biomass production impossible via the function named `calculateMCS()`. Therefore, the desired target metabolic task (represented in the field *c* of the structure) will be the biomass reaction.

```
model.rxns(logical(model.c))
```

```
ans = 'rBio'
```

We will calculate 10 MCSs and we will set the length of the largest MCS to be calculated to 7 (the number of reactions), in order to calculate all the existing MCSs.

```
m_MCS = 10;  
max_len_MCS = 7;
```

Now, the different optional arguments of the function must be set, if needed. In this case, we will calculate MCSs involving reactions 1 to 6. The biomass reaction (rBio) is omitted since it is the target metabolic task.

```
optional_inputs.rxn_set = {'r1'; 'r2'; 'r3'; 'r4'; 'r5'; 'r6'};
```

The time limit for the calculation of each MCS will be set to 30 seconds.

```
optional_inputs.timelimit = 30;
```

Although not shown here, other optional arguments may be set, as detailed in the documentation of the function.

We will now proceed with the calculation of the MCSs.

```
[MCSs, MCS_time] = calculateMCS(model, m_MCS, max_len_MCS, optional_inputs);
```

```
CPXPARAM_Preprocessing_Fill          50  
CPXPARAM_Preprocessing_Aggregator    50  
CPXPARAM_Preprocessing_Dependency     1  
CPXPARAM_TimeLimit                   30  
CPXPARAM_Preprocessing_Dual           1  
CPXPARAM_Preprocessing_NumPass        50  
CPXPARAM_Output_CloneLog              -1  
CPXPARAM_Preprocessing_CoeffReduce    2  
CPXPARAM_Preprocessing_BoundStrength  1  
CPXPARAM_MIP_Strategy_HeuristicFreq   1000  
CPXPARAM_Preprocessing_Relax          1  
CPXPARAM_Emphasis_MIP                 4  
CPXPARAM_Preprocessing_Symmetry       1  
CPXPARAM_MIP_Strategy_RINGHeur        50  
CPXPARAM_MIP_Pool_RelGap               0.10000000000000001  
CPXPARAM_MIP_Limits_Populate          40
```

```
Populate: phase I  
Tried aggregator 2 times.  
MIP Presolve eliminated 2 rows and 4 columns.  
Aggregator did 3 substitutions.  
Reduced MIP has 10 rows, 12 columns, and 26 nonzeros.  
Reduced MIP has 6 binaries, 0 generals, 0 SOSs, and 6 indicators.  
Presolve time = 0.00 sec. (0.02 ticks)
```

```
Root node processing (before b&c):  
  Real time       = 0.00 sec. (0.06 ticks)  
Parallel b&c, 0 threads:  
  Real time       = 0.00 sec. (0.00 ticks)  
  Sync time (average) = 0.00 sec.  
  Wait time (average) = 0.00 sec.
```

```
Total (root+branch&cut) = 0.00 sec. (0.06 ticks)  
CPXPARAM_Preprocessing_Fill          50  
CPXPARAM_Preprocessing_Aggregator    50  
CPXPARAM_Preprocessing_Dependency     1  
CPXPARAM_TimeLimit                   30  
CPXPARAM_Preprocessing_Dual           1  
CPXPARAM_Preprocessing_NumPass        50  
CPXPARAM_Output_CloneLog              -1  
CPXPARAM_Preprocessing_CoeffReduce    2  
CPXPARAM_Preprocessing_BoundStrength  1  
CPXPARAM_MIP_Strategy_HeuristicFreq   1000  
CPXPARAM_Preprocessing_Relax          1  
CPXPARAM_Emphasis_MIP                 4  
CPXPARAM_MIP_Limits_Populate          40
```

```

CPXPARAM_Preprocessing_Symmetry      1
CPXPARAM_MIP_Strategy_RINGHeur      50
CPXPARAM_MIP_Pool_RelGap             0.10000000000000001
CPXPARAM_MIP_Limits_Populate         40

```

```

Populate: phase I
Tried aggregator 2 times.
MIP Presolve eliminated 2 rows and 4 columns.
Aggregator did 3 substitutions.
Reduced MIP has 10 rows, 12 columns, and 26 nonzeros.
Reduced MIP has 6 binaries, 0 generals, 0 SOSs, and 6 indicators.
Presolve time = 0.00 sec. (0.02 ticks)
Found incumbent of value 2.000000 after 0.00 sec. (0.03 ticks)
Probing time = 0.00 sec. (0.00 ticks)
Tried aggregator 1 time.
Reduced MIP has 10 rows, 12 columns, and 26 nonzeros.
Reduced MIP has 6 binaries, 0 generals, 0 SOSs, and 6 indicators.
Presolve time = 0.00 sec. (0.01 ticks)
Probing time = 0.00 sec. (0.00 ticks)
MIP emphasis: hidden feasible solutions.
MIP search method: dynamic search.
Parallel mode: deterministic, using up to 8 threads.
Root relaxation solution time = 0.00 sec. (0.01 ticks)

```

	Nodes		Cuts/			
	Node Left	Objective	Inf	Best Integer	Best Bound	ItCnt Gap
*	0+ 0			2.0000	0.0000	100.00%
	0 0	cutoff		2.0000		0 0.00%

```

Root node processing (before b&C):
  Real time       = 0.00 sec. (0.07 ticks)
Parallel b&C, 8 threads:
  Real time       = 0.00 sec. (0.00 ticks)
  Sync time (average) = 0.00 sec.
  Wait time (average) = 0.00 sec.
Total (root+branch&cut) = 0.00 sec. (0.07 ticks)

```

```

Populate: phase II
MIP emphasis: hidden feasible solutions.
MIP search method: dynamic search.
Parallel mode: deterministic, using up to 8 threads.

```

```

Root node processing (before b&C):
  Real time       = 0.00 sec. (0.01 ticks)
Parallel b&C, 8 threads:
  Real time       = 0.00 sec. (0.00 ticks)
  Sync time (average) = 0.00 sec.
  Wait time (average) = 0.00 sec.
Total (root+branch&cut) = 0.00 sec. (0.01 ticks)

```

```

CPXPARAM_Preprocessing_Fill          50
CPXPARAM_Preprocessing_Aggregator    50
CPXPARAM_Preprocessing_Dependency     1
CPXPARAM_TimeLimit                   30
CPXPARAM_Preprocessing_Dual           1
CPXPARAM_Preprocessing_NumPass       50
CPXPARAM_Output_CloneLog             -1
CPXPARAM_Preprocessing_CoeffReduce    2
CPXPARAM_Preprocessing_BoundStrength  1
CPXPARAM_MIP_Strategy_HeuristicFreq  1000
CPXPARAM_Preprocessing_Relax          1
CPXPARAM_Emphasis_MIP                4
CPXPARAM_Preprocessing_Symmetry       1
CPXPARAM_MIP_Strategy_RINGHeur      50
CPXPARAM_MIP_Pool_RelGap             0.10000000000000001
CPXPARAM_MIP_Limits_Populate         40

```

```

Populate: phase I
Reduced MIP has 17 rows, 20 columns, and 43 nonzeros.
Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
Presolve time = 0.00 sec. (0.01 ticks)

```

Warning: No solution found from 1 MIP starts.
 Retaining values of one MIP start for possible repair.
 Tried aggregator 2 times.
 MIP Presolve eliminated 2 rows and 5 columns.
 Aggregator did 3 substitutions.
 Reduced MIP has 11 rows, 12 columns, and 28 nonzeros.
 Reduced MIP has 6 binaries, 0 generals, 0 SOSs, and 6 indicators.
 Presolve time = 0.00 sec. (0.02 ticks)
 Probing time = 0.00 sec. (0.00 ticks)
 Tried aggregator 1 time.
 Reduced MIP has 11 rows, 12 columns, and 28 nonzeros.
 Reduced MIP has 6 binaries, 0 generals, 0 SOSs, and 6 indicators.
 Presolve time = 0.00 sec. (0.01 ticks)
 Probing time = 0.00 sec. (0.00 ticks)
 Clique table members: 1.
 MIP emphasis: hidden feasible solutions.
 MIP search method: dynamic search.
 Parallel mode: deterministic, using up to 8 threads.
 Root relaxation solution time = 0.00 sec. (0.01 ticks)

	Nodes			Cuts/		
	Node Left	Objective	Inf	Best Integer	Best Bound	ItCnt Gap
	0	0	2.0000	1	2.0000	0
*	0+	0		2.0000	2.0000	0.00%

Root node processing (before b&cut):
 Real time = 0.02 sec. (0.16 ticks)
 Parallel b&cut, 8 threads:
 Real time = 0.00 sec. (0.00 ticks)
 Sync time (average) = 0.00 sec.
 Wait time (average) = 0.00 sec.

 Total (root+branch&cut) = 0.02 sec. (0.16 ticks)

Populate: phase II
 MIP emphasis: hidden feasible solutions.
 MIP search method: dynamic search.
 Parallel mode: deterministic, using up to 8 threads.

Root node processing (before b&cut):
 Real time = 0.02 sec. (0.09 ticks)
 Parallel b&cut, 8 threads:
 Real time = 0.33 sec. (0.11 ticks)
 Sync time (average) = 0.24 sec.
 Wait time (average) = 0.00 sec.

 Total (root+branch&cut) = 0.34 sec. (0.20 ticks)

CPXPARAM_Preprocessing_Fill	50
CPXPARAM_Preprocessing_Aggregator	50
CPXPARAM_Preprocessing_Dependency	1
CPXPARAM_TimeLimit	30
CPXPARAM_Preprocessing_Dual	1
CPXPARAM_Preprocessing_NumPass	50
CPXPARAM_Output_CloneLog	-1
CPXPARAM_Preprocessing_CoeffReduce	2
CPXPARAM_Preprocessing_BoundStrength	1
CPXPARAM_MIP_Strategy_HeuristicFreq	1000
CPXPARAM_Preprocessing_Relax	1
CPXPARAM_Emphasis_MIP	4
CPXPARAM_Preprocessing_Symmetry	1
CPXPARAM_MIP_Strategy_RINGHeur	50
CPXPARAM_MIP_Pool_RelGap	0.100000000000000001
CPXPARAM_MIP_Limits_Populate	40

Populate: phase I
 Reduced MIP has 20 rows, 23 columns, and 52 nonzeros.
 Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
 Presolve time = 0.00 sec. (0.01 ticks)
 Warning: No solution found from 3 MIP starts.
 Retaining values of one MIP start for possible repair.
 Tried aggregator 2 times.
 MIP Presolve eliminated 2 rows and 8 columns.

```

Aggregator did 3 substitutions.
Reduced MIP has 14 rows, 12 columns, and 34 nonzeros.
Reduced MIP has 6 binaries, 0 generals, 0 SOSs, and 6 indicators.
Presolve time = 0.00 sec. (0.03 ticks)

Root node processing (before b&c):
  Real time               = 0.00 sec. (0.11 ticks)
Parallel b&c, 0 threads:
  Real time               = 0.00 sec. (0.00 ticks)
  Sync time (average)     = 0.00 sec.
  Wait time (average)     = 0.00 sec.

Total (root+branch&cut) = 0.00 sec. (0.11 ticks)
CPXPARAM_Preprocessing_Fill          50
CPXPARAM_Preprocessing_Aggregator    50
CPXPARAM_Preprocessing_Dependency     1
CPXPARAM_TimeLimit                   30
CPXPARAM_Preprocessing_Dual           1
CPXPARAM_Preprocessing_NumPass        50
CPXPARAM_Output_CloneLog             -1
CPXPARAM_Preprocessing_CoeffReduce    2
CPXPARAM_Preprocessing_BoundStrength  1
CPXPARAM_MIP_Strategy_HeuristicFreq  1000
CPXPARAM_Preprocessing_Relax          1
CPXPARAM_Emphasis_MIP                 4
CPXPARAM_Preprocessing_Symmetry       1
CPXPARAM_MIP_Strategy_RINGHeur        50
CPXPARAM_MIP_Pool_RelGap              0.10000000000000001
CPXPARAM_MIP_Limits_Populate          40

```

```

Populate: phase 1
Reduced MIP has 20 rows, 23 columns, and 52 nonzeros.
Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
Presolve time = 0.00 sec. (0.01 ticks)
Warning: No solution found from 3 MIP starts.
Retaining values of one MIP start for possible repair.
Tried aggregator 2 times.
MIP Presolve eliminated 2 rows and 8 columns.
Aggregator did 3 substitutions.
Reduced MIP has 14 rows, 12 columns, and 34 nonzeros.
Reduced MIP has 6 binaries, 0 generals, 0 SOSs, and 6 indicators.
Presolve time = 0.02 sec. (0.03 ticks)
Probing fixed 4 vars, tightened 3 bounds.
Probing time = 0.00 sec. (0.00 ticks)
Tried aggregator 2 times.
MIP Presolve eliminated 10 rows and 8 columns.
Aggregator did 1 substitutions.
Reduced MIP has 3 rows, 3 columns, and 6 nonzeros.
Reduced MIP has 1 binaries, 0 generals, 0 SOSs, and 2 indicators.
Presolve time = 0.02 sec. (0.01 ticks)
Probing time = 0.00 sec. (0.00 ticks)
Tried aggregator 1 time.
Reduced MIP has 3 rows, 3 columns, and 6 nonzeros.
Reduced MIP has 1 binaries, 0 generals, 0 SOSs, and 2 indicators.
Presolve time = 0.00 sec. (0.00 ticks)
Probing time = 0.00 sec. (0.00 ticks)
Clique table members: 1.
MIP emphasis: hidden feasible solutions.
MIP search method: dynamic search.
Parallel mode: deterministic, using up to 8 threads.
Root relaxation solution time = 0.00 sec. (0.00 ticks)

```

	Nodes				Cuts/			
	Node	Left	Objective	IInf	Best Integer	Best Bound	ItCnt	Gap
*	0	0	integral	0	3.0000	3.0000	0	0.00%

```

Root node processing (before b&c):
  Real time               = 0.05 sec. (2.06 ticks)
Parallel b&c, 0 threads:
  Real time               = 0.00 sec. (0.00 ticks)
  Sync time (average)     = 0.00 sec.
  Wait time (average)     = 0.00 sec.

```

Wait time (average) = 0.00 sec.
 Total (root+branch&cut) = 0.05 sec. (2.06 ticks)

Populate: phase II
 MIP emphasis: hidden feasible solutions.
 MIP search method: dynamic search.
 Parallel mode: deterministic, using up to 8 threads.

	Nodes	Objective	IInf	Best Integer	Cuts/ Best Bound	ItCnt	Gap
	Node Left						
	0	2	3.0000	1	3.0000	3.0000	0 0.00%

Elapsed time = 0.05 sec. (2.06 ticks, tree = 0.01 MB, solutions = 1)

Root node processing (before b&c):
 Real time = 0.00 sec. (0.02 ticks)
 Parallel b&c, 8 threads:
 Real time = 0.00 sec. (0.01 ticks)
 Sync time (average) = 0.00 sec.
 Wait time (average) = 0.00 sec.

Total (root+branch&cut) = 0.00 sec. (0.03 ticks)

CPXPARAM_Preprocessing_Fill	50
CPXPARAM_Preprocessing_Aggregator	50
CPXPARAM_Preprocessing_Dependency	1
CPXPARAM_TimeLimit	30
CPXPARAM_Preprocessing_Dual	1
CPXPARAM_Preprocessing_NumPass	50
CPXPARAM_Output_CloneLog	-1
CPXPARAM_Preprocessing_CoeffReduce	2
CPXPARAM_Preprocessing_BoundStrength	1
CPXPARAM_MIP_Strategy_HeuristicFreq	1000
CPXPARAM_Preprocessing_Relax	1
CPXPARAM_Emphasis_MIP	4
CPXPARAM_Preprocessing_Symmetry	1
CPXPARAM_MIP_Strategy_RINGHeur	50
CPXPARAM_MIP_Pool_RelGap	0.10000000000000001
CPXPARAM_MIP_Limits_Populate	40

Populate: phase I
 Reduced MIP has 22 rows, 25 columns, and 60 nonzeros.
 Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
 Presolve time = 0.00 sec. (0.01 ticks)
 Warning: No solution found from 2 MIP starts.
 Retaining values of one MIP start for possible repair.
 Tried aggregator 2 times.
 MIP Presolve eliminated 2 rows and 10 columns.
 Aggregator did 3 substitutions.
 Reduced MIP has 16 rows, 12 columns, and 40 nonzeros.
 Reduced MIP has 6 binaries, 0 generals, 0 SOSs, and 6 indicators.
 Presolve time = 0.00 sec. (0.04 ticks)

Root node processing (before b&c):
 Real time = 0.02 sec. (0.12 ticks)
 Parallel b&c, 8 threads:
 Real time = 0.00 sec. (0.00 ticks)
 Sync time (average) = 0.00 sec.
 Wait time (average) = 0.00 sec.

Total (root+branch&cut) = 0.02 sec. (0.12 ticks)

CPXPARAM_Preprocessing_Fill	50
CPXPARAM_Preprocessing_Aggregator	50
CPXPARAM_Preprocessing_Dependency	1
CPXPARAM_TimeLimit	30
CPXPARAM_Preprocessing_Dual	1
CPXPARAM_Preprocessing_NumPass	50
CPXPARAM_Output_CloneLog	-1
CPXPARAM_Preprocessing_CoeffReduce	2
CPXPARAM_Preprocessing_BoundStrength	1
CPXPARAM_MIP_Strategy_HeuristicFreq	1000
CPXPARAM_Preprocessing_Relax	1
CPXPARAM_Emphasis_MIP	4

CPXPARAM_Preprocessing_Symmetry	1
CPXPARAM_MIP_Strategy_RINGHeur	50
CPXPARAM_MIP_Pool_RelGap	0.10000000000000001
CPXPARAM_MIP_Limits_Populate	40

Populate: phase I

Reduced MIP has 22 rows, 25 columns, and 60 nonzeros.
 Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
 Presolve time = 0.00 sec. (0.01 ticks)
 Warning: No solution found from 2 MIP starts.
 Retaining values of one MIP start for possible repair.
 Row 'c6' infeasible, all entries at implied bounds.
 Presolve time = 0.00 sec. (0.02 ticks)

Root node processing (before b&c):

Real time	=	0.00 sec. (0.04 ticks)
-----------	---	------------------------

Parallel b&c, 8 threads:

Real time	=	0.00 sec. (0.00 ticks)
Sync time (average)	=	0.00 sec.
Wait time (average)	=	0.00 sec.

Total (root+branch&cut) = 0.00 sec. (0.04 ticks)

CPXPARAM_Preprocessing_Fill	50
CPXPARAM_Preprocessing_Aggregator	50
CPXPARAM_Preprocessing_Dependency	1
CPXPARAM_TimeLimit	30
CPXPARAM_Preprocessing_Dual	1
CPXPARAM_Preprocessing_NumPass	50
CPXPARAM_Output_CloneLog	-1
CPXPARAM_Preprocessing_CoeffReduce	2
CPXPARAM_Preprocessing_BoundStrength	1
CPXPARAM_MIP_Strategy_HeuristicFreq	1000
CPXPARAM_Preprocessing_Relax	1
CPXPARAM_Emphasis_MIP	4
CPXPARAM_Preprocessing_Symmetry	1
CPXPARAM_MIP_Strategy_RINGHeur	50
CPXPARAM_MIP_Pool_RelGap	0.10000000000000001
CPXPARAM_MIP_Limits_Populate	40

Populate: phase I

Reduced MIP has 22 rows, 25 columns, and 60 nonzeros.
 Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
 Presolve time = 0.00 sec. (0.01 ticks)
 Warning: No solution found from 2 MIP starts.
 Retaining values of one MIP start for possible repair.
 Row 'c9' infeasible, all entries at implied bounds.
 Presolve time = 0.00 sec. (0.02 ticks)

Root node processing (before b&c):

Real time	=	0.00 sec. (0.04 ticks)
-----------	---	------------------------

Parallel b&c, 8 threads:

Real time	=	0.00 sec. (0.00 ticks)
Sync time (average)	=	0.00 sec.
Wait time (average)	=	0.00 sec.

Total (root+branch&cut) = 0.00 sec. (0.04 ticks)

CPXPARAM_Preprocessing_Fill	50
CPXPARAM_Preprocessing_Aggregator	50
CPXPARAM_Preprocessing_Dependency	1
CPXPARAM_TimeLimit	30
CPXPARAM_Preprocessing_Dual	1
CPXPARAM_Preprocessing_NumPass	50
CPXPARAM_Output_CloneLog	-1
CPXPARAM_Preprocessing_CoeffReduce	2
CPXPARAM_Preprocessing_BoundStrength	1
CPXPARAM_MIP_Strategy_HeuristicFreq	1000
CPXPARAM_Preprocessing_Relax	1
CPXPARAM_Emphasis_MIP	4
CPXPARAM_Preprocessing_Symmetry	1
CPXPARAM_MIP_Strategy_RINGHeur	50
CPXPARAM_MIP_Pool_RelGap	0.10000000000000001
CPXPARAM_MIP_Limits_Populate	40

```

Populate: phase I
Reduced MIP has 22 rows, 25 columns, and 60 nonzeros.
Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
Presolve time = 0.00 sec. (0.01 ticks)
Warning: No solution found from 2 MIP starts.
Retaining values of one MIP start for possible repair.
Presolve time = 0.00 sec. (0.00 ticks)

Root node processing (before b&c):
  Real time             =    0.02 sec. (0.02 ticks)
Parallel b&c, 8 threads:
  Real time             =    0.00 sec. (0.00 ticks)
  Sync time (average)   =    0.00 sec.
  Wait time (average)   =    0.00 sec.

Total (root+branch&cut) =    0.02 sec. (0.02 ticks)
CXPARAM_Preprocessing_Fill          50
CXPARAM_Preprocessing_Aggregator    50
CXPARAM_Preprocessing_Dependency     1
CXPARAM_TimeLimit                   30
CXPARAM_Preprocessing_Dual           1
CXPARAM_Preprocessing_NumPass        50
CXPARAM_Output_CloneLog              -1
CXPARAM_Preprocessing_CoeffReduce     2
CXPARAM_Preprocessing_BoundStrength   1
CXPARAM_MIP_Strategy_HeuristicFreq  1000
CXPARAM_Preprocessing_Relax           1
CXPARAM_Emphasis_MIP                 4
CXPARAM_Preprocessing_Symmetry        1
CXPARAM_MIP_Strategy_RINGHeur         50
CXPARAM_MIP_Pool_RelGap               0.10000000000000001
CXPARAM_MIP_Limits_Populate           40

```

```

Populate: phase I
Reduced MIP has 22 rows, 25 columns, and 60 nonzeros.
Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
Presolve time = 0.00 sec. (0.01 ticks)
Warning: No solution found from 2 MIP starts.
Retaining values of one MIP start for possible repair.
Presolve time = 0.00 sec. (0.00 ticks)

```

```

Root node processing (before b&c):
  Real time             =    0.00 sec. (0.02 ticks)
Parallel b&c, 8 threads:
  Real time             =    0.00 sec. (0.00 ticks)
  Sync time (average)   =    0.00 sec.
  Wait time (average)   =    0.00 sec.

Total (root+branch&cut) =    0.00 sec. (0.02 ticks)

```

Despite having tried to calculate 10 MCSs, only 6 exist for this Toy Example. The results are shown in the following piece of code:

```
MCSs{1}
```

```
ans =
    'r5'
    'r6'
```

```
MCSs{2}
```

```
ans =
    'r1'
    'r6'
```

```
MCSs{3}
```

```
ans =
    'r1'
    'r6'
```

```
MCSs{4}
```

```
ans =
    'r2'
    'r6'
```

MCSs(5)

```
ans =
    'r2'
    'r3'
    'r4'
```

MCSs(6)

```
ans =
    'r3'
    'r4'
    'r5'
```

We now translate these minimal reaction knockout strategies to the gene level following the gRrules. The following table shows the genetic interventions which must be fulfilled to accomplish the respective reaction knockout:

Minimal Cut Set	Gene knockout
r_2, r_6	g_2, g_4
r_2, r_5	g_2, g_5
r_2, r_6	g_2, g_6
r_2, r_5	g_5
	g_2, g_6
r_2, r_3, r_4	g_2, g_3, g_4
r_2, r_6, r_5	g_2, g_5, g_6, g_3
	g_2, g_3, g_4, g_6

In order to check if the gene knockouts that have to be carried out to perform the inhibition of the found MCSs are minimal, we will calculate gMCSs for the same toy example using the function `calculateGeneMCS()`.

First, we need to define the name of the model to create the gene knockout constraints matrix, G . The binary G matrix defines for each row the set of blocked reactions arising from the knockout of an irreducible subset of genes. The subset of genes associated with each row in G is interrelated and their simultaneous knockout is required to delete at least one of the reactions in the metabolic network. This matrix may be needed for other calculations. We will name here 'toy_example_gMCS' and again will calculate 10 gMCSs. The function will look for the G matrix in ['G_' model_name '.mat'] (here 'G_toy_example_gMCS.mat'). If this structure is not available, the function `buildGmatrix()` is called and the G matrix for the model under consideration generated and saved. In this case, the length of the largest gMCS calculated will be set to 6 (the number of genes).

```
model_name = 'toy_example_gMCS';
n_gMCS = 10;
max_len_gMCS = 6;
```

Next, we set the optional inputs. The maximum time for the calculation of each gMCS will be 30 seconds.

```
optional_inputs.timelimit = 30;
```

Note that, again, some more optional inputs may be set, as detailed in the documentation of the function. However, they are not needed for the calculation of the problem presented in this tutorial.

We will now proceed with the calculation of the gMCSs.

```
[gMCSs, gMCS_time] = calculateGeneMCS(model_name, model, n_gMCS, max_len_gMCS, optional_inputs);
```

```
G MATRIX - Summary
    'n_rxns_@_genes'      [1]
    'n_rxns_!_gene'      [4]
    'n_rxns_only_or'      [1]
    'n_rxns_only_and'     [1]
    'n_rxns_or_and'       [0]
    'n_rxns_total'        [7]
G MATRIX - STEP 1
G MATRIX - STEP 2
```

G MATRIX - STEP 3
G MATRIX - STEP 4

G MATRIX - Delete Repeats
G MATRIX - Check Relations
The G Matrix has been successfully calculated

CPXPARAM_Preprocessing_Fill	50
CPXPARAM_Preprocessing_Aggregator	50
CPXPARAM_Preprocessing_Dependency	1
CPXPARAM_TimeLimit	30
CPXPARAM_Preprocessing_Dual	1
CPXPARAM_Preprocessing_NumPass	50
CPXPARAM_Output_CloneLog	-1
CPXPARAM_Preprocessing_CoeffReduce	2
CPXPARAM_Preprocessing_BoundStrength	1
CPXPARAM_MIP_Strategy_HeuristicFreq	1000
CPXPARAM_Preprocessing_Relax	1
CPXPARAM_Emphasis_MIP	4
CPXPARAM_Preprocessing_Symmetry	1
CPXPARAM_MIP_Strategy_RINGHeur	50
CPXPARAM_MIP_Pool_RelGap	0.10000000000000001
CPXPARAM_MIP_Limits_Populate	40

Populate: phase I
Tried aggregator 2 times.
MIP Presolve eliminated 4 rows and 6 columns.
MIP Presolve modified 2 coefficients.
Aggregator did 3 substitutions.
Reduced MIP has 8 rows, 10 columns, and 19 nonzeros.
Reduced MIP has 5 binaries, 0 generals, 0 SOSs, and 5 indicators.
Presolve time = 0.00 sec. (0.03 ticks)
Probing fixed 5 vars, tightened 5 bounds.
Probing time = 0.00 sec. (0.00 ticks)
Tried aggregator 1 time.
MIP Presolve eliminated 8 rows and 10 columns.
All rows and columns eliminated.
Presolve time = 0.00 sec. (0.01 ticks)

Root node processing (before b&C):
Real time = 0.02 sec. (0.06 ticks)
Parallel b&C, 8 threads:
Real time = 0.00 sec. (0.00 ticks)
Sync time (average) = 0.00 sec.
Wait time (average) = 0.00 sec.

Total (root+branch&cut) = 0.02 sec. (0.06 ticks)

Populate: phase II
Tried aggregator 2 times.
MIP Presolve eliminated 4 rows and 6 columns.
MIP Presolve modified 2 coefficients.
Aggregator did 3 substitutions.
Reduced MIP has 8 rows, 10 columns, and 19 nonzeros.
Reduced MIP has 5 binaries, 0 generals, 0 SOSs, and 5 indicators.
Presolve time = 0.00 sec. (0.03 ticks)
Probing fixed 5 vars, tightened 5 bounds.
Probing time = 0.00 sec. (0.00 ticks)
Clique table members: 1.
MIP emphasis: hidden feasible solutions.
MIP search method: dynamic search.
Parallel mode: deterministic, using up to 8 threads.
Root relaxation solution time = 0.00 sec. (0.00 ticks)

	Nodes				Cuts/			
	Node	Left	Objective	Inf	Best Integer	Best Bound	ItCnt	Gap
*	0+	0			1.0000	0.0000		100.00%
	0	0	1.0000	0	1.0000	1.0000	0	0.00%
	0	0	1.0000	0	1.0000	1.0000	0	0.00%

Elapsed time = 0.02 sec. (0.15 ticks, tree = 0.01 MB, solutions = 1)

Root node processing (before b&C):
Real time = 0.00 sec. (0.00 ticks)

```

Parallel b&c, 8 threads:
  Real time      = 0.00 sec. (0.01 ticks)
  Sync time (average) = 0.00 sec.
  Wait time (average) = 0.00 sec.

Total (root+branch&cut) = 0.00 sec. (0.00 ticks)
CPXPARAM_Preprocessing_Fill      50
CPXPARAM_Preprocessing_Aggregator 50
CPXPARAM_Preprocessing_Dependency 1
CPXPARAM_TimeLimit              30
CPXPARAM_Preprocessing_Dual      1
CPXPARAM_Preprocessing_NumPass   50
CPXPARAM_Output_CloneLog        -1
CPXPARAM_Preprocessing_CoeffReduce 2
CPXPARAM_Preprocessing_BoundStrength 1
CPXPARAM_MIP_Strategy_HeuristicFreq 1000
CPXPARAM_Preprocessing_Relax     1
CPXPARAM_Emphasis_MIP            4
CPXPARAM_Preprocessing_Symmetry   1
CPXPARAM_MIP_Strategy_RINGHeur    50
CPXPARAM_MIP_Pool_RelGap          0.10000000000000001
CPXPARAM_MIP_Limits_Populate     40

```

```

Populate: phase I
Reduced MIP has 18 rows, 19 columns, and 45 nonzeros.
Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
Presolve time = 0.00 sec. (0.01 ticks)
Warning: No solution found from 1 MIP starts.
Retaining values of one MIP start for possible repair.
Row 'c3' infeasible, all entries at implied bounds.
Presolve time = 0.00 sec. (0.01 ticks)

```

```

Root node processing (before b&c):
  Real time      = 0.00 sec. (0.03 ticks)
Parallel b&c, 8 threads:
  Real time      = 0.00 sec. (0.00 ticks)
  Sync time (average) = 0.00 sec.
  Wait time (average) = 0.00 sec.

```

```

Total (root+branch&cut) = 0.00 sec. (0.03 ticks)
CPXPARAM_Preprocessing_Fill      50
CPXPARAM_Preprocessing_Aggregator 50
CPXPARAM_Preprocessing_Dependency 1
CPXPARAM_TimeLimit              30
CPXPARAM_Preprocessing_Dual      1
CPXPARAM_Preprocessing_NumPass   50
CPXPARAM_Output_CloneLog        -1
CPXPARAM_Preprocessing_CoeffReduce 2
CPXPARAM_Preprocessing_BoundStrength 1
CPXPARAM_MIP_Strategy_HeuristicFreq 1000
CPXPARAM_Preprocessing_Relax     1
CPXPARAM_Emphasis_MIP            4
CPXPARAM_Preprocessing_Symmetry   1
CPXPARAM_MIP_Strategy_RINGHeur    50
CPXPARAM_MIP_Pool_RelGap          0.10000000000000001
CPXPARAM_MIP_Limits_Populate     40

```

```

Populate: phase I
Reduced MIP has 18 rows, 19 columns, and 45 nonzeros.
Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
Presolve time = 0.00 sec. (0.01 ticks)
Warning: No solution found from 1 MIP starts.
Retaining values of one MIP start for possible repair.
Tried aggregator 2 times.
MIP Presolve eliminated 7 rows and 18 columns.
MIP Presolve modified 2 coefficients.
Aggregator did 3 substitutions.
Reduced MIP has 5 rows, 6 columns, and 10 nonzeros.
Reduced MIP has 3 binaries, 0 generals, 0 SOSs, and 3 indicators.
Presolve time = 0.00 sec. (0.03 ticks)
Probing fixed 3 vars, tightened 2 bounds.
Probing time = 0.00 sec. (0.00 ticks)

```

Tried aggregator 1 time.
MIP Presolve eliminated 5 rows and 6 columns.
All rows and columns eliminated.
Presolve time = 0.00 sec. (0.00 ticks)

Root node processing (before b&C):
Real time = 0.00 sec. (0.05 ticks)
Parallel b&C, 8 threads:
Real time = 0.00 sec. (0.00 ticks)
Sync time (average) = 0.00 sec.
Wait time (average) = 0.00 sec.
Total (root+branch&cut) = 0.00 sec. (0.05 ticks)

Populate: phase II
Tried aggregator 2 times.
MIP Presolve eliminated 7 rows and 10 columns.
MIP Presolve modified 2 coefficients.
Aggregator did 3 substitutions.
Reduced MIP has 5 rows, 6 columns, and 10 nonzeros.
Reduced MIP has 3 binaries, 0 generals, 0 SOSs, and 3 indicators.
Presolve time = 0.00 sec. (0.03 ticks)
Probing fixed 3 vars, tightened 2 bounds.
Probing time = 0.00 sec. (0.00 ticks)
Clique table members: 1.
MIP emphasis: hidden feasible solutions.
MIP search method: dynamic search.
Parallel mode: deterministic, using up to 8 threads.
Root relaxation solution time = 0.00 sec. (0.00 ticks)

	Nodes			Cuts/			
	Node	Left	Objective	IInf	Best Integer	Best Bound	ItCnt
*	0+	0			2.0000	1.0000	50.00%
	0	0	2.0000	0	2.0000	2.0000	0 0.00%
	0	0	2.0000	0	2.0000	2.0000	0 0.00%

Elapsed time = 0.02 sec. (0.12 ticks, tree = 0.01 MB, solutions = 1)

Root node processing (before b&C):
Real time = 0.00 sec. (0.06 ticks)
Parallel b&C, 8 threads:
Real time = 0.27 sec. (0.01 ticks)
Sync time (average) = 0.21 sec.
Wait time (average) = 0.00 sec.

Total (root+branch&cut) = 0.27 sec. (0.07 ticks)

CPXPARAM_Preprocessing_Fill	50
CPXPARAM_Preprocessing_Aggregator	50
CPXPARAM_Preprocessing_Dependency	1
CPXPARAM_TimeLimit	30
CPXPARAM_Preprocessing_Dual	1
CPXPARAM_Preprocessing_NumPass	50
CPXPARAM_Output_CloneLog	-1
CPXPARAM_Preprocessing_CoeffReduce	2
CPXPARAM_Preprocessing_BoundStrength	1
CPXPARAM_MIP_Strategy_HeuristicFreq	1000
CPXPARAM_Preprocessing_Relax	1
CPXPARAM_Emphasis_MIP	4
CPXPARAM_Preprocessing_Symmetry	1
CPXPARAM_MIP_Strategy_RINGHeur	50
CPXPARAM_MIP_Pool_RelGap	0.10000000000000001
CPXPARAM_MIP_Limits_Populate	40

Populate: phase I
Reduced MIP has 19 rows, 20 columns, and 48 nonzeros.
Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
Presolve time = 0.00 sec. (0.01 ticks)
Warning: No solution found from 1 MIP starts.
Retaining values of one MIP start for possible repair.
Row 'c3' infeasible, all entries at implied bounds.
Presolve time = 0.02 sec. (0.02 ticks)

Root node processing (before b&C):

```

Real time           = 0.02 sec. (0.04 ticks)
Parallel b&c, 8 threads:
Real time           = 0.00 sec. (0.00 ticks)
Sync time (average) = 0.00 sec.
Wait time (average) = 0.00 sec.
-----
Total (root+branch&cut) = 0.02 sec. (0.04 ticks)
CPXPARAM_Preprocessing_Fill          50
CPXPARAM_Preprocessing_Aggregator    50
CPXPARAM_Preprocessing_Dependency    1
CPXPARAM_TimeLimit                   30
CPXPARAM_Preprocessing_Dual          1
CPXPARAM_Preprocessing_NumPass       50
CPXPARAM_Output_CloneLog             -1
CPXPARAM_Preprocessing_CoeffReduce   2
CPXPARAM_Preprocessing_BoundStrength 1
CPXPARAM_MIP_Strategy_HeuristicFreq 1000
CPXPARAM_Preprocessing_Relax         1
CPXPARAM_Emphasis_MIP                4
CPXPARAM_Preprocessing_Symmetry      1
CPXPARAM_MIP_Strategy_RINGHeur       50
CPXPARAM_MIP_Pool_RelGap              0.10000000000000001
CPXPARAM_MIP_Limits_Populate         40

```

```

Populate: phase I
Reduced MIP has 19 rows, 20 columns, and 40 nonzeros.
Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
Presolve time = 0.00 sec. (0.01 ticks)
Warning: No solution found from 1 MIP starts.
Retaining values of one MIP start for possible repair.
Tried aggregator 1 time.
MIP Presolve eliminated 13 rows and 20 columns.
All rows and columns eliminated.
Presolve time = 0.00 sec. (0.03 ticks)

```

```

Root node processing (before b&c):
Real time           = 0.00 sec. (0.04 ticks)
Parallel b&c, 8 threads:
Real time           = 0.00 sec. (0.00 ticks)
Sync time (average) = 0.00 sec.
Wait time (average) = 0.00 sec.
-----
Total (root+branch&cut) = 0.00 sec. (0.04 ticks)

```

```

Populate: phase II
Tried aggregator 1 time.
MIP Presolve eliminated 13 rows and 20 columns.
All rows and columns eliminated.
Presolve time = 0.00 sec. (0.03 ticks)

```

```

Root node processing (before b&c):
Real time           = 0.00 sec. (0.03 ticks)
Parallel b&c, 8 threads:
Real time           = 0.00 sec. (0.00 ticks)
Sync time (average) = 0.00 sec.
Wait time (average) = 0.00 sec.
-----

```

```

Total (root+branch&cut) = 0.00 sec. (0.03 ticks)
CPXPARAM_Preprocessing_Fill          50
CPXPARAM_Preprocessing_Aggregator    50
CPXPARAM_Preprocessing_Dependency    1
CPXPARAM_TimeLimit                   30
CPXPARAM_Preprocessing_Dual          1
CPXPARAM_Preprocessing_NumPass       50
CPXPARAM_Output_CloneLog             -1
CPXPARAM_Preprocessing_CoeffReduce   2
CPXPARAM_Preprocessing_BoundStrength 1
CPXPARAM_MIP_Strategy_HeuristicFreq 1000
CPXPARAM_Preprocessing_Relax         1
CPXPARAM_Emphasis_MIP                4
CPXPARAM_Preprocessing_Symmetry      1
CPXPARAM_MIP_Strategy_RINGHeur       50
CPXPARAM_MIP_Pool_RelGap              0.10000000000000001
CPXPARAM_MIP_Limits_Populate         40

```

Populate: phase I
 Reduced MIP has 20 rows, 21 columns, and 52 nonzeros.
 Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
 Presolve time = 0.00 sec. (0.01 ticks)
 Warning: No solution found from 1 MIP starts.
 Retaining values of one MIP start for possible repair.
 Row 'c3' infeasible, all entries at implied bounds.
 Presolve time = 0.00 sec. (0.02 ticks)

Root node processing (before b&C):
 Real time = 0.00 sec. (0.04 ticks)
 Parallel b&C, 8 threads:
 Real time = 0.00 sec. (0.00 ticks)
 Sync time (average) = 0.00 sec.
 Wait time (average) = 0.00 sec.
 Total (root+branch&cut) = 0.00 sec. (0.04 ticks)
 CPXPARAM_Preprocessing_Fill 50
 CPXPARAM_Preprocessing_Aggregator 50
 CPXPARAM_Preprocessing_Dependency 1
 CPXPARAM_TimeLimit 30
 CPXPARAM_Preprocessing_Dual 1
 CPXPARAM_Preprocessing_NumPass 50
 CPXPARAM_Output_CloneLog -1
 CPXPARAM_Preprocessing_CoeffReduce 2
 CPXPARAM_Preprocessing_BoundStrength 1
 CPXPARAM_MIP_Strategy_HeuristicFreq 1000
 CPXPARAM_Preprocessing_Relax 1
 CPXPARAM_Emphasis_MIP 4
 CPXPARAM_Preprocessing_Symmetry 1
 CPXPARAM_MIP_Strategy_RINGHeur 50
 CPXPARAM_MIP_Pool_RelGap 0.10000000000000001
 CPXPARAM_MIP_Limits_Populate 40

Populate: phase I
 Reduced MIP has 20 rows, 21 columns, and 52 nonzeros.
 Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
 Presolve time = 0.00 sec. (0.01 ticks)
 Warning: No solution found from 1 MIP starts.
 Retaining values of one MIP start for possible repair.
 Row 'c10' infeasible, all entries at implied bounds.
 Presolve time = 0.00 sec. (0.02 ticks)

Root node processing (before b&C):
 Real time = 0.00 sec. (0.03 ticks)
 Parallel b&C, 8 threads:
 Real time = 0.00 sec. (0.00 ticks)
 Sync time (average) = 0.00 sec.
 Wait time (average) = 0.00 sec.
 Total (root+branch&cut) = 0.00 sec. (0.03 ticks)
 CPXPARAM_Preprocessing_Fill 50
 CPXPARAM_Preprocessing_Aggregator 50
 CPXPARAM_Preprocessing_Dependency 1
 CPXPARAM_TimeLimit 30
 CPXPARAM_Preprocessing_Dual 1
 CPXPARAM_Preprocessing_NumPass 50
 CPXPARAM_Output_CloneLog -1
 CPXPARAM_Preprocessing_CoeffReduce 2
 CPXPARAM_Preprocessing_BoundStrength 1
 CPXPARAM_MIP_Strategy_HeuristicFreq 1000
 CPXPARAM_Preprocessing_Relax 1
 CPXPARAM_Emphasis_MIP 4
 CPXPARAM_Preprocessing_Symmetry 1
 CPXPARAM_MIP_Strategy_RINGHeur 50
 CPXPARAM_MIP_Pool_RelGap 0.10000000000000001
 CPXPARAM_MIP_Limits_Populate 40

Populate: phase I
 Reduced MIP has 20 rows, 21 columns, and 52 nonzeros.

Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
 Presolve time = 0.00 sec. (0.01 ticks)
 Warning: No solution found from 1 MIP starts.
 Retaining values of one MIP start for possible repair.
 Presolve time = 0.00 sec. (0.00 ticks)

Root node processing (before b&C):
 Real time = 0.02 sec. (0.02 ticks)
 Parallel b&C, 8 threads:
 Real time = 0.00 sec. (0.00 ticks)
 Sync time (average) = 0.00 sec.
 Wait time (average) = 0.00 sec.

Total (root+branch&cut) = 0.02 sec. (0.02 ticks)

CPXPARAM_Preprocessing_Fill	50
CPXPARAM_Preprocessing_Aggregator	50
CPXPARAM_Preprocessing_Dependency	1
CPXPARAM_TimeLimit	30
CPXPARAM_Preprocessing_Dual	1
CPXPARAM_Preprocessing_NumPass	50
CPXPARAM_Output_CloneLog	-1
CPXPARAM_Preprocessing_CoeffReduce	2
CPXPARAM_Preprocessing_BoundStrength	1
CPXPARAM_MIP_Strategy_HeuristicFreq	1000
CPXPARAM_Preprocessing_Relax	1
CPXPARAM_Emphasis_MIP	4
CPXPARAM_Preprocessing_Symmetry	1
CPXPARAM_MIP_Strategy_RINGHeur	50
CPXPARAM_MIP_Pool_RelGap	0.10000000000000001
CPXPARAM_MIP_Limits_Populate	40

Populate: phase I
 Reduced MIP has 20 rows, 21 columns, and 52 nonzeros.
 Reduced MIP has 7 binaries, 0 generals, 0 SOSs, and 7 indicators.
 Presolve time = 0.00 sec. (0.01 ticks)
 Warning: No solution found from 1 MIP starts.
 Retaining values of one MIP start for possible repair.
 Presolve time = 0.00 sec. (0.00 ticks)

Root node processing (before b&C):
 Real time = 0.00 sec. (0.02 ticks)
 Parallel b&C, 8 threads:
 Real time = 0.00 sec. (0.00 ticks)
 Sync time (average) = 0.00 sec.
 Wait time (average) = 0.00 sec.

Total (root+branch&cut) = 0.00 sec. (0.02 ticks)

In the same way as with MCSs, 3 gMCSs have been calculated in total.

```
gMCSs(1)
```

```
ans = 'g5'
```

```
gMCSs(2)
```

```
ans =  
'g1'  
'g4'
```

```
gMCSs(3)
```

```
ans =  
'g2'  
'g3'  
'g4'
```

As shown in the previous table, calculating MCSs would result in 8 different genetic intervention strategies even when, as we have just demonstrated, only 3 minimal genetic interventions exist. Moving on to gMCSs seems, therefore, a more efficient strategy to calculate minimal gene knockout strategies.

2. gMCSs in large metabolic networks (20 min ~ 1 hour)

The algorithm presented in this tutorial is able to calculate intervention strategies in large metabolic networks. In addition, it is sufficiently flexible to calculate gMCSs involving a particular gene knockout. Interesting results regarding this issue can be found in Apadlaza et al., 2017[a]².

We are now going to calculate 6 gMCSs for the human metabolic model Recon2.v04⁴ involving gene RIFM1 (Entrez ID: 6240). To do so, the following piece of code has to be executed.

First, we are going to load the metabolic model.

```
global CBTDIR
load([CBTDIR filesep 'test' filesep 'models' filesep 'mat' filesep 'Recon2.v04.mat']);
```

Next, in the same way as in the toy example, we will proceed to set the name of the model ('Recon2'), the number of gMCSs to be calculated (6), the length of the largest gMCS we want to calculate (10) and the optional input variables. Regarding the latter, the maximum time for the calculation of gMCSs will be set to 2 minutes (120 seconds), the KO will be '6240', namely the Entrez ID of RIFM1. In this case, we will also have to set the "separate_transcript" field to '.', because, if we do not, the calculation of gMCSs will be done at the transcript level as a consequence of the usage of the aforementioned character in Recon2.v04 to differentiate the transcripts of the same gene.

```
model_name = 'Recon2';
n_gMCS = 6;
max_len_gMCS = 10;
optional_inputs.KO = '6240';
optional_inputs.separate_transcript = '.';
optional_inputs.timelimit = 2*60;
```

Finally, we will calculate the gMCSs. Turning the parallel pool on is recommended if the G matrix has not been calculated yet.

```
% parpool;
[gMCSs, gMCS_time] = calculateGeneMCS(model_name, modelID04, n_gMCS, max_len_gMCS, optional_inputs);
```

```
G MATRIX - Summary
'n_rxns_0_genes' [2619]
'n_rxns_1_gene' [2917]
'n_rxns_only_or' [1426]
'n_rxns_only_and' [ 231]
'n_rxns_or_and' [ 247]
'n_rxns_total' [7440]

G MATRIX - STEP 1
G MATRIX - STEP 2
G MATRIX - STEP 3
Calculating Networks for GPR rules...
156 of 247 rxns
155 of 247 rxns
84 of 247 rxns
83 of 247 rxns
125 of 247 rxns
124 of 247 rxns
42 of 247 rxns
41 of 247 rxns
154 of 247 rxns
153 of 247 rxns
152 of 247 rxns
151 of 247 rxns
158 of 247 rxns
149 of 247 rxns
148 of 247 rxns
147 of 247 rxns
146 of 247 rxns
145 of 247 rxns
144 of 247 rxns
143 of 247 rxns
142 of 247 rxns
141 of 247 rxns
140 of 247 rxns
139 of 247 rxns
138 of 247 rxns
137 of 247 rxns
136 of 247 rxns
135 of 247 rxns
```

134 of 247 rows
133 of 247 rows
132 of 247 rows
131 of 247 rows
130 of 247 rows
129 of 247 rows
128 of 247 rows
127 of 247 rows
126 of 247 rows
82 of 247 rows
81 of 247 rows
80 of 247 rows
79 of 247 rows
78 of 247 rows
77 of 247 rows
76 of 247 rows
75 of 247 rows
74 of 247 rows
73 of 247 rows
72 of 247 rows
71 of 247 rows
70 of 247 rows
69 of 247 rows
68 of 247 rows
67 of 247 rows
66 of 247 rows
65 of 247 rows
64 of 247 rows
63 of 247 rows
123 of 247 rows
122 of 247 rows
121 of 247 rows
120 of 247 rows
119 of 247 rows
118 of 247 rows
117 of 247 rows
116 of 247 rows
115 of 247 rows
114 of 247 rows
113 of 247 rows
112 of 247 rows
111 of 247 rows
110 of 247 rows
40 of 247 rows
39 of 247 rows
38 of 247 rows
37 of 247 rows
36 of 247 rows
35 of 247 rows
34 of 247 rows
33 of 247 rows
32 of 247 rows
31 of 247 rows
30 of 247 rows
29 of 247 rows
28 of 247 rows
27 of 247 rows
26 of 247 rows
25 of 247 rows
24 of 247 rows
62 of 247 rows
61 of 247 rows
60 of 247 rows
59 of 247 rows
58 of 247 rows
57 of 247 rows
56 of 247 rows
55 of 247 rows
54 of 247 rows
53 of 247 rows
52 of 247 rows
51 of 247 rows
50 of 247 rows

49 of 247 rows
48 of 247 rows
47 of 247 rows
46 of 247 rows
45 of 247 rows
44 of 247 rows
43 of 247 rows
189 of 247 rows
188 of 247 rows
187 of 247 rows
186 of 247 rows
185 of 247 rows
184 of 247 rows
183 of 247 rows
182 of 247 rows
181 of 247 rows
180 of 247 rows
99 of 247 rows
98 of 247 rows
97 of 247 rows
96 of 247 rows
95 of 247 rows
94 of 247 rows
93 of 247 rows
92 of 247 rows
91 of 247 rows
90 of 247 rows
89 of 247 rows
88 of 247 rows
87 of 247 rows
86 of 247 rows
85 of 247 rows
179 of 247 rows
178 of 247 rows
177 of 247 rows
176 of 247 rows
175 of 247 rows
174 of 247 rows
173 of 247 rows
172 of 247 rows
171 of 247 rows
170 of 247 rows
169 of 247 rows
168 of 247 rows
167 of 247 rows
166 of 247 rows
165 of 247 rows
164 of 247 rows
163 of 247 rows
162 of 247 rows
161 of 247 rows
160 of 247 rows
159 of 247 rows
158 of 247 rows
157 of 247 rows
156 of 247 rows
155 of 247 rows
154 of 247 rows
153 of 247 rows
152 of 247 rows
151 of 247 rows
150 of 247 rows
149 of 247 rows
148 of 247 rows
147 of 247 rows
146 of 247 rows
145 of 247 rows
144 of 247 rows
143 of 247 rows
142 of 247 rows
141 of 247 rows
140 of 247 rows

[illegible]

1 of 247 rows
G MATRIX - STEP 4

%	[%	[%	[
G MATRIX - Delete Repeats					
G MATRIX - Check Relations					
The G Matrix has been successfully calculated					
CPXPARAM_Preprocessing_Fill		50			
CPXPARAM_Preprocessing_Aggregator		50			
CPXPARAM_Preprocessing_Dependency		1			
CPXPARAM_TimeLimit		120			
CPXPARAM_Preprocessing_Dual		1			
CPXPARAM_Preprocessing_NumPass		50			
CPXPARAM_Output_CloneLog		-1			
CPXPARAM_Preprocessing_CoeffReduce		2			
CPXPARAM_Preprocessing_BoundStrength		1			
CPXPARAM_MIP_Strategy_HeuristicFreq		1000			
CPXPARAM_Preprocessing_Relax		1			
CPXPARAM_Emphasis_MIP		4			
CPXPARAM_Preprocessing_Symmetry		1			
CPXPARAM_MIP_Strategy_RINGHeur		50			
CPXPARAM_MIP_Pool_RelGap		0.10000000000000001			
CPXPARAM_MIP_Limits_Populate		40			

Populate: phase I
Tried aggregator 12 times.
MIP Presolve eliminated 9344 rows and 10409 columns.
MIP Presolve modified 9523 coefficients.
Aggregator did 3520 substitutions.
Reduced MIP has 7520 rows, 7817 columns, and 46898 nonzeros.

The results obtained are the following:

gPCSs{1}

```
ans =
'2987'
'6248'
```

gPCSs{2}

```
ans =
'1716'
'6248'
'7296'
```

gPCSs{3}

```
ans =
'1716'
'58484'
'6248'
```

gPCSs{4}

```
ans =
'1633'
'1635'
'6248'
'7296'
```

gPCSs{5}

```
ans =
'26289'
'51727'
'6248'
'7296'
```

gPCSs{6}

'2766'
'3251'
'51292'
'6248'
'8833'

6 gMCSs have been calculated involving 2, 3, 3, 4, 4 and 5 genes, respectively. It is important to note that no more gMCSs have been found as a consequence of setting the number of gMCSs to be calculated to 6. If we increase the aforementioned input, more gMCSs involving IRM1 will be calculated. It is important to note that the calculation of a minimal intervention strategy involving 5 genes with an exhaustive combinatorial strategy is actually infeasible.

TIMING

1. Equipment Setup: ~25 sec.
2. Toy Example: ~5 sec.
3. gMCSs in large metabolic networks: ~5 min.

Note that both `calculateMCS()` and `calculateGeneMCS()` functions return `MCS_time` and `gMCS_time`, respectively, which contain the timing for all the solving steps.

REFERENCES

1. von Kamp, A. & Klamt, S. Enumeration of smallest intervention strategies in genome-scale metabolic networks. *PLoS computational biology*, 10(1), e1003378 (2014).
2. Apolaza, I., et al. An in-silico approach to predict and exploit synthetic lethality in cancer metabolism. *Nature Communications*, 8(1), 459 (2017) (a)).
3. Apolaza, I., José-Eneriz, E. S., Aguirre, X., Prósper, F. & Planas, E. J. COBRA methods and metabolic drug targets in cancer. *Molecular & Cellular Oncology*, (just-accepted), 00-00 (2017) (b)).
4. Thiele, I., et al. A community-driven global reconstruction of human metabolism. *Nature biotechnology*, 31(5), 419-425 (2013).