

Sending the First API Request

Step-by-Step Guide to Sending a GET Request in Postman

Hands-On	4
Scenario	Sending the First API Request
Tool	Postman (Desktop or Web)
Method	GET
Endpoint URL	https://simple-tool-rental-api.glitch.me/status
Duration	15 minutes
Prerequisite	Workspace and Collection already created

Objective

The objective of this assignment is to send the first API request from Postman by creating a new **GET** request inside an existing collection, configuring the endpoint URL, and clicking **Send** to receive the server's response. This builds the foundation for all later API testing tasks — status code validation, header inspection, and response body assertions.

About the Target API

The endpoint used in this assignment is the **Simple Tool Rental API**, a free public API hosted on Glitch. The **/status** endpoint is a lightweight health-check endpoint that returns a small JSON payload indicating whether the API service is up and running.

Steps to Send the First API Request

1 Open Postman

Launch the **Postman** application on the desktop, or open the web version by visiting <https://web.postman.co/>.

Sign in with the registered Postman account if not already logged in.

2 Go to the Right Workspace

Click the **Workspaces** dropdown in the upper-left corner.

Select the workspace that was created in the previous assignment (for example, *Bitcoin API Tests* or any custom-named workspace).

The selected workspace becomes active and its name appears in the Postman header.

3 Go to the Right Collection

In the left sidebar, click the **Collections** tab.

Locate and click the collection created earlier (for example, *Bitcoin Rate API Tests* or *Tool Rental APIs*).

The collection expands to show its contents (initially empty).

4 Add a New Request

Click the **Add a request** link displayed inside the empty collection.

Alternatively, click the three-dot (...) menu next to the collection name and select **Add request** from the dropdown.

5 New Tab with the Empty Request Opens

Postman opens a new request tab in the central panel.

By default it is named *Untitled Request*, with the HTTP method set to **GET** and an empty URL field.

6 Give the Request a Meaningful Name

Click on *Untitled Request* at the top of the tab (or right-click the request in the sidebar and choose **Rename**).

Enter a clear, descriptive name such as *GET Tool Rental API Status* or *API Health Check*.

Press **Enter** (or save with **Ctrl + S** / **Cmd + S**) to apply the new name.

7 Set the HTTP Method to GET

On the request line, click the **method dropdown** (located to the left of the URL field).

Select **GET** from the list of HTTP methods. **GET** is used to retrieve data from the server without modifying any resource.

8 Enter the Request URL

Click into the URL field on the request line.

Type or paste the following endpoint URL:

<https://simple-tool-rental-api.glitch.me/status>

No query parameters, headers, or body are required for this request.

9 Click the “Send” Button

Click the blue **Send** button on the right side of the URL bar.

Postman dispatches the GET request to the API and displays the server's response in the lower **Response** panel.

The response panel shows three key pieces of information:

- **Status** — an HTTP status code such as **200 OK** (success).
- **Time** — how long the request took to complete.
- **Size** — the size of the response payload.

The **Body** tab below displays the JSON content returned by the API, indicating that the API service is up and reachable.

Expected Response

On a successful request, the response panel will show a status code of **200 OK** along with a small JSON body similar to the following:

```
{
  "app": "Simple Tool Rental API",
  "status": "up"
}
```

Verification

To confirm the first API request was sent successfully:

- 1 The response status indicator should display **200 OK** in green.
- 2 The **Body** tab of the response panel should contain a JSON document with a *status* field.
- 3 The newly created request should appear inside the chosen collection in the left sidebar with the assigned name.
- 4 Save the request with **Ctrl + S** (or **Cmd + S** on Mac) so it persists inside the collection.

Conclusion

The first API request has been successfully created, configured and sent from Postman. The Simple Tool Rental API responded with a healthy **200 OK** status, confirming that Postman is correctly set up

and able to communicate with public APIs. This forms the foundation for the upcoming assignments that involve sending POST/PUT/DELETE requests, writing test scripts, and chaining requests in collections.

Tip: Always save (Ctrl + S / Cmd + S) requests after sending them so they persist inside the collection. Unsaved requests appear with an orange dot next to the request name.