Project Documentation

MicroGoals – Secure Goal Management Backend API

1.Instroduction

Project Title : Microgoal
Team ID:
Team leader : R.Sai Sharan & 24bca42acas@gmail.com

Team members:

1.Irfana Banu.H & 24bca14acas@gmail.com
2.Reena.S & 24bca41acas@gmail.com
3.Sakthi Sree.R & 24bca43acas@gmail.com

Project Overview

MicroGoals is a secure backend RESTful API developed using Node.js, Express.js, and MongoDB. It enables users to register, log in, and manage their personal goals through CRUD operations. The system uses JWT authentication and middleware to ensure data security and user-specific access control.

The System includs

- ***User Registration & Login***
- ***JWT-based Authentication***
- ***CRUD Operations for Goals***
- ***Protected Routes***
- ***Centralized Error Handling***

The main objective is to provide a secure and scalable backend system for digital goal management.

Project Instruction

- **The project follows REST API principles.**
- **Authentication is handled using JWT.**
- **MongoDB is used as the database.**
- **APIs are tested using Thunder Client.**
- **The project follows MVC architecture.**

Pre-requisites

- ***Node.js (v18 or higher)***
- ***Express.js***
- ***MongoDB (Local / Atlas)***
- ***VS Code***
- ***Thunder Client (Extension)***

Basic knowledge of JavaScript & REST APIs

Project Architecture Image (Text Representation)



PROJECT ARCHITECTURE

PROJECT ARCHITECTURE

- Runtime: Node.js
- Framework: Express.js
- Database: MongoDB
- Architecture Pattern: MVC
- Authentication: JWT

ER DIAGRAM

Entities:
1.User

- ***_id***
- ***name***
- ***email***
- ***password***

2.Goal

- ***_id***
- ***title***
- ***completed***
- ***userId (Reference to User)***

Relationship:
One User → Many Goals

User entities link to multiple Goal entities via foreign key



FEATURES

- ***User Registration***
- ***Secure Login with JWT***
- ***Create Goal***
- ***Update Goal***
- ***Delete Goal***
- ***View User-specific Goals***
- ***Protected Routes***
- ***Centralized Error Handling***

ROLES AND RESPONSIBILITIES

Role	Responsibility
User	Register, Login, Manage Goals
Developer	API Development & Testing

USERS FLOW

User registers

User logs in

JWT token generated

User sends token in header

Access protected routes

Perform CRUD operations



PROJECT SETUP AND CONFIGURATION

🔹 Folder Structure

```
MicroGoals/
├──── middleware/
│   ├──── authMiddleware.js
│   └──── errorMiddleware.js
├────Schema/
├────User.js
├────GoalSchema.js
├──── models/
│   ├──── userModel.js
│   └──── goalModel.js
```

```
│
├──── routes/
│   ├──── authRoutes.js
│   └──── goalRoutes.js
│
├──── .env
├──── Index.js
└──── package.json
```


MicroProjectApi
Backend
Middlewares
authMiddleware.js
errormiddleware.js
Model
GoalModel.js
UserModel.js
node_modules
Router
AuthRouter.js
GoalRouter.js
Schema
GoalSchema.js
User.js
utills
genratetoken.js
validation
userValidation.js
.env
.gitignore
Index.js
package-lock.json
package.json
Frontend
Portfolio
PracticeBackend
Project_simon says
OUTLINE

🔹 ***Project Setup***

1.npm init -y

Install dependencies:

npm install express mongoose jsonwebtoken bcryptjs dotenv

2.Start server:

3.node server.js

BACKEND DEVELOPMENT:

- ***Created Express Server***

An Express server was set up to handle API requests, connect routes, and enable JSON parsing for backend operations

```js
Index.js
require("dotenv").config();
const express = require("express");
const app = express();
const mongoose = require("mongoose");
const cors = require("cors");
app.use(cors());
const errormiddleware = require("./Middlewares/errormiddleware");
app.use(express.urlencoded({ extended: true }));
const bodyParser = require("body-parser");
app.use(express.json());
const PORT = process.env.PORT;
const Mongo_Url = process.env.MONGO_URL;
const authRoute = require("./Router/AuthRouter");
const GoalRouter = require("./Router/GoalRouter");

//mongoDB connection
mongoose
  .connect(Mongo_Url)
  .then(() => console.log("MongoDB Connected"))
  .catch((err) => console.log(err));

//route
app.use("/", authRoute);
app.use("/", GoalRouter);

app.use(errormiddleware);
app.listen(PORT, () => {
  console.log("Server running on port 8000");
});
```

- ***Connected MongoDB***

For Connection with MongoDB:-

```js
//mongoDB connection
mongoose
  .connect(Mongo_Url)
  .then(() => console.log("MongoDB Connected"))
  .catch((err) => console.log(err));
```

- ***Implemented Authentication APIs***

User registration and login APIs were created with password hashing and JWT token generation for secure authentication.

```
Index.js    AuthRouter.js
const express = require("express");
const router = express.Router();
const bcrypt = require("bcryptjs");
const jwt = require("jsonwebtoken");
const userValidation = require("../validation/userValidation");
const userModel = require("../Model/UserModel");
const genrateToken = require("../utills/genratetoken");
router.post("/signup", async (req, res, next) => {
  try {
    const { error } = userValidation.validate(req.body);
    if (error) {
      return res.status(400).json({
        success: false,
        message: "enter the data correctly",
      });
    }
    const { name, email, password } = req.body;
    const exist = await userModel.findOne({ email });
    if (exist) {
      return res.status(400).json({ message: "User already exists" });
    }
    const hashpassword = await bcrypt.hash(password, 10);
    const user = new userModel({
      name: name,
      email: email,
      password: hashpassword,
    });
    await user.save();
    const token = genrateToken(user._id);
    res.status(200).json({
      success: true,
      message: "user is created",
      token: token,
      data: user,
    });
  } catch (err) {
    return next(err);
  }
});

router.post("/login", async (req, res, next) => {
  try {
    const { email, password } = req.body;
    const user = await userModel.findOne({ email });

    if (!user) {
      const err = new Error("user not found");
      err.status = 400;
      return next(err);
    }

    const isMatch = await bcrypt.compare(password, user.password);
    if (!isMatch) {
      const err = new Error("Wrong Password");
      err.status = 400;
      return next(err);
    }
    const token = genrateToken(user._id);
    res.status(200).json({
      success: true,
      message: "login succesfully",
      token: token,
      data: user,
    });
  } catch (error) {
    return next(error);
  }
});
```

- ***Implemented Goal CRUD APIs***

Goal CRUD APIs were implemented to allow authenticated users to perform full Create, Read, Update, and Delete operations on their personal goals. These APIs follow

RESTful architecture principles and are designed to ensure secure and structured data management.

The Create API enables users to add new goals to the database. Each goal is associated with a specific user using a userId reference, ensuring user-specific data isolation.

The Read API allows authenticated users to retrieve only their own goals from the database. Data filtering is applied using the authenticated user's ID to prevent unauthorized data access.

The Update API enables users to modify existing goals. Proper validation checks ensure that only the owner of the goal can update it. The Delete API allows users to permanently remove their goals from the system. Secure route protection ensures that users cannot delete goals belonging to others.

All CRUD routes are protected using Authentication Middleware, which verifies the JWT token before granting access. If the token is missing or invalid, the system returns a 401 Unauthorized error.

Additionally, Error Middleware is implemented to handle runtime and validation errors centrally. It captures exceptions from CRUD operations and returns consistent JSON responses with appropriate HTTP status codes such as 200, 201, 400, 401, and 404.

This structured implementation ensures secure data handling, proper authorization, and reliable API behavior across all goal management operations

```
const express = require("express");
const router = express.Router();
const goalModel = require("../Model/GoalModel");
const authmiddleware = require("../Middlewares/authMiddleware");

router.post("/create", authmiddleware, async (req, res, next) => {
 try {

const { title } = req.body;
 const goal = new goalModel({
 title: title,
 user: req.user,
 });
 await goal.save();
 res.status(200).json({
 success: true,
 data: goal,
 });
 } catch (err) {
 return next(err);
 }
});

router.get("/:id", authmiddleware, async (req, res, next) => {
 try {
 const id = req.params.id;
 const data = await goalModel.findOne({
 _id: id,
 user: req.user,
 });
 res.status(200).json({
```

```
success: true,
 data: data,
 });
 } catch (error) {
 return next(error);
 }
});

router.put("/:id", authmiddleware, async (req, res, next) => {
 try {
 const goal = await goalModel.findOneAndUpdate(
 { _id: req.params.id, user: req.user },
 { completed: req.body.completed },
 { new: true },
 );
 res.status(200).json({
 success: true,
 message: "the goal is completed",
 });
 } catch (error) {
 return next(error);
 }
});

router.delete("/:id", authmiddleware, async (req, res, next) => {
 try {
 await goalModel.findOneAndDelete({
 _id: req.params.id,
 });

 res.status(200).json({ message: "Goal deleted" });
 } catch (error) {
 next(error);
 }
});

module.exports = router;
```

- Added Auth Middleware
- Auth middleware was implemented to verify JWT tokens and secure protected routes from unauthorized access.

JS Index.js JS authMiddleware.js

```javascript
const jwt = require("jsonwebtoken");
require("dotenv").config();

const authmiddleware = (req, res, next) => {
  try {
    const header = req.headers.authorization;

    if (!header) {
      return res.status(401).json({ message: "No token" });
    }

    const token = header.split(" ")[1];

    const decoded = jwt.verify(token, process.env.SECRET_KEY);

    req.user = decoded.userId;

    next();
  } catch (error) {
    return res.status(401).json({ message: "Invalid token" });
  }
};
module.exports = authmiddleware;
```

- Added Error Middleware

An error middleware was added to handle application errors centrally and return proper status codes and messages.

```js
errormiddleware.js
const errormiddleware = (err, req, res, next) => {
  console.log(err);
  const status = err.status.code || 500;
  const message = err.message || "server error";
  res.status(status).json({
    success: false,
    message: message,
  });
};

module.exports = errormiddleware;
```

D***ATABASE DEVELOPMENT***

CONFIGURE MongoDB

- Use MongoDB Atlas or Local MongoDB
- Store connection string in .env

CREATE DATABASE CONNECTION

Index.js file:

- Use mongoose.connect()

```
//mongoDB connection
mongoose
  .connect(Mongo_Url)
  .then(() => console.log("MongoDB Connected"))
  .catch((err) => console.log(err));
```

- Handle connection errors

CREATE SCHEMA AND MODELS

User Schema

The User Schema defines the user data structure with name, email (unique), and hashed password fields.

```
JS User.js

const mongoose = require("mongoose");
const Schema = mongoose.Schema;
const userSchema = new Schema({
  name: {
    type: String,
    required: true,
  },
  email: {
    type: String,
    unique: true,
  },
  password: {
    type: String,
    required: true,
  },
});
module.exports=userSchema;
```

Goal Schema (with userId reference)

The Goal Schema stores goal details and includes a user Id reference to associate each goal with a specific user.

JS GoalSchema.js

```javascript
const mongoose = require("mongoose");
const Schema = mongoose.Schema;

const goalSchema = new Schema({
  title: {
    type: String,
    required: true,
    trim: true,
  },

  completed: {
    type: Boolean,
    default: false,
  },

  user: {
    type: mongoose.Schema.Types.ObjectId,
    ref: "User",
    required: true,
  },
});

module.exports=goalSchema;
```

PROJECT EXECUTION

Project Execution Steps

- Start MongoDB
- Run server
- Test APIs in Thunder Client
- Register User
- Login and get JWT
- Perform CRUD operations
- Project Output Screenshots

● Successful User Registration(Signup/Login)
● In this Api call the user register or login and token was genrated



- JWT Token Response

After successful login user the api generate the token and these token was sent with every request to every api



- Goal Created Successfully
- After the login and token is generated the user give post request to api for creating there goals and goal was save in MongoDB which was the database



- Protected Route Working
- If the user does not have token which was generated by backend api then he cannot access the api so Route are protectedZ



Project Demo Video

Record video showing:

- Registration
- Login
- Token usage
- CRUD operations
- Error handling

video:Microgoal video
Drive:-MicroGoal(Backend)

THANK YOU