Practical 1

Aim: Linux System Administration and File Management for Marketing Analytics Team.


Problem definition:
Scenario: You have recently joined DataAnalytics Inc. as a Linux System Administrator. The company runs its analytics platform on Linux servers where project data, reports, scripts, and user accounts must be managed efficiently.
Your manager has assigned you the responsibility of setting up the project environment, managing files and directories, monitoring system resources, securing data, and creating backups for the Marketing Analytics team.

GitHub Link:


https://github.com/24dit061-Satyarajsinh/24DIT061_CSUE301_BDA

Observation / Output
Task :

1. Identify the current user.




2. Find the current working directory.



3. Display system information.



4. Check system uptime and date.




5. Create a directory named MarketingAnalytics.

```
Tue Aug  4 23:39:17 IST 2026
┌──[user@parrot]─[~]
└─$mkdir MarketingAnalytics
┌──[user@parrot]─[~]
└─$cd MarketingAnalytics
┌──[user@parrot]─[~/MarketingAnalytics]
└─$
```

6. Create subdirectories: RawData, ProcessedData, Reports.

```
┌──[user@parrot]─[~/MarketingAnalytics]
└─$mkdir RawData ProcessedData Reports Backup
┌──[user@parrot]─[~/MarketingAnalytics]
└─$
```



7. Create data and report files.

```
└─$mkdir RawData ProcessedData Reports Ba
┌──[user@parrot]─[~/MarketingAnalytics]
└─$touch RawData/sales.txt
┌──[user@parrot]─[~/MarketingAnalytics]
└─$touch RawData/customers.csv
┌──[user@parrot]─[~/MarketingAnalytics]
└─$touch Reports/report1.txt
┌──[user@parrot]─[~/MarketingAnalytics]
└─$touch Reports/report2.txt
┌──[user@parrot]─[~/MarketingAnalytics]
└─$
```

8. Add sample content.

```
┌──[✗]─[user@parrot]─[~/MarketingAnalytics]
└─$echo "Sales Data for July" > RawData/sales.txt
┌──[user@parrot]─[~/MarketingAnalytics]
└─$echo "Customer List" > RawData/customers.csv
┌──[user@parrot]─[~/MarketingAnalytics]
└─$
```

9. Display file contents.

```
┌──[user@parrot]─[~/MarketingAnalytics]
└─$cat RawData/sales.txt
Sales Data for July
┌──[user@parrot]─[~/MarketingAnalytics]
└─$
```

10. List all files and directories.

```
[user@parrot]-[~/MarketingAnalytics]
 $ls
Backup  ProcessedData  RawData  Reports
[user@parrot]-[~/MarketingAnalytics]
 $ls -l
total 0
drwxrwxr-x 1 user user  0 Aug  4 23:41 Backup
drwxrwxr-x 1 user user  0 Aug  4 23:41 ProcessedData
drwxrwxr-x 1 user user 44 Aug  4 23:43 RawData
drwxrwxr-x 1 user user 44 Aug  4 23:43 Reports
[user@parrot]-[~/MarketingAnalytics]
 $ls -R
.:
Backup  ProcessedData  RawData  Reports
```

11. Search for report files.

```
[user@parrot]-[~/MarketingAnalytics]
 $find . -name "*.txt"
./RawData/sales.txt
./Reports/report1.txt
./Reports/report2.txt
[user@parrot]-[~/MarketingAnalytics]
 $
```

12. Search specific content inside files.

```
[✗]-[user@parrot]-[~/MarketingAnalytics]
 $grep "Sales" RawData/sales.txt
Sales Data for July
[user@parrot]-[~/MarketingAnalytics]
 $
```

13. Copy report files to Backup directory.

```
[user@parrot]-[~/MarketingAnalytics]
 $cp RawData/*.txt Backup/
[user@parrot]-[~/MarketingAnalytics]
 $ls Backup
sales.txt
[user@parrot]-[~/MarketingAnalytics]
 $
```

14. Rename files.

```
[user@parrot]-[~/MarketingAnalytics]
 $mv Reports/report1.txt Reports/AnnualReport.txt
[user@parrot]-[~/MarketingAnalytics]
 $ls Reports
AnnualReport.txt  report2.txt
[user@parrot]-[~/MarketingAnalytics]
 $
```

15. Move files between directories.

```
[user@parrot]-[~/MarketingAnalytics]
 $mv RawData/customers.csv ProcessedData/
[user@parrot]-[~/MarketingAnalytics]
 $ls ProcessedData
customers.csv
[user@parrot]-[~/MarketingAnalytics]
 $
```

16. Delete a file.

```
customers.csv
┌─[user@parrot]─[~/MarketingAnalytics]
└──╼ $rm Reports/report2.txt
┌─[user@parrot]─[~/MarketingAnalytics]
└──╼ $ls Reports
AnnualReport.txt
┌─[user@parrot]─[~/MarketingAnalytics]
└──╼ $
```

17. Delete an empty directory.

```
┌─[user@parrot]─[~/MarketingAnalytics]
└──╼ $mkdir temp
┌─[user@parrot]─[~/MarketingAnalytics]
└──╼ $ls
Backup  ProcessedData  RawData  Reports  temp
┌─[user@parrot]─[~/MarketingAnalytics]
└──╼ $rmdir temp
┌─[user@parrot]─[~/MarketingAnalytics]
└──╼ $ls
Backup  ProcessedData  RawData  Reports
┌─[user@parrot]─[~/MarketingAnalytics]
└──╼ $
```

Key Questions /Analysis:

1. **What is the difference between absolute and relative paths?**
   An absolute path specifies the complete location of a file starting from the root directory.
   A relative path specifies the location of a file relative to the current working directory.
   Absolute: /home/kali/MarketingAnalytics/Reports/report1.txt
   Relative: Reports/report1.txt

2. **Why are Linux permissions important for file security?**
   Linux permissions protect files and directories by controlling who can read, write, or execute them. This helps prevent unauthorized access, accidental modifications, and data loss.

3. **What is the purpose of the grep command?**
   The grep command searches for specific words or patterns inside files and displays the matching lines. It is commonly used to quickly locate required information from large files.

4. **How does Linux support efficient file management?**
   Linux provides commands such as mkdir, cp, mv, rm, find, and grep to efficiently organize, search, copy, move, and manage files and directories.
5. **Why are backups important in enterprise environments?**
   Backups help recover important data after accidental deletion, hardware failure, malware attacks, or system crashes, ensuring business continuity and minimizing downtime.

Conclusion:

This practical demonstrated the basic Linux system administration and file management operations such as creating directories, managing files, searching data, monitoring the system, and performing backups. These commands are essential for efficiently organizing project data and maintaining secure, reliable Linux environments used in enterprise organizations.