

mad 2 qz 1

Question 1 : 6406532158917

View Solutions (0) Total Mark : 2.00 | Type : MSQ

Consider running the following in Browser console:

```
console.log(typeof setTimeout)
console.log(typeof document)
```

Which of the following statements are correct?

Options :

☐ The first line prints .

"function"

☐ The second line prints .

"undefined"

☐ will work in Browser by default because V8 provides the DOM.

document.querySelector()

☐ Different runtimes (browser, Node.js, etc.) can provide different APIs even if they use the same JavaScript engine.

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Question 2 : 6406532158918

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Which of the following are advantages of component-based frontend frameworks like Vue.js?

Options :

- ☐ Code reusability
- ☐ Better maintainability
- ☐ Automatic SQL query optimization
- ☐ Easier UI management

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 3 : 6406532158919

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Which of the following cases is a function being used as a callback?

Options :

☐

```
items.forEach(item => console.log(item))
```

☐

```
setTimeout(showMessage, 1000)
```

☐

```
const result = showMessage()
```

☐

```
button.addEventListener("click", handleClick)
```

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 4 : 6406532158920

View Solutions (0) Total Mark : 3.00 | Type : MCQ

What is the correct output order for the following code?

```
console.log("1")

setTimeout(() => {
  console.log("2")
  setTimeout(() => console.log("3"), 0)
}, 0)

console.log("4")
```

Options :

1 2 3 4

1 4 2 3

2 1 4 3

4 1 2 3

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 5 : 6406532158923

View Solutions (0) Total Mark : 3.00 | Type : MCQ

A child component is initially visible using

`v-if="show"`

. The parent first updates a prop passed to the child, and then sets

`show = false`

. After the child has already mounted once, which sequence can occur in the child after initial render?

Options :

→ → →

`beforeUpdate`

`updated`

`beforeDestroy`

`destroyed`

→ → →

`beforeDestroy`

`destroyed`

`beforeUpdate`

`updated`

→ → →

`created`

mounted

beforeUpdate

destroyed

→ → →

updated

beforeCreate

destroyed

mounted

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Advertisement

Remove Ads

Question 6 : 6406532158926

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code snippet.

```
let var1 = 20;
var var2 = 30;
const val = 10;

{
  let var1 = 40;
  console.log(var1 + val);
}

console.log(var1 + val);

{
  var var2 = 50;
  console.log(var2 + val);
}

console.log(var2 + val);
```

What will be the output of the above code on the browsers' console?

Options :

50 50 60 40

50 50 60 60

50 30 60 60

50 30 60 40

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 7 : 6406532158929

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code snippet.

```

const obj1 = {
  prop1: "Germany",
  prop2: "Spain",
  prop3: 50,
  method1: function(){
    console.log(`The European countries are ${this.prop2} and ${this.prop1}.`)
  },
  method2: function(param){
    let value = param + 2*this.prop3;
    console.log(`The final numerical value is: ${value}.`)
  }
}

const obj2 = {
  prop1: "England",
  prop2: "Italy",
  prop3: "25"
}

const func1 = obj1.method1;
const func2 = obj1.method2;

func1.apply(obj1);
func2.bind(obj2)(15);

```

What will be the output of the above code on the browsers' console?

Options :

The European countries are Spain and Germany. The final numerical value is: 115.

The European countries are Italy and England. The final numerical value is: 65.

The European countries are Spain and Germany. The final numerical value is: 65.

The European countries are Italy and England. The final numerical value is: 115.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 8 : 6406532158930

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code snippet.

```
const obj1 = {
  prop1: "Aluminium",
  prop2: "Gold",
  prop3: "Silver"
}

const obj2 = {
  propA: "Argon",
  propB: "Neon"
}

const {prop2: element1, propA: element2} = {...obj2, ...obj1};

console.log(`The selected elements are: ${element1} and ${element2}`);
```

What will be the output of the above code on the browsers' console?

Options :

- The selected elements are: Gold and Argon
- The selected elements are: Aluminium and Silver
- The selected elements are: Argon and Neon
- The selected elements are: Gold and Neon
- The selected elements are: Argon and Gold

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 9 : 6406532158921

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following Vue directives are correctly matched with their purpose?

Options :

- v-show → fetching api
- v-for → Iteration over lists
- v-bind → Conditional rendering

v-model → Event handling only

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 10 : 6406532158922

View Solutions (0)Total Mark : 3.00 | Type : MSQ

Given the following parent-child setup in Vue 2:

```
<child-box :message="parentMsg" @reply="handleReply"></child-box>
```

and inside the child:

```
this.$emit('reply', 'ok')
```

Which statements are correct?

Options :

- ☐ flows from parent to child through props.

message

- ☐ is a custom event sent from child to parent.

reply

- ☐ The child should directly change to update the parent source of truth.

message

- ☐ If changes in the parent, the child can receive the updated prop value.

parentMsg

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 11 : 6406532158924

View Solutions (0) Total Mark : 3.00 | Type : MSQ

Identify the issue in the following Vue.js code:

```
<div id="app">
  <p>{{ message }}</p>
  <button @click="changeMessage">Click</button>
</div>

<script>
new Vue({
  el: '#app',
  data: {
    message: "Hello"
  },
  methods: {
    changeMessage: () => {
      this.message = "Updated"
    }
  }
})
</script>
```

Why does the

message

value not update correctly when the button is clicked?

Options :

☐ should be used instead of

`v-on`

`@click`

☐ Arrow functions do not bind their own

`this`

☐ should be a function in all Vue instances

`data`

☐ Vue.js does not support external methods

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 12 : 6406532158932

View Solutions (0)Total Mark : 3.00 | Type : MSQ

Consider the following JavaScript code snippet.

```

class MathUtils {
    static add(a, b) {
        return a + b;
    }
    multiply(a, b) {
        return a * b;
    }
}

const utils = new MathUtils();

```

Which of the following statements is/are correct?

Options :

- ☐ will work correctly and return 8

```
MathUtils.add(5, 3)
```

- ☐ will work correctly and return 8

```
utils.add(5, 3)
```

- ☐ will work correctly and return 15

```
utils.multiply(5, 3)
```

- ☐ will work correctly and return 15

```
MathUtils.multiply(5, 3)
```

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 13 : 6406532158925

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code snippet.

```
var var1 = 25;
var var2 = 35;

const obj = {
  var1: 45,
  var2: 55,
  func1: function(){
    console.log(`You are accessing: ${var1}`)
  },
  func2: () => {
    console.log(`You are accessing: ${this.var2}`)
  },
}

obj.func1()
obj.func2()
```

What will be the output of the above code on the browsers' console?

Options :

You are accessing: 45 You are accessing: 55

You are accessing: 25 You are accessing: 35

You are accessing: 25 You are accessing: 55

You are accessing: 45 You are accessing: 35

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Question 14 : 6406532158927

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code snippet.

```
console.log(z);
var a = "alpha";
console.log(a);
let b = "beta";
console.log(b);
d();
console.log(c);
const c = "charlie";
function d(){
    console.log("delta")
}
var z = function(){
    console.log("zeta")
}
```

What will be the output of the above code on the browsers' console in correct order?

Options :

undefined alpha beta delta Reference Error

zeta undefined beta delta Reference Error

undefined Reference Error beta charlie undefined

zeta Reference Error beta charlie undefined

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Question 15 : 6406532158928

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code snippet.

```
let myArr = ["January", "March", "April", "August", "September", "October"]

let modArr = myArr.map((m) => m.slice(2)).
    filter((m) => m.length < 5).
    sort();
console.log(modArr[1]);
```

What will be the output of the above code on the browsers' console?

Options :

['gust', 'rch', 'ril']

['rch', 'ril', 'gust']

ril

rch

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 16 : 6406532158931

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code snippet.

```

function first() {
    console.log("First start");
    setTimeout(function () {
        console.log("First timeout");
    }, 0);
    console.log("First end");
}

function second() {
    console.log("Second start");
    setTimeout(function () {
        console.log("Second timeout");
    }, 0);
}

console.log("Program start");
first();
second();
console.log("Program end");

```

What will be the output of the above code on the browsers' console?

Options :

Program start First start First timeout First end Second start Second timeout
Program end

Program start First start First end First timeout Second start Second timeout
Program end

Program start First timeout First start First end Second timeout Second start
Program end

Program start First start First end Second start Program end First timeout Second
timeout

Your score : 0

Question 1 : 6406531951416

View Solutions (0) Total Mark : 2.00 | Type : MSQ

Which of the following statements about JavaScript scope is/are correct in the browser?

Options :

☐ is function-scoped

var

☐ and are block-scoped

let

const

☐ Variables declared with are hoisted and initialized with

let

undefined

☐ variables can be declared without initialization

const

- ☐ Global variables are always attached to window (as a property)

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 2 : 6406531951417

View Solutions (0) Total Mark : 2.00 | Type : MSQ

Which of the following statements about JavaScript functions is/are true?

Options :

- ☐ Every function in JavaScript is an object.
- ☐ Arrow functions have their own "this" binding
- ☐ Function declarations are hoisted.
- ☐ Function expressions assigned to variables are hoisted with their function value.

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 3 : 6406531951418

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code:

```
var a = 3;
const obj1 = {
  a: 20,
  show: function () {
    console.log(this.a);
  }
};
const obj2 = { a: 10 };

obj1.show.apply(obj1);
```

What will be printed on the console?

Options :

20

10

undefined

3

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 4 : 6406531951419

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code:

```
function addItemToCart(item) {
    let cart = JSON.parse(localStorage.getItem('cart')) || [];
    cart.push(item);
    localStorage.setItem('cart', JSON.stringify(cart));
}

function getCartItems() {
    return localStorage.getItem('cart') || [];
}

addItemToCart({ id: 1, name: 'Laptop' }.name);

console.log(getCartItems());
```

The above code is initially loaded in the browser, and then the browser is refreshed two times. What will be the final output printed in the console?

Options :

`[]`

`['Laptop', 'Laptop', 'Laptop']`

`[{ id: 1, name: 'Laptop' }]`

`[undefined]`

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 5 : 6406531951420

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Match the following storage mechanisms used in the browser with their correct characteristics.

Storage Type	Characteristic
1. Session Storage	A. Data automatically encrypts itself without developer intervention.
2. Token Storage	B. Data persists only until the browser/tab is closed.
3. Cookie Storage	C. Often used to store authentication tokens securely on the client side.
	D. Data persists across sessions, typically stored on the client and sent with every HTTP request.

Which of the following is the correct matching?

Options :

1 → B, 2 → C, 3 → A

1 → B, 2 → A, 3 → C

1 → A, 2 → C, 3 → B

1 → B, 2 → C, 3 → D

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Advertisement

Remove Ads

Question 6 : 6406531951422

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following Vue application with markup index.html and javascript file app.js. index.html:

```
<div id="app">
  <h4>total payable amount is {{totalPayableAmount}}</h4>
</div>
<script src = "app.js"> </script>
```

app.js:

```

const app = new Vue({
  el: '#app',
  data: {
    principal: 0,
    annualInterestRate: 0,
    duration: 0,
    totalPayableAmount: 0,
  },
  computed: {
    simpleInterest() {
      return (this.principal * this.annualInterestRate * this.duration) /
100
    },
  },
})

appData = [
  [2000, 10, 2],
  [3000, 20, 3],
  [5000, 30, 4],
]
let handler = setInterval(() => {
  data = appData.pop()
  app.principal = data[0]
  app.annualInterestRate = data[1]
  app.duration = data[2]
  app.totalPayableAmount += app.simpleInterest
}, 1000)

```

What will be rendered by the browser after 4 seconds?

Options :

total payable amount is 6000

total payable amount is 8200

total payable amount is 1800

total payable amount is 7800

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 7 : 6406531951423

View Solutions (0) Total Mark : 3.00 | Type : MCQ

What will be the output of the following program ?

```
const course = {
  courseName: 'Modern Application Development 2' ,
  courseCode: 'mad2' ,
}
const student = {
  __proto__: course,
  studentName: 'Rakesh' ,
  studentCity: 'Delhi' ,
}
const { courseName } = student
console.log(courseName)
```

Options :

Undefined

Modern Application Development 2

Will throw syntax error

None of these

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Question 8 : 6406531951421

View Solutions (0) Total Mark : 3.00 | Type : SA

Consider the following JavaScript code snippet:

```
let x = 2;
function op(x) {
  x *= 3;
  x += 4;
  x -= 1;
}
op();
op();
console.log(x);
```

What is the final value of x, logged on the console?

Answer (Numeric):

Accepted Answer : 2

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 9 : 6406531951424

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following best describes UI State (Ephemeral State) in frontend applications?

Options :

It includes all data stored permanently in the database and is shared across users

It represents the complete system data such as users, products, and transactions

It refers to short-lived interface elements like loading indicators or selected tabs

It handles complex application logic and long-term session management

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 10 : 6406531951425

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Given that HTTP is stateless, which approach is commonly used to manage application state between the client and the server?

Options :

Storing all state permanently in frontend memory across sessions

Allowing the frontend to handle complex business logic and data storage

Client or server maintaining state and explicitly exchanging it through requests

Eliminating state entirely from web applications

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 11 : 6406531951426

View Solutions (0)Total Mark : 4.00 | Type : MCQ

Consider the below Javascript function:

```
function outer() {  
  let count = 0;  
  return function inner() {  
    return count++;  
  };  
}  
  
const c1 = outer();  
const c2 = outer();  
  
console.log(c1())  
console.log(c1())  
console.log(c2())
```

What will be the output of the above program ?

Options :

1 2 1

0 0 0

1 2 3

0 1 0

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 12 : 6406531951427

View Solutions (0)Total Mark : 5.00 | Type : MCQ

Consider the following Vue app with html and javascript file given below: File: index.html

```
<div id="app">
  <my-comp>
    <h3>Exploring Vue Js</h3>

    <slot v-slot:last>
      <h3>Learning App Dev 2</h3>
    </slot>
  </my-comp>
</div>
```

File: script.js

```

const MyComp = {
  name: 'my-comp',
  props: ['tech'],
  template: `
    <div class="container">
      <slot name="complete">
        <h3>Learned DBMS</h3>
      </slot>

      <slot>
        Exploring Frontend
      </slot>

      <slot name="last"></slot>
    </div>
  `,
};

const app = new Vue({
  el: '#app',
  components: {
    MyComp
  }
});

```

What will be rendered on the browser for the code setup given above ?

Options :

Learned DBMS

Exploring Backend

Learned DBMS

Exploring Vue Js

This is Last Course

Learned DBMS

Exploring Vue Js

None of these.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 13 : 6406531951429

View Solutions (0)Total Mark : 5.00 | Type : MCQ

Consider the following JavaScript code:

```

function createCounter(start) {
  let count = start;

  return function (step) {
    if (typeof step === "number") {
      count += step;
      return count;
    }

    return (function () {
      let temp = count;

      return function (reset = false) {
        if (reset) {
          count = start;
        } else {
          count++;
        }
        return temp + count;
      };
    })();
  };
}

const counter = createCounter(3);

let a = counter(2);
let d = counter()(true);

a + d;

```

What would be the end result at the end of execution of the code?

Options :

5

13

8

11

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 14 : 6406531951428

[View Solutions \(0\)](#) Total Mark : 4.00 | Type : MSQ

Consider the following JavaScript code:

```
class Device {
  constructor(type) {
    this.type = type;
  }

  info() {
    return `${this.type} device`;
  }
}

class Mobile extends Device {
  constructor(type, brand) {
    super(type);
    this.brand = brand;
  }

  info(brand = "type") {
    return `${this.brand} is a ${this.type} device`;
  }
}

let d = new Device("Electronic");
let m = new Mobile("Electronic", "Samsung");

let x = m.info;
```

Which of the following statements are TRUE?

Options :

☐ returns "Electronic device"

`d.info()`

☐ returns "Samsung is a Electronic device"

`m.info()`

☐ Calling throws a runtime error

`x()`

☐ returns "Electronic device"

`d.constructor()`

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 15 : 6406531951430

Total Mark : 0.00 | Type : COMPREHENSION

Consider the following HTML and Vue component code carefully and answer the given sub-questions. File: index.html

```
<div id="app">
  <p id="text">{{ message }}</p>
</div>
```

File: script.js

```

new Vue({
  el: "#app",
  data: {
    message: "Start"
  },
  beforeMount() {
    this.message = this.message + " A";
    console.log("beforeMount message:", this.message);
  },
  mounted() {
    const el = document.getElementById("text");
    if (el) {
      el.innerText = el.innerText + " DOM";
      console.log("DOM text after manipulation:", el.innerText);
    }
  }
});

```

Your score : 0

Broken Format?

Question 16 : 6406531951431

View Parent QNView Solutions (0) Total Mark : 3.00 | Type : MCQ

When the

`beforeMount()`

lifecycle hook is invoked, which of the following statements becomes TRUE?

Options :

The `el` element exists in the DOM but still contains `{{ message }}`

`<p id="text">`

The DOM content already reflects the updated value "Start A"

The hook has already executed

mounted()

The DOM does not exist at all

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 17 : 6406531951432

View Parent QNView Solutions (0)Total Mark : 3.00 | Type : MCQ

What will be the final text content displayed in the browser inside the

<p>

element after the component is fully mounted and all statements in the

mounted()

hook have executed?

Options :

Start A

Start A B

Start A B DOM

Start A DOM

Your score : 0

Question 1 : 6406531527676

Total Mark : 0.00 | Type : MCQ

THIS IS QUESTION PAPER FOR THE SUBJECT "**DIPLOMA LEVEL : MODERN APPLICATION DEVELOPMENT II (COMPUTER BASED EXAM)**" ARE YOU SURE YOU HAVE TO WRITE EXAM FOR THIS SUBJECT? CROSS CHECK YOUR HALL TICKET TO CONFIRM THE SUBJECTS TO BE WRITTEN. (IF IT IS NOT THE CORRECT SUBJECT, PLS CHECK THE SECTION AT THE TOP FOR THE SUBJECTS REGISTERED BY YOU)

Options :

YES

NO

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 2 : 6406531527677

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Which of the following Vue 2 template syntaxes are valid?

Options :

☐

`{{ message }}` for interpolation

☐

`v-bind:title="msg"` for binding attributes

☐

`v-on:@click="doSomething"` for click event binding



`<input v-model="inputValue"></input>` for two-way binding

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 3 : 6406531527678

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Which of the following statements about Vue 2 templates are correct?

Options :

- ☐ **v-if** removes elements from DOM when false
- ☐ **v-show** toggle initiates re-render of the Vue component
- ☐ **v-bind** can bind attributes and class dynamically
- ☐ Vue 2 templates must use double curly braces for all text interpolation

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 4 : 6406531527679

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code:

```
let employees = [  
  { name: "Rahul", age: 28 },  
  { name: "Priya", age: 24 },  
  { name: "Amit", age: 32 }  
];  
employees.sort((a, b) => a.age - b.age);  
console.log(employees.map(e => e.name).join(" - "));
```

What will be printed on the console?

Options :

Rahul - Priya - Amit

Priya - Rahul - Amit

Amit - Rahul - Priya

Priya - Amit - Rahul

Your score : 0

Discussions (0)Suggest Correction

Question 5 : 6406531527680

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code snippet.

```
const users = [
  { name: "Amit", age: 25 },
  { name: "Bhavna", age: 20 },
  { name: "Chirag", age: 30 },
];

const names = users
  .filter((u) => u.age >= 25)
  .map((u) => u.name.toUpperCase())
  .sort();

console.log(JSON.stringify(names));
```

What is logged on the console?

Options :

['Amit', 'Chirag']

['CHIRAG', 'AMIT']

['AMIT', 'CHIRAG']

['AMIT', 'Bhavna', 'CHIRAG']

Your score : 0

Discussions (0)Suggest Correction

Advertisement

Remove Ads

Question 6 : 6406531527681

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code snippet.

```
let subject = "Dog";

function camera() {
  let subject = "Deer";
  function click() {
    console.log(`clicked picture of ${subject}`);
  }
  subject = "Cat";
  return click;
}

let cameraPicture = camera();
cameraPicture();
```

What is logged to the console?

Options :

clicked picture of Dog

clicked picture of Deer

clicked picture of Cat

clicked picture of undefined

Your score : 0

Discussions (0)Suggest Correction

Question 7 : 6406531527682

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Match the following Vue 2 directives in Column A with their correct functionality in Column B:

Column A	Column B
1. v-bind	A. Creates two-way data binding between form inputs and Vue data properties
2. v-model	B. Conditionally shows or hides elements using CSS display property
3. v-on	C. Binds HTML attributes or component properties to Vue data expressions
4. v-show	D. Attaches event listeners to DOM elements for handling user interactions
5. v-cloak	E. Prevents the flash of un-compiled template content before Vue initializes

Options :

1-C, 2-D, 3-A, 4-E, 5-B

1-A, 2-C, 3-B, 4-D, 5-E

1-C, 2-A, 3-D, 4-B, 5-E

1-E, 2-A, 3-D, 4-C, 5-B

Your score : 0

Discussions (0)Suggest Correction

Question 8 : 6406531527683

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following HTML, with the correct Vue 2 CDN links included

```
<body>
  <div id="app">
    <p>Coffee</p>
    <button @click="orderCoffee">Order</button>
    <p>Total Cost: {{totalCost}}</p>
    <p>Order Count: {{orderCount}}</p>
  </div>
  <script>
    new Vue({
      el: '#app',
      data() {
        return {
          totalCost: '0',
          unitPrice: 25,
          orderCount: 0
        }
      },
      methods: {
        orderCoffee() {
          this.totalCost += this.unitPrice;
          this.orderCount++;
        }
      }
    })
  </script>
</body>
```

What will be displayed for "Total Cost" and "Order Count" when the Order button is clicked three times?

Options :

Total Cost: 75, Order Count: 3

Total Cost: 02525, Order Count: 3

Total Cost: 252525, Order Count: 3

Total Cost: 0252525, Order Count: 3

Your score : 0

Discussions (0)Suggest Correction

Question 9 : 6406531527684

View Solutions (0)Total Mark : 3.00 | Type : MSQ

Consider this nested loop is written in JavaScript:

```
let result = "";
for (let i = 0; i < 2; i++) {
  for (var j = 0; j < 2; j++) {
    result += i + j;
  }
}
console.log(result);
```

Which of the following statements is/are true?

Options :

☐

The output is "0011".

☐

The inner loop runs 2 times for each outer loop iteration.

☐

The output is "0123"

☐

The values are concatenated into a **string**, not added as numbers.

Your score : 0

Discussions (0)Suggest Correction

Question 10 : 6406531527685

View Solutions (0)Total Mark : 3.00 | Type : MSQ

Consider the following HTML and JavaScript code.

HTML file

```
<button id="btn">Click Me</button>

<script>
  const btn = document.getElementById('btn');
  btn.addEventListener('click', () => console.log('A'));
  btn.onclick = () => console.log('B');
  btn.addEventListener('click', () => console.log('C'));
  btn.click();
</script>
```

Among the following console log statements, which ones will be logged when the code executes?

(Select **all** that apply, irrespective of the order.)

Options :

- ☐ A
- ☐ B
- ☐ C
- ☐ None

Your score : 0

Discussions (0)Suggest Correction

Question 11 : 6406531527686

View Solutions (0)Total Mark : 3.00 | Type : SA

Consider the following HTML and JavaScript, assume Vue 2 CDN link to be already included.

index.html:

```
<div id="app">
  <p v-for="n in numbers">{{ n }}</p>
</div>
<script src="app.js" />
```

app.js:

```
var app = new Vue({
  el: "#app",
  data: { numbers: [1, 2, 3] },
});

app.data.numbers.push(4);
```

How many <p> elements will be rendered?

Answer (Numeric):

Accepted Answer : 3

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 12 : 6406531527687

[View Solutions \(0\)](#) Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code snippet:

```
const products = [
  { name: 'Laptop', price: 1200, category: 'Electronics', inStock: true },
  { name: 'Book', price: 25, category: 'Education', inStock: false },
  { name: 'Phone', price: 800, category: 'Electronics', inStock: true },
  { name: 'Pen', price: 5, category: 'Stationery', inStock: true },
  { name: 'Tablet', price: 600, category: 'Electronics', inStock: false }
];

const result = products
  .filter(item => item.category === 'Electronics' && item.inStock)
  .map(item => ({ ...item, discountedPrice: item.price * 0.9 }))
  .filter(item => item.discountedPrice > 500);

console.log(result.length);
console.log(result[0].name);
```

What will be the output of the above code on the browser's console?

Options :

3
Laptop

2
Laptop

1
Phone

2
Phone

Your score : 0

Discussions (0)Suggest Correction

Question 13 : 6406531527688

[View Solutions \(0\)](#) Total Mark : 4.50 | Type : MCQ

Consider the below JavaScript program:

```
const globalVar = 50;

const object1 = {
  globalVar: 100,
  method1: function() {
    console.log(globalVar, this.globalVar);
    return () => {
      console.log(globalVar, this.globalVar);
    }
  }
}

const object2 = {
  globalVar: 200,
  method2: () => {
    console.log(globalVar, this.globalVar);
    return function() {
      console.log(globalVar, this.globalVar);
    }
  }
}

const fn1 = object1.method1();
fn1();
const fn2 = object2.method2();
fn2();
```

What will be the output of the above program on the browser's console, if executed?

Options :

```
50 100
50 100
50 undefined
50 undefined
```

```
50 100
50 100
50 undefined
50 200
```

```
100 50
100 50
200 50
200 50
```

```
50 100
50 100
50 undefined
50 this
```

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 14 : 6406531527689

[View Solutions \(0\)](#) Total Mark : 4.50 | Type : MSQ

Consider the following JavaScript code:

```
class Region {
  constructor(region) {
    this.region = region;
  }
  describe() {
    return `${this.region} is a region.`;
  }
}

class Country extends Region {
  constructor(region, name) {
    super(region);
    this.name = name;
  }
  describe() {
    return `${this.name} is in ${this.region}.`;
  }
}

let r = new Region("Asia");
let c = new Country("Europe", "Germany");
let f = c.describe;
```

Which of the following statements are **true**?

Options :

☐

Calling `r.describe()` prints "Asia is a region."

☐

Calling `c.describe()` prints "Germany is in Europe."

☐

Calling `f()` directly will still print "Germany is in Europe."

☐

The `Country` class overrides both the **constructor** and the **describe()** method from `Region`.

☐

The call to `super(region)` inside `Country`'s constructor is **not required** to initialize `this.region`.

Your score : 0

Discussions (0)Suggest Correction

Question 15 : 6406531527690

View Solutions (0)Total Mark : 4.50 | Type : MSQ

Consider the following JavaScript function definitions. Which of the following will correctly return the product of three numbers and handle the case where any parameter is undefined by treating it as 1?

Options :

☐

```
let multiply = (a, b, c) => {  
  a = a || 1;  
  b = b || 1;  
  c = c || 1;  
  return a * b * c;  
}
```

☐

```
function multiply(a = 1, b = 1, c = 1) {  
    return a * b * c;  
}
```



```
let multiply = (a, b, c) => {  
    return (a ?? 1) * (b ?? 1) * (c ?? 1);  
}
```



```
const multiply = function(a, b, c) {  
    if(a === undefined) a = 1;  
    if(b === undefined) b = 1;  
    if(c === undefined) c = 1;  
    a * b * c;  
}
```

Your score : 0

Discussions (0) [Suggest Correction](#)

Question 16 : 6406531527691

Total Mark : 0.00 | Type : COMPREHENSION

Read the Vue.js code and answer the given subquestions. The parent binds an input with `v-model` and passes the value as a prop to a child component; the child contains a named slot that shows the message in uppercase.

```
<div id="app">
  <p>{{ message }}</p>
  <input v-model="message" />
  <child-component :title="message">
    <template slot="header">
      <h3>{{ message.toUpperCase() }}</h3>
    </template>
  </child-component>
</div>

<script>
Vue.component('child-component', {
  props: ['title'],
  template: `
    <div>
      <h2>{{ title }}</h2>
      <slot name="header"></slot>
      <p>Child Content</p>
    </div>
  `
});

new Vue({
  el: '#app',
  data: {
    message: 'Hello Vue'
  }
});
</script>
```

Your score : 0

Question 17 : 6406531527692

View Parent QNView Solutions (0) Total Mark : 2.00 | Type : MCQ

If the user types "hi" into the input box,
what happens on the page, choose
the closest to correct?

Options :

Only <p> updates to "hi", but <h2> remains "Hello Vue".

Both <p> and <h2> update and display "hi".

Only <h3> changes to "HI", but <p> and <h2> remain unchanged.

Nothing updates at all.

Your score : 0

Discussions (0)Suggest Correction

Question 18 : 6406531527693

View Parent QNView Solutions (0) Total Mark : 2.00 | Type : MSQ

Which Vue.js features are shown in
the code?

Options :

☐

Two-way data binding using v-model.

☐

Use of a named slot inside a child component.

☐

Passing values from parent to child using props.

☐

Use of lifecycle hooks.

Your score : 0

Question 1 : 6406531294349

Total Mark : 0.00 | Type : MCQ

THIS IS QUESTION PAPER FOR THE SUBJECT "**DIPLOMA LEVEL : MODERN APPLICATION DEVELOPMENT II (COMPUTER BASED EXAM)**" ARE YOU SURE YOU HAVE TO WRITE EXAM FOR THIS SUBJECT? CROSS CHECK YOUR HALL TICKET TO CONFIRM THE SUBJECTS TO BE WRITTEN. (IF IT IS NOT THE CORRECT SUBJECT, PLS CHECK THE SECTION AT THE TOP FOR THE SUBJECTS REGISTERED BY YOU)

Options :

YES

NO

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 2 : 6406531294350

View Solutions (0)Total Mark : 2.00 | Type : MCQ

In Vue 2, what happens when you update a data property?

Options :

DOM is immediately updated without virtual DOM

The page reloads

The virtual DOM detects changes and updates efficiently

A full component re-renders from scratch

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 3 : 6406531294351

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Consider the following HTML, with the correct Vue 2 CDN links included:

Html code:

```
<div id="app">
  <h3>Shopping Cart</h3>
  <p>Items: {{itemCount}}</p>
  <p>Total Cost: ${{totalCost}}</p>
  <button @click="addItem">Add Item ($15)</button>
  <button @click="removeItem">Remove Item</button>
  <p>Status: {{status}}</p>
</div>
```

script:

```
const app = new Vue({
  el: '#app',
  data() {
    return {
      itemCount: 0,
      itemPrice: 15,
      totalCost: 0
    }
  },
  computed: {
    status() {
      if (this.itemCount === 0) {
        return 'Empty Cart';
      } else if (this.itemCount < 3) {
        return 'Few Items';
      } else {
        return 'Full Cart';
      }
    }
  },
  methods: {
    addItem() {
      this.itemCount++;
      this.totalCost += this.itemPrice;
    },
    removeItem() {
      if (this.itemCount > 0) {
        this.itemCount--;
        this.totalCost -= this.itemPrice;
      }
    }
  }
})
```

If the user clicks the "Add Item" button 3 times, then clicks the "Remove Item" button 1 time, what will be displayed for Items, Total Cost, and Status?

Options :

Items: 2, Total Cost: \$30, Status: Few Items

Items: 2, Total Cost: \$45, Status: Few Items

Items: 3, Total Cost: \$30, Status: Full Cart

Items: 2, Total Cost: \$30, Status: Full Cart

Items: 1, Total Cost: \$15, Status: Few Items

Your score : 0

Discussions (0)Suggest Correction

Question 4 : 6406531294352

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Consider the following code.

```
const arr = [1, 2, 3];  
const result = arr.map(function(item, index) {  
  return this[index] * item;  
}, [10, 20, 30]);  
console.log(result);
```

What will be the output?

Options :

[1, 2, 3]

[10, 40, 90]

[10, 20, 30]

[NaN, NaN, NaN]

Your score : 0

Discussions (0)Suggest Correction

Question 5 : 6406531294353

View Solutions (0)Total Mark : 2.00 | Type : MCQ

In Vue 2, which of the following will NOT trigger reactivity?

```
data() {  
  return {  
    items: [1, 2, 3],  
    obj: { a: 1 }  
  }  
}
```

Options :

this.items.push(4)

this.items[0] = 10

this.items = [10, 2, 3]

this.obj.a = 2

Your score : 0

Discussions (0)[Suggest Correction](#)

Advertisement

[Remove Ads](#)

Question 6 : 6406531294354

[View Solutions \(0\)](#) Total Mark : 3.00 | Type : MCQ

What will be the output of this code?

```
function createFunctions() {  
  var funcs = [];  
  for (var i = 0; i < 3; i++) {  
    funcs.push(function() {  
      return i;  
    });  
  }  
  return funcs;  
}  
  
const functions = createFunctions();  
console.log(functions[0](), functions[1](), functions[2]());
```

Options :

0, 1, 2

1, 2, 3

undefined, undefined, undefined

3, 3, 3

Your score : 0

Discussions (0)Suggest Correction

Question 7 : 6406531294355

[View Solutions \(0\)](#)Total Mark : 3.00 | Type : MCQ

Which computed property implementation is **INCORRECT**?

Options :

```
computed: {  
  fullName() {  
    return this.firstName + ' ' + this.lastName;  
  }  
}
```

```
computed: {
  fullName: {
    get() { return this.firstName + ' ' + this.lastName; },
    set(value) {
      const names = value.split(' ');
      this.firstName = names[0];
      this.lastName = names[1];
    }
  }
}
```

```
computed: {
  async fullName() {
    return await this.fetchFullName();
  }
}
```

```
computed: {
  fullName: function() {
    return this.firstName + ' ' + this.lastName;
  }
}
```

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 8 : 6406531294356

[View Solutions \(0\)](#) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code:

```
const products = [
  { id: 101, name: "laptop", price: 800 },
  { id: 102, name: "mouse", price: 25 },
  { id: 103, name: "keyboard", price: 60 },
  { id: 104, name: "monitor", price: 300 }
];

const priorities = { "102": 1, "104": 2, "101": 3, "103": 4 };

products
  .filter((product) => product.price > 50)
  .map((product) => {
    return { ...product, priority: priorities[product.id] }
  })
  .sort((a, b) => a.priority - b.priority)
  .forEach((product) => {
    console.log(product.name);
  });
```

What will be the output of the code?

Options :

```
laptop
keyboard
monitor
```

```
monitor
laptop
keyboard
```

```
mouse
monitor
laptop
keyboard
```

```
laptop  
mouse  
keyboard  
monitor
```

The code will throw an error

Your score : 0

Discussions (0)Suggest Correction

Question 9 : 6406531294357

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code to answer the below question:

```
const grandParent = {
  username: 'GrandParent',
  getName: function () {
    return this.username;
  },
  parent: {
    username: 'Parent',
    getName: function () {
      return this.username;
    },
    child: {
      username: 'Child',
      getNameArrow: () => {
        return this.username;
      },
      getNameFunc: function () {
        return this.username;
      }
    }
  }
};

console.log("A: " + grandParent.getName());
console.log("B: " + grandParent.parent.getName());
console.log("C: " + grandParent.parent.child.getNameFunc());
console.log("D: " + grandParent.parent.child.getNameArrow());
```

What will be the result of all the console.log after execution of the above code?

Options :

```
A: GrandParent
B: Parent
C: Child
D: Reference Error
```

```
A: GrandParent  
B: Parent  
C: undefined  
D: Child
```

```
A: GrandParent  
B: GrandParent  
C: Parent  
D: GrandParent
```

```
A: GrandParent  
B: Parent  
C: Child  
D: undefined
```

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 10 : 6406531294358

[View Solutions \(0\)](#) Total Mark : 4.50 | Type : MCQ

Consider the following Vue.js (Vue 2) code to answer the following question:

```
<div id="app">
  <my-counter :start="5"></my-counter>
</div>

<script>
Vue.component('my-counter', {
  props: ['start'],
  data: function () {
    return {
      count: this.start
    };
  },
  template: `
    <div>
      <p>{{ count }}</p>
      <button @click="increment">Increment</button>
    </div>
  `,
  methods: {
    increment() {
      this.count++;
    }
  }
});

new Vue({
  el: '#app',
  data: { start: 10 }
});
</script>
```

What will be displayed when the page loads, and what happens when you click the button?

Options :

The counter starts at 10, and increments by 1 on each button click.

The counter starts at 5, and increments by 1 on each button click.

Nothing is rendered because the Vue component template is invalid when using Vue via CDN.

Vue throws a warning about compiling templates in the browser and fails to bind the component.

Your score : 0

Discussions (0)Suggest Correction

Question 11 : 6406531294359

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript program:

```
function createMultiplier(base) {  
  let multiplier = base;  
  
  function updateMultiplier(newValue) {  
    multiplier = newValue;  
    return multiplier;  
  }  
  
  function multiply(num) {  
    return num * multiplier;  
  }  
  
  return {  
    update: updateMultiplier,  
    calculate: multiply,  
    getMultiplier: function() { return multiplier; }  
  };  
}  
  
const math1 = createMultiplier(3);  
const math2 = createMultiplier(5);  
  
console.log(math1.calculate(4));  
console.log(math2.calculate(2));  
console.log(math1.update(7));  
console.log(math1.calculate(4));  
console.log(math2.getMultiplier());  
console.log(math1.getMultiplier());
```

What will be the output of the above program?

Options :

12, 10, 7, 12, 5, 7

12, 10, 7, 28, 5, 7

12, 10, 3, 28, 5, 3

15, 10, 7, 28, 7, 7

12, 10, 7, 21, 5, 7

Your score : 0

Discussions (0)Suggest Correction

Question 12 : 6406531294360

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code snippet:

```
var globalScore = 25;

const player1 = {
  score: 150,
  getScore: function() {
    return this.score;
  },
  displayScore: function(bonus) {
    return this.score + (bonus || 0);
  }
};

const player2 = { score: 200 };
const player3 = { score: 75 };

const method1 = player1.getScore;
const method2 = player1.getScore.bind(player2);
const method3 = player1.displayScore.bind(player3);

console.log(method1());
console.log(method2());
console.log(method3(50));
console.log(method3.call(player1, 25));
```

What will be the output of the above JavaScript code?

Options :

undefined, 200, 125, 175

25, 200, 125, 175

150, 200, 125, 100

25, 200, 125, 100

undefined, 200, 125, 100

Your score : 0

Discussions (0)Suggest Correction

Question 13 : 6406531294361

View Solutions (0) Total Mark : 3.00 | Type : MSQ

Consider the following JavaScript code to answer the below question:

```
function normalFunc() {
  console.log(this.constructor.name);
}

const arrowFunc = () => {
  console.log(this.constructor.name);
};

const objj = {
  name: 'Test',
  normalMethod: normalFunc,
  arrowMethod: arrowFunc,
  outer: function () {
    return () => {
      console.log(this.name);
    };
  }
};

const inner = objj.outer();

objj.normalMethod();
objj.arrowMethod();
inner();
new arrowFunc();
```

Which of the following statements is/are TRUE?

Options :

☐

`objj.normalMethod()` prints "Object"

☐

`obj.arrowMethod()` prints "Window" or throws an error in strict mode

☐

`inner()` prints "Test"

☐

`new arrowFunc()` throws an error because arrow functions cannot be used as constructors

Your score : 0

Discussions (0)Suggest Correction

Question 14 : 6406531294362

Total Mark : 0.00 | Type : COMPREHENSION

Based on the above data, answer the given subquestions.

You're building a basic Vue app using **Vue 2 via CDN** to show a user's login form.

You want to:

- Show a welcome message once the user enters a name and clicks "Login".
- Bind the input using `v-model`.

But this code is yet to be tested, you have to test this code and push it to production.

```
<body>

<div id="app">
  <input v-model="username">
  <button @click="loggedIn = true">Login</button>

  <p v-if="loggedIn">
    Welcome, {{ username }}!
  </p>
</div>

<script>
  new Vue({
    el: '#app',
    data: {
      username: '',
      loggedIn: false
    }
  });
</script>

</body>
</html>
```

Your score : 0

Broken Format?

Question 15 : 6406531294363

View Parent QNView Solutions (0) Total Mark : 3.00 | Type : MCQ

Which line of code should be changed to make this code work properly?

Options :

`<input v-model="username">` should be replaced with `<input v-bind="username">`

`@click="loggedIn = true"` should be replaced with `v-on:click="login()"`

`v-if="loggedIn"` should be replaced with `v-show="loggedIn"`

The code works correctly; no change is required.

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Question 16 : 6406531294364

View Parent QNView Solutions (0) Total Mark : 3.00 | Type : MCQ

If you wanted to make this app more maintainable by moving logic to methods, which line would you replace?

Options :

Replace `@click="loggedIn = true"` with `@click="login"` and define a method

Replace `<input v-model="username">` with `v-on:input="updateUsername"`

Replace `v-if="loggedIn"` with
`v-else="loggedIn"`

This code is best, no changes required.

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 17 : 6406531294365

Total Mark : 0.00 | Type : COMPREHENSION

Consider the following HTML with relevant Vue 2 CDN link attached and answer the given subquestions.

Html file:

```
<div id="app">
  <div :class="[baseClass, { highlighted: isHighlighted,
    'btn-primary': isPrimary, 'btn-disabled': !isEnabled }]">
    {{ buttonText }}
  </div>
  <button @click="toggleState">Toggle State</button>
</div>
```

script

```
const app = new Vue({
  el: '#app',
  data: {
    buttonText: 'Click Me',
    baseClass: 'btn',
    isHighlighted: false,
    isPrimary: true,
    isEnabled: true
  },
  methods: {
    toggleState() {
      this.isHighlighted = !this.isHighlighted;
      this.isPrimary = !this.isPrimary;
      this.isEnabled = !this.isEnabled;
    }
  }
})
```

Your score : 0

Question 18 : 6406531294366

[View Parent QNView Solutions \(0\)](#) Total Mark : 3.00 | Type : MCQ

What classes will be applied to the `<div>` initially (before any button clicks)?

Options :

btn, highlighted, btn-primary

btn, btn-primary

baseClass, btn-primary

btn, highlighted, btn-primary, btn-disabled

Your score : 0

Discussions (0)Suggest Correction

Question 19 : 6406531294367

View Parent QNView Solutions (0) Total Mark : 3.00 | Type : MCQ

What classes will be applied to the `<div>` after clicking the "Toggle State" button once?

Options :

btn, highlighted

btn, btn-disabled

btn, highlighted, btn-disabled

baseClass, highlighted, btn-disabled

Your score : 0

Question 1 : 6406531104761

Total Mark : 0.00 | Type : MCQ

THIS IS QUESTION PAPER FOR THE SUBJECT "**DIPLOMA LEVEL : MODERN APPLICATION DEVELOPMENT II (COMPUTER BASED EXAM)**" ARE YOU SURE YOU HAVE TO WRITE EXAM FOR THIS SUBJECT? CROSS CHECK YOUR HALL TICKET TO CONFIRM THE SUBJECTS TO BE WRITTEN. (IF IT IS NOT THE CORRECT SUBJECT, PLS CHECK THE SECTION AT THE TOP FOR THE SUBJECTS REGISTERED BY YOU)

Options :

YES

NO

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 2 : 6406531104762

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following statements is true regarding "v-if" and "v-show" directives in VueJS?

Options :

The "v-if" directive adds/removes elements from the DOM, while v-show onlytoggles visibility using CSS.

The "v-show" directive adds/removes elements from the DOM, while v-if onlytoggles visibility using CSS.

Both the "v-if" and "v-show" directives add/remove elements from the DOM.

Both the "v-if" and "v-show" directives toggle visibility using CSS.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 3 : 6406531104763

View Solutions (1)Total Mark : 2.00 | Type : MCQ

Consider the below JavaScript program.

```
let x = 5;  
(function () {  
  console.log(x);  
  let x = 10;  
})();
```

What will be the output of the above program?

Options :

5

10

undefined

Reference Error

null

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 4 : 6406531104764

[View Solutions \(0\)](#) Total Mark : 2.00 | Type : MCQ

What is the output of this code?

```
console.log(myVar);  
console.log(myFunc());  
  
var myVar = "hello";  
function myFunc() {  
  return "world";  
}
```

Options :

hello, world

undefined, world

ReferenceError

undefined, undefined

Your score : 0

Discussions (0)Suggest Correction

Question 5 : 6406531104765

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following statements is **true** about the let, const, and var keywords in JavaScript?

Options :

var is block-scoped, while let and const are function-scoped.

const variables must always be initialized at the time of declaration.

Variables declared with let and const are hoisted and initialized with undefined.

let, const, and var have identical scoping rules.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Advertisement

Remove Ads

Question 6 : 6406531104766

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the below JavaScript program.

```
function outer() {  
  let count = 0;  
  return function inner() {  
    return ++count;  
  };  
}  
  
const counter1 = outer();  
const counter2 = outer();  
  
console.log(counter1());  
console.log(counter1());  
console.log(counter2());
```

What will be the output of the above program?

Options :

12 3

11 1

12 1

01 0

01 1

Your score : 0

Discussions (0)Suggest Correction

Question 7 : 6406531104767

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the 4 JavaScript code snippets given below.

Code Snippet 1:

```
let x = 10;  
const y;
```

Code Snippet 2:

```
let { a: b } = undefined;
```

Code Snippet 3:

```
const arr = [1, 2];  
arr = [3, 4];
```

Code Snippet 4:

```
const a = 10, b = 20;  
(() => { return a + b; })();
```

Which of the above JavaScript code snippet(s) will throw an error?

Options :

1 and 2

1, 2 and 3

2, 3 and 4

All 4

Your score : 0

Discussions (0)Suggest Correction

Question 8 : 6406531104768

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the below VueJS application.

```
<div id="app">
  <p>{{ counter }}</p>
  <button @click="updateCounter">Click Me</button>
</div>

<script>
new Vue({
  el: '#app',
  data: {
    counter: 1,
  },
  methods: {
    updateCounter() {
      this.counter *= 2;
    },
  },
});
</script>
```

What will the “p” tag display when the button with the text “Click Me” is clicked three times?

Options :

1

4

8

16

Your score : 0

Discussions (0)Suggest Correction

Question 9 : 6406531104769

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code snippet shown below.

```
let length = 5;

function countLen(item){
    console.log(this.length);
}

const data = [countLen, "Apple", length]

data[0]('Script')
```

What will be output on browser's console for the above JavaScript code?

Options :

- 6
- 5
- 4
- 3

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 10 : 6406531104770

[View Solutions \(1\)](#) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code snippet shown below.

```
var value = 50;

const mainObj = {
  value: 42,
  getValue: function() {
    return this.value;
  }
};

const nextObj = {
  value: 100
};

const getValue1 = mainObj.getValue.bind()(nextObj);
const getValue2 = mainObj.getValue.bind(nextObj)();

console.log(getValue1);
console.log(getValue2);
```

What will be output on browser's console for the above JavaScript code?

Options :

50
100

42
50

100
100

undefined
100

undefined
50

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 11 : 6406531104771

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code

```
let Tree = {  
  name: "Oak",  
  size: 5,  
  description: function (size) {  
    return `A ${this.size > 10 ? 'large' : 'medium'} ${this.name} tree.`;  
  }  
}  
  
const willow = {  
  name: 'Willow'  
};  
  
const returnedString = Tree.description.call(willow, 15);  
  
console.log(returnedString)
```

What will be the output of the code?

Options :

A large Oak tree

A medium Oak tree

A large Willow tree

A medium Willow tree

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 12 : 6406531104772

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following HTML with relevant Vue CDN link attached.

```
<div id="app">
  <div :class="{ active: isActive, 'text-danger': hasError }">
    {{ message }}
  </div>
</div>

<script>
  new Vue({
    el: '#app',
    data: {
      message: 'Hello!',
      isActive: true,
      hasError: false
    }
  })
</script>
```

Given the Vue.js application above, which classes will be applied to the div containing the message?

Options :

Only 'active'

'text-danger' and 'active'

No classes

Only 'text-danger'

Your score : 0

Discussions (0) **Suggest Correction**

Question 13 : 6406531104774

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Consider the following Vue2 app and the index file given below.

index.html

```
<body>
  <div id="app">
    <h4>{{ state }}</h4>
  </div>
  <script
    src="https://cdn.jsdelivr.net/npm/vue@2.7.16/dist/vue.js">
  </script>
  <script src="./script.js"></script>
</body>
</html>
```

script.js

```
const app = new Vue({
  el: '#app',
  data: {
    terminal: ['3', '2', '1'],
    curr_status: ["arrived", "departed", "delayed"]
  },
  computed: {
    state: () => {
      return `The flight 103 has ${this.curr_status[1]} from terminal
${this.terminal[2]}.`
    }
  }
})
```

What will be the output on the browser?

Options :

The flight 103 has departed from terminal 1.

The flight 103 has arrived from terminal 2.

The flight 103 has delayed from terminal 3.

The flight 103 has from terminal.

ReferenceError

Your score : 0

Discussions (0)Suggest Correction

Question 14 : 6406531104775

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Consider the following Vue App and the HTML document given below.

index.html

```
<body>
  <div id="app">
    <my-comp>
      <h3>Exploring Vue JS</h3>
      <template v-slot:ongoing>
        <h3>Learning App Dev 2</h3>
      </template>
    </my-comp>
  </div>
  <script src="./script.js"></script>
</body>
```

script.js

```
const MyComp = {
  name: 'my-comp',
  props: ['tech'],
  template : `<div class="container">
    <slot name="complete"><h3>Learned DBMS</h3></slot>
    <slot name="ongoing"></slot>
    <slot>Exploring Frontend</slot>
  </div>`
}

const app = new Vue({
  el: '#app',
  components: {
    MyComp
  }
})
```

What will be rendered on the browser for code setup given above?

Options :

Learning App Dev 2Exploring Vue JS

Learning App Dev 2Exploring Frontend

Learned DBMSLearning App Dev 2 Exploring Frontend

Learned DBMSLearning App Dev 2 Exploring Vue JS

Your score : 0

Discussions (0)Suggest Correction

Question 15 : 6406531104776

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following HTML with relevant Vue CDN link attached.

```

<div id="app1">
  {{ messageA }}
</div>
<div id="app2">
  {{ messageB }}
</div>

<script>
  const vm1 = new Vue({
    el: '#app1',
    data: {
      messageA: 'Hello from App 1'
    }
  })

  const vm2 = new Vue({
    el: '#app2',
    data: {
      messageB: 'Hello from App 2'
    }
  })

  vm1.messageA = 'Updated App 1';
</script>

```

After the code execution above, what will be displayed on the page?

Consider the following HTML with relevant Vue CDN link attached.

Options :

- "Updated App 1" and "Hello from App 2"
- "Hello from App 1" and "Hello from App 2"
- "Updated App 1" and blank second div
- Both divs will be blank

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 16 : 6406531104777

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Consider the following HTML with relevant Vue CDN attached.

```
<div id="app">
  <input v-model.number="price" type="number">
  <input v-model.number="quantity" type="number">
  <p>Total: {{ total }}</p>
  <p>Last Updated By: {{ lastUpdatedBy }}</p>
</div>

<script>
  new Vue({
    el: '#app',
    data: {
      price: 10,
      quantity: 1,
      total: 10,
      lastUpdatedBy: 'initial'
    },
    watch: {
      price: {
        handler(newVal) {
          this.total = newVal * this.quantity;
          this.lastUpdatedBy = 'price';
        }
      },
      quantity: {
        handler(newVal) {
          this.total = this.price * newVal;
          this.lastUpdatedBy = 'quantity';
        }
      }
    }
  })
</script>
```

If the user changes the price to 20 and then immediately changes the quantity to 2, what will be the final values of total and lastUpdatedBy?

Consider the following HTML with relevant Vue CDN attached.

Options :

total: 20, lastUpdatedBy: "price"

total: 40, lastUpdatedBy: "quantity"

total: 20, lastUpdatedBy: "quantity"

total: 40, lastUpdatedBy: "price"

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 17 : 6406531104773

View Solutions (0) Total Mark : 3.00 | Type : MSQ

Consider the following JavaScript Code.

```
class Person {  
  constructor(name) {  
    this.name = name;  
  }  
  
  greet() {  
    console.log(`Hello, my name is ${this.name}`);  
  }  
  
  static identify() {  
    console.log("I am a Person class");  
  }  
}  
  
const john = new Person("John");
```

Which of the following expression(s) will cause an error?

Options :

☐

```
john.greet();
```

☐

```
Person.greet();
```

☐

```
john.identify();
```

☐

```
Person.identify();
```

☐

```
console.log(john.name);
```

Your score : 0

Question 1 : 640653995581

Total Mark : 0.00 | Type : MCQ

THIS IS QUESTION PAPER FOR THE SUBJECT "DIPLOMA LEVEL : MODERN APPLICATION DEVELOPMENT II (COMPUTER BASED EXAM)" ARE YOU SURE YOU HAVE TO WRITE EXAM FOR THIS SUBJECT? CROSS CHECK YOUR HALL TICKET

TO CONFIRM THE SUBJECTS TO BE WRITTEN. (IF IT IS NOT THE CORRECT SUBJECT, PLS CHECK THE SECTION AT THE TOP FOR THE SUBJECTS REGISTERED BY YOU)

Options :

YES

NO

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 2 : 640653995585

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Consider the following HTML, with the correct Vue 2 CDN links included.

```
<body>
  <div id="app" :class="['box', { active: isActive }]">
    Vue Component
  </div>
  <script>
    new Vue({
      el: '#app',
      data() {
        return {
          isActive: false,
        };
      },
    });
  </script>
</body>
```

What will be the final rendered class attribute of the <div> ?

Options :

box

active

box active

box inactive

Your score : 0

Discussions (0)Suggest Correction

Question 3 : 640653995597

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following is an example of ephemeral state in a web application?

Options :

A user's authentication token stored in local storage

A form input value that changes as the user types

The list of favorite items saved in a user's profile

A shopping cart saved between sessions

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 4 : 640653995582

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code

```
const juices = [
  { id: 1, name: "grape", rating: 8.1 },
  { id: 2, name: "apple", rating: 5.0 },
  { id: 3, name: "orange", rating: 6.9 },
  { id: 4, name: "banana", rating: 10 },
]

mapping = { "4": 1, "3": 2, "2": 3, "1": 4 }

juices.map((juice) => { return { ...juice, rank: mapping[juice.id] } })
  .sort((a, b) => a.rank - b.rank)
  .map((juice) => { console.log(juice.name) })
```

What will be the output of the code?

Options :

apple
orange
grape
banana

banana
grape
orange
apple

banana
orange
apple
grape

undefined

Your score : 0

Discussions (0)Suggest Correction

Question 5 : 640653995583

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code snippet

```
var name = 'Taylor'

const person = {
  name: 'Jeremy',
  talk() {
    return () => `${this.name} says Hello!`
  }
}

talkReturn = person.talk()
console.log(talkReturn())
```

What will be the output of the code?

Options :

undefined says Hello!

Jeremy says Hello!

Taylor says Hello!

ReferenceError

Your score : 0

Discussions (0)Suggest Correction

Advertisement

Remove Ads

Question 6 : 640653995587

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following code snippet

```
function createCounter() {  
  let count = 0;  
  
  return function() {  
    count++;  
    setTimeout(() => {  
      console.log(count);  
    }, 1000);  
  };  
}  
  
const counter = createCounter();  
counter();  
counter();  
counter();
```

What will be the output **after 1 second**?

Options :

1

1

1

1

1

2

3

3

3

3

Your score : 0

Discussions (0)Suggest Correction

Question 7 : 640653995590

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the below javascript program.

```
const obj = {  
  a: 10,  
  b() {  
    return this.a;  
  }  
};  
  
const c = obj.b;  
const d = obj.b.bind(obj);  
  
console.log(c(), d());
```

What will be the output of the above program?

Options :

10 10

undefined 10

10 undefined

undefined undefined

Error

Your score : 0

Discussions (0)Suggest Correction

Question 8 : 640653995595

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the below Vue component.

```
<template>
  <div>
    <p>{{ computedMessage }}</p>
    <button @click="update">Update</button>
  </div>
</template>

<script>
export default {
  data() {
    return {
      message: 'Initial'
    };
  },
  computed: {
    computedMessage() {
      return this.message + ' - Computed';
    }
  },
  methods: {
    update() {
      this.message = 'Updated';
    }
  }
};
</script>
```

What will be displayed in the <p> element, after the button with text “Update” is clicked?

Options :

"Initial - Computed"

"Updated - Computed"

"Initial - Computed Updated"

"Updated"

Your score : 0

Discussions (0)Suggest Correction

Question 9 : 640653995584

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following HTML, with the correct Vue 2 CDN links included.

```
<body>
  <div id="app">
    <p>pineapple 🍍 </p>
    <button @click="addPineapple">Buy</button>
    <p>Amount : {{amount}}</p>
  </div>
  <script>
    new Vue({
      el: '#app',
      data() {
        return {
          amount: '',
          price: 40,
        }
      },
      methods: {
        addPineapple() {
          this.amount += this.price;
        }
      }
    })
  </script>
</body>
```

What will be shown in the **amount** placeholder when the **Buy button** is clicked **two** times?

Options :

40

80

4040

undefined

Your score : 0

Discussions (0)Suggest Correction

Question 10 : 640653995586

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following HTML, with the correct Vue 2 CDN links included.

```
<div id="app">
  <p>Original Order: {{ customerOrder }}</p>
  <p>Updated Order: {{ updatedOrder }}</p>
  <server-component :order="customerOrder"
  @order-updated="updateOrder"></server-component>
</div>

<script>
  Vue.component('server-component', {
    props: ['order'],
    template: `
      <div>
        <button @click="modifyOrder">Send Updated Order</button>
      </div>
    `,
    methods: {
      modifyOrder() {
        this.$emit('order-updated', this.order + ' - Extra mayo');
      }
    }
  });

  new Vue({
    el: '#app',
    data() {
      return {
        customerOrder: 'Burger',
        updatedOrder: ''
      };
    },
    methods: {
      updateOrder(newOrder) {
        this.updatedOrder = newOrder;
      }
    }
  });
</script>
```

What will be displayed in the **<p>** tags after the **button** on the **server-component** is clicked?

Options :

Original Order: Burger
Updated Order:

Original Order:
Updated Order:

Original Order: Burger
Updated Order: - Extra mayo

Original Order: Burger
Updated Order: Burger - Extra mayo

Your score : 0

Discussions (0)Suggest Correction

Question 11 : 640653995588

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the below javascript program.

```
const numbers = [10, 20, 30];
const modifiedNumbers = numbers.reduce((acc, num) => {
  if (num % 2 === 0) {
    acc.push(num * 2);
  } else {
    acc.push(num / 2);
  }
  return acc;
}, []);

const finalOutput = modifiedNumbers.filter(num => num > 20);
console.log(finalOutput);
```

What will be the output of the above program?

Options :

[]

[10, 20, 30]

[20, 40, 60]

[40, 60]

[40]

Your score : 0

Discussions (0)Suggest Correction

Question 12 : 640653995596

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the below Vue component.

```
<template>
  <div>
    <ul>
      <li v-for="item in filteredItems" :key="item.id">{{ item.name }}</li>
    </ul>
  </div>
</template>

<script>
export default {
  data() {
    return {
      items: [
        { id: 1, name: "Item 1" },
        { id: 2, name: "Item 2" },
        { id: 3, name: "Item 3" },
      ],
      filterActive: true,
    };
  },
  computed: {
    filteredItems() {
      return this.filterActive
        ? this.items.filter((item) => item.id !== 2)
        : this.items;
    },
  },
};
</script>
```

What will be displayed in the `<ul>` when `filterActive` is true?

Options :

Item 1, Item 3

Item 2

Item 1, Item 2, Item 3

The list will be empty.

Your score : 0

Discussions (0)Suggest Correction

Question 13 : 640653995589

View Solutions (0)Total Mark : 3.00 | Type : MSQ

Which of the following statements is/are true about JavaScript's "this" keyword behavior in different contexts?

Options :

- ☐ In a regular function call, "this" refers to the global object in non-strict mode and "undefined" in strict mode.
- ☐ In an arrow function, "this" is lexically inherited from the enclosing execution context.
- ☐ Inside a method of an object, "this" always refers to the object itself, regardless of how the method is called.
- ☐ The value of "this" can be explicitly set using "call()", apply(), or "bind()" methods, inside a method of an object.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 14 : 640653995591

View Solutions (0)Total Mark : 3.00 | Type : MSQ

Considering the differences between "var", "let", and "const" in terms of scope, hoisting, and reassignment, which of the following statements is/are true?

Options :

- ☐ "var" is function-scoped, hoisted, and allows reassignments.
- ☐ "let" is block-scoped, hoisted, and allows reassignments.
- ☐ "const" is block-scoped, hoisted, does not allow reassignments, and its value must be assigned at the time of declaration.

☐ "let" and "const" behave identically except that const variables cannot be redeclared, while let variables can be redeclared in the same block.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 15 : 640653995592

View Solutions (0)Total Mark : 3.00 | Type : MSQ

Which of the following statements is/are true?

Options :

- ☐ call() and apply() immediately invoke the function, while bind() returns a newfunction that can be called later.
- ☐ call() accepts arguments as a comma-separated list, whereas apply() accepts a single array of arguments.
- ☐ bind() permanently sets the "this" context for a function, but the resultingfunction must still be explicitly called to execute.
- ☐ All three methods are used to permanently change the "this" context of functions.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 16 : 640653995593

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Which of the following scenario(s) represent ephemeral state(s) in a web application?

Options :

- ☐ The user's current scroll position on a webpage.
- ☐ The user's authentication token, saved in localStorage.
- ☐ The temporary state of a dropdown menu.
- ☐ All of these

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 17 : 640653995594

View Solutions (0)Total Mark : 2.00 | Type : MSQ

What are the differences between Vue's computed properties and methods?

Options :

- ☐ Computed properties are cached based on their reactive dependencies, whereas methods are recalculated every time they are called.
- ☐ Methods can be used to perform operations that do not need to be cached.
- ☐ Computed properties can be used as methods if they require parameters.
- ☐ Methods are always reactive and update automatically when their dependencies change.

Your score : 0

Question 1 : 640653827380

Total Mark : 0.00 | Type : MCQ

THIS IS QUESTION PAPER FOR THE SUBJECT "DIPLOMA LEVEL : MODERN APPLICATION DEVELOPMENT II (COMPUTER BASED EXAM)" ARE YOU SURE YOU HAVE TO WRITE EXAM FOR THIS SUBJECT? CROSS CHECK YOUR HALL TICKET TO CONFIRM THE SUBJECTS TO BE WRITTEN. (IF IT IS NOT THE CORRECT SUBJECT, PLS CHECK THE SECTION AT THE TOP FOR THE SUBJECTS REGISTERED BY YOU)

Options :

YES

NO

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 2 : 640653827381

[View Solutions \(0\)](#) Total Mark : 2.00 | Type : MCQ

Which of the following methods is not a valid DOM method in JavaScript?

Options :

`getElementById()`

`getElementByPropertyName()`

`getElementsByTagName()`

`getElementByClassName()`

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 3 : 640653827384

[View Solutions \(0\)](#) Total Mark : 2.00 | Type : MCQ

What will be the output of the following code snippet?

```
let result = "";
for (let i = 0; i < 3; i++) {
  for (let j = 0; j < 2; j++) {
    result += " " + i + j + " ";
  }
}
console.log(result);
```

Options :

0 1 1 2 2 3

0 1 1 2 2 3 3 4

0 1 2 3 4 5

00 01 10 11 20 21

Your score : 0

Discussions (0)Suggest Correction

Question 4 : 640653827387

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following statements best describes the ephemeral state?

Options :

Data that persists across browser sessions.

Data that is stored in a server-side database.

Temporary data that is not preserved across re-renders.

Data that is cached in the client's browser.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 5 : 640653827389

View Solutions (0) Total Mark : 2.00 | Type : MCQ

What is the difference between v-bind and v-model directives in Vue.js?

Options :

"v-bind" is used for one-way data binding, while "v-model" is used for two-way data binding.

"v-bind" is used for two-way data binding, while "v-model" is used for one-way data binding.

Both "v-bind" and "v-model" are used for one-way data binding.

Both "v-bind" and "v-model" are used for two-way data binding.

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Advertisement

[Remove Ads](#)

Question 6 : 640653827382

View Solutions (0) Total Mark : 3.00 | Type : MCQ

What will be the output of the following JavaScript code?

```
let x = undefined;
let y = null;
let z = NaN;
console.log(x == y, x === y, y == z, y === z, isNaN(z));
```

Options :

true false false true false

false false false false true

true false false false true

false true true false false

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 7 : 640653827383

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the below JavaScript program.

```
const a = 15;

const obj1 = {
  a: 20,
  b: function () {
    console.log(this.a);
    this.b();
  }
}

const obj2 = {
  a: 10,
  b: () => {
    console.log(this.a);
  }
}

obj1.b.apply(obj2);
```

What will be the output of the above program, if executed?

Options :

20

20

20

undefined

undefined
undefined

10
undefined

The program will crash due to maximum call stack size exceeded error.

Your score : 0

Discussions (0)Suggest Correction

Question 8 : 640653827385

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the below JavaScript program.

```
let users = [  
  { name: "Alice", age: 25 },  
  { name: "Bob", age: 22 },  
  { name: "Charlie", age: 30 },  
];  
users.sort((a, b) => a.age - b.age);  
console.log(users.map((user) => user.name).join(", "));
```

What will be the output when the code is executed?

Options :

Alice, Bob, Charlie

Bob, Alice, Charlie

Charlie, Alice, Bob

Charlie, Bob, Alice

Your score : 0

Discussions (0)Suggest Correction

Question 9 : 640653827386

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the below javascript program.

```
const words = ['apple', 'banana', 'orange', 'grape', 'kiwi'];
const result = words.map(word => word.length).filter(len => len > 5);
console.log(result);
```

What will be the output of the above program, if executed?

Options :

['apple', 'banana', 'orange', 'grape', 'kiwi']

[5, 6, 6, 5, 4]

['banana', 'orange']

[6, 6]

[5, 5]

[true, true]

Your score : 0

Discussions (0)Suggest Correction

Question 10 : 640653827388

View Solutions (0)Total Mark : 3.00 | Type : MCQ

What is state management in the context of a web application?

Options :

Organizing and storing data on the server-side database.

Handling and updating the state of client-side components and data.

Managing user session data using browser cookies.

Coordinating the state of HTTP requests and responses between client and server.

Your score : 0

Discussions (0) Suggest Correction Broken Format?

Question 11 : 640653827390

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript program.

```
const obj1={
  age: 29,
  toy: 'kite'
}

const obj2={
  __proto__: obj1,
  animal: 'dogs',
  members: 45
}

console.log(obj1.toy)
console.log(obj1.animal)
console.log(obj2.age)
console.log(obj2.members)
console.log(Object.keys(obj2))
```

What will be the output of the above program, if executed?

Options :

```
kite
undefined
29
45
['animal', 'members', 'age', 'toy']
```

```
kite
dogs
undefined
45
['age', 'toy', 'animal', 'members']
```

```
kite
dogs
undefined
45
['age', 'toy']
```

```
kite
undefined
29
45
['animal', 'members']
```

Your score : 0

Discussions (0)Suggest Correction

Question 12 : 640653827395

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following html.

```
<div id="app">
  <p>{{ message }}</p>
  <button @click="updateMessage">Click me</button>
</div>

<script>
new Vue({
  el: '#app',
  data: {
    message: 'Hello!'
  },
  methods: {
    updateMessage() {
      this.message += '!';
    }
  }
});
</script>
```

Assuming vue cdn has been added to the html and the html format is correct. What would be the output on the screen after clicking the button twice?

Options :

Hello

Hello!

Hello!!

Hello!!!

Your score : 0

Discussions (0)**Suggest Correction**

Question 13 : 640653827391

View Solutions (0) Total Mark : 3.00 | Type : MSQ

Which of the following is/are correct definition(s) of an arrow function that accepts a number and returns its square?

Options :

☐

```
let func = (num) => return num1*num1;
```

☐

```
let func = (num) => { num1*num1; }
```

☐

```
let func = (num) => num1*num1;
```

☐

```
let func = (num) => { return num1*num1; }
```

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 14 : 640653827392

[View Solutions \(0\)](#) Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code embedded in the body of the HTML document given below.

```
<html>
<body>
  <div id="mybox">Test JS</div>
  <script>
    let count = 0;
    let change = setInterval(()=>{
      let box = document.getElementById('mybox');
      if(count % 2 == 1){
        box.style.backgroundColor = 'red';
        count++;
      }
      else if(count % 3 == 1){
        box.style.backgroundColor = 'green';
        count++;
      }
      else{
        box.style.backgroundColor = 'yellow';
        count++;
      }
    }, 1000)
  </script>
</body>
</html>
```

If the document is rendered on the browser, what will be the sequence of background colors taken by the element with id="mybox" in the first 6 seconds of execution?

Options :

Red → Green → Yellow → Red → Green → Yellow

Red → Green → Red → Yellow → Red → Yellow

Yellow → Green → Yellow → Green → Yellow → Green

Yellow → Red → Yellow → Red → Green → Red

Your score : 0

Discussions (0)Suggest Correction

Question 15 : 640653827393

[View Solutions \(0\)](#) Total Mark : 4.50 | Type : MCQ

Consider the below JavaScript program.

```
class Region{
  constructor(region){
    this.region = region;
  }
  get describe(){
    return `${this.region} is one of the major geographical regions.`
  }
}

class Country extends Region {
  constructor(region, country, nation){
    super(region)
    this.country = country;
    this.nation = nation;
  }

  get describe(){
    return `${this.country} is a ${this.nation} nation in the region of
    ${this.region}.`
  }
}

let Australia = new Region('Australia and NZ', 'Australia', 'developed')
let Germany = new Country('Europe', 'Germany', 'developed')
console.log(Australia.describe)
console.log(Germany.describe)
```

What will be the output of the above program, if executed?

Options :

Australia is a developed nation in the region of Australia and NZ.
Germany is a developed nation in the region of Europe.

Australia and NZ is one of the major geographical regions.
Germany is one of the major geographical regions.

Australia is a developed nation in the region of Australia and NZ.
Germany is one of the major geographical regions.

Australia and NZ is one of the major geographical regions.
Germany is a developed nation in the region of Europe.

Your score : 0

Discussions (0)Suggest Correction

Question 16 : 640653827394

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following Vue application with markup index.html and JavaScript file app.js.

File: index.html

```
<div id = "app">
  <div>Welcome to Frontend Development</div>
  <new>Vue is a Frontend Framework</new>
</div>
<script src="script.js"></script>
```

File: script.js

```
Vue.component('new', {
  template : `<div>
    <slot>Vue is JS Framework</slot>
    <div>Learn Vue 2 and Vue 3</div>
  </div>
`
});

new Vue({
  el : "#app",
})
```

What will be rendered on the browser screen?

Options :

Welcome to Frontend Development
Vue is a JS Framework
Vue is a Frontend Framework
Learn Vue 2 and Vue 3

Welcome to Frontend Development
Vue is a Frontend Framework
Vue is a JS Framework
Learn Vue 2 and Vue 3

Welcome to Frontend Development
Vue is a Frontend Framework
Learn Vue 2 and Vue 3

Welcome to Frontend Development
Vue is a JS Framework
Learn Vue 2 and Vue 3

Your score : 0

Discussions (0)Suggest Correction

Question 17 : 640653827396

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following html.

```
<div id="app">
  <parent-component :title="parentTitle">
    <template slot="header">
      <h2>{{ headerTitle }}</h2>
    </template>
  </parent-component>
</div>

<script>
Vue.component('parent-component', {
  props: ['title'],
  template: `
    <div>
      <h1>{{ title }}</h1>
      <slot name="header"></slot>
      <p>Main Content</p>
    </div>
  `
});

new Vue({
  el: '#app',
  data: {
    parentTitle: 'Parent Component Title',
    headerTitle: 'Header Content'
  }
});
</script>
```

Assuming Vue CDN has been added to the HTML and the HTML format is correct.
What would be the output on the screen?

Options :

Parent Component Title
Main Content

Parent Component Title

Header Content

Main Content

Parent Component Title

<h2>{{ headerTitle }}</h2>

Main Content

Header Content

Main Content

Your score : 0

Question 1 : 640653738012

Total Mark : 0.00 | Type : MCQ

THIS IS QUESTION PAPER FOR THE SUBJECT "DIPLOMA LEVEL : MODERN APPLICATION DEVELOPMENT II (COMPUTER BASED EXAM)" ARE YOU SURE YOU HAVE TO WRITE EXAM FOR THIS SUBJECT? CROSS CHECK YOUR HALL TICKET TO CONFIRM THE SUBJECTS TO BE WRITTEN. (IF IT IS NOT THE CORRECT SUBJECT, PLS CHECK THE SECTION AT THE TOP FOR THE SUBJECTS REGISTERED BY YOU)

Options :

YES

NO

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 2 : 640653738013

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code. What will be logged on to the console once the code is executed?

```
function checkThis() {  
    return this.name  
}  
  
const Obj1 = {  
    name: 'Obj1',  
    checkThis: checkThis,  
}  
  
const Obj2 = {  
    name: 'Obj2',  
    checkThis: checkThis,  
}  
  
console.log(Obj2.checkThis(), Obj1.checkThis.call(Obj2))
```

Options :

Obj1 Obj1

Obj1 Obj2

Obj2 Obj1

Obj2 Obj2

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 3 : 640653738014

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code. What will be logged on to the console once the code is executed?

```
const stateManager = function () {  
  let defaultState = false  
  function alterState() {  
    defaultState = !defaultState  
  }  
  return {  
    currentState() {  
      return defaultState  
    },  
    changeState() {  
      alterState()  
    },  
  }  
}  
  
const sm1 = stateManager()  
sm1.changeState()  
const sm2 = stateManager()  
  
console.log(sm1.currentState(), sm2.currentState())
```

Options :

true true

true false

false true

false false

Your score : 0

Discussions (0)Suggest Correction

Question 4 : 640653738015

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Consider the following JavaScript code. What will be logged on to the console once the code is executed?

```
const player = {  
  name: 'Rohit',  
  state: 'Maharashtra',  
}  
  
const batsman = Object.create(player)  
  
console.log(batsman.name)
```

Options :

Rohit

undefined

null

None of these

Your score : 0

Discussions (0)[Suggest Correction](#)

Question 5 : 640653738016

[View Solutions \(0\)](#) Total Mark : 2.00 | Type : MCQ

Consider the following JavaScript code. What will be logged on to the console once the code is executed?

```
const emails = [
  'user1@study.iitm.ac.in',
  'user2@gmail.com',
  'user3@study.iitm.ac.in',
]

const studentsEmail = emails.filter((email) =>
  email.endsWith('study.iitm.ac.in')
)
console.log(studentsEmail)
```

Options :

[\[user1@study.iitm.ac.in, user2@gmail.com, user3@study.iitm.ac.in \]](#)

[\[user1@study.iitm.ac.in, user3@study.iitm.ac.in \]](#)

[\[user2@gmail.com, user3@study.iitm.ac.in \]](#)

[\[user2@gmail.com \]](#)

Your score : 0

Discussions (0)[Suggest Correction](#)

[Advertisement](#)

[Remove Ads](#)

Question 6 : 640653738017

[View Solutions \(0\)](#) Total Mark : 3.00 | Type : MCQ

Consider the following Vue application with markup index.html and JavaScript app.js

index.html

```
<body>
  <div id="app"></div>
  <script
src="https://cdn.jsdelivr.net/npm/vue@2/dist/vue.js"></script>
  <script src="./app.js"></script>
</body>
```

app.js

```
new Vue({
  el: '#app',
  template: `
<div>
  {{text}}
  <div>
    <input type="text" v-model="userInput" />
    <div id="match">
      {{hasMatched?"Not Matched":"Matched"}}
    </div>
  </div>
</div>`,
  data: {
    text: 'This is text',
    userInput: null,
  },
  computed: {
    hasMatched() {
      return this.text.startsWith(this.userInput)
    },
  },
})
```

Suppose the application is running on "<http://localhost:8080/>". If the User inputs "This" in the input box. What will be rendered inside the div with id "match"?

Options :

Not Matched

Matched

undefined

null

Your score : 0

Discussions (0)Suggest Correction

Question 7 : 640653738018

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following Vue application with markup index.html and JavaScript app.js

index.html

```
<body>
  <div id="app"></div>
  <script
src="https://cdn.jsdelivr.net/npm/vue@2/dist/vue.js"></script>
  <script src="./app.js"></script>
</body>
```

app.js

```
new Vue({
  el: '#app',
  template: `<div>
<div id="holiday">{{isHoliday?"Holiday":"Not Holiday"}}</div>
<button @click="increeseCount">Increese Count</button>
</div>`,
  data: {
    count: 1,
    isHoliday: false,
  },
  watch: {
    count() {
      if (this.count % 5 == 0) {
        this.isHoliday = true
      }
    },
  },
  methods: {
    increeseCount() {
      this.count += 6
    },
  },
})
```

Suppose the application is running on "<http://localhost:8080>" if the user clicks on button "Increese Count" 5 times. What will be rendered inside the div with id "holiday"?

Options :

Holiday

Not Holiday

true

false

Your score : 0

Discussions (0)Suggest Correction

Question 8 : 640653738019

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code. What will be logged on to the console once the code is executed?

```
class Album {
  constructor(creator, albumName) {
    this.creator = creator
    this.albumName = albumName
    this.songs = []
  }
  addSong(song) {
    this.songs.push(song)
  }
}

class Song {
  constructor(name, duration) {
    this.name = name
    this.duration = duration
    this.album = null
  }
  addAlbum(album) {
    this.album = album
  }
}

a1 = new Album('creator1', 'Album1')
s1 = new Song('Song1')
a1.addSong(s1)
console.log(a1.songs.length)
```

Options :

0

1

2

None of these

Your score : 0

Discussions (0)Suggest Correction

Question 9 : 640653738020

[View Solutions \(0\)](#) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code. What will be logged on to the console once the code is executed?

```
class Album {
  constructor(creator, albumName) {
    this.creator = creator
    this.albumName = albumName
    this.songs = []
  }
  addSong(song) {
    this.songs.push(song)
  }
}

class Song {
  constructor(name, duration) {
    this.name = name
    this.duration = duration
    this.album = null
  }
  addAlbum(album) {
    this.album = album
  }
}

a1 = new Album('creator1', 'Album1')
s1 = new Song('Song1')

s1.addAlbum(a1)
console.log(a1.songs.length)
```

Options :

0

1

2

None of these

Your score : 0

Discussions (0)Suggest Correction

Question 10 : 640653738021

View Solutions (0)Total Mark : 3.00 | Type : MSQ

Which of the following statement(s) is/are true regarding JavaScript language?

Options :

- ☐ Any variable declared using "var" keyword has a global scope.
- ☐ Any variable declared using "let" keyword has a block based scope.
- ☐ The language supports the concept of arrays.
- ☐ The language uses a call stack to execute the functions in the program.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 11 : 640653738022

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the below JavaScript program.

```
const obj = [{
  id: "1"
}, {
  id: "2"
}, {
  id: "3"
}, {
  id: " 4"
}, {
  id: " 5 "
}];
const finalObj = obj.map((element) => element.id).map((element) =>
element.trim()).map((element) => parseInt(element)).filter((element) =>
element % 2);
console.log(finalObj, finalObj.length);
```

What will be the output of the above program, if executed?

Options :

['1', '3', '5'] 3

['2', '4'] 2

[1, 3, 5] 3

[2, 4] 2

['1', '2', '3', '4', '5'] 5

[1, 2, 3, 4, 5] 5

Your score : 0

Discussions (0)Suggest Correction

Question 12 : 640653738023

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Which of the following is/are example(s) of application state (i.e., system as seen by an individual user)?

Options :

☐ Shopping cart of an e-commerce application

- ☐ Loading icons
- ☐ Currently selected tab in a multipage / document
- ☐ Followed news items in a news app

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 13 : 640653738024

View Solutions (0)Total Mark : 3.00 | Type : MSQ

Which of the following statement(s) is/are true?

Options :

- ☐ The computed properties are auto triggered when any of the reactivdependencies changes.
- ☐ The computed properties are cached based on their reactive dependencies.
- ☐ The watchers need to be manually triggered when the watched property isassigned a new value.
- ☐ The watchers can be defined globally, and apply to all instances of a Vuecomponent.

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 14 : 640653738025

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Which of the following is a valid function definition to return the sum of 2 numbers passed as parameter?

Options :

- let add = (x, y) $\Rightarrow$ x + y
- let add = (x, y) $\Rightarrow$ { x + y; }
- function add (x, y) { return x + y; }

All of these

Your score : 0

Discussions (2)[Suggest Correction](#)[Broken Format?](#)

Question 15 : 640653738026

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Consider the below JavaScript program.

```
const property1 = 10;
const obj1 = {
  property1: 20,
  property2: function () {
    console.log(property1, this.property1);
    return this.property1;
  }
}

const obj2 = {
  property1: 30,
  property2: () => {
    console.log(property1, this.property1);
    console.log(this.property2);
  }
}
obj2.property2();
```

What will be the output of the above program, if executed?

Options :

10 3020

10 30undefined

10 undefined30

10 undefinedundefined

10 3010 2020

10 undefined10 undefinedundefined

Your score : 0

Discussions (0)Suggest Correction

Question 16 : 640653738027

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following is not a valid Vue directive?

Options :

v-model

v-click

v-if

v-show

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 17 : 640653738028

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the below javascript program.

```
const a = 2;
const b = "";

const obj1 = {
  property1: 10,
  property2: 20
}

const obj2 = {
  a: 1,
  b: 2,
  ...(a && !b && { obj1 })
};

console.log(obj2);
```

What will be the output of the above program, if executed?

Options :

{ a: 1, b: 2, property1: 10, property2: 20 }

{ a: 1, b: 2, obj1: { property1: 10, property2: 20 } }

{ property1: 10, property2: 20 }

{ a: 1, b: 2 }

Your score : 0

Question 1 : 640653669213

Total Mark : 0.00 | Type : MCQ

THIS IS QUESTION PAPER FOR THE SUBJECT "DIPLOMA LEVEL : MODERN APPLICATION DEVELOPMENT II (COMPUTER BASED EXAM)" ARE YOU SURE YOU HAVE TO WRITE EXAM FOR THIS SUBJECT? CROSS CHECK YOUR HALL TICKET TO CONFIRM THE SUBJECTS TO BE WRITTEN. (IF IT IS NOT THE CORRECT SUBJECT, PLS CHECK THE SECTION AT THE TOP FOR THE SUBJECTS REGISTERED BY YOU)

Options :

YES

NO

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 2 : 640653669214

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following statements is true regarding, var, let & const?

Options :

A variable created using "var" is always added as a property to the global object.

A variable created using "let" is never added as a property to the global object.

A variable created using "const" is not hoisted.

All of these

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 3 : 640653669216

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following is not a valid IIFE (Immediately Invoked Function Expression)?

Options :

```
(function ( ) {  
    // some code here  
})();
```

```
( ( ) => {  
    // some code here  
})();
```

```
function ( ) {  
    // some code here  
} ( );
```

```
(function myIIFE (arg1, arg2) {  
    // some code here  
})(10, 20);
```

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 4 : 640653669220

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following is not an example of application or UI (ephemeral) state?

Options :

User Preferences & Recommendations

Loading Icons

Dashboard Displays

User Database of NPTEL

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 5 : 640653669222

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Which of the following statements are correct regarding a variable declared using var keyword?

Options :

Variable is always globally scoped.

Variable declared inside the function can be accessed outside the function.

Variable declared inside a function can only be accessed inside the function.

None of these

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Advertisement

Remove Ads

Question 6 : 640653669215

View Solutions (0) Total Mark : 3.00 | Type : MSQ

Which of the following is/are correct definition(s) of an arrow function that accepts 2 numbers and return the addition of their squares?

Options :

- ☐ let func = (num1, num2) ⇒ return num1*num1 + num2*num2;
- ☐ let func = (num1, num2) ⇒ num1*num1 + num2*num2;
- ☐ let func = (num1, num2) ⇒ { return num1*num1 + num2*num2; }
- ☐ let func = (num1, num2) ⇒ { num1*num1 + num2*num2; }

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Question 7 : 640653669217

View Solutions (0) Total Mark : 3.00 | Type : MSQ

Which of the following statement(s) is/are true regarding event loop in javascript?

Options :

- ☐ The event loop makes sure that each function is processed (or executed) completely before any other function is executed.
- ☐ The event loop takes the function from the callback queue, and sends the function to the call stack for execution.
- ☐ The event loop can stop any function in running state to allow some other function to run on priority.
- ☐ All of these

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Question 8 : 640653669219

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Which of the following shows the correct output for the below javascript program?

```
var a = 100;

const obj1 = {
  a : 10,
  b : 20,

  func : function (a) {
    console.log("Value:", a);
  }
}

const obj2 = {
  a : 40,
  b : 50,

  func : function (a) {
    this.func(a);
  }
}

obj2.func.apply(obj2, []);
```

Which of the following shows the correct output for the below javascript program?

Options :

Value: 100

The program will crash due to repeated function calls

Value: 40

Value: 10

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 9 : 640653669224

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript program.

```
const userDetails = {  
  name: 'user1',  
  email: 'user1@email.com',  
  password: '12345',  
}  
  
function user({ userName: name = 'Name1', password }) {  
  return `Username: ${name}, Password: ${password}`  
}  
  
console.log(user(userDetails))
```

Consider the following JavaScript program. What will be logged on to the console?

Options :

Username: Name1, Password: 12345

Username: user1, Password: 12345

Username: Name1, Password: undefined

Username: user1, Password: undefined

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 10 : 640653669226

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code.

```

class Ball {
  constructor(batsman, run = 0, extra = false) {
    this.batsman = batsman
    this.run = run
    this.extra = extra
  }
}

class Over {
  constructor(overNo) {
    this.overNo = overNo
    this.balls = []
  }
}

class Inning {
  constructor(team, striker, nonStriker) {
    this.team = team
    this.striker = striker
    this.nonStriker = nonStriker
    this.overs = []
    this.currentOver = new Over(1)
  }
  changeStrike() {
    ;[this.striker, this.nonStriker] = [this.nonStriker,
this.striker]
  }
  changeOver() {
    this.currentOver = new Over(this.currentOver.overNo + 1)
    this.changeStrike()
  }
}

const inning = new Inning('India', 'Rohit', 'Gill')
const runs = [0, 4, 3, 6, 2, 6, 4, 1, 3]
runs.forEach((run, index) => {
  const ball = new Ball(inning.striker, run)
  inning.currentOver.balls.push(ball)
  if (run % 2 == 0) {
    inning.changeStrike()
  }
  if ((index + 1) % 3 == 0) {
    inning.overs.push(inning.currentOver)
    inning.changeOver()
  }
})

```

Consider the following JavaScript code. What will be logged on to the console for the statement "console.log(inning.overs[0].balls[2].batsman)"?

Options :

Rohit

Gill

Virat

None of these

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 11 : 640653669227

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the following JavaScript code.

```

class Ball {
  constructor(batsman, run = 0, extra = false) {
    this.batsman = batsman
    this.run = run
    this.extra = extra
  }
}

class Over {
  constructor(overNo) {
    this.overNo = overNo
    this.balls = []
  }
}

class Inning {
  constructor(team, striker, nonStriker) {
    this.team = team
    this.striker = striker
    this.nonStriker = nonStriker
    this.overs = []
    this.currentOver = new Over(1)
  }
  changeStrike() {
    ;[this.striker, this.nonStriker] = [this.nonStriker,
this.striker]
  }
  changeOver() {
    this.currentOver = new Over(this.currentOver.overNo + 1)
    this.changeStrike()
  }
}

const inning = new Inning('India', 'Rohit', 'Gill')
const runs = [0, 4, 3, 6, 2, 6, 4, 1, 3]
runs.forEach((run, index) => {
  const ball = new Ball(inning.striker, run)
  inning.currentOver.balls.push(ball)
  if (run % 2 == 0) {
    inning.changeStrike()
  }
  if ((index + 1) % 3 == 0) {
    inning.overs.push(inning.currentOver)
    inning.changeOver()
  }
})

```

Consider the following JavaScript code. What will be logged on to the console for the statement "console.log(inning.currentOver.overNo)"?

Options :

- 1
- 2
- 3
- 4

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 12 : 640653669218

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Which of the following is not a correct way to destructure (or unpack) an array?

Options :

```
const array = [1, 2, 3, 4, 5]
const [a, b, c] = array
```

```
const array = [1, 2, 3, 4, 5]
const [a, , c] = array
```

```
const array = [1, 2, 3, 4, 5]
const [a, ...remaining, c] = array
```

```
const array = [1, 2, 3, 4, 5]
const [a, b, ...remaining] = array
```

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 13 : 640653669221

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following Vue application with markup index.html and javascript file app.js.

index.html:

```
<div id = "app">
  Some Data for App
  <new>Fallback Data</new>
</div>
<script src = "app.js"> </script>
```

app.js:

```
Vue.component('new', {
  template : `<div>
    <slot>Main Data</slot>
    <h1>End of Data</h1>
  </div>
`
});

new Vue({
  el : "#app",
})
```

What will be rendered on the browser screen (ignore the formatting and styling)?

Consider the following Vue application with markup index.html and javascript file app.js.

Options :

Some Data for App
Fallback Data
End of Data

Some Data for App
Main Data
End of Data

Some Data for App
Fallback Data
Main Data
End of Data

Some Data for App
End of Data

A warning will be issue for using an undefined tag, i.e., new

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 14 : 640653669223

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code.

```
let sayHello = 'Hello from outside'
var greet = 'Greetings from outside'

{
  let sayHello = 'Hello from inside'
  var greet = 'Greetings from inside'
}

console.log(sayHello)
console.log(greet)
```

Consider the following JavaScript code. What will be logged on the console?

Options :

Hello from outside
Greetings from outside

Hello from inside
Greetings from inside

Hello from outside
Greetings from inside

Hello from inside
Greetings from outside

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 15 : 640653669225

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript code.

```
function getName() {
  return this.userName
}

const getEmail = () => this.email

const User1 = { userName: 'Test User1', email: 'user1@email.com' }
const User2 = { userName: 'Test User2', email: 'user2@email.com' }

User1.getName = getName
User2.getEmail = getEmail

console.log(User1.getName())
console.log(User2.getEmail())
```

Consider the following JavaScript code. What will be logged on to the console?

Options :

Test User1
Undefined

Test User1
[user2@email.com](#)

Test User1
Test User2

Test User2
[user2@email.com](#)

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 16 : 640653669228

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following Vue application with markup index.html and JavaScript app.js

index.html

```
<div id="app"></div>
```

app.js

```
new Vue({
  el: '#app',
  template: '<div> Total Count: {{count}}</div>',
  data: {
    count: 0,
  },
  beforeCreate() {
    this.count += 1
  },
  created() {
    this.count += 1
  },
  beforeMount() {
    this.count += 1
  },
  mounted() {
    this.count += 1
  },
})
```

Suppose the application is running on "<http://127.0.0.1:8080>". What will be rendered by the browser?

Consider the following Vue application with markup index.html and JavaScript app.js

Options :

Total Count: 2

Total Count: 3

Total Count: 4

Total Count: 5

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 17 : 640653669229

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following Vue application with markup index.html and JavaScript app.js

index.html

```
<div id="app"></div>
```

app.js

```
const Counter = {
  template: `<div> <b>{{counter}}</b><button @click='changeStatus'>
Click Me </button></div>`,
  props: ['initial'],
  data() {
    return {
      wasClicked: false,
      counter: this.initial,
    }
  },
  methods: {
    changeStatus() {
      this.wasClicked = !this.wasClicked
    },
  },
  watch: {
    wasClicked(val) {
      if (val) {
        this.counter += 1
      }
    },
  },
},

new Vue({
  el: '#app',
  template: `<div><counter :initial=3 /></div>`,
  components: {
    counter: Counter,
  },
})
```

Suppose the application is running on "<http://127.0.0.1:8080>". What will be the value of data property "counter" of "Counter" component if the user clicks on click me button 5 times.

Consider the following Vue application with markup index.html and JavaScript app.js

Options :

0

5

6

8

Your score : 0

Question 1 : 640653577711

Total Mark : 0.00 | Type : MCQ

THIS IS QUESTION PAPER FOR THE SUBJECT "**DIPLOMA LEVEL : MODERN APPLICATION** DEVELOPMENT II (COMPUTER BASED EXAM)" ARE YOU SURE YOU HAVE TO WRITE EXAM FOR THIS SUBJECT? CROSS CHECK YOUR HALL TICKET TO CONFIRM THE SUBJECTS TO BE WRITTEN. (IF IT IS NOT THE CORRECT SUBJECT, PLS CHECK THE SECTION AT THE TOP FOR THE SUBJECTS REGISTERED BY YOU)

Options :

YES

NO

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 2 : 640653577712

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Suppose you are given the below HTML.

```
<body>
  <p id = "id1" class = "class1">Content A</p>      <!-- Statement 1 -->
  <p id = "id2" class = "class1">Content B</p>      <!-- Statement 2 -->
</body>
```

Suppose you are given the below HTML. Which of the following code(s) can be used to access the HTML paragraph element at "Statement 1" using JavaScript?

Options :

- ☐ document.getElementById("id2")
- ☐ document.getElementById("id1")
- ☐ document.getElementsByClassName("class1")
- ☐ document.getElementsByClassName("class1")[0]

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 3 : 640653577717

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Which of the following is/are not example(s) of system level state?

Options :

- ☐ Gmail Inbox of a given user
- ☐ User database of LinkedIn
- ☐ YouTube Recommendations after signing in
- ☐ Countdown timer in a game

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 4 : 640653577720

View Solutions (0) Total Mark : 2.00 | Type : MSQ

Which of the following statements is/are true?

Options :

- ☐ Lexical scope describes how the parser resolves the variable name in case of nested functions.
- ☐ Inner functions have access to the outer functions variables in JavaScript.
- ☐ Inner functions do not have access to the outer functions variables in JavaScript.
- ☐ None of these.

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Question 5 : 640653577713

View Solutions (0) Total Mark : 2.00 | Type : MCQ

Which of the following statements is correct regarding "<noscript>" tag in HTML?

Options :

This tag is used to insert the JavaScript code to be run when the page opens.

This tag is used to insert HTML, if the browser doesn't support script or is disabled.

This tag, if used in a web page, does not let the browser cache the page contents.

None of these

Your score : 0

Discussions (0) [Suggest Correction](#)

[Advertisement](#)

[Remove Ads](#)

Question 6 : 640653577715

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the below JavaScript program, and predict the output, if executed.

```
class Person {
  constructor(name) {
    this.name = name;
    this.age = 23;
  }
  static fromJson(obj) {
    let new_obj = new Person(obj.name);
    new_obj.sound = obj.sound;
    return new_obj;
  }
}
result = new Person('Abhi');
console.log(Person.fromJson(JSON.parse(JSON.stringify(result))).constructor.name);
```

Consider the below JavaScript program, and predict the output, if executed.

Options :

Person

Abhi

constructor

Reference Error

Your score : 0

Discussions (0) [Suggest Correction](#) [Broken Format?](#)

Question 7 : 640653577716

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the below JavaScript program, and predict the output, if executed.

```

let x = 50;
const obj1 = {
  x : 10,
  func : function () {
    console.log(this.x)
  }
}

const obj2 = {
  x : 20,
  func : () => {
    function abc () {
      console.log(x, "and", this.x)
      obj1.func.call(this)
    }
    abc()
  }
}

obj2.func()

```

Consider the below JavaScript program, and predict the output, if executed.

Options :

50 and 20
10

50 and 20
undefined

50 and undefined
undefined

50 and undefined
10

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 8 : 640653577718

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

index.html:

```
<body>
  <div id = "app">
    <ol>
      <li v-for="item in items" :key="item.id">{{ item.name }}</li>
    </ol>
  </div>
</body>
<script src = "app.js"> </script>
```

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

app.js:

```
const a = new Vue({
  el : '#app',
  data : {
    items: [
      { id: 1, name: 'App Dev I Theory' },
      { id: 2, name: 'App Dev I Project' },
      { id: 3, name: 'App Dev II Theory' },
      { id: 4, name: 'App Dev II Project' }
    ]
  },
})
```

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js". Suppose you open the "index.html" file in a browser, what will be rendered by the browser?

Options :

App Dev II Project
App Dev II Theory
App Dev I Project
App Dev I Theory

App Dev I Theory
App Dev I Project

App Dev II Theory
App Dev II Project

App Dev I Theory
App Dev I Project
App Dev II Theory
App Dev II Project

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 9 : 640653577719

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

index.html:

```
<body>
  <div id = "app">
    <ol>
      <li v-for="item in items" :key="item.id">
        <blog-post :post-title = "item.name" :post-content =
"item.message"> </blog-post>
      </li>
    </ol>
  </div>
</body>
<script src = "app.js"> </script>
```

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

app.js:

```
Vue.component('blog-post', {
```

Consider the below Vue application with markup file "index.html", and javascript file "app.js". Suppose you open the "index.html" file in a browser, what will be rendered by the browser?

Options :

1. IITM BS

2. IITM ES

3. NPTEL

1. IITM BS

The World's first 4-year BS degree in DS and Applications

2. IITM ES

Learn Electronic Systems from top-notch IIT Madras faculty

3. NPTEL

Online Learning Initiatives by IITs and IISc

1. The World's first 4-year BS degree in DS and Applications

2. Learn Electronic Systems from top-notch IIT Madras faculty

3. Online Learning Initiatives by IITs and IISc

A. NPTEL

Online Learning Initiatives by IITs and IISc

B. IITM ES

Learn Electronic Systems from top-notch IIT Madras faculty

C. IITM BS

The World's first 4-year BS degree in DS and Applications

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 10 : 640653577721

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript program.

```
function doSomething(n, ...params) {  
  return params  
    .map((x) => {  
      return x ** n  
    })  
    .sort()  
}  
  
console.log(doSomething(2, 5, 10))
```

Consider the following JavaScript program. What will be logged on to console?

Options :

[5, 10]

[25, 100]

[10, 5]

[100, 25]

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 11 : 640653577722

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript program.

```
function coolerPlace({...obj }) {  
  let tmp = 0  
  let cty = null  
  Object.entries(obj).forEach(([city, temp]) => {  
    if (temp > tmp) {  
      cty = city  
    }  
  })  
  return cty  
}  
console.log(coolerPlace({ UP: 37, Delhi: 40 })))
```

Consider the following JavaScript program. What will be logged on to console?

Options :

UP

Delhi

37

40

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 12 : 640653577723

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript program.

```

const address1 = {
  state: 'Tamil Nadu',
  city: 'Chennai',
  place: 'IIT Madras',
  getAddress() {
    return `State: ${this.state}, city: ${this.city},
place:${this.place}`
  },
}

const address3 = {
  place: 'Taramani',
  __proto__: address1,
}

console.log(address3.getAddress())

```

Consider the following JavaScript program. What will be logged on to console?

Options :

- State: Tamil Nadu, city: Chennai, place: Taramani
- State: Tamil Nadu, city: Chennai, place: IIT Madras
- State: , city: , place:Taramani
- State: , city: , place:

Your score : 0

Discussions (0)[Suggest Correction](#)[Broken Format?](#)

Question 13 : 640653577724

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Consider the following JavaScript program.

```
let x = 1
let y = 2
{
  let x = 4
  let y = 5
}
function outer() {
  function inner() {
    return x + y
  }
  return inner
}
console.log(outer()())
```

Consider the following JavaScript program. What will be logged on to console?

Options :

9

3

NaN

undefined

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 14 : 640653577714

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the below JavaScript program, and predict the output. Also, predict the number of times the while loop will run.

```
function do_something(arr, val){
  var i1 = 0;
  var i2 = arr.length;
  while(i2 > i1){
    var i3 = Math.floor((i1 + i2)/2);
    if(val > arr[i3]){
      i1 = i3 + 1;
    }
    else if(val < arr[i3]){
      i2 = i3;
    }
    else{
      return true;
    }
  }
  return false;
}

result = do_something([3, 6, 34, 39, 48, 56, 78, 87], 40)
console.log(result)
```

Consider the below JavaScript program, and predict the output. Also, predict the number of times the while loop will run.

Options :

- ☐ true
The while loop will run 3 times
- ☐ false
The while loop will run 4 times
- ☐ false
The while loop will run 3 times
- ☐ true
The while loop will run 4 times

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 15 : 640653577725

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

app.js

```
new Vue({  
  el: '#app',
```

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

index.html

```
<div id="app"></div>
  <script
src="https://cdn.jsdelivr.net/npm/vue@2/dist/vue.js"></script>
<script src="./app.js"></script>
```

Suppose the application is running on <http://localhost:8080>.

What will be rendered by the browser?

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

Options :

The nearest city to you is: City1

The nearest city to you is: City2

The nearest city to you is: City3

The nearest city to you is: City4

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 16 : 640653577726

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

app.js

```
new Vue({
  el: '#app',
  template: `<div>
    <input type='text' v-model='num'></input>
    <div id='lon'>Lucky or not? {{lucky?'Lucky':'Not Lucky'}}</div>
  </div>`,
  data: {
    num: 1,
    prev: 0,
    current: 1,
    lucky: false,
  },
  watch: {
    num(num1, num2) {
      if (num1 == '') {
        return
      }
      this.prev = this.current
      this.current = Number(num1)
      this.current > this.prev ? (this.lucky = true) : (this.lucky =
false)
    },
  },
})
```

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

index.html

```
<div id="app"></div>
  <script
src="https://cdn.jsdelivr.net/npm/vue@2/dist/vue.js"></script>
  <script src="./app.js"></script>
```

Suppose the application is running on '<http://localhost:8080>'. Suppose the user inputs 7 and then 5. What will be rendered inside the div with id 'lon'?

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

Options :

Lucky or not? Lucky

Lucky or not? Not Lucky

Lucky or not?

None of these

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 17 : 640653577727

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

app.js

```
const Sender = {
  template: `<div> Message: <input type='text'
v-model='message'></input> </div>`,
  data() {
    return {
      message: null,
    }
  },
  watch: {
    message(msg) {
      this.$emit('newmsg', this.message)
    },
  },
}

const Receiver = {
  template: '<div id="msg"> {{msg}} </div>',
  props: ['msg'],
}

new Vue({
  el: '#app',
  template: `<div>
<Sender @newmsg = 'updateMessage' />
<Receiver :msg='message' />
</div>`,
  data: {
    message: null,
  },
  methods: {
    updateMessage(msg) {
      this.message = msg.split('').reverse().join('').toUpperCase()
    },
  },
  components: {
    Sender,
    Receiver,
  },
})
```

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

index.html

```
<div id="app"></div>
  <script
src="https://cdn.jsdelivr.net/npm/vue@2/dist/vue.js"></script>
  <script src="./app.js"></script>
```

Suppose the application is running on <http://localhost:8080>. If the user inputs 'hello' inside the input box, what will be rendered inside the div with ID 'msg'?

Consider the below Vue application with markup file "index.html", and JavaScript file "app.js".

Options :

OLLEH

Your score : 0

Question 1 : 640653388583

Total Mark : 0.00 | Type : MCQ

Options :

Yes

No

Your score : 0

Discussions (0)Suggest Correction

Question 2 : 640653388589

View Solutions (0)Total Mark : 2.00 | Type : MCQ

Options :

Header SectionMain SectionFooter Section

The app will show a warning, and nothing will be shown on the browser.

Header SectionFooter Section

The app will not show any warning, but nothing will be shown on the browser.

Your score : 0

Discussions (0)Suggest Correction

Question 3 : 640653388586

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Options :

Number is: 20

Number is: 40

Number is: undefined

Number is:

Your score : 0

Discussions (0)Suggest Correction

Question 4 : 640653388590

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Options :

Before Click: Number : 32After Click: Number : 149

Before Click: Number : 32After Click: Number : 32.5

Before Click: Number : 8.25After Click: Number : 106

Before Click: Number : 8.25After Click: Number : 149

Your score : 0

Discussions (0)Suggest Correction

Question 5 : 640653388591

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Options :

20

NaN

Undefined

ReferenceError

Your score : 0

Discussions (0)Suggest Correction

Advertisement

Remove Ads

Question 6 : 640653388592

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Options :

Undefined

89

Will return a function reference

71

Your score : 0

Discussions (0)Suggest Correction

Question 7 : 640653388593

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Options :

Your score : 0

Discussions (0)Suggest Correction

Question 8 : 640653388595

View Solutions (0)Total Mark : 3.00 | Type : MCQ

Options :

200, 1200

1200, 200

1200, 1200

200, 200

Your score : 0

Discussions (0)Suggest Correction

Question 9 : 640653388596

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Options :

Your score : 0

Discussions (0)Suggest Correction

Question 10 : 640653388597

View Solutions (0) Total Mark : 3.00 | Type : MCQ

Options :

Black, White

White, Black

Black, Black

White, White

Your score : 0

Discussions (0)Suggest Correction

Question 11 : 640653388587

View Solutions (0) Total Mark : 4.50 | Type : MCQ

Options :

Number 1: 10 Number 2: 30 Sum: 90

Number 1: 20 Number 2: 30 Sum: 100

Number 1: 30 Number 2: 20 Sum: 100

Number 1: 30 Number 2: 10 Sum: 90

Your score : 0

Discussions (0)Suggest Correction

Question 12 : 640653388594

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Options :

Undefined, Undefined

45, 15

15, 45

15, Undefined

Your score : 0

Discussions (0)Suggest Correction

Question 13 : 640653388598

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Options :

Total: 10, Virat Kohli: 0, Rohit Sharma: 10

Total: 40, Rohit Sharma: 6, Virat Kohli: 4

Total: 40, Virat Kohli:6, Rohit Sharma: 4

Total: 10, Rohit Sharma: 0, Virat Kohli: 10

Your score : 0

Discussions (0)Suggest Correction

Question 14 : 640653388599

View Solutions (0)Total Mark : 4.50 | Type : MCQ

Options :

Black, Black

Black, Red

Red, Black

Red, Red

Your score : 0

Discussions (0)Suggest Correction

Question 15 : 640653388584

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Which of the following statement(s) is/are false regarding javascript language?

Options :

- ☐ The equality operator "==" is used to avoid coercion in the language.
- ☐ A variable declared using the keyword "var" can be used anywhere in the program
- ☐ The keyword "break" is used to terminate the execution of the program in the language
- ☐ The JavaScript language is a dynamically typed language

Your score : 0

Discussions (0)Suggest CorrectionBroken Format?

Question 16 : 640653388585

View Solutions (0)Total Mark : 2.00 | Type : MSQ

Which of the following statement(s) is/are true regarding javascript language?

Options :

- ☐ The variables declared outside all functions using "var" keyword are initialized with the value "undefined", until the code execution reaches the initialization statement for that particular variable.
- ☐ The variables declared outside all functions using "const" keyword are initialized with the value "null", until the code execution reaches the initialization statement for that particular variable.
- ☐ The function expressions in the language are not hoisted
- ☐ A javascript object can not have its own functions or methods

Your score : 0

Discussions (0) Suggest Correction Broken Format?

Question 17 : 640653388588

View Solutions (0) Total Mark : 2.00 | Type : MSQ

Which of the following statement(s) is/are false regarding the state of a web application?

Options :

- ☐ The system state is usually a huge collection of information
- ☐ The system state is dependent on the user interface.
- ☐ Your Amazon wish list is an example of application state.
- ☐ Your Amazon wish list is an example of system state

Your score : 0