

## What is numpy?

NumPy is the fundamental package for scientific computing in Python. It is a Python library that provides a multidimensional array object, various derived objects (such as masked arrays and matrices), and an assortment of routines for fast operations on arrays, including mathematical, logical, shape manipulation, sorting, selecting, I/O, discrete Fourier transforms, basic linear algebra, basic statistical operations, random simulation and much more.

At the core of the NumPy package, is the ndarray object. This encapsulates n-dimensional arrays of homogeneous data types

## NumPy Arrays Vs Python Sequences

- NumPy arrays have a fixed size at creation, unlike Python lists (which can grow dynamically). Changing the size of an ndarray will create a new array and delete the original.
- The elements in a NumPy array are all required to be of the same data type, and thus will be the same size in memory.
- NumPy arrays facilitate advanced mathematical and other types of operations on large numbers of data. Typically, such operations are executed more efficiently and with less code than is possible using Python's built-in sequences.
- A growing plethora of scientific and mathematical Python-based packages are using NumPy arrays; though these typically support Python-sequence input, they convert such input to NumPy arrays prior to processing, and they often output NumPy arrays.

## Creating Numpy Arrays

```
# np.array
import numpy as np

a = np.array([1,2,3])
print(a)

[1 2 3]

# 2D and 3D
b = np.array([[1,2,3],[4,5,6]])
print(b)

[[1 2 3]
 [4 5 6]]

c = np.array([[[1,2],[3,4]],[[5,6],[7,8]]])
print(c)

[[[1 2]
  [3 4]]
```

```

[[5 6]
 [7 8]]

# dtype
np.array([1,2,3],dtype=float)

array([1., 2., 3.])

# np.arange
np.arange(1,11,2)

array([1, 3, 5, 7, 9])

# with reshape
np.arange(16).reshape(2,2,2,2)

array([[[[ 0,  1],
          [ 2,  3]],

        [[ 4,  5],
          [ 6,  7]]],

       [[[ 8,  9],
          [10, 11]],

        [[12, 13],
          [14, 15]]]])

# np.ones and np.zeros
np.ones((3,4))

array([[1., 1., 1., 1.],
       [1., 1., 1., 1.],
       [1., 1., 1., 1.]])

np.zeros((3,4))

array([[0., 0., 0., 0.],
       [0., 0., 0., 0.],
       [0., 0., 0., 0.]])

# np.random
np.random.random((3,4))

array([[0.85721156, 0.31248316, 0.08807828, 0.35230774],
       [0.96813914, 0.44681708, 0.56396358, 0.53020065],
       [0.03277116, 0.28543753, 0.09521082, 0.87967034]])

# np.linspace
np.linspace(-10,10,10,dtype=int)

```

```
array([-10, -8, -6, -4, -2, 1, 3, 5, 7, 10])

# np.identity
np.identity(3)

array([[1., 0., 0.],
       [0., 1., 0.],
       [0., 0., 1.]])
```

## Array Attributes

```
a1 = np.arange(10, dtype=np.int32)
a2 = np.arange(12, dtype=float).reshape(3, 4)
a3 = np.arange(8).reshape(2, 2, 2)

a3
array([[[0, 1],
        [2, 3]],
       [[4, 5],
        [6, 7]]])

# ndim
a3.ndim

3

# shape
print(a3.shape)
a3

(2, 2, 2)

array([[[0, 1],
        [2, 3]],
       [[4, 5],
        [6, 7]]])

# size
print(a2.size)
a2

12

array([[ 0.,  1.,  2.,  3.],
       [ 4.,  5.,  6.,  7.],
       [ 8.,  9., 10., 11.]])

# itemsize
a3.itemsize
```

8

```
# dtype
print(a1.dtype)
print(a2.dtype)
print(a3.dtype)
```

```
int32
float64
int64
```

## Changing Datatype

```
# astype
a3.astype(np.int32)

array([[0, 1],
       [2, 3]],

      [[4, 5],
       [6, 7]]], dtype=int32)
```

## Array Operations

```
a1 = np.arange(12).reshape(3,4)
a2 = np.arange(12,24).reshape(3,4)

a2

array([[12, 13, 14, 15],
       [16, 17, 18, 19],
       [20, 21, 22, 23]])

# scalar operations

# arithmetic
a1 ** 2

array([[ 0,  1,  4,  9],
       [16, 25, 36, 49],
       [64, 81, 100, 121]])

# relational
a2 == 15

array([[False, False, False,  True],
       [False, False, False, False],
       [False, False, False, False]])
```

```

# vector operations
# arithmetic
a1 ** a2

array([[          0,          1,
        16384,
           14348907],
       [ 4294967296, 762939453125,
        101559956668416,
           11398895185373143],
       [ 1152921504606846976, -1261475310744950487,
        1864712049423024128,
           6839173302027254275]])

```

## Array Functions

```

a1 = np.random.random((3,3))
a1 = np.round(a1*100)
a1

array([[43., 28., 71.],
       [27., 93., 36.],
       [31., 18., 7.]])

# max/min/sum/prod
# 0 -> col and 1 -> row
np.prod(a1,axis=0)

array([35991., 46872., 17892.])

# mean/median/std/var
np.var(a1,axis=1)

array([317.55555556, 854.        , 96.22222222])

# trigonometric functions
np.sin(a1)

array([[ -0.83177474,  0.27090579,  0.95105465],
       [ 0.95637593, -0.94828214, -0.99177885],
       [-0.40403765, -0.75098725,  0.6569866 ]])

# dot product
a2 = np.arange(12).reshape(3,4)
a3 = np.arange(12,24).reshape(4,3)

np.dot(a2,a3)

array([[114, 120, 126],
       [378, 400, 422],
       [642, 680, 718]])

```

```

# log and exponents
np.exp(a1)

array([[4.72783947e+18, 1.44625706e+12, 6.83767123e+30],
       [5.32048241e+11, 2.45124554e+40, 4.31123155e+15],
       [2.90488497e+13, 6.56599691e+07, 1.09663316e+03]])

# round/floor/ceil
np.ceil(np.random.random((2,3))*100)

array([[48.,  4.,  6.],
       [ 3., 18., 82.]])

```

## Indexing and Slicing

```

a1 = np.arange(10)
a2 = np.arange(12).reshape(3,4)
a3 = np.arange(8).reshape(2,2,2)

a3
array([[[0, 1],
        [2, 3]],

       [[4, 5],
        [6, 7]]])

a1
array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])

a2
array([[ 0,  1,  2,  3],
       [ 4,  5,  6,  7],
       [ 8,  9, 10, 11]])

a2[1,0]
4

a3
array([[[0, 1],
        [2, 3]],

       [[4, 5],
        [6, 7]]])

a3[1,0,1]
5

```

```

a3[1,1,0]
6
a1
array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
a1[2:5:2]
array([2, 4])
a2
array([[ 0,  1,  2,  3],
       [ 4,  5,  6,  7],
       [ 8,  9, 10, 11]])
a2[0:2,1::2]
array([[1, 3],
       [5, 7]])
a2[:,2,1::2]
array([[ 1,  3],
       [ 9, 11]])
a2[1,::3]
array([4, 7])
a2[0,: ]
array([0, 1, 2, 3])
a2[:,2]
array([ 2,  6, 10])
a2[1:,1:3]
array([[ 5,  6],
       [ 9, 10]])
a3 = np.arange(27).reshape(3,3,3)
a3
array([[[ 0,  1,  2],
        [ 3,  4,  5],
        [ 6,  7,  8]],
       [[ 9, 10, 11],
        [12, 13, 14],
        [15, 16, 17]],
       [[18, 19, 20],
        [21, 22, 23],
        [24, 25, 26]]])

```

```
[15, 16, 17]],  
[[18, 19, 20],  
 [21, 22, 23],  
 [24, 25, 26]]])
```

```
a3[:,2,0,::2]
```

```
array([[ 0,  2],  
       [18, 20]])
```

```
a3[2,1:,1:]
```

```
array([[22, 23],  
       [25, 26]])
```

```
a3[0,1,:]
```

```
array([3, 4, 5])
```

## Iterating

```
a1
```

```
for i in a1:  
    print(i)
```

```
0  
1  
2  
3  
4  
5  
6  
7  
8  
9
```

```
a2
```

```
array([[ 0,  1,  2,  3],  
       [ 4,  5,  6,  7],  
       [ 8,  9, 10, 11]])
```



```

for i in a2:
    print(i)

[0 1 2 3]
[4 5 6 7]
[ 8  9 10 11]

a3
array([[ 0,  1,  2],
       [ 3,  4,  5],
       [ 6,  7,  8]],

      [[ 9, 10, 11],
       [12, 13, 14],
       [15, 16, 17]],

      [[18, 19, 20],
       [21, 22, 23],
       [24, 25, 26]])

for i in a3:
    print(i)

[[0 1 2]
 [3 4 5]
 [6 7 8]]
[[ 9 10 11]
 [12 13 14]
 [15 16 17]]
[[18 19 20]
 [21 22 23]
 [24 25 26]]

for i in np.nditer(a3):
    print(i)

0
1
2
3
4
5
6
7
8
9
10
11
12
13

```

```
14
15
16
17
18
19
20
21
22
23
24
25
26
```

## Reshaping

```
# reshape

# Transpose
np.transpose(a2)
a2.T

array([[ 0,  4,  8],
       [ 1,  5,  9],
       [ 2,  6, 10],
       [ 3,  7, 11]])

# ravel
a3.ravel()

array([ 0,  1,  2,  3,  4,  5,  6,  7,  8,  9, 10, 11, 12, 13, 14, 15,
        16,
        17, 18, 19, 20, 21, 22, 23, 24, 25, 26])
```

## Stacking

```
# horizontal stacking
a4 = np.arange(12).reshape(3,4)
a5 = np.arange(12,24).reshape(3,4)
a5

array([[12, 13, 14, 15],
       [16, 17, 18, 19],
       [20, 21, 22, 23]])

np.hstack((a4,a5))

array([[ 0,  1,  2,  3, 12, 13, 14, 15],
       [ 4,  5,  6,  7, 16, 17, 18, 19],
       [ 8,  9, 10, 11, 20, 21, 22, 23]])
```

```
# Vertical stacking
np.vstack((a4,a5))

array([[ 0,  1,  2,  3],
       [ 4,  5,  6,  7],
       [ 8,  9, 10, 11],
       [12, 13, 14, 15],
       [16, 17, 18, 19],
       [20, 21, 22, 23]])
```

## Splitting

```
# horizontal splitting
a4
```

```
array([[ 0,  1,  2,  3],
       [ 4,  5,  6,  7],
       [ 8,  9, 10, 11]])
```

```
np.hsplit(a4,5)
```

```
-----
-----
ValueError                                Traceback (most recent call
last)
<ipython-input-227-59485ca7f23c> in <module>
----> 1 np.hsplit(a4,5)

<__array_function__ internals> in hsplit(*args, **kwargs)

/usr/local/lib/python3.8/dist-packages/numpy/lib/shape_base.py in
hsplit(ary, indices_or_sections)
    938         raise ValueError('hsplit only works on arrays of 1 or
more dimensions')
    939     if ary.ndim > 1:
--> 940         return split(ary, indices_or_sections, 1)
    941     else:
    942         return split(ary, indices_or_sections, 0)

<__array_function__ internals> in split(*args, **kwargs)

/usr/local/lib/python3.8/dist-packages/numpy/lib/shape_base.py in
split(ary, indices_or_sections, axis)
    870     N = ary.shape[axis]
    871     if N % sections:
--> 872         raise ValueError(
    873             'array split does not result in an equal
division') from None
    874     return array_split(ary, indices_or_sections, axis)

ValueError: array split does not result in an equal division
```

```
# vertical splitting
```

```
a5
```

```
array([[12, 13, 14, 15],  
       [16, 17, 18, 19],  
       [20, 21, 22, 23]])
```

```
np.vsplit(a5,2)
```

```
-----  
-----  
ValueError                                Traceback (most recent call  
last)
```

```
<ipython-input-230-5b73f701499e> in <module>
```

```
----> 1 np.vsplit(a5,2)
```

```
<__array_function__ internals> in vsplit(*args, **kwargs)
```

```
/usr/local/lib/python3.8/dist-packages/numpy/lib/shape_base.py in  
vsplit(ary, indices_or_sections)
```

```
    989     if _nx.ndim(ary) < 2:  
    990         raise ValueError('vsplit only works on arrays of 2 or  
more dimensions')
```

```
--> 991     return split(ary, indices_or_sections, 0)
```

```
    992  
    993
```

```
<__array_function__ internals> in split(*args, **kwargs)
```

```
/usr/local/lib/python3.8/dist-packages/numpy/lib/shape_base.py in  
split(ary, indices_or_sections, axis)
```

```
    870     N = ary.shape[axis]  
    871     if N % sections:  
--> 872         raise ValueError(  
    873             'array split does not result in an equal  
division') from None
```

```
    874     return array_split(ary, indices_or_sections, axis)
```

```
ValueError: array split does not result in an equal division
```