

OFFSET DRILLING REPORT - LOSS CIRCULATION

SYNTHETIC DEMONSTRATION DOCUMENT - NOT REAL OPERATIONAL DATA (SIH PROTOTYPE)

WELL IDENTIFIER: NWIS-W007

FORMATION: Demo-Barail

EVENT TYPE: MUD_LOSS

OPERATIONAL DATE: 2024-03-24

MEASURED DEPTH: 3010.0 m

SEVERITY LEVEL: HIGH

INCIDENT OVERVIEW

Drilling 8-1/2 inch hole section in Demo-Barail mature oil reservoir sand at 3010m. Experienced severe mud loss into depleted offset reservoir; 50 bbls active pit loss in 35 minutes. This matches the identical thief zone behavior observed in nearby well NWIS-W002 at 2980m.

GEOLOGICAL INTERPRETATION

Inter-well pressure depletion communication across permeable Barail channel facies. Regional reservoir pressure drawdown requires lower equivalent circulating density (ECD).

ACTION PLAN & MITIGATION

1. Mixed 45 bbls high-fluid-loss squeeze LCM pill with blended cellulosic fibers and nut plug.
2. Squeezed pill into thief formation at 3010m; hesitation squeeze held 250 psi.
3. Reduced circulation rate to 1750 L/min and reduced mud weight from 1.32 to 1.21 SG.