Teman: Security Self-Assessment Report

2026 Shenzhen International FinTech Competition · Topic A · Deliverable 05

Contents

1. Purpose and scope 1
2. Security design summary 1
3. Permission tiers 3
4. Risk rules and decision thresholds 4
5. Signed approvals, guardian approval and family limits 5
6. AI components and data handling 7
7. Threat analysis and evidence 9
8. Audit and test evidence 10
9. Known risks and prototype boundaries 11
10. Standards alignment 12
11. Conclusion 12

Repository: https://github.com/25006675-png/Teman · Configuration `2026-10-17.1` · Assessed 20 Oct 2026

Related: Technical Documentation · Execution Evidence · Evaluation results

---

1. Purpose and scope

This report describes the security controls in Teman, how payment authority is divided between people, AI components and fixed rules, what evidence supports each control, and the known risks of the current prototype. It is a **team self-assessment**, not an independent audit or a compliance certification.

Teman helps an older user review bills, manage a budget and request payments, with her son approving risky ones. The prototype uses a **simulated bank sandbox**: it does not hold or move real money. All data is synthetic.

In scope: input handling (photo, voice, chat, typed fields), the payment decision flow, the transaction state machine, signed approvals and family limits, guardian approval, the AI components, the audit log and data handling. **Out of scope:** real bank integration, user authentication and device security, hosting and network security, since the prototype runs on `127.0.0.1`.

---


2. Security design summary

Core principle: AI may help, but it can never authorise a payment. Every payment is decided by fixed rules and executed only against a digitally signed approval from a person, or from a limit a person signed in advance.

Every request passes three checkpoints, and no AI controls any of them:

Checkpoint	Control
Input	OCR, speech and forwarded text are **data, never instructions**. They are only searched for fields and scam phrases. Fields are validated: integer sen amounts, ISO dates, required fields, and a photo amount must match the biller's issued bill
Execution	Blocking rules and a risk score decide the outcome. A payment executes only in an allowed state, for an allowed role, with a valid signed approval, in one atomic conditional update

Checkpoint	Control
Output	Risk messages and buttons come from a fixed template dictionary. The assistant's own replies are fact-checked against what its tools actually did; an unsupported claim replaces the whole reply with template text




The frontend sends only a `tx_id`. Amount and payee are frozen in the database when the request is created, so they can't be changed after the fact.

---

3. Permission tiers

3.1 Tiers by risk



Tier	What it covers	Who can complete it	Authorisation required
🟢 **Tier 1: Read only**	Today's budget, bills waiting, weekly report, audit log	Ah Por, Ah Ming, the assistant	None; no money moves
🔵 **Tier 2: Safe payment** (APPROVE, score < 20; WARN, 20–39)	Recognised biller, normal amount	Ah Por (1-second hold or voice 「確認」; WARN needs an explicit "Pay anyway"). The assistant or pay-later scheduler, **only** for APPROVE inside a family-signed limit	Signed present approval (60 s, single use), or a valid signed family limit
🟠 **Tier 3a: Review** (score ≥ 40)	Unknown payee, over the auto-pay limit, AI-flagged tactic, reported by one family, rapid transfers	**Only** Ah Ming, with his PIN, within 2 minutes (+5 once)	PIN + signed guardian approval. Never to his own account
🔴 **Tier 3b: Block**	Scam phrase, blacklisted payee, reported by 2+ families, over RM 500	**Nobody**. Not Ah Por, not Ah Ming, not the assistant	Not possible: refused at every entry point

3.2 Permission matrix by actor

This is how the tiers are enforced in code. "Role" is fixed per endpoint in the demo (see §9, R1).

Capability	Ah Por	Ah Ming	Assistant	AI scam analyst	Pay-later scheduler	Shadow model
Read budget,	✅	✅	✅	—	—	—

Capability	Ah Por	Ah Ming	Assistant	AI scam analyst	Pay-later scheduler	Shadow model
bills, report						
Create a payment request	✅	—	✅ via `services.analyze()` only	—	✅ re-runs `analyze()`	—
Choose amount or payee	✅ (from bill / typed)	—	❌ picks a stored bill only	—	❌ saved bill only	—
Execute APPROVE / WARN	✅ signed	❌	APPROVE only, inside a signed family limit	❌	APPROVE only, inside a signed family limit	❌
Execute REVIEW	❌ (can only "Ask my child")	✅ PIN + signed	❌ (can only `ask_family`)	❌	❌	❌
Execute BLOCK	❌	❌	❌	❌	❌	❌
Raise risk	—	✅ report scam	—	✅ +40 only	—	❌
Lower risk / unblock	❌	❌	❌	❌	❌	❌
Change limits, whitelist, rules	❌	Signs limits at setup	❌	❌	❌	❌
Pause the assistant	—	✅	—	—	—	—

Where it's enforced:

Rule	Code
Ah Por can execute only APPROVE/WARN; the guardian only REVIEW	`transactions._execute` (`allowed_bands`)
Blocked requests refused (status, outcome, risk code or fired rule)	`transactions._is_blocked`, plus `risk_code NOT IN ('SCAM_SIGNAL','OVER_HARD_CAP')` in the execution SQL
Guardian can't approve money to his own accounts	`transactions.pays_guardian` → `SELF_APPROVAL`
Assistant has no approve, add-payee or change-limit tool	`agent.TOOLS` (7 tools)
Automatic payment only with a valid family limit	`mandates.delegated_validator`

3.3 Family limits (delegated mandates)

Demo values, signed at setup and valid 365 days: **TNB up to RM 80 per bill, once a month; Air Selangor up to RM 40, once a month.** These are synthetic setup values. An edited limit fails its signature and automatic payment stops.

---

4. Risk rules and decision thresholds

Blocking rules run first; the first match stops the decision:

Order	Condition	Code	Outcome
1	Missing payee, or no positive amount	`DATA_INSUFFICIENT`	Ask again
2	Configured scam phrase (English and Chinese)	`SCAM_SIGNAL`	Block; son alerted
3	Blacklisted payee	`SCAM_SIGNAL`	Block
4	Reported by ≥ 2 distinct families	`SCAM_SIGNAL`	Block
5	Amount above RM 500	`OVER_HARD_CAP`	Block

Risk score: if no blocking rule matches, the weights of every signal that fires are added:

Signal	Points
Payee is not an exact, normalised whitelist match	40
Amount above the payee's auto-pay limit	40
Amount above 1.2 × the median past bill	20
One family has reported the payee	40
≥ 2 transfers in the previous 24 hours	40
AI scam analyst identifies at least one tactic	40

Bands: below 20 → APPROVE · 20 to below 40 → WARN (explicit acknowledgement required, enforced server-side) · 40 or above → REVIEW.

- The auto-pay limit is 1.5 × the payee's median bill when at least 3 past bills exist. With fewer, the limit is RM 50 and the high-amount rule is skipped.
- Whitelist matching is exact after normalisation: a typo payee such as "Tenaga Nasinal Berhad" is **not** treated as TNB.
- Scam phrase matching normalises Unicode (NFKC), case and spacing, and also checks a letters-and-digits-only copy, catching spacing, punctuation and zero-width-character variants.
- Each decision record stores every rule checked, fired signals, weights, score, outcome, rule that stopped the check, and `config_version`.
- All thresholds live in `data/*.json`. The files must share one `config_version`, or the server refuses to start. No AI component can write to them.

---


5. Signed approvals, guardian approval and family limits

5.1 Present approvals

When Ah Por confirms or Ah Ming approves, the server issues a record signed with **ECDSA P-256 / SHA-256** over canonical JSON. The record holds: transaction ID, payee, stored amount, decision, role, method, issue and expiry time, and a 128-bit random nonce.

Before payment the server verifies, in order:

1. The signature is valid.
2. Every signed field matches the stored transaction.
3. The role is eligible for the outcome band.
4. The record is within its **60-second** validity.
5. The nonce is unused. It is consumed with a conditional update in the **same database transaction** as the payment, so a failed payment rolls it back and a replay is rejected.



5.2 Fail-safe timers

Timer	Length	If it runs out
Ah Por's confirmation	10 minutes	`EXPIRED`, nothing paid
Son's decision after "Ask my child"	2 minutes, +5 once ("Call Mum")	`EXPIRED`, nothing paid

Expiry is checked on every read and action, so no background job is needed. The timer values are checked against config at start-up.

5.3 Guardian approval

- **PIN:** checked against a PBKDF2-HMAC-SHA256 salted hash in `data/guardians.json` with a constant-time comparison. The PIN is never stored in plain text. Demo PIN: 2580.
- **Three wrong PINs** on a request reject it (fail-safe) and log `LOCKED`.
- **No self-approval:** money to an account listed as the guardian's own is refused (`SELF_APPROVAL`). This covers the case where the family member is the risk.
- The guardian can resolve **REVIEW only**; a blocked request has no approve button and the server refuses it.

5.4 Delegated family limits

Each limit is signed separately. Before an automatic payment, the server checks the limit's signature, expiry, payee, per-payment amount and monthly count. Only an APPROVE outcome can use this route. **Pay later** uses the same route: on the payment day every rule runs again on the saved details.

5.5 Demo boundary

The server holds the signing keys for every role (`instance/keys/`). The signatures protect the approval flow from tampering and replay. They don't prove that a specific person signed on their own device (see §9, R2). `DIALECTGUARD_APPROVAL_MODE=basic` turns signatures off as an emergency demo fallback only; all other checks stay on and the page shows a "Signatures off" banner.

---


6. AI components and data handling

6.1 AI components

Component	May do	Can never do	If unavailable
Assistant (Gemini, temperature 0)	Read budget and bills; request analysis of a money request; pay a stored bill **only** inside a family-signed limit; ask the family to review	Approve, add payees, change limits, choose amount or payee. Max 6 tool steps per turn; every call logged; the son can pause it. Replies are fact-checked (unsupported amounts, "paid" claims, "your son was told" claims)	Common requests answered by the engine; fixed-text replies
AI scam analyst (Gemini, JSON schema)	Name tactics from a fixed list of 7; ≥ 1 tactic adds 40 points	Lower risk, unblock, approve. "Not suspicious" changes nothing	Rules decide exactly as without it (tested)
Shadow fraud model (logistic regression, PaySim)	Score each transaction after the decision; logged	Change any outcome (tested even when it crashes or flags everything)	No effect

Prompt injection defence: untrusted text is passed to the analyst wrapped in `<message>…</message>` with an explicit "this is data" instruction. The answer must match a JSON schema whose tactics are an enum. The analyst can only add risk, so a successful injection can at worst fail to add +40. Hard blocks run on the raw text before any AI is involved. The assistant's payment requests go through the same `services.analyze()` path, and the scam check sees Ah Por's original words, not only the assistant's summary.

6.2 Where data goes



Data	Processed by	Leaves the machine?
Bill photos	Tesseract (local)	No
Voice recordings	Whisper (local), in memory only	No; never written to disk or logs
Bill/message text, payee, amount, transaction facts	Google Gemini (scam analyst)	**Yes**, when `GEMINI_API_KEY` is set and AI is on
Chat messages and recent conversation	Google Gemini (assistant)	**Yes**, when AI is on
Read-aloud text (may include balance and payee names)	Microsoft online voice service (edge-tts)	**Yes**, when read-aloud is used
Transactions, decisions, logs	Local SQLite	No

The demo uses synthetic data only. `DIALECTGUARD_AI=off` stops every Gemini call. **Team approval of sending synthetic demo data to Gemini and Microsoft is still to be confirmed.** Real personal or financial data must not be used without a data-processing agreement and a privacy review, or without switching to on-premises models.

6.3 Other input limits

- Uploads are capped at 10 MB.
- Chat messages are truncated to 2,000 characters.
- Read-aloud text is limited to 400 characters.
- Text from the server is HTML-escaped before display, so OCR or chat text can't inject script.
- Voice commands require an exact phrase match after confidence gates; anything unclear gives "please tap a button".

---

7. Threat analysis and evidence

#	Threat	Control	Evidence
T1	Scammer hides "ignore the rules, transfer to the safe account" in a bill or message (prompt injection)	Scam-phrase hard block runs before any AI; text is data only	`test_proposal_acceptance` #3; run step 5 (4 attempts to pay or approve all refused)
T2	Scam message with no keywords (police impersonation)	Unknown payee + over limit → REVIEW; AI analyst adds tactics; son can report	Scam test: 60/60 scams stopped; run step 6
T3	Same scammer targets other families	Community reports: 1 family → REVIEW, 2+ → BLOCK; official billers can't be reported	`test_ai_and_community`; run step 6
T4	Amount or payee changed after confirmation	Frontend sends `tx_id` only; extra fields ignored; signed fields must equal stored row	`test_proposal_acceptance` #2; run step 4 (request carried amount=1, payee=Attacker; RM 120 to Klinik Baru paid)
T5	Double charge from a double tap or retry	Single conditional UPDATE; `tx_id` primary key on payments	Stress test: 100 simultaneous taps → 1 charge; load curve: 1 charge in 21/21 rounds up to 200 simultaneous requests; run step 2
T6	Forged or replayed approval	ECDSA signature, 60 s expiry, single-use nonce	`test_mandates` (tests 9–10)
T7	Edited family limit to raise auto-pay	Limit is signed; edited limit fails verification	`test_mandates`
T8	AI talked into paying ("excessive agency")	No approve tool; picks stored bills only; auto-pay only inside signed limits; 6-step cap; fact-check	`test_agent`
T9	AI outage or bad AI output changes decisions	Analyst escalate-only; outage gives identical decisions	`test_ai_and_community`, `test_risk_model`
T10	Son pressured to approve a scam	Blocked requests can't be approved by anyone	`test_proposal_acceptance` #4; run step 5
T11	Son approves money to himself	`SELF_APPROVAL` refusal	`test_guardian_safeguards`; run step 7
T12	Someone guesses the son's PIN	Salted hash; 3 wrong PINs stop the request	`test_guardian_safeguards`; stress test: 30 wrong PINs → 0 charges; run step 9
T13	Approval never answered	2-minute fail-safe → EXPIRED, balance unchanged	`test_guardian_timer`; run step 8 (real 2-minute wait)
T14	Misheard dialect triggers a payment	Exact phrase match; confidence gates; amounts never from speech	Speech test: 0 wrong actions in 108 clips; run step 10
T15	Misread bill photo pays the wrong amount	Photo amount must match the biller's issued bill	Photo test: 63/63 safe (2 unsafe before the fix)
T16	Rapid draining by repeated transfers	3rd transfer in 24 h needs the son	`test_ai_and_community`
T17	Audit history rewritten	SQLite triggers refuse UPDATE/DELETE of logs and payments and illegal state changes	`test_transactions`; `db_tamper_checks.json` (6/6 edits refused)

#	Threat	Control	Evidence
T18	Accidental tap by a shaky hand	1-second hold, then a 5-second undo before anything is sent	Demo page; screenshots 06

"Run step" refers to execution_evidence/RUN_RESULTS.md, produced against the real server.

The controls for T4, T5, T10–T13 and T17 are also exercised together by the randomised attack test (§8): 10,000 random actions with 0 safety rules broken.


---

8. Audit and test evidence

- **Audit log.** Decisions and transaction events are written to SQLite. Triggers reject updates and deletes of `logs` and `sandbox_payments` and enforce the allowed state transitions. `GET /logs` exports events and decision records as JSON (`dialectguard.logs.v1`). Logs hold no audio.

- **Automated tests. 248 tests pass, plus 23 sub-tests** (`python -m pytest`, about 15 s). They cover API scenarios, states and expiry, double-payment protection, signature tampering and replay, scam blocking, guardian PIN and self-approval, AI behaviour and assistant guardrails, OCR, speech and shadow-model isolation. Tests use temporary databases and keys; Gemini calls are mocked.

- **Evaluation (19 Oct).** 60/60 synthetic scams stopped; 0 wrong actions in 108 Cantonese voice clips; 63/63 degraded photos handled safely; 1 charge from 100 simultaneous taps. Method and limits: EVIDENCE.md.



- **Randomised attack test (Monte Carlo, 20 Oct).** 200 random sequences of 50 actions on the real app, with the AI off and a controllable clock. The actions are random requests (including hidden scam phrases and every threshold edge), taps, voice words, right and wrong PINs, simultaneous bursts, cancels, reports, pay later, requests carrying a different amount, and jumps in time. After every action, 11 safety rules were checked against the database: **0 broken in 10,000 actions** (110,000 checks), with 412 legitimate payments and 0 server errors. To prove the test can fail, it was re-run with the PIN check and then the own-account check switched off; both runs reported violations. Details: Technical documentation §8.3.



- **Execution evidence.** A scripted run of every demo scenario against the real server, with its `/logs` export: execution_evidence/.

The audit log is evidence of demo execution. It is **not** an externally anchored, tamper-proof record: someone with file access can replace the database file, and the demo's `/reset` rebuilds it (R5).

---

9. Known risks and prototype boundaries

These are limits of the prototype, not gaps in the safeguards shown above. Severity is the impact if the prototype were exposed as-is.

#	Risk	Severity	Current mitigation	Production fix
R1	**No login.** Endpoints assume a role from the action called; anyone who can reach the server can call the son's endpoints (still needs his PIN to approve)	High	Run on `127.0.0.1` only; PIN on approvals	Per-role authentication; son's app on his own device
R2	**Server holds all signing keys.** Signatures prove integrity, not that a person signed on their device	High	Keys stay local in `instance/keys/`	Keys in each user's device secure enclave, unlocked by biometrics
R3	**No CSRF or rate limiting.** A malicious webpage open in the same browser could POST to `127.0.0.1:8000/reset`. Transaction IDs are 128-bit random, so payment endpoints can't be targeted without one	Medium	Demo machine only; synthetic data	Auth tokens, CSRF protection, rate limits, remove `/reset`
R4	**Wrong-PIN count is per request and kept in memory.** It resets on restart; a 4-digit PIN allows 3 guesses per new review request	Medium	Each guess needs a new review request that Ah Por starts; all logged	Per-guardian lock-out stored in the database; device biometrics
R5	**Audit log not externally anchored.** `/reset` and file access can replace it	Medium	Triggers stop in-app edits; JSON export after each run	Write-once storage or an external hash anchor
R6	**External AI and voice processing.** Gemini and Microsoft receive text when enabled (§6.2); team approval pending	Medium	Synthetic data; `DIALECTGUARD_AI=off`	Data agreement or on-premises models
R7	**Detection not validated on real data.** Whitelist has 2 billers; thresholds and scam phrases are demo values; scam test uses synthetic messages; AI flags 7% of genuine review cards	Medium	Unknown payees default to REVIEW (fail-safe); AI can only add risk	Real scam corpus; bank biller directory; threshold tuning

#	Risk	Severity	Current mitigation	Production fix
R8	**Speech and OCR tested on synthetic inputs.** Computer voices and computer-made bill images	Low	Speech can't set amounts; photo cross-check; buttons always available	Consented recordings from elderly speakers; real bill photos
R9	**Basic approvals mode** turns signatures off	Low	Off by default; banner shown; other checks stay on	Remove from production builds
R10	**Simulated bank and push.** Payments are a sandbox ledger; both phones share one backend	— (scope)	Clearly labelled in the UI and docs	Bank partner or licensed payment provider
R11	**Ah Por can't cancel once a request is with her son**	Low	It ends when he decides or after 2 minutes	Team decision pending

10. Standards alignment

Standard	How Teman relates	Claim
OWASP Top 10 for LLM Applications	LLM01 Prompt Injection: untrusted input treated as data, hard blocks before AI, schema-constrained analyst. LLM06 Excessive Agency: assistant has no approve tool, signed limits, step cap, pause switch, fact-check	Addressed in design; not a certification
Google Agent Payments Protocol (AP2)	Same principle as AP2 mandates: the AI pays only against a signed, limited, verifiable authorisation from a person	Same principle; **not** an AP2 implementation or compliance claim
Open Banking payment initiation	Request → challenge (signed approval) → execute pattern	Conceptual only; no real bank integration

11. Conclusion

Teman separates AI assistance from payment authority:

- Deterministic rules make every risk decision.
- Hard blocks can't be overridden by anyone.
- Eligible payments need a signed, single-use approval or a valid family-signed limit.
- Amounts and payees are frozen at creation.
- The audit trail is enforced by the database.

These controls are shown by 248 automated tests, by a randomised attack test (10,000 random actions, 0 safety rules broken), by evaluation on synthetic scams, voices and photos, and by a scripted run against the real server.

The main gaps before any real deployment:

1. Authentication per role
2. User-held signing keys
3. CSRF protection and rate limiting
4. An externally anchored audit log
5. Validation on real scam messages, real bills and elderly speakers