4. Test Data

Use a dedicated test environment and test accounts. The following is sample test data; it does not represent real accounts.

Data ID	Username	Password	Data type	Expected outcome
TD_01	`testuser01`	`Test@12345`	Valid credentials	Login successful
TD_02	`unknown_user`	`Test@12345`	Invalid username	Login rejected
TD_03	`testuser01`	`Wrong@12345`	Invalid password	Login rejected
TD_04	`unknown_user`	`Wrong@12345`	Both invalid	Login rejected
TD_05	Empty	`Test@12345`	Missing username	Validation error
TD_06	`testuser01`	Empty	Missing password	Validation error
TD_07	Empty	Empty	Missing credentials	Validation error
TD_08	Three spaces	`Test@12345`	Whitespace username	Validation error or rejection
TD_09	`testuser01`	Three spaces	Whitespace password	Login rejected
TD_10	`' OR '1'='1`	`Anything123!`	Security input	Login rejected safely
TD_11	`testuser01`	`Test@123456789`	Incorrect password	Login rejected

Test Data Table for SauceDemo Login Page

Website: SauceDemo

Test Case ID	Test Scenario	Username	Password	Expected Result
TC_01	Valid username and password	`standard_user`	`secret_sauce`	Login successful; user is redirected to the Products page.
TC_02	Invalid username	`invalid_user`	`secret_sauce`	Login fails; an error message is displayed.
TC_03	Invalid password	`standard_user`	`wrong_password`	Login fails; an error message is displayed.
TC_04	Empty username	*(Blank)*	`secret_sauce`	Login fails; an error message indicates the username is required.
TC_05	Empty password	`standard_user`	*(Blank)*	Login fails; an error message indicates the password is required.

Note: SauceDemo provides `standard_user` and `secret_sauce` as its standard test credentials. For invalid credentials, the application typically displays an error message and prevents access to the Products page.



