Intro. to Secure Programming Study Groups at NCYU

Chih-Hsuan Yang(SCC)

zxc25077667@pm.me

April 21, 2021

About me

- ▶ 楊志璿
- NSYSU Information security club founder
- Resume
- ► Linux, Modern C++

Outline

Background

Programmer's qualities

Binary search

ReDoS

Arithmetic overflow


Memory safe

Real cyber attacks

Labs

Background

Maslow's pyramid of code review



Maslow's pyramid of code review

- ► Correct:做到預期的行為了嗎?能夠處理各式邊際狀況 嗎?即便其他人修改程式碼後,主體的行為仍符合預期嗎?
- ▶ Secure: 面對各式輸入條件或攻擊,程式仍可正確運作嗎?
- ▶ Readable:程式碼易於理解和維護嗎?
- ► Elegant:程式碼夠「美」嗎?可以簡潔又清晰地解決問題嗎?
- ► Altruist:除了滿足現有的狀況,軟體在日後能夠重用嗎? 甚至能夠抽離一部分元件,給其他專案使用嗎?

Programmer's qualities

Binary search

```
int wrong(int *arr, size_t len, int target)
  {
3
      int begin = 0, end = len;
      while (begin <= end)
4
5
           int mid = (begin + end) / 2;
6
           if (arr[mid] == target)
7
               return mid;
8
           else if (arr[mid] < target)</pre>
9
               end = mid;
10
           else
11
               begin = mid;
12
13
      return -1;
14
15 }
```

Binary search

```
int correct(int *arr, size_t len, int target)
2
  {
3
      int begin = 0, end = len;
      while (begin <= end)
4
5
           int mid = (begin >> 1) + (end >> 1);
6
           if (arr[mid] == target)
7
               return mid;
8
           else if (arr[mid] < target)</pre>
9
               end = mid;
10
           else
11
               begin = mid;
12
13
      return -1;
14
15 }
```

Binary search

- ▶ 1946 idea
- ▶ 1960 mathematical analysis
- ▶ 1988 find bugs.

Donald Knuth

Although the basic idea of binary search is comparatively straightforward, the details can be surprisingly tricky.

Appendix here - Donald Knuth

- ► T_FX
- ► The Art of Computer Programming (TAOCP)




ReDoS






Regex

- Regular expression
- ► Finite state machine



Regex basic



Input

ababababababababababa

- (ababababababababababab) Nope
- (abababababababababab)(ab) Nope
- (abababababababababab)(abab) Nope
- (abababababababababab)(ab)(ab) Nope
- (ababababababababab)(ababab) Nope
- (ababababababababab)(abab)(ab) Nope
- (ababababababababab)(ab)(abab) Nope
- ► (abababababababababab)(ab)(ab)(ab) Nope



$$extstyle extstyle NP-Hard \ dp[0]=1 \ dp[N]=\sum_{i=0}^N dp[i]+dp[N-i] \ \sim O(3^N)$$

ReDoS

So, please check what you did. User provides regex should have a timeout threshold. Don't believe the user inputs.

Appendix here

- 1. Halting problem
- 2. Dynamic programming
- 3. Finite state machine


Dynamic programming

Finite state machine

Arithmetic overflow

Data Model					
Туре	LP32	ILP32	LP64	ILP64	LLP64
char	8	8	8	8	8
short	16	16	16	16	16
int	16	32	32	64	32
long	32	32	64	64	32
long long	64	64	64	64	64
pointer	32	32	64	64	64

Bits field



2's complement

Eg:

- ► 0x1234ABCD
- ► 0x00BADBAD
- ► 0xFFFFFFF

Integer overflow

2002 FreeBSD

```
#define KSIZE 1024
char kbuf[KSIZE];
int copy_from_kernel(void *user_dest, int maxlen) {
   int len = KSIZE < maxlen ? KSIZE : maxlen;
   memcpy(user_dest, kbuf, len);
   return len;
}</pre>
```

What if maxlen < 0?

Integer overflow

2002 External data representation (XDR)

```
void *copy_elements(void *ele_src[], int ele_cnt, int
     ele size) {
   void *result = malloc(ele_cnt * ele_size);
    if (result == NULL)
      return NULL:
   void *next = result;
6
    for (int i = 0; i < ele_cnt; i++) {</pre>
      memcpy(next, ele_src[i], ele_size);
8
      next += ele_size;
9
    return result:
10
11
```

What if ele_cnt = 10^{22} , ele_size = 10^{10} ?


Appendix here

- ► Operating system
- kernel

Operating system



Kernel



Memory safe

Buffer overflow

Memory leakage

Real cyber attacks

Labs