

TMP: template meta-programming (I)

Deep dive into C++

scc@teamt5.org

Outline



Template 101 and type deduction

Perfect forwarding and reference collapsing

Variadic template and parameter pack

SFINAE

CTAD

Expression template

Concepts and constraints

CRTP and compile time polymorphism

Template 101 & type deduction

Generic type?

```
int square(int num) {  
    return num * num;  
}
```

```
template<typename T>  
T square(T num) {  
    return num * num;  
}
```

_Generic (C11)

```
// Specific square functions for different types
```

```
int square_int(int num) {  
    return num * num;  
}
```

```
double square_double(double num) {  
    return num * num;    #define square(X) _Generic((X), \  
    int: square_int,    \  
    double: square_double,    \  
    default: square_int    \  
    ) (X)
```

_Generic (C11)

// Specific version for different types

```
int square_int(int num) {  
    return num * num;  
}
```

1. Hand-write name mangling
2. Lots of types
3. C89 you should write the specific version

```
double square_double(double num) {
```

```
    return num * num;  
}
```

```
#define square(X) _Generic((X), \n\n    int: square_int, \n\n    double: square_double, \n\n    default: square_int \n\n)(X)
```



Template 101

```
template<typename T>  
  
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Template 101

`template<parameter-list >`

`template<typename T>`

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```


Template 101

`template`<`parameter-list` >

`template`<`typename` **T**>

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Type

Non-type

Template

Template 101

template<parameter-list >

Type

Non-type

Template

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Template 101

`template`<`parameter-list` >

Type

Non-type

Template

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Type template parameter

<i>type-parameter-key name</i> (optional)	(1)	
<i>type-parameter-key name</i> (optional) = default	(2)	
<i>type-parameter-key ... name</i> (optional)	(3)	(since C++11)
<i>type-constraint name</i> (optional)	(4)	(since C++20)
<i>type-constraint name</i> (optional) = default	(5)	(since C++20)
<i>type-constraint ... name</i> (optional)	(6)	(since C++20)

Template 101

`template`<`parameter-list` >

Type

Non-type

Template

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Type template parameter

<code>typename</code> <i>key name</i> (<i>optional</i>)	(1)	
<i>type-parameter-key name</i> (<i>optional</i>) = <i>default</i>	(2)	
<i>type-parameter-key</i> ... <i>name</i> (<i>optional</i>)	(3)	(since C++11)
<i>type-constraint name</i> (<i>optional</i>)	(4)	(since C++20)
<i>type-constraint name</i> (<i>optional</i>) = <i>default</i>	(5)	(since C++20)
<i>type-constraint</i> ... <i>name</i> (<i>optional</i>)	(6)	(since C++20)

Template 101

`template`<`parameter-list` >

Type

Non-type

Template

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Template 101

`template`<`parameter-list` >

Type

Non-type

Template

```
T max(T a, T b) {  
    return a > b ? a :  
}
```

Non-type template parameter

<i>type name</i> (optional)	(1)	
<i>type name</i> (optional) = default	(2)	
<i>type ... name</i> (optional)	(3)	(since C++11)
<i>placeholder name</i> (optional)	(4)	(since C++17)
<i>placeholder name</i> (optional) = default	(5)	(since C++17)
<i>placeholder ... name</i> (optional)	(6)	(since C++17)

Template 101

`template`<`parameter-list` >

Type

Non-type

Template

```
T max(T a, T b) {  
    return a > b ? a :  
}
```

Non-type template parameter

size_t N _{optional}	(1)	
<i>type name</i> _{optional} = default	(2)	
<i>type ... name</i> _{optional}	(3)	(since C++11)
<i>placeholder name</i> _{optional}	(4)	(since C++17)
<i>placeholder name</i> _{optional} = default	(5)	(since C++17)
<i>placeholder ... name</i> _{optional}	(6)	(since C++17)

Template 101

`template`<parameter-list >

Type

Non-type

Template

```
T max(T a, T b) {
```

```
    return a > b ? a :
```

Non-type template parameter

`size_t N` optional (1)

`type name` optional = *default* (2)

`optional` (3) (since C++11)

`name` optional (4) (since C++17)

`name` optional = *default* (5) (since C++17)

`name` optional (6) (since C++17)

```
template<typename T, size_t N>
```

```
size_t strlen(const T(&)[N]) {
```

```
    return N - 1;
```

```
}
```


Template 101

template<parameter-list >

Type

Non-type

Template

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Template 101

template<parameter-list >

Type

Non-type

Template

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Template template parameter

template < <i>parameter-list</i> > <i>type-parameter-key name</i> (<i>optional</i>)	(1)
template < <i>parameter-list</i> > <i>type-parameter-key name</i> (<i>optional</i>) = <i>default</i>	(2)
template < <i>parameter-list</i> > <i>type-parameter-key</i> ... <i>name</i> (<i>optional</i>)	(3) (since C++11)

Template 101

template<parameter-list >

Type

Non-type

Template

```
T max(T a, T b) {
```

Template template parameter

```
template < parameter-list > type-parameter-key name(optional)
```

(1)

```
template<typename T, template<typename> typename Container>
```

```
void print(Container<T> v) {
```

```
    for (const auto& item : v)
```

```
        std::cout << item << " ";
```

```
}
```

Template specialization

`std::vector<bool>`

```
template<typename T>
class Vector {
    std::vector<T> data;


public:
    void push_back(const T& v) { data.push_back(v); }
    void push_back(T&& v) { data.push_back(std::forward<T>(v)); }
    const T& at(size_t pos) const { return data[pos]; }
    T& at(size_t pos) { return data[pos]; }
    size_t size() const { return data.size(); }
};
```

```
template<>
class Vector<bool> {
    using T = bool;
    std::vector<char> data;


public:
    void push_back(const T& v) { data.push_back(v); }
    void push_back(T&& v) { data.push_back(std::forward<T>(v)); }
    bool at(size_t pos) const { return data[pos]; }
    size_t size() const { return data.size(); }
};
```

Type deductions

Fundamental types



Compound types



頭腦體操

```
print_type<decltype (1 + 1ull)>(); // unsigned long long
print_type<decltype (1. + 1)>(); // double
print_type<decltype (+ -+-+--+ +true)>(); // int
print_type<decltype ([]{})>(); // lambda type
print_type<decltype ("dummy")>(); // const char (&) [6]
print_type<decltype (struct {})>(); // (anonymous struct)
print_type<void (*) ()>(); // void (*) ()
print_type<decltype (nullptr)>(); // std::nullptr_t
print_type<decltype (3.14f * 'a')>(); // float
print_type<decltype (0b1010 + 0xFF)>(); // int
print_type<decltype (~~~0u)>(); // unsigned int
print_type<decltype ("C++Expert" [3])>(); // const char &
```

So, it's easy



```
template<typename T>
void print_type() {
    auto me = std::string(__PRETTY_FUNCTION__);
    // ...
}
```

So, it's easy

```
void print_type(auto v) {  
    auto me = std::string(__PRETTY_FUNCTION__);  
    // ...  
}
```

C++20
syntactic sugar



Deducting type from Args

```
template<typename Para>
```

```
void f(Para param);
```

```
f(expr);
```

Template 101

```
template<parameter-list >
```

Type

Non-type

Template

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Type template parameter

<code>type-parameter-key name(optional)</code>	(1)
<code>type-parameter-key name(optional) = default</code>	(2)
<code>type-parameter-key ... name(optional)</code>	(3) (since C++11)
<code>type-constraint name(optional)</code>	(4) (since C++20)
<code>type-constraint name(optional) = default</code>	(5) (since C++20)
<code>type-constraint ... name(optional)</code>	(6) (since C++20)

Deducting type from Args

```
template<typename Para>
```

```
void f(Para param);
```

```
f(expr);
```

A parameter is a variable defined in a function.

An argument is the value **passed** to the function when called.



Deducting type from Args

```
template<typename Para>
```

```
void f(Para param);
```

```
f(expr);
```

Deducing Args type and
making Para being defined.

A parameter is a variable defined in a function.

An argument is the value **passed** to the function when called.



Deducting type from Args

```
template<typename Para>
```

```
void f(Para param);
```

```
f(expr);
```

Deducing Args type and
making Para being defined.

A parameter is a variable defined in a function.

An argument is the value **passed** to the function when called.

Template
Argument
Deduction



template type

```
template<typename Para>
```

```
void f(Para param);
```

```
f(expr);
```

Regular

Reference

Universal/Forwarding
reference

template type

Regular

Reference

Universal/Forwarding
reference

template type

Regular

Reference

Universal/Forwarding
reference

頭腦體操

```
print_type<decltype(1 + 1ull)>();           // unsigned long long
print_type<decltype(1. + 1)>();             // double
print_type<decltype(+ -+ -+ + true)>();     // int
print_type<decltype([]{})>();              // lambda type
print_type<decltype("dummy")>();          // const char (c) [6]
print_type<decltype(struct {})>();         // (anonymous struct)
print_type<decltype(void (*)())>();        // void (*)()
print_type<decltype(nullptr)>();           // std::nullptr_t
print_type<decltype(3.14f * 'a')>();       // float
print_type<decltype(0b1010 + 0xFF)>();     // int
print_type<decltype(~~0u)>();              // unsigned int
print_type<decltype("C++Expert"[3])>();   // const char &
```

Regular

Ignore the cv-qualifier and any references. Copy it anyway.

```
template<typename T>
```

```
void f(T param);
```

```
int x = 27;
```

```
const int cx = x;
```

```
const int& rx = x;
```

```
f(x); // T's and param's types are both int
```

```
f(cx); // T's and param's types are again both int
```

```
f(rx); // T's and param's types are still both int
```

template type

Regular

```
int main() {  
    print_type<decltype(std::move(1))>();  
    print_type<decltype(1)>();  
}
```

Reference

```
int a = 42;  
print_type<decltype(&a)>();  
print_type<int&>();  
//print_type<std::unwrap_reference_t<  
    decltype(std::ref(a))>>();  
}
```

Universal/Forwarding
reference

Type: int&&	(reference type)
Type: int	(not a reference type)
Type: int*	(not a reference type)
Type: int&	(reference type)

Reference

ParamType is a Reference or Pointer, but not a Universal Reference

1. If *expr*'s type is a reference, **ignore** the reference part.
2. Then pattern-match *expr*'s type against *ParamType* to determine T.

```
template<typename T>
```

```
void f(T& param);
```

```
int x = 27;
```

```
const int cx = x;
```

```
const int& rx = x;
```

Reference

ParamType is a Reference or Pointer, but not a Universal Reference

1. If *expr*'s type is a reference, **ignore** the reference part.
2. Then pattern-match *expr*'s type against *ParamType* to determine T.

```
template<typename T>
```

```
void f(T& param);
```

```
    f(x);    // T is int, param's type is int&
```

```
    f(cx);   // T is const int, param's type is const  
            int&
```

```
int x = 27;
```

```
const int cx = x, f(rx); // T is const int, param's type is const  
                       int&
```

```
const int& rx = x;
```


template type

Regular

Reference

Universal/Forwarding
reference

We discuss it later.
It's a key point that
C++ can be faster
than C.



頭腦體操



```
int x = 27;  
const int cx = x;  
const int& rx = x;
```

```
F(x);    // T and param's type is int  
F(cx);   // T and param's type is int (const is ignored)  
F(rx);   // T and param's type is int (const and ref are ignored)  
F(27);   // T and param's type is int (rvalue)
```

```
template<typename T>
```

```
void F(T param) {}
```

頭腦體操



```
template<typename T>
```

```
void F(T param) {}
```

```
const char* const ptr = "Fun with templates";
```

```
// T and param's type are const char* (const from pointer itself is ignored)
```

```
F(ptr);
```

```
// Both T and param's type are const char* (array decays to pointer)
```

```
F("temporary string");
```

auto type deduction

- Almost the same as template-type deduction
- `auto` keyword, no longer be a storage specifier, type specifier instead
- `auto&&` is a universal reference (forwarding reference)

auto type deduction

```
template<class T>
void printall(const vector<T>& v) {
    for (typename vector<T>::const_iterator p = v.begin(); p!=v.end(); ++p )
        cout << *p << "\n";
}
```

```
template<class T>
void printall(const vector<T>& v) {
    for (auto p = v.begin(); p!=v.end(); ++p)
        cout << *p << "\n";
}
```

auto type deduction

```
#include <initializer_list>
template<typename T>
void foo(T v) {}

int main() {
    auto v = {1, 2, 4}; // OK.
    foo({1, 2, 4});     // template could not deduce the T
}
```

auto type deduction

```
#include <initializer_list>
template<typename T>
void foo(T v) {}
```

```
int main() {
    auto v = {1, 2, 4}; // OK.
    foo({1, 2, 4});    // template conversion error
}
```

I wonder this myself. Alas, I have not been able to find a convincing explanation. But the rule is the rule...



Effective
Modern C++

42 SPECIFIC WAYS TO IMPROVE YOUR USE OF C++11 AND C++14

Scott Meyers

auto type deduction C++14

```
auto foo() { // 14  
    return 42;  
}
```

```
auto foo() -> int { // 11  
    return 42;  
}
```

decltype(auto)

```
int arr[10];  
  
auto foo() {  
    return arr[3]; // return int type  
}
```


decltype(auto)

```
int arr[10];
```

```
auto foo() {  
    return arr[3]; // return int type  
}
```

Regular

Ignore the cv-qualifier and any references. Copy it anyway.

```
template<typename T>
```

```
void f(T param);
```

```
int x = 27;
```

```
const int cx = x;
```

```
const int& rx = x;
```

```
f(x); // T's and param's types are both int
```

```
f(cx); // T's and param's types are again both int
```

```
f(rx); // T's and param's types are still both int
```

decltype(auto)

```
int arr[10];
```

```
auto foo() {  
    return arr[3]; // return int type  
}
```

Regular

Ignore the cv-qualifier and any references. Copy it anyway.

```
template<typename T>
```

```
void f(T param);
```

```
int x = 27;
```

```
const int cx = x;
```

```
const int& rx = x;
```

```
f(x); // T's and param's type
```

```
f(cx); // T's and param's type
```

```
f(rx); // T's and param's type
```

How to return a
reference type?



decltype(auto)

```
int arr[10];
```

```
auto foo() -> decltype(auto) {  
    return arr[3]; // return int type  
}
```

decltype(auto)

```
int arr[10];
```

```
auto foo() -> decltype(arr[3]) {  
    return arr[3]; // return int type  
}
```

decltype(auto)

```
int arr[10];
```

int &

```
auto foo() -> decltype(arr[3]) {  
    return arr[3]; // return int type  
}
```

Take away

Template Argument Deduction

- Deducing parameter type from argument
- CV-qualifiers are in the type system

Auto type deduction is similar to TAD, but not initialized_list

- Be careful on curly braces {} initialization

decltype(auto)

- Deduce type from the return expression

Thank you!

scc@teamt5.org



Deducting type from Params

```
template<typename ParamType>
```

```
void f(ParamType param);
```

```
f(expr);
```

Template 101

```
template<parameter-list >
```

Type

Non-type


Template

```
T max(T a, T b) {  
    return a > b ? a : b;  
}
```

Type template parameter

<code>type-parameter-key name(optional)</code>	(1)
<code>type-parameter-key name(optional) = default</code>	(2)
<code>type-parameter-key ... name(optional)</code>	(3) (since C++11)
<code>type-constraint name(optional)</code>	(4) (since C++20)
<code>type-constraint name(optional) = default</code>	(5) (since C++20)
<code>type-constraint ... name(optional)</code>	(6) (since C++20)

Reference type





Reference type

The value categories

The biggest change since C++11.

SCC




Reference

Declares a named variable as a reference, that is, an alias to an already-existing object or function.


Lvalue reference

Rvalue reference



Reference

Declares a named variable as a reference, that is, an alias to an already-existing object or function.



Rules in templates

An *id-expression* naming a non-type *template-parameter* of class type T denotes a static storage duration object of type `const T`, known as a *template parameter object*, which is template-argument-equivalent ([`temp.type`]) to the corresponding template argument after it has been converted to the type of the *template-parameter* ([`temp.arg.nontype`]). No two template parameter objects are template-argument-equivalent.

[*Note 3*: If an *id-expression* names a non-type non-reference *template-parameter*, then it is a prvalue if it has non-class type. Otherwise, if it is of class type T, it is an lvalue and has type `const T` ([`expr.prim.id.unqual`]). — *end note*]

頭腦體操！

```
using X = int;  
struct A {};  
template<const X& x, int i, A a> void f() {  
    i++;  
    &x;  
  
    &i;  
    &a;  
    int& ri = i;  
    const int& cri = i;  
    const A& ra = a;  
}
```



頭腦體操！

```
using X = int;  
struct A {};  
template<const X& x, int i, A a> void f() {
```

i++;

&x;

&i;

&a;

int& ri = i;

const int& cri = i;

const A& ra = a;

}



頭腦體操！

```
using X = int;  
struct A {};  
template<const X& x, int i, A a> void f() {
```

```
i++; // error: change of template-parameter value
```

```
&x;
```

```
&i;
```

```
&a;
```

```
int& ri = i;
```

```
const int& cri = i;
```

```
const A& ra = a;
```

```
}
```



頭腦體操！

```
using X = int;  
struct A {};  
template<const X& x, int i, A a> void f() {  
    i++;
```

&x;

```
    &i;  
    &a;  
    int& ri = i;  
    const int& cri = i;  
    const A& ra = a;  
}
```



頭腦體操！

```
using X = int;  
struct A {};  
template<const X& x, int i, A a> void f() {  
    i++;
```

&x; // OK

```
&i;  
&a;  
int& ri = i;  
const int& cri = i;  
const A& ra = a;  
}
```



頭腦體操！

```
using X = int;  
struct A {};  
template<const X& x, int i, A a> void f() {  
    i++;  
    &x;
```

&i;

```
    &a;  
    int& ri = i;  
    const int& cri = i;  
    const A& ra = a;  
}
```



頭腦體操！

```
using X = int;  
struct A {};  
template<const X& x, int i, A a> void f() {  
    i++;  
    &x;
```

&i; // error: address of non-reference template-parameter

```
&a;  
int& ri = i;  
const int& cri = i;  
const A& ra = a;  
}
```



頭腦體操！

```
using X = int;  
struct A {};  
template<const X& x, int i, A a> void f() {  
    i++;  
    &x;  
  
    &i;  
    &a;  
    int& ri = i;  
    const int& cri = i;  
    const A& ra = a;  
}
```



頭腦體操！

```
using X = int;  
struct A {};  
template<const X& x, int i, A a> void f() {  
    i++;  
    &x;  
  
    &i;  
    &a;  
    int& ri = i;  
    const int& cri = i;  
    const A& ra = a;  
}
```

