PROBLEM CL11

# VTOL Propulsion Device in Hover: Nozzle Angle and Flow State

Original statement · CL11.pdf


Thrust vectoring | Bernoulli | Linear momentum | Energy

## OFFICIAL PROBLEM STATEMENT

The propulsion device of a VTOL (vertical take-off and landing) aircraft includes a horizontal intake of cross section $A_i$ and a thrust vectoring nozzle of variable angle $\alpha$ and exit cross section $A_e$. When the aircraft is hovering (suspended at a fixed point), the engine must provide a force $\bar{F} = F_x \bar{e}_x + F_y \bar{e}_y$, such that the lift $F_y$ equals the weight of the aircraft ($Mg$), while the thrust $F_x$ is identically zero. The work per unit time on the air stream through the mobile blades is $W$ and the amount of heat added per unit time is $Q$ (including heat losses through the walls). For the analysis of the problem, one may introduce the following assumptions regarding the air motion:

- The effect of gravity is entirely negligible.
- Flow properties at the entrance and exit sections are uniform.
- The air around the engine casing is at rest with uniform pressure $p_a$.
- Upstream from the inlet the flow is inviscid and with constant density, such that $\rho_i = \rho_a$ and one may use Bernoulli's equation along any streamline to relate the ambient pressure $p_a$ with that found at the entrance $p_i$.

With the above simplifications, write the equations that determine the values of $U_i$, $U_e$, $p_i$, $\rho_e$ and $\alpha$ in terms of the known quantities ($p_a$, $Mg$, $\rho_a$, $A_i$, $A_e$, $\gamma$, $W$, and $Q$).




Statement figure (redrawn from CL11.pdf, p. 1): intake $A_i$ ($p_i$, $U_i$, $\rho_a$), heat $Q$ and blades $W$ inside the duct, nozzle of exit section $A_e$ at the angle $\alpha$ from the vertical ($U_e$, $\rho_e$, $p_a$); axes $x$, $y$ at the centre of the rotating joint

`Source: CL11.pdf (page 1). Notes.pdf: integral mass balance Eq. 3.10, integral momentum balance Eq. 3.35, integral total energy balance Eq. 3.46, Bernoulli's equation Eq. 4.17.`

**Worked solution (4-phase method)**

`PHASE 1`

## Hypotheses, Data and Unknowns

- Steady (on average); neglect $\bar{g}$; uniform properties at $i$ and $e$; perfect gas, $h = \frac{\gamma}{\gamma-1}\frac{p}{\rho}$; ambient air at rest at $p_a$ around the casing.


- Inlet: $\rho_i = \rho_a$ (constant density upstream) and Bernoulli from the still air to the inlet. Exit: free jet at $p_a$, density $\rho_e$.
- Geometry (figure): air enters along $-\bar{e}_x$ through the horizontal intake; the jet leaves downwards and backwards, $\bar{v}_e = -U_e(\sin\alpha\,\bar{e}_x + \cos\alpha\,\bar{e}_y)$, with $\alpha$ measured from the vertical.
- Hover: $F_x = 0, F_y = Mg$. Data: $[p_a,\ \rho_a,\ Mg,\ A_i,\ A_e,\ \gamma,\ \dot{W},\ \dot{Q}]$. Unknowns: $[U_i,\ U_e,\ p_i,\ \rho_e,\ \alpha]$: five equations are needed.

| Symbol | Meaning | SI unit |
|---|---|---|
| $A_i, A_e$ | intake and exit areas | $m^2$ |
| $U_i, U_e$ | intake and exit velocities | m/s |
| $p_i, \rho_e$ | intake pressure, exit density | Pa, $kg/m^3$ |
| $\alpha$ | nozzle angle from the vertical | rad |
| $\dot{W}, \dot{Q}$ | power and heat given to the air | W |
| $p_a, \rho_a, Mg, \gamma$ | ambient pressure and density, weight of the aircraft, specific-heat ratio | Pa, $kg/m^3$, N, 1 |

PHASE 2

## Frames, Control Volume and Surfaces

- Frame fixed to the hovering aircraft (inertial while hovering); $\bar{e}_x$ horizontal, $\bar{e}_y$ vertical upwards.
- Surfaces: $\Sigma_i$ (intake, $\bar{n} = +\bar{e}_x, \bar{v} = -U_i\bar{e}_x$), $\Sigma_e$ (exit, $\bar{n} = \bar{v}_e/U_e$), $\Sigma_w$ (fixed walls) and $\Sigma_m$ (mobile blades).




Control volume of the solution: $\Sigma_i$ (intake, $\bar{n} = +\bar{e}_x$, $\bar{v} = -U_i \bar{e}_x$), $\Sigma_e$ (exit, $\bar{n} = \bar{v}_e / U_e$), the fixed walls $\Sigma_w$ and the mobile blades $\Sigma_m$ (dashed around them)

$$\boxed{\bar{F} = F_x \bar{e}_x + F_y \bar{e}_y = \int_{\Sigma_w, \Sigma_m} \left[ (p - p_a)\, \bar{n} - \bar{\bar{\tau}}' \cdot \bar{n} \right] d\sigma} \qquad \text{(force of the air on the engine)}$$

PHASE 3

## Balances, Surface by Surface

Mass (Notes Eq. 3.10)

$$\underbrace{\frac{d}{dt} \cancel{\int_{V_c} \rho \, dV}}_{0 \text{ (steady)}} + \int_{\Sigma_c} \rho \left( \bar{v} - \bar{v}_c \right) \cdot \bar{n} \, d\sigma = 0$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

| **Surface** | $\int \rho\,(\bar{v}-\bar{v}_c)\cdot\bar{n}\,d\sigma$ |
|---|---|
| $\Sigma_i$ | $\rho_a(-U_i)A_i$ |
| $\Sigma_e$ | $+\rho_e U_e A_e$ |
| $\Sigma_w$, $\Sigma_m$ | $0$ |

$$\boxed{\rho_a U_i A_i = \rho_e U_e A_e = \dot{m}} \tag{1}$$

Entrance region (Notes Eq. 4.17, from the still ambient air to the inlet):

$$\boxed{p_a = p_i + \tfrac{1}{2}\rho_a U_i^2} \tag{2}$$

`Linear momentum (Notes Eq. 3.35)`

$$\underbrace{\frac{d}{dt}\int_{V_c}\rho\bar{v}\,dV}_{0\ \text{(steady)}} + \int_{\Sigma_c}\rho\bar{v}\,[(\bar{v}-\bar{v}_c)\cdot\bar{n}]\,d\sigma = -\int_{\Sigma_c}(p-p_a)\,\bar{n}\,d\sigma + \int_{\Sigma_c}\bar{\bar{\tau}}'\cdot\bar{n}\,d\sigma + \underbrace{\int_{V_c}\rho\bar{g}\,dV}_{\text{neglect }\bar{g}}$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

| **Surface** | $\int \rho\bar{v}\,[(\bar{v}-\bar{v}_c)\cdot\bar{n}]\,d\sigma$ | $-\int(p-p_a)\,\bar{n}\,d\sigma$ | $\int\bar{\bar{\tau}}'\cdot\bar{n}\,d\sigma$ |
|---|---|---|---|
| $\Sigma_i$ | $\rho_a(-U_i\bar{e}_x)(-U_i)A_i = \rho_a U_i^2 A_i\,\bar{e}_x$ | $-(p_i-p_a)A_i\,\bar{e}_x$ | $0$ |
| $\Sigma_e$ | $-\rho_e U_e^2 A_e(\sin\alpha\,\bar{e}_x+\cos\alpha\,\bar{e}_y)$ | $0$ (free jet) | $0$ |
| $\Sigma_w$, $\Sigma_m$ | $0$ | $-\int(p-p_a)\,\bar{n}\,d\sigma$ | $\int\bar{\bar{\tau}}'\cdot\bar{n}\,d\sigma$ |

Boxed terms: $-\bar{F} = -F_x\bar{e}_x - F_y\bar{e}_y$. $x$ component with $F_x = 0$, (2) and (1): $\rho_a U_i^2 A_i - \rho_e U_e^2 A_e\sin\alpha = \tfrac{1}{2}\rho_a U_i^2 A_i$, i.e. $\tfrac{1}{2}\rho_a U_i^2 A_i = \rho_a U_i A_i\,U_e\sin\alpha$. $y$ component with $F_y = Mg$: $-\rho_e U_e^2 A_e\cos\alpha = -Mg$.

$$\boxed{U_i = 2\,U_e \sin\alpha} \quad (3) \qquad \boxed{Mg = \rho_e U_e^2 A_e \cos\alpha = \rho_a U_i^2 A_i \,\frac{\cos\alpha}{2\sin\alpha}} \quad (4)$$

**Total energy (Notes Eq. 3.46; $Q_R \equiv Q_c + Q_r$ is the volumetric heat release)**

$$\underbrace{\frac{d}{dt}\cancel{\int_{V_c} \rho\left(e + \frac{v^2}{2}\right) dV}}_{0\ \text{(steady)}} + \int_{\Sigma_c} \rho\left(e + \frac{v^2}{2}\right)\left[(\bar{v} - \bar{v}_c)\cdot\bar{n}\right] d\sigma = -\int_{\Sigma_c} p\,\bar{v}\cdot\bar{n}\,d\sigma + \int_{\Sigma_c} \bar{v}\cdot(\bar{\bar{\tau}}'\cdot\bar{n})\,d\sigma + \underbrace{\cancel{\int_{V_c} \rho\bar{g}\cdot\bar{v}\,dV}}_{\text{neglect } \bar{g}} - \int_{\Sigma_c} \bar{q}\cdot\bar{n}\,d\sigma + \int_{V_c} Q_R\,dV$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

| **Surface** | $\int \rho\left(e + \frac{v^2}{2}\right)(\bar{v}\cdot\bar{n})\,d\sigma$ | $-\int p\,\bar{v}\cdot\bar{n}\,d\sigma$ | $\int \bar{v}\cdot(\bar{\bar{\tau}}'\cdot\bar{n})\,d\sigma$ | $-\int \bar{q}\cdot\bar{n}\,d\sigma$ |
|---|---|---|---|---|
| $\Sigma_i$ | $-\dot{m}\left(e_i + \frac{U_i^2}{2}\right)$ | $+p_i U_i A_i$ | $0$ | $0$ |
| $\Sigma_e$ | $+\dot{m}\left(e_e + \frac{U_e^2}{2}\right)$ | $-p_a U_e A_e$ | $0$ | $0$ |
| $\Sigma_m$ | $0$ | $-\int_{\Sigma_m} p\,\bar{v}\cdot\bar{n}\,d\sigma$ | $\int_{\Sigma_m} \bar{v}\cdot(\bar{\bar{\tau}}'\cdot\bar{n})\,d\sigma$ | $-\int_{\Sigma_m} \bar{q}\cdot\bar{n}\,d\sigma$ |
| $\Sigma_w$ | $0$ | $0$ | $0$ | $-\int_{\Sigma_w} \bar{q}\cdot\bar{n}\,d\sigma$ |

Boxed terms: the work on $\Sigma_m$ is $\dot{W}$; the heat through the walls plus the volume term $\int_{V_c} Q_R\,dV$ is $\dot{Q}$ (net, including the losses). With $h = e + p/\rho = \frac{\gamma}{\gamma-1}\frac{p}{\rho}$:

$$\boxed{\rho_a U_i A_i \left[\left(\frac{\gamma}{\gamma-1}\frac{p_a}{\rho_e} + \frac{U_e^2}{2}\right) - \left(\frac{\gamma}{\gamma-1}\frac{p_i}{\rho_a} + \frac{U_i^2}{2}\right)\right] = \dot{W} + \dot{Q}} \quad (5)$$

(1) to (5) are five equations for $U_i$, $U_e$, $p_i$, $\rho_e$ and $\alpha$, which answers the question.

PHASE 4

## Interpretation, Limits and Dimensional Check

- (3) says that the backward component of the jet momentum must cancel the intake momentum plus the suction force at the intake: because the intake is at a lower pressure than ambient (2), only half of $\rho_a U_i^2 A_i$ has to be balanced.

- (4): the lift is the vertical momentum flux of the jet. For $\alpha \to 0$ (vertical jet), (3) would require $U_i \to 0$: the intake momentum could not be balanced, so a hovering engine with a horizontal intake needs $\alpha > 0$.
- Dimensions (SI): $[\rho_e U_e^2 A_e] = \mathrm{N} = [Mg]$; $[\dot{m}\,\gamma p/((\gamma-1)\rho)] = \mathrm{W}$.
- Numerical illustration (hypothetical data, extension): $\rho_a = 1.2$ kg/m$^3$, $p_a = 101325$ Pa, $A_i = 10$ m$^2$, $A_e = 12$ m$^2$, $Mg = 20$ kN, $\dot{W} + \dot{Q} = 5$ MW, $\gamma = 1.4$. For a given $\alpha$, (3), (1) and (4) fix $U_e^2 = Mg/(\rho_a A_i \sin 2\alpha)$, $U_i = 2U_e \sin\alpha$ and $\rho_e = 2\rho_a (A_i/A_e)\sin\alpha$, and (5) is then solved for $\alpha$ by bisection: $\alpha = 36.227^\circ$, $U_e = 41.809$ m/s, $U_i = 49.417$ m/s, $p_i = 99860$ Pa, $\rho_e = 1.1820$ kg/m$^3$ (all five equations satisfied to better than $10^{-9}$ in relative terms). The intake Mach number is about $0.14$ and $p_i/p_a = 0.986$, so the constant-density hypothesis behind (2) holds.
- Agreement with the official solution: CL11.pdf obtains (1) to (5).