PROBLEM CL22

Water in a Shrinking Cylinder: Level, Velocity, Force and Power

Original statement · CL22.pdf


Unsteady | Deforming CV | Kinetic energy | Power

OFFICIAL PROBLEM STATEMENT

Figure (a) of CL22.pdf shows a cylinder of radius a_0 closed at the bottom that contains a volume $\pi a_0^2 h_0$ of water. The water is in contact with the stagnant atmosphere at a pressure p_a. At time $t = 0$ the cylinder radius $a(t)$ starts decreasing and the level of water rises, as shown in figure (b) for a generic instant of time t. If $a(t)$ is known,

- Define clearly a control volume and use the mass conservation principle to determine the level of water $h(t)$ and the velocity of the free surface $\dot{h}(t)$ for a generic instant of time t.
- Using control volume V_2, as shown in the figure (b), use the continuity equation to obtain the z-component of the velocity $v_z(z,t)$ in the liquid at an arbitrary level z, as sketched in figure b.
- Using the previous results, and specifying the control volume used in the analysis, determine separately the force exerted by both the liquid and the atmosphere on the cylinder. Calculate the net force exerted by both fluids on the cylinder.
- Using the kinetic energy equation, and neglecting v_r^2 in the kinetic energy, obtain the mechanical power exerted on the solid walls by both the liquid and the atmosphere. Determine the net power exerted by both fluids on the liquid.

Note: Neglect viscous dissipation within the liquid, viscous stresses at the free surface and take the pressure in the air as a constant p_a.



Statement figure (redrawn from CL22.pdf, p. 1): (a) at $t = 0$, radius a_0 and level h_0; (b) at $t > 0$, radius $a(t)$, level $h(t)$ and the fixed control volume V_2 up to the level z

Source: CL22.pdf (pages 1-3, exam of 28-10-2018, with handwritten solution). Notes.pdf, Chapter 3: Reynolds transport theorem for a moving control volume Eqs. 3.7-3.8, integral mass balance Eq. 3.10, integral momentum balance Eq. 3.35, kinetic-energy balance Eq. 4.24 (with Eq. 3.8).

Worked solution (4-phase method)

PHASE 1

Hypotheses, Data and Unknowns

- Unsteady flow of an incompressible liquid (water, ρ constant) with gravity $\bar{g} = -g\bar{e}_z$ (here gravity is kept); viscous dissipation and stresses at the free surface neglected; air at constant p_a.


- The radius $a(t)$ is a known function with $a(0) = a_0$, $\dot{a} < 0$; the bottom is fixed at $z = 0$; the free surface stays flat at $z = h(t)$.
- The axial velocity is assumed uniform over each horizontal section, $v_z(z,t)$, and the kinetic energy of the radial motion (v_r^2) is neglected (statement).
- Data: $[a(t),\ a_0,\ h_0,\ \rho,\ g,\ p_a]$. Unknowns: $[h,\ \dot{h},\ v_z,\ F_{L\to W},\ F_{A\to W},\ \dot{W}_{L\to W},\ \dot{W}_{A\to W}]$.

Symbol	Meaning	SI unit
$a(t)$, a_0	cylinder radius, initial radius	m
$h(t)$, h_0	water level, initial level	m
$v_z(z,t)$	axial velocity of the water	m/s
F	axial force on the cylinder	N
$\dot{W}$	mechanical power on the walls	W

PHASE 2

Frames, Control Volumes and Surfaces

- Inertial frame fixed to the bottom; cylindrical coordinates (r, θ, z), $\bar{e}_z$ upwards.
- Control volume 1 (the water itself, a material volume): Σ_s (free surface, $\bar{v}_c = \dot{h}\bar{e}_z$, $\bar{n} = \bar{e}_z$), Σ_L (lateral wall, $\bar{v}_c = \dot{a}\bar{e}_r$, $\bar{n} = \bar{e}_r$) and Σ_b (bottom, $\bar{v}_c = 0$, $\bar{n} = -\bar{e}_z$). Each surface follows the liquid in the normal direction, $(\bar{v} - \bar{v}_c)\cdot\bar{n} = 0$ ($v_z(h) = \dot{h}$, $v_r(a) = \dot{a}$, $v_z(0) = 0$), so no flux crosses Σ_c; the tangential velocity may differ from that of the surface (ideal liquid).
- Control volume V_2: from the bottom to a fixed level z: Σ_b, Σ_{L2} (lateral wall, moving with $\dot{a}\bar{e}_r$) and Σ_z (fixed horizontal section, $\bar{v}_c = 0$, $\bar{n} = \bar{e}_z$).
- Axial forces on the cylinder: $F_{L\to W}$ (liquid on Σ_L, Σ_b) and $F_{A\to W}$ (atmosphere on the outer surface: radial on the lateral wall, $+p_a\pi a^2$ on the outer face of the bottom; the air inside above the water also pushes only radially).



(1) control volume 1: the water
every surface moves with the fluid

(2) control volume V_2
top fixed at the level z, side moving with the wall

Control volumes of the solution: (1) the water, with Σ_s, Σ_L, Σ_b and their outward normals, used for mass, momentum and kinetic energy; (2) V_2, with the fixed section Σ_z, the moving wall Σ_{L2} and Σ_b, used for $v_z(z,t)$ (after the official solution, CL22.pdf, p. 2)

PHASE 3

Balances, Surface by Surface

1. Mass on control volume 1 (Notes Eq. 3.10)

$$\frac{d}{dt}\int_{V_c(t)} \rho \, dV + \int_{\Sigma_c(t)} \rho \, (\bar{v} - \bar{v}_c) \cdot \bar{n} \, d\sigma = 0$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

Surface	$\int \rho \, (\bar{v} - \bar{v}_c) \cdot \bar{n} \, d\sigma$
Σ_s	0 ($v_z - \dot{h} = 0$ at $z = h$)
Σ_L	0 ($v_r - \dot{a} = 0$ at $r = a$)
Σ_b	0 ($v_z = 0$, $\bar{v}_c = 0$)

Therefore $\frac{d}{dt}\left[\rho\pi a^2 h\right] = 0$ and $\rho\pi a^2(t)h(t) = \rho\pi a_0^2 h_0$. Differentiating $h = a_0^2 h_0 a^{-2}$ with the chain rule, $\frac{dh}{dt} = a_0^2 h_0\,(-2)a^{-3}\dot{a}$:

$$\boxed{h(t) = \frac{a_0^2}{a^2(t)}\,h_0} \quad (1) \qquad \boxed{\dot{h} = -\frac{2a_0^2 h_0\,\dot{a}}{a^3} = -2h\,\frac{\dot{a}}{a}} \quad (2)$$

2. Mass on V_2 (Notes Eq. 3.10)

$$\frac{d}{dt}\int_{V_2(t)} \rho\, dV + \int_{\Sigma_2(t)} \rho\,(\bar{v} - \bar{v}_c)\cdot\bar{n}\, d\sigma = 0$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

Surface	$\int \rho\,(\bar{v} - \bar{v}_c)\cdot\bar{n}\, d\sigma$
Σ_z	$\rho\, v_z\, \pi a^2$ ($\bar{v}_c = 0$)
Σ_{L2}	0 ($v_r - \dot{a} = 0$)
Σ_b	0

Volume term: $\frac{d}{dt}(\rho\pi a^2 z) = \rho\pi z\frac{d(a^2)}{dt} = 2\rho\pi z a\dot{a}$ (z fixed).

$$2\rho\pi z a\dot{a} + \rho v_z \pi a^2 = 0 \implies \boxed{v_z(z,t) = -\frac{1}{a^2}\frac{d(a^2)}{dt}\,z = -\frac{2\dot{a}(t)}{a(t)}\,z} \quad (3)$$

Check: at $z = h$, $v_z = -2\dot{a}h/a = \dot{h}$, the velocity of the free surface (2). It is also consistent with the differential continuity equation: with $v_r = \dot{a}r/a$ (so that $v_r = \dot{a}$ at the wall), $\frac{1}{r}\frac{\partial(r v_r)}{\partial r} + \frac{\partial v_z}{\partial z} = \frac{2\dot{a}}{a} - \frac{2\dot{a}}{a} = 0$ (extension).

3. Momentum, z component, on control volume 1 (Notes Eq. 3.35)

$$\frac{d}{dt}\int_{V_c}\rho v_z\,dV+\underbrace{\cancel{\int_{\Sigma_c}\rho v_z\left[(\bar v-\bar v_c)\cdot\bar n\right]d\sigma}}_{0}=-\int_{\Sigma_c}p\,n_z\,d\sigma+\int_{\Sigma_c}(\bar{\bar\tau}'\cdot\bar n)_z\,d\sigma-\int_{V_c}\rho g\,dV$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

Surface	$-\int p\,n_z\,d\sigma$	$\int(\bar{\bar\tau}'\cdot\bar n)_z\,d\sigma$
Σ_s	$-p_a\pi a^2$	0 (neglected)
Σ_L	$-\int_{\Sigma_L} p\,n_z\,d\sigma$	$\int_{\Sigma_L}(\bar{\bar\tau}'\cdot\bar n)_z\,d\sigma$
Σ_b	$-\int_{\Sigma_b} p\,n_z\,d\sigma$	$\int_{\Sigma_b}(\bar{\bar\tau}'\cdot\bar n)_z\,d\sigma$

Boxed Σ_L, Σ_b terms: the force of the walls on the liquid, $-F_{L\to W}$. Volume terms: $\int_{V_c}\rho v_z\,dV=\int_0^h\rho\left(-\frac{2\dot a}{a}z\right)\pi a^2\,dz=-2\rho\pi a\dot a\left[\frac{z^2}{2}\right]_0^h=-\rho\pi a\dot a h^2$, and the weight $\rho g\pi a_0^2h_0$.

$$\frac{d}{dt}\left(-\rho\pi a\dot a h^2\right)=-F_{L\to W}-p_a\pi a^2-\rho g\pi a_0^2h_0 \tag{4}$$

Product rule: $\frac{d}{dt}(a\dot a h^2)=\dot a^2h^2+a\ddot a h^2+2a\dot a h\dot h$, and with (2), $2a\dot a h\dot h=2a\dot a h\left(-2h\frac{\dot a}{a}\right)=-4\dot a^2h^2$, so $\frac{d}{dt}(a\dot a h^2)=h^2\left(a\ddot a-3\dot a^2\right)$ with $h^2=\frac{a_0^4h_0^2}{a^4}$ from (1). From (4):

$$\boxed{F_{L\to W}=\rho\pi\,\frac{a_0^4h_0^2}{a^4}\left(a\ddot a-3\dot a^2\right)-p_a\pi a^2-\rho g\pi a_0^2h_0} \tag{5}$$

$$\boxed{F_{A\to W}=p_a\pi a^2}$$

$$\boxed{F = F_{L\to W} + F_{A\to W} = \rho\pi a_0^2\left[\frac{a_0^2 h_0^2}{a^4}\left(a\ddot{a} - 3\dot{a}^2\right) - g h_0\right]} \tag{6}$$

4. Kinetic energy on control volume 1 (Notes Eq. 4.24 with Eq. 3.8)

$$\frac{d}{dt}\int_{V_c}\rho\frac{v_z^2}{2}\,dV + \underbrace{\cancel{\int_{\Sigma_c}\rho\frac{v^2}{2}(\bar{v}-\bar{v}_c)\cdot\bar{n}\,d\sigma}}_{0} = -\int_{\Sigma_c} p\,\bar{v}\cdot\bar{n}\,d\sigma + \int_{\Sigma_c}\bar{v}\cdot(\bar{\bar{\tau}}'\cdot\bar{n})\,d\sigma + \int_{V_c}\rho\bar{g}\cdot\bar{v}\,dV + \underbrace{\cancel{\int_{V_c} p\,\nabla\cdot\bar{v}\,dV}}_{0\text{ (incompressible)}} - \underbrace{\cancel{\int_{V_c}\Phi_v\,dV}}_{\text{neglect}}$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

Surface	$-\int p\,\bar{v}\cdot\bar{n}\,d\sigma$	$\int\bar{v}\cdot(\bar{\bar{\tau}}'\cdot\bar{n})\,d\sigma$
Σ_s	$-p_a\dot{h}\,\pi a^2$	0 (neglected)
Σ_L	$-\int_{\Sigma_L} p\,\dot{a}\,d\sigma$	$\int_{\Sigma_L}\bar{v}\cdot(\bar{\bar{\tau}}'\cdot\bar{n})\,d\sigma$
Σ_b	0 ($\bar{v}=0$)	0 ($\bar{v}=0$)

Boxed Σ_L terms: the power of the walls on the liquid, $-\dot{W}_{L\to W}$. Volume terms: $\int_{V_c}\rho\bar{g}\cdot\bar{v}\,dV = -\rho g\int_0^h v_z\pi a^2\,dz = -\rho g\pi a^2\int_0^h\left(-\frac{2\dot{a}z}{a}\right)dz = 2\rho g\pi a\dot{a}\left[\frac{z^2}{2}\right]_0^h = \rho g\pi a\dot{a}h^2$ and $\int_{V_c}\rho\frac{v_z^2}{2}dV = \frac{\rho\pi a^2}{2}\frac{4\dot{a}^2}{a^2}\left[\frac{z^3}{3}\right]_0^h = \frac{2}{3}\rho\pi\dot{a}^2h^3$.

$$\frac{d}{dt}\left(\frac{2}{3}\rho\pi\dot{a}^2h^3\right) = -\dot{W}_{L\to W} - p_a\pi a^2\dot{h} + \rho g\pi a\dot{a}h^2 \tag{7}$$

Chain and product rule with (2): $\frac{d}{dt}(\dot{a}^2h^3) = 2\dot{a}\ddot{a}h^3 + 3\dot{a}^2h^2\dot{h} = 2\dot{a}\ddot{a}h^3 - 6\dot{a}^3\frac{h^3}{a} = 2h^3\dot{a}\left(\ddot{a} - 3\frac{\dot{a}^2}{a}\right)$, with $h^3 = \frac{a_0^6h_0^3}{a^6}$; and $-p_a\pi a^2\dot{h} = 2p_a\pi\frac{a_0^2}{a}h_0\dot{a}$. From (7):

$$\boxed{\dot{W}_{L\to W} = -\frac{4}{3}\rho\pi\left(\frac{a_0}{a}\right)^6 h_0^3\,\dot{a}\left(\ddot{a} - \frac{3\dot{a}^2}{a}\right) + 2p_a\pi\frac{a_0^2}{a}h_0\,\dot{a} + \rho g\pi a\dot{a}h^2} \tag{8}$$

Atmosphere on the walls: only the outer lateral surface below the water level moves against an unbalanced p_a (above the level, the air acts on both faces), and the bottom does not move: $\dot{W}_{A\to W} = -\int p_a\,\bar{v}\cdot\bar{n}_{out}\,d\sigma = -p_a\dot{a}\,2\pi a h$:

$$\boxed{\dot{W}_{A\to W} = -2p_a\pi\frac{a_0^2}{a}h_0\,\dot{a}}$$

$$\boxed{\dot{W} = \dot{W}_{L\to W} + \dot{W}_{A\to W} = -\frac{4}{3}\rho\pi\left(\frac{a_0}{a}\right)^6 h_0^3\,\dot{a}\left(\ddot{a} - \frac{3\dot{a}^2}{a}\right) + \rho g\pi a\dot{a}h^2} \quad (9)$$

PHASE 4

Interpretation, Limits and Dimensional Check

- At rest ($\dot{a} = \ddot{a} = 0$): $F_{L\to W} = -p_a\pi a^2 - \rho g\pi a_0^2 h_0$ (the water and the air above it push the bottom down with p_a and the weight), the atmosphere pushes the bottom up with $p_a\pi a^2$, and the net force is the weight. The ambient pressure cancels in the net force (6) and in the net power (9).
- The term $\rho\pi\frac{a_0^4 h_0^2}{a^4}(a\ddot{a} - 3\dot{a}^2)$ is minus the rate of change of the momentum of the water: the walls must accelerate the rising column.
- The statement asks finally for 'the net power exerted by both fluids on the liquid'; from the context (and the official solution) the intended quantity is the net power of both fluids on the walls, (9).
- Dimensions (SI): $[\rho a_0^4 h_0^2\dot{a}^2/a^4] = \mathrm{N}$; $[\rho(a_0/a)^6 h_0^3\dot{a}\ddot{a}] = \mathrm{W}$; $[p_a a_0^2 h_0\dot{a}/a] = \mathrm{W}$.
- Numerical cross-check (hypothetical data): $a(t) = a_0(1 - 0.15t + 0.04t^2)$, $a_0 = 0.1$ m, $h_0 = 0.3$ m, $\rho = 1000$ kg/m^3, $g = 9.81$ m/s^2 at $t = 0.7$ s: differentiating numerically the momentum and the kinetic energy of the water (quadrature of the integrals of 3 and 4) reproduces $F_{L\to W} = -2755.01$ N and $\dot{W}_{L\to W} = -199.696$ W from (5) and (8) to 12 digits; the net values are $F = -92.27$ N and $\dot{W} = -3.399$ W.
- Agreement with the official solution: CL22.pdf obtains (1) to (9).