PROBLEM CL6

# Elbow Discharging a Vertical Jet: Velocity, Force and Heat


Original statement · CL6.pdf

Elbow | Linear momentum | Energy | Heat through the walls

## OFFICIAL PROBLEM STATEMENT

A liquid of density $\rho$ and specific heat $c$ flows through the elbow-shaped pipe shown in CL6.pdf, discharging to the atmosphere as a vertical jet through an outlet section of surface area $A_o$, different from the value $A_i$ at the inlet. Gravity is assumed to have a negligible effect on the fluid motion. Besides, uniform flow properties are assumed at the inlet and outlet sections, where readings from a thermometer give different values $T_i$ and $T_o$ for the temperature. The velocity at the outlet section is measured to be $v_o$ and a manometer is used to determine the value $p_i$ for the pressure at the inlet section. In terms of all of these quantities, determine:

- The value of the velocity at the inlet $v_i$.
- The two components of the force $(F_x, F_z)$ exerted on the pipe.
- The amount of heat $Q$ transferred per unit time to the liquid by heat conduction through the pipe walls.




Statement figure (redrawn from CL6.pdf, p. 1): inlet section $A_i$ with $v_i$, $p_i$, $T_i$; outlet $A_o$ discharging a vertical jet $v_o$, $T_o$ into $p_a$; force components $F_x$, $F_z$ on the pipe and heat $Q$ through its walls

Source: CL6.pdf (page 1), also solved in class (class notes, CL6). Notes.pdf, Chapter 3: integral mass balance Eq. 3.11, integral momentum balance Eq. 3.36, integral total energy balance Eq. 3.46.

**Worked solution (4-phase method)**

PHASE 1

## Hypotheses, Data and Unknowns


- Steady, incompressible liquid, $e = cT$; neglect $\bar{g}$; uniform properties at inlet and outlet (no viscous stresses or conduction across them).
- Free jet: $p = p_a$ over the outlet section. The outer face of the pipe is in contact with the ambient air at $p_a$, so the force on the pipe is computed with gauge pressure $p - p_a$.
- Geometry (figure): the liquid enters horizontally along $+\bar{e}_x$ and leaves as a vertical jet along $-\bar{e}_z$ ($\bar{e}_z$ upwards).
- Data: $[\rho,\ c,\ A_i,\ A_o,\ v_o,\ p_i,\ p_a,\ T_i,\ T_o]$. Unknowns: $[v_i,\ F_x,\ F_z,\ \dot{Q}]$.

| Symbol | Meaning | SI unit |
|---|---|---|
| $A_i, A_o$ | inlet and outlet areas | $m^2$ |
| $v_i, v_o$ | inlet and outlet velocities | m/s |
| $p_i, p_a$ | inlet and ambient pressures | Pa |
| $T_i, T_o$ | inlet and outlet temperatures | K |
| $c$ | specific heat of the liquid | J/(kg·K) |
| $\dot{Q}$ | heat per unit time into the liquid | W |

PHASE 2

## Frames, Control Volume and Surfaces

- Frame fixed to the pipe, $\bar{e}_x$ horizontal (inlet flow direction), $\bar{e}_z$ vertical upwards. Fixed control volume: the liquid inside the pipe, $\bar{v}_c = 0$.
- Surfaces: $\Sigma_i$ (inlet, $\bar{n} = -\bar{e}_x$, $\bar{v} = v_i\bar{e}_x$), $\Sigma_o$ (outlet, $\bar{n} = -\bar{e}_z$, $\bar{v} = -v_o\bar{e}_z$), $\Sigma_w$ (pipe wall, $\bar{v} = 0$).




Control volume of the solution (as in the class notes): the liquid inside the pipe, with $\Sigma_i$ (inlet, $\bar{n} = -\bar{e}_x$), $\Sigma_o$ (outlet, $\bar{n} = -\bar{e}_z$) and the wall $\Sigma_w$, where the force and the heat are collected

Force of the liquid and the ambient air on the pipe, and heat through the walls, written on $\Sigma_w$:

$$\boxed{\bar{F} = F_x \bar{e}_x + F_z \bar{e}_z = \int_{\Sigma_w} (p - p_a)\, \bar{n}\, d\sigma - \int_{\Sigma_w} \bar{\bar{\tau}}' \cdot \bar{n}\, d\sigma}$$

$$\boxed{\dot{Q} = -\int_{\Sigma_w} \bar{q} \cdot \bar{n}\, d\sigma}$$

PHASE 3

## Balances, Surface by Surface

Mass (Notes Eq. 3.11)

$$\underbrace{\frac{d}{dt}\cancel{\int_{V_c}\rho\,dV}}_{0\ \text{(steady)}} + \int_{\Sigma_c}\rho\,(\bar{v}-\underbrace{\bar{v}_c}_{0})\cdot\bar{n}\,d\sigma = 0$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

| **Surface** | $\int \rho\,\bar{v}\cdot\bar{n}\,d\sigma$ |
|---|---|
| $\Sigma_i$ | $\rho\,v_i\bar{e}_x\cdot(-\bar{e}_x)A_i = -\rho v_i A_i$ |
| $\Sigma_o$ | $\rho\,(-v_o\bar{e}_z)\cdot(-\bar{e}_z)A_o = +\rho v_o A_o$ |
| $\Sigma_w$ | $0$ |

$$\boxed{v_i = \frac{A_o}{A_i}\,v_o}, \qquad \dot{m} = \rho v_i A_i = \rho v_o A_o \tag{1}$$

Linear momentum (Notes Eq. 3.36)

$$\underbrace{\frac{d}{dt}\cancel{\int_{V_c}\rho\bar{v}\,dV}}_{0\ \text{(steady)}} + \int_{\Sigma_c}\rho\bar{v}\,[(\bar{v}-\underbrace{\bar{v}_c}_{0})\cdot\bar{n}]\,d\sigma = -\int_{\Sigma_c}(p-p_a)\,\bar{n}\,d\sigma + \int_{\Sigma_c}\bar{\bar{\tau}}'\cdot\bar{n}\,d\sigma + \underbrace{\cancel{\int_{V_c}\rho\bar{g}\,dV}}_{\text{neglect }\bar{g}}$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

| **Surface** | $\int \rho\bar{v}\,(\bar{v}\cdot\bar{n})\,d\sigma$ | $-\int(p-p_a)\,\bar{n}\,d\sigma$ | $\int \bar{\bar{\tau}}'\cdot\bar{n}\,d\sigma$ |
|---|---|---|---|
| $\Sigma_i$ | $\rho v_i\bar{e}_x\,(-v_i)A_i = -\rho v_i^2 A_i\,\bar{e}_x$ | $-(p_i-p_a)(-\bar{e}_x)A_i = (p_i-p_a)A_i\,\bar{e}_x$ | $0$ |
| $\Sigma_o$ | $\rho(-v_o\bar{e}_z)\,(v_o)A_o = -\rho v_o^2 A_o\,\bar{e}_z$ | $0$ (free jet) | $0$ |
| $\Sigma_w$ | $0$ | $-\int_{\Sigma_w}(p-p_a)\,\bar{n}\,d\sigma$ | $\int_{\Sigma_w}\bar{\bar{\tau}}'\cdot\bar{n}\,d\sigma$ |

Boxed $\Sigma_w$ terms: $-\bar{F}$.

$$-\rho v_i^2 A_i\,\bar{e}_x - \rho v_o^2 A_o\,\bar{e}_z = (p_i - p_a)A_i\,\bar{e}_x - \bar{F} \implies \boxed{F_x = \left[\rho v_i^2 + (p_i - p_a)\right] A_i, \qquad F_z = \rho v_o^2 A_o} \quad (2)$$

**Total energy (Notes Eq. 3.46)**

$$\underbrace{\frac{d}{dt}\int_{V_c} \rho\left(e + \frac{v^2}{2}\right) dV}_{0\ \text{(steady)}} + \int_{\Sigma_c} \rho\left(e + \frac{v^2}{2}\right)\left[(\bar{v} - \underbrace{\bar{v}_c}_{0})\cdot\bar{n}\right] d\sigma = -\int_{\Sigma_c} p\,\bar{v}\cdot\bar{n}\,d\sigma + \int_{\Sigma_c} \bar{v}\cdot(\bar{\bar{\tau}}'\cdot\bar{n})\,d\sigma + \underbrace{\int_{V_c} \rho\bar{g}\cdot\bar{v}\,dV}_{\text{neglect } \bar{g}} - \int_{\Sigma_c} \bar{q}\cdot\bar{n}\,d\sigma + \underbrace{\int_{V_c} Q_H\,dV}_{0}$$

Each surface integral, surface by surface (the vertical line drawn under each integral in class):

| **Surface** | $\int \rho\left(e + \frac{v^2}{2}\right)(\bar{v}\cdot\bar{n})\,d\sigma$ | $-\int p\,\bar{v}\cdot\bar{n}\,d\sigma$ | $\int \bar{v}\cdot(\bar{\bar{\tau}}'\cdot\bar{n})\,d\sigma$ | $-\int \bar{q}\cdot\bar{n}\,d\sigma$ |
|---|---|---|---|---|
| $\Sigma_i$ | $-\dot{m}\left(cT_i + \frac{v_i^2}{2}\right)$ | $+p_i v_i A_i$ | $0$ | $0$ (uniform $T$) |
| $\Sigma_o$ | $+\dot{m}\left(cT_o + \frac{v_o^2}{2}\right)$ | $-p_a v_o A_o$ | $0$ | $0$ (uniform $T$) |
| $\Sigma_w$ | $0$ | $0$ ($\bar{v} = 0$) | $0$ ($\bar{v} = 0$) | $-\int_{\Sigma_w} \bar{q}\cdot\bar{n}\,d\sigma$ |

Boxed $\Sigma_w$ term: $\dot{Q}$. Using (1), $p_i v_i A_i - p_a v_o A_o = (p_i - p_a)\,v_o A_o$.

$$\dot{m}\left[c(T_o - T_i) + \frac{v_o^2 - v_i^2}{2}\right] = (p_i - p_a)\,v_o A_o + \dot{Q} \implies \boxed{\dot{Q} = \rho v_o A_o\left[c(T_o - T_i) + \frac{v_o^2 - v_i^2}{2}\right] + (p_a - p_i)\,v_o A_o} \quad (3)$$

PHASE 4

## Interpretation, Limits and Dimensional Check

- $F_x > 0$: the pipe is pushed along the incoming flow by the momentum flux and the gauge pressure at the inlet. $F_z > 0$: the jet leaves downwards, so the pipe is pushed upwards.
- (3) splits the heat into the rise of internal energy, the change of kinetic energy and the flow work. If no heat were exchanged and there were no losses, (3) with $\dot{Q} = 0$ and $T_o = T_i$ would reduce to Bernoulli's equation $p_i + \frac{1}{2}\rho v_i^2 = p_a + \frac{1}{2}\rho v_o^2$.

- Dimensions (SI): $[\rho v_i^2 A_i] = [(p_i - p_a) A_i] = \mathrm{N}$; $[\rho v_o A_o \, c \, \Delta T] = (\mathrm{kg/s})(\mathrm{J/(kg\,K)})\,\mathrm{K} = \mathrm{W}$; $[(p_a - p_i) v_o A_o] = \mathrm{Pa \cdot m^3/s} = \mathrm{W}$.
- Numerical illustration (hypothetical data): water, $c = 4186$ J/(kg K), $A_i = 0.01$ m$^2$, $A_o = 0.004$ m$^2$, $v_o = 6$ m/s, $p_i = 1.6 \times 10^5$ Pa, $p_a = 101325$ Pa, $T_o - T_i = 0.5$ K give $v_i = 2.4$ m/s, $F_x = 644.35$ N, $F_z = 144$ N and $\dot{Q} = 49187$ W.
- Agreement with the official and class solutions: (1), (2) and (3) are the results of CL6.pdf (which labels the vertical axis $y$: $F_y = \rho v_o^2 A_o$) and of the class notes.