MECHANICS APPLIED TO AEROSPACE ENGINEERING - PART I

Topic 4: Angular Momentum and Central Forces - Problem Sets

Department of Continuum Mechanics and Aeronautical Engineering • BSc in Aerospace Engineering, UC3M

Source: sources/cuatrimestre-1/03-engineering-mechanics/problemas/Problems.pdf (2026 Edition)

Statements and solutions: Each card gives the statement from the official collection (with the PDF page) and a worked solution in four phases: hypotheses and data, frames and change-of-basis matrices, step-by-step derivation, and interpretation with unit and limit checks. Only Problems 17 and 39 (part f) have an official key entry; the other results are derived here and checked numerically.

PROBLEM 42

Particle Attracted to the Origin by $F = m\mu/r^{\alpha}$

Original statement · Problems.pdf, p. 29

Binet + Effective Potential

(Advanced problem.) A point particle P of mass m is attracted by the origin of coordinates O of the inertial reference frame S_0 by a force with magnitude

$$F = \frac{m\mu}{r^{\alpha}}$$

where r is the distance between O and P, and μ, α are known constants.

Notation.

The official text writes $F = m\alpha/r^{\beta}$ (strength α, exponent β) and asks for $\beta = 1, 2, 3, 4$. Here the strength is called μ and the exponent α, so the cases "$\alpha = 1, 2, 3, 4$" below are the official $\beta = 1, 2, 3, 4$, and μ/h^2 is the official α/h^2.

(a) Show that the angular momentum vector and the mechanical energy of P are conserved quantities of motion, and that the motion of P occurs in a plane.

(b) Using polar coordinates (r, θ) in the plane of motion, find a second-order differential equation to solve for $u \equiv 1/r$ as a function of θ (i.e., $u = u(\theta)$).

(c) Find a first integral of this equation and discuss the limits of motion of u as a function of μ/h^2, α, and the values of u and $u' \equiv du/d\theta$ at $t = 0$, where h is the magnitude of the angular momentum vector about the origin per unit mass. For $\alpha = 1, 2, 3$, and 4, determine under which conditions: (i) the particle escapes to infinity ($u \to 0$); (ii) the particle reaches $r = 0$ ($u \to \infty$); (iii) the particle oscillates between two values of u.

Hint: try to solve first the problem with $\alpha = 2$, and then try the other values.

Worked Solution (4-Phase Methodology)

PHASE 1

Constraints, Degrees of Freedom & Coordinates

- **System:** a particle P of mass m attracted to the fixed point O by $\mathbf{F} = -\dfrac{m\mu}{r^{\alpha}}\mathbf{e}_r$, where $r = \|\overrightarrow{OP}\|$.
- **Hypotheses:** S_0 is inertial; $\mu > 0$ and $\alpha > 0$ are constants; no other force acts; $h \neq 0$ unless stated.
- **Constraints:** none. P is a free particle, so $\mathrm{CDOF} = 3$. Part (a) proves that the motion is planar; that is a consequence of the dynamics, not an imposed constraint. In the plane, $\mathrm{CDOF} = 2$.

- **Coordinates:** polar coordinates (r, θ) in the plane of motion. For the orbit equation we also use $u(\theta) = 1/r(\theta)$ and $u' = du/d\theta$; h is the magnitude of the angular momentum per unit mass.
- **Special case $h = 0$:** the motion is then radial and the Binet formulation does not apply. It is treated at the end of part (c).
- **Notation:** the official text writes $F = m\alpha/r^{\beta}$ and asks for $\beta = 1, 2, 3, 4$. Here the strength is μ and the exponent is α.

Symbol	Meaning	SI unit
μ	force strength per unit mass, $F/m = \mu/r^{\alpha}$	$\mathrm{m}^{\alpha+1}/\mathrm{s}^2$
h	specific angular momentum	m^2/s
u	reciprocal radius	m^{-1}
ξ	specific mechanical energy	J/kg = $\mathrm{m}^2/\mathrm{s}^2$

PHASE 2

Reference Frames & Vector Bases

- **Inertial frame:** $S_0 = \{O; \mathbf{i}, \mathbf{j}, \mathbf{k}\}$ with its origin at the attracting centre.
- **Polar basis.** Take $\mathbf{k}$ along $\mathbf{H}_O$ (justified in 3.3). The polar basis $\mathcal{B}_1 = \{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{k}\}$ is the inertial basis $\mathcal{B}_0 = \{\mathbf{i}, \mathbf{j}, \mathbf{k}\}$ rotated by $\theta(t)$ about $\mathbf{k}$:

$$[{}_0R_1] = \begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}, \qquad \det[{}_0R_1] = \cos^2\theta + \sin^2\theta = 1, \qquad [{}_0R_1]^T[{}_0R_1] = I$$

Multiplying out, RR^T has diagonal entries $\cos^2 + \sin^2 = 1$ of the rotation angle (and 1) and off-diagonal entries $\pm(\cos\sin - \sin\cos) = 0$, so it is the identity.

- **Angular velocity and angular acceleration of $\mathcal{B}_1$ with respect to S_0: $\boldsymbol{\omega}_{10} = \dot\theta\,\mathbf{k}$** and **$\boldsymbol{\alpha}_{10} = \ddot\theta\,\mathbf{k}$**.
- **Time derivatives of the unit vectors (Poisson's formula $\dot{\mathbf{e}} = \boldsymbol{\omega} \times \mathbf{e}$):**

$$\dot{\mathbf{e}}_r = \dot\theta\,\mathbf{k} \times \mathbf{e}_r = \dot\theta\,\mathbf{e}_\theta, \qquad \dot{\mathbf{e}}_\theta = \dot\theta\,\mathbf{k} \times \mathbf{e}_\theta = -\dot\theta\,\mathbf{e}_r$$

PHASE 3

Derivation

3.1 Kinematics

Pedagogical Justification: the force acts along the line OP, so the position vector is simply $r\mathbf{e}_r$. The basis vector $\mathbf{e}_r$ is not constant in S_0, so each derivative uses the product rule and Poisson's formula. These planar polar formulas are valid for a motion contained in the plane of the basis; that the motion is indeed planar is proved in 3.3, and here it only fixes the choice of $\mathbf{k}$.

$$\mathbf{r} = r\,\mathbf{e}_r$$

$$\mathbf{v} = \frac{d}{dt}\left(r\mathbf{e}_r\right) = \dot{r}\,\mathbf{e}_r + r\,\dot{\mathbf{e}}_r = \dot{r}\,\mathbf{e}_r + r\dot{\theta}\,\mathbf{e}_\theta$$

$$\mathbf{a} = \ddot{r}\,\mathbf{e}_r + \dot{r}\,\dot{\mathbf{e}}_r + \left(\dot{r}\dot{\theta} + r\ddot{\theta}\right)\mathbf{e}_\theta + r\dot{\theta}\,\dot{\mathbf{e}}_\theta = \left(\ddot{r} - r\dot{\theta}^2\right)\mathbf{e}_r + \left(r\ddot{\theta} + 2\dot{r}\dot{\theta}\right)\mathbf{e}_\theta$$

- The angular momentum per unit mass about O follows from the velocity:

$$\mathbf{h} = \mathbf{r}\times\mathbf{v} = r\mathbf{e}_r \times \left(\dot{r}\mathbf{e}_r + r\dot{\theta}\mathbf{e}_\theta\right) = r^2\dot{\theta}\,\mathbf{k}, \qquad h = r^2\dot{\theta}$$

3.2 Forces

- **Applied force:** the attraction $\mathbf{F} = -\dfrac{m\mu}{r^\alpha}\mathbf{e}_r$. It is central: its line of action always passes through O.
- **Constraint forces:** none. **Inertia forces:** none, because Newton's second law is written in the inertial frame S_0.

Pedagogical Justification: the force is purely radial and depends only on r, so its elementary work $\mathbf{F}\cdot d\mathbf{r} = F(r)\,dr$ is the exact differential of a function of r (equivalently,

$\nabla \times \mathbf{F} = \mathbf{0}$). The force is therefore conservative. The potential energy per unit mass is minus the work per unit mass from a reference radius to r (Barrow's rule). For $\alpha > 1$ the reference is at infinity, and the term at the lower limit $s \to \infty$ vanishes because $1 - \alpha < 0$:

$$V_0(r) = -\int_{\infty}^{r} \left(-\frac{\mu}{s^{\alpha}}\right) ds = \mu \left[\frac{s^{1-\alpha}}{1-\alpha}\right]_{\infty}^{r} = \mu \left[\frac{r^{1-\alpha}}{1-\alpha} - \lim_{s\to\infty} \frac{s^{1-\alpha}}{1-\alpha}\right] = -\frac{\mu}{(\alpha-1)\, r^{\alpha-1}}$$

For $\alpha \leq 1$ the integral from infinity diverges, so the reference radius r_* is arbitrary. For $\alpha = 1$:

$$V_0(r) = -\int_{r_*}^{r} \left(-\frac{\mu}{s}\right) ds = \mu \left[\ln s\right]_{r_*}^{r} = \mu \ln \frac{r}{r_*}$$

- In all cases the force per unit mass is recovered by differentiating, e.g. for $\alpha > 1$, $V_0'(r) = -\dfrac{\mu}{\alpha - 1} \cdot \left(-(\alpha-1)\, r^{-\alpha}\right) = \dfrac{\mu}{r^{\alpha}}$, and for $\alpha = 1$, $V_0'(r) = \mu / r$.

3.3 Equations of Motion

Pedagogical Justification: the torque about the fixed point O vanishes because $\mathbf{F}$ is parallel to $\mathbf{r}$. The angular momentum theorem about a fixed point (Notes Eq. 4.53) is a consequence of Newton's second law and gives a first integral right away.

$$\mathbf{M}_O = \mathbf{r} \times \mathbf{F} = r\mathbf{e}_r \times \left(-\frac{m\mu}{r^{\alpha}}\mathbf{e}_r\right) = \mathbf{0} \implies \left.\frac{d\mathbf{H}_O}{dt}\right|_0 = \mathbf{0} \implies \mathbf{H}_O = m\, \mathbf{r} \times \mathbf{v} = \text{const}$$

- **Planar motion.** From $\mathbf{H}_O = m\, \mathbf{r} \times \mathbf{v}$, both $\mathbf{r} \cdot \mathbf{H}_O \equiv 0$ and $\mathbf{v} \cdot \mathbf{H}_O \equiv 0$. Then P stays in the plane through O perpendicular to $\mathbf{H}_O$, and we orient $\mathbf{k}$ along $\mathbf{H}_O$.
- **Newton's second law in the plane.** With $\mathbf{a}$ from 3.1 and $\mathbf{F}$ from 3.2, projected on $\mathbf{e}_r$ and $\mathbf{e}_\theta$:

$$m\left(\ddot{r} - r\dot{\theta}^2\right) = -\frac{m\mu}{r^{\alpha}}, \qquad m\left(r\ddot{\theta} + 2\dot{r}\dot{\theta}\right) = 0$$

- **Check of closure:** two unknowns, $r(t)$ and $\theta(t)$, and two independent scalar equations.
- **Angular momentum from the transverse equation.** Multiplying by r/m and using the product rule:

$$\frac{d}{dt}\left(r^2\dot\theta\right) = 2r\dot r\dot\theta + r^2\ddot\theta = r\left(r\ddot\theta + 2\dot r\dot\theta\right) = 0 \implies h = r^2\dot\theta = \text{const}$$

- **Energy from the radial equation.** The force is conservative (3.2), so the mechanical energy per unit mass $\xi = \frac{1}{2}\left(\dot r^2 + r^2\dot\theta^2\right) + V_0(r)$ is a first integral. Differentiating with the product and chain rules, and using $V_0'(r) = \mu/r^\alpha$:

$$\dot\xi = \dot r\ddot r + r\dot r\dot\theta^2 + r^2\dot\theta\ddot\theta + V_0'(r)\dot r = \dot r\left(\ddot r - r\dot\theta^2\right) + r\dot\theta\left(r\ddot\theta + 2\dot r\dot\theta\right) + \frac{\mu}{r^\alpha}\dot r$$

$$\dot\xi = \dot r\left(-\frac{\mu}{r^\alpha}\right) + 0 + \frac{\mu}{r^\alpha}\dot r = 0 \implies \xi = \tfrac{1}{2}v^2 + V_0(r) = \text{const}$$

3.4 Integration and Answers

(a) Conserved quantities and planar motion

- The angular momentum $\mathbf{H}_O = m\,\mathbf{r}\times\mathbf{v}$ and the mechanical energy $\xi = \frac{1}{2}v^2 + V_0(r)$ are conserved, and the motion occurs in the plane through O perpendicular to $\mathbf{H}_O$. All three statements were proved in 3.3.

(b) Binet equation for a power law

> **Pedagogical Justification:** we want the orbit $u(\theta)$, so time is eliminated with $h = r^2\dot\theta$, i.e. $\dot\theta = hu^2$. The chain rule for $r = u^{-1}$ gives $dr/d\theta = -u'/u^2$.

$$\dot r = \frac{dr}{d\theta}\dot\theta = \left(-\frac{u'}{u^2}\right)\left(hu^2\right) = -hu', \qquad \ddot r = \frac{d}{dt}\left(-hu'\right) = -hu''\,\dot\theta = -h^2u^2u''$$

- The radial equation $\ddot r - r\dot\theta^2 = -\mu/r^\alpha = -\mu u^\alpha$ with $r\dot\theta^2 = \frac{1}{u}\left(hu^2\right)^2 = h^2u^3$ becomes

$$-h^2u^2u'' - h^2u^3 = -\mu u^\alpha \quad \overset{\div(-h^2u^2)}{\Longrightarrow} \quad \boxed{u'' + u = \frac{\mu}{h^2}\,u^{\alpha-2}}$$

(c) First integral and limits of the motion

> **Pedagogical Justification:** write the specific energy with $\dot r = -hu'$ and $r\dot\theta = hu$. Since ξ is constant, the result is a first integral (a quadrature) with no second derivative.

$$\xi = \tfrac{1}{2}h^2\left[(u')^2 + u^2\right] + V_0\!\left(\frac{1}{u}\right) \implies \boxed{(u')^2 + W_{\text{eff}}(u) = E^*}, \quad E^* \equiv \frac{2\xi}{h^2}, \quad W_{\text{eff}}(u) = u^2 + \frac{2V_0(1/u)}{h^2}$$

- **Derivative of W_{eff} (chain rule).** With $\dfrac{d}{du}\left(\dfrac{1}{u}\right) = -\dfrac{1}{u^2}$ and $V_0'(r) = \mu/r^\alpha$ evaluated at $r = 1/u$:

$$\frac{d}{du}V_0\!\left(\frac{1}{u}\right) = V_0'\!\left(\frac{1}{u}\right)\left(-\frac{1}{u^2}\right) = \mu u^\alpha\left(-\frac{1}{u^2}\right) = -\mu u^{\alpha-2} \implies W_{\text{eff}}'(u) = 2u - \frac{2\mu}{h^2}u^{\alpha-2}$$

- **Check.** $\dfrac{d}{d\theta}\left[(u')^2 + W_{\text{eff}}\right] = u'\left(2u'' + W_{\text{eff}}'\right) = 0$. Where $u' \neq 0$ this gives $u'' = -\tfrac{1}{2}W_{\text{eff}}'$, which is the Binet equation; at the points where $u' = 0$ the Binet equation holds by continuity.
- **Limits of the motion.** Because $(u')^2 \geq 0$, motion exists only where $W_{\text{eff}}(u) \leq E^*$. The turning points ($u' = 0$) are the roots of $W_{\text{eff}}(u) = E^*$, and a minimum or a maximum of W_{eff} is a circular orbit. The constant is fixed by the initial data $u_0 = u(0)$ and $u_0' = u'(0)$:

$$E^* = (u_0')^2 + W_{\text{eff}}(u_0)$$

- The three questions are: **(i)** escape, $u \to 0$; **(ii)** reaching the origin, $u \to \infty$; **(iii)** oscillation between two values of u.

Case $\alpha = 2$: inverse square (Kepler)

- Binet: $u'' + u = \mu/h^2$. Potential: $V_0 = -\mu u$, so $W_{\text{eff}} = u^2 - \dfrac{2\mu}{h^2}u = \left(u - \dfrac{\mu}{h^2}\right)^2 - \left(\dfrac{\mu}{h^2}\right)^2$, a parabola with minimum $-(\mu/h^2)^2$ at $u = \mu/h^2$. The constant is $E^* = (u_0')^2 + u_0^2 - \dfrac{2\mu}{h^2}u_0$.
- **(i) Escape:** possible if and only if $E^* \geq W_{\text{eff}}(0) = 0$, i.e. $(u_0')^2 + u_0^2 \geq \dfrac{2\mu}{h^2}u_0$ (parabola or hyperbola). For $E^* > 0$ a particle moving inward ($u_0' > 0$) is first reflected at the positive root and then escapes.
- **(ii) Reaching $r = 0$:** impossible for $h \neq 0$, because $W_{\text{eff}} \to +\infty$ as $u \to \infty$.
- **(iii) Oscillation:** for $-(\mu/h^2)^2 < E^* < 0$: u oscillates between the two roots (periapsis and apoapsis of an ellipse); $E^* = -(\mu/h^2)^2$ is the circular orbit.

Case $\alpha = 1$: $F \propto 1/r$

- Binet: $u'' + u = \dfrac{\mu}{h^2 u}$. With the reference radius r_*, $V_0 = \mu \ln(r/r_*) = -\mu \ln(ur_*)$, so $W_{\text{eff}} = u^2 - \dfrac{2\mu}{h^2}\ln(ur_*)$ and $E^* = (u_0')^2 + u_0^2 - \dfrac{2\mu}{h^2}\ln(u_0 r_*)$.
- $W_{\text{eff}} \to +\infty$ both as $u \to 0$ (because $-\ln u \to +\infty$) and as $u \to \infty$. Its minimum is at $W_{\text{eff}}' = 2u - \dfrac{2\mu}{h^2 u} = 0$, i.e. $u_c = \sqrt{\mu}/h$.
- **(i)** Escape is impossible for any finite energy. **(ii)** Reaching $r = 0$ is impossible. **(iii)** Every orbit with $E^* > W_{\text{eff}}(u_c)$ oscillates between two finite turning points; $E^* = W_{\text{eff}}(u_c)$ is the circular orbit $r = h/\sqrt{\mu}$. Since $E^* \geq W_{\text{eff}}(u_c)$ always, every motion with $h \neq 0$ is of type (iii) or circular.

Case $\alpha = 3$: $F \propto 1/r^3$

- $V_0 = -\dfrac{\mu}{2r^2} = -\dfrac{\mu}{2}u^2$. Binet: $u'' + \lambda u = 0$ with $\lambda \equiv 1 - \mu/h^2$. Then $W_{\text{eff}} = \lambda u^2$ and $(u')^2 + \lambda u^2 = E^*$.
- **$h^2 > \mu$ ($\lambda = \kappa^2 > 0$, $\kappa = \sqrt{1 - \mu/h^2}$):** $u = A\cos(\kappa\theta + \delta)$; the initial conditions $u_0 = A\cos\delta$ and $u_0' = -\kappa A \sin\delta$ give, squaring and adding, $A = \sqrt{u_0^2 + (u_0'/\kappa)^2}$. The cosine vanishes at a finite angle, so $u \to 0$ in every case: **(i) the particle always escapes**; a particle moving inward ($u_0' > 0$) is first reflected at the periapsis $u = A$. **(ii)** never, since $u \leq A$. **(iii)** no oscillation between two positive values.
- **$h^2 < \mu$ ($\lambda = -\kappa^2 < 0$, $\kappa = \sqrt{\mu/h^2 - 1}$):** $u = C_1 e^{\kappa\theta} + C_2 e^{-\kappa\theta}$ with $C_1 = \frac{1}{2}(u_0 + u_0'/\kappa)$, $C_2 = \frac{1}{2}(u_0 - u_0'/\kappa)$. If $C_1 > 0$ (i.e. $u_0' > -\kappa u_0$), $u \to \infty$: **(ii) the particle reaches the origin**. If $C_1 < 0$ ($u_0' < -\kappa u_0$), u reaches 0 at a finite angle: **(i) escape**. If $C_1 = 0$, $u = u_0 e^{-\kappa\theta} \to 0$ only asymptotically (spiral $r = r_0 e^{\kappa\theta}$), a limiting case of escape. **(iii)** no oscillation.
- **$h^2 = \mu$ ($\lambda = 0$):** $u'' = 0 \Rightarrow u = u_0 + u_0'\theta$ (reciprocal spiral). $u_0' > 0$: reaches the origin; $u_0' < 0$: escapes at $\theta = u_0/|u_0'|$; $u_0' = 0$: circle $r = 1/u_0$.

Case $\alpha = 4$: $F \propto 1/r^4$

- Binet: $u'' + u = \dfrac{\mu}{h^2}u^2$. $V_0 = -\dfrac{\mu}{3}u^3$, so $W_{\text{eff}} = u^2 - \dfrac{2\mu}{3h^2}u^3 = u^2\left(1 - \dfrac{2\mu}{3h^2}u\right)$ and $E^* = (u_0')^2 + u_0^2 - \dfrac{2\mu}{3h^2}u_0^3$.
- $W_{\text{eff}}'(u) = 2u - \dfrac{2\mu}{h^2}u^2 = 2u\left(1 - \dfrac{\mu}{h^2}u\right)$: stationary points $u = 0$ (minimum, $W = 0$) and $u_b = h^2/\mu$ (maximum, barrier $W_{\max} = u_b^2 - \dfrac{2\mu}{3h^2}u_b^3 = \dfrac{h^4}{3\mu^2}$). For $u > u_b$, W_{eff} decreases without bound and crosses zero at $u_z = 3h^2/(2\mu) > u_b$.
- **There is no interior minimum**, so the allowed set $\{W_{\text{eff}} \le E^*\}$ either contains $u = 0$ or extends to $u \to \infty$. Because $\dot\theta = hu^2 > 0$, u' has the sign of $\dot u$.
- **Allowed regions by energy** (with $u_0 > 0$):
  - $E^* < 0$: only $u \ge u_2$ with $u_2 > u_z$ is allowed.
  - $E^* = 0$: $u = 0$ is a double root, so the allowed set is $\{0\} \cup [u_z, \infty)$; a particle at finite r has $u_0 \ge u_z$.
  - $0 < E^* < W_{\max}$: two roots $u_1 \in (0, u_b)$ and $u_2 > u_b$; allowed $u \le u_1$ or $u \ge u_2$.
  - $E^* = W_{\max}$: u_b is a stationary point of W_{eff}; the unstable circular orbit $u = u_b$ and the motions that approach it asymptotically.
  - $E^* > W_{\max}$: no turning points.
- **Motion in each region.** For $0 < E^* < W_{\max}$ and $u_0 \le u_1$: if $u_0' > 0$ the particle is reflected at u_1, and in any case it escapes. For $u_0 \ge u_2$: if $u_0' < 0$ it is reflected at u_2, and in any case it falls to the origin. For $E^* = W_{\max}$: with $u_0 < u_b$, $u_0' < 0$ escapes and $u_0' > 0$ approaches u_b asymptotically; with $u_0 > u_b$, $u_0' > 0$ falls to the origin and $u_0' < 0$ approaches u_b asymptotically. For $E^* > W_{\max}$, $u_0' < 0$ escapes and $u_0' > 0$ falls to the origin.
- **(i)** escape: $0 < E^* < W_{\max}$ with $u_0 < u_b$; or $E^* = W_{\max}$ with $u_0 < u_b$ and $u_0' < 0$; or $E^* > W_{\max}$ with $u_0' < 0$.
- **(ii)** reaching $r = 0$: $E^* \le 0$ (then $u_0 \ge u_z$); or $0 < E^* < W_{\max}$ with $u_0 > u_b$; or $E^* = W_{\max}$ with $u_0 > u_b$ and $u_0' > 0$; or $E^* > W_{\max}$ with $u_0' > 0$.
- **(iii)** bounded oscillation between two values of u: **does not occur**; it would need an interior minimum of W_{eff}, and the only bounded motion is the unstable circle $u = u_b$.

Special case $h = 0$ (radial motion)

> **Pedagogical Justification:** with $h = 0, \dot\theta = 0$ and the particle moves on a straight line through O. The Binet equation does not apply ($u = 1/r$ cannot be expressed as a function of θ), so we use the radial equation and the energy directly: $\ddot r = -\mu/r^\alpha < 0$ and $\frac{1}{2}\dot r^2 + V_0(r) = \xi$.

- **(ii)** A particle with $\dot{r}_0 < 0$ reaches $r = 0$ for every α, since the acceleration is always inward. **(i)** Escape requires $\dot{r}_0 > 0$ and $\xi \geq \lim_{r\to\infty} V_0 = 0$, which exists only for $\alpha > 1$; for $\alpha \leq 1$, $V_0 \to +\infty$ and the particle always turns back. **(iii)** Without angular momentum, a particle that turns back falls to the origin, so there is no oscillation between two values.

PHASE 4

Interpretation & Checks

- **Dimensional check:** $[F/m] = \mathrm{m/s^2} = [\mu]/\mathrm{m}^\alpha$ gives $[\mu] = \mathrm{m}^{\alpha+1}/\mathrm{s}^2$. With $[h^2] = \mathrm{m}^4/\mathrm{s}^2$ and $[u] = \mathrm{m}^{-1}$, $\dfrac{\mu}{h^2}u^{\alpha-2}$ has units $\mathrm{m}^{\alpha-3}\,\mathrm{m}^{-(\alpha-2)} = \mathrm{m}^{-1}$, the same as u and u'' (θ is dimensionless).
- **Stability of circular orbits (consequence of the first integral):** for general α, $W'_{\text{eff}}(u_c) = 0$ gives $u_c^{\alpha-3} = h^2/\mu$ and $W''_{\text{eff}}(u_c) = 2 - 2(\alpha-2)\dfrac{\mu}{h^2}u_c^{\alpha-3} = 2(3-\alpha)$, so the circular orbit is a minimum (stable) for $\alpha < 3$ and a maximum (unstable) for $\alpha > 3$, in agreement with the cases above ($\alpha = 4$: barrier at $u_b = h^2/\mu$).
- **Check against the official key:** `Problems.pdf` has no entry for Problem 42 in its solution keys, so the result is verified by independent derivation. A symbolic check with sympy confirms the substitution $\dot{r} = -hu'$, $\ddot{r} = -h^2u^2u''$, the Binet equation, the first integral $\frac{d}{d\theta}\left[(u')^2 + W_{\text{eff}}\right] = 0$, the barrier $W_{\max} = h^4/(3\mu^2)$ and $W''_{\text{eff}} = 2(3-\alpha)$.
- **Numerical check** (Python, DOP853 with relative tolerance 10^{-12} on $u'' = -u + (\mu/h^2)u^{\alpha-2}$, units with $\mu = h = 1$ unless stated). Blow-up angles are given for the cut-off $u = 10^6$; they change by less than 0.003 rad when the cut-off is 10^9.

Case	Initial data (u_0, u'_0)	Predicted	Integration result
$\alpha = 2$	$(1.5, 0)$	bounded, 0.5 to 1.5	$u \in [0.5000, 1.5000]$ over 60 rad
$\alpha = 2$	$(0.5, -0.9)$, $E^* > 0$	escape	$u = 0$ at $\theta = 0.823$
$\alpha = 4$	$(0.5, 0)$, $E^* = 1/6 < 1/3$	reflected, then escape	$u = 0$ at $\theta = 2.078$
$\alpha = 4$	$(1.2, 0)$, $E^* = 0.288 < 1/3$	collapse	$u \to \infty$ at $\theta = 4.058$
$\alpha = 4$	$(0.5, 0.9)$, $E^* = 0.977 > 1/3$	collapse	$u \to \infty$ at $\theta = 3.604$
$\alpha = 4$	$(0.5, -0.9)$, $E^* = 0.977 > 1/3$	escape	$u = 0$ at $\theta = 0.524$
$\alpha = 4$	$(1, 0)$, $E^* = W_{\max}$	unstable circular orbit	$u = 1$ for 20 rad

Case	Initial data (u_0, u_0')	Predicted	Integration result
$\alpha = 4$	$(1.5, 0)$, $E^* = 0$, $u_0 = u_z$	collapse	$u \to \infty$ at $\theta = 3.139$
$\alpha = 4$	$(0.5, -0.408)$, $E^* = W_{\max}$	escape	$u = 0$ at $\theta = 0.975$
$\alpha = 4$	$(0.5, +0.408)$, $E^* = W_{\max}$	tends to $u_b = 1$ asymptotically	follows $u \to 1$ until round-off, amplified by e^{θ}, takes it off the separatrix at $\theta \approx 34$
$\alpha = 3$, $\mu/h^2 = 2$	$(1, 0.2)$, $C_1 > 0$	collapse	$u = \cosh\theta + 0.2\sinh\theta$ grows without bound with θ and no zero appears
$\alpha = 3$, $\mu/h^2 = 2$	$(1, -1.5)$, $C_1 < 0$	escape	$u = 0$ at $\theta = 0.805$
$\alpha = 3$, $\mu/h^2 = 1/2$	$(1, 0)$	escape	$u = 0$ at $\theta = 2.221$, equal to $\dfrac{\pi/2}{\sqrt{1/2}}$
$\alpha = 3$, $\mu = h^2$	$(1, -0.1)$	escape at $\theta = 10$	$u = 1 - 0.1\theta$, zero at $\theta = 10$
$\alpha = 1$	$(0.5, 0.3)$	bounded	$u \in [0.471, 1.653]$ over 100 rad

Source: Problems.pdf (PDF page 29); no key available

PROBLEM 43

Two Connected Particles through a Hole

Original statement · Problems.pdf, p. 30

Angular Momentum + Energy

We consider a smooth horizontal plane wih [sic] a small hole in it. One of the ends of a massless cord of length $2a$ is passed through the hole and then, two point particles, P_1 and P_2, each with the same mass m, are attached to the ends of the cord. Therefore, P_1 is constrained to move on the plane and P_2 moves along a vertical line below the hole.

Initially, half of the cord lies under the plane and half of the cord is on the plane. At that instant, P_1 is pushed with a speed v_0 perpendicular to the cord, counterclockwise as seen from above. Assume that the cord is always in tension.




Figure: Smooth horizontal plane with a small hole, particle P1 on the plane at distance r from the hole and particle P2 hanging below it, both of mass m (Problems.pdf, p. 30).

(a) What is the value of v_0 if P_1 describes a circumference?

(b) In that case, what is the value of the tension in the cord?

(c) If $v_0 = \sqrt{8ag/3}$, reduce the problem to integrals (i.e., quadratures).

(d) Show that for this value of v_0, P_1 oscillates between $r = a$ and $r = 2a$.

(e) Apply Newton's law to P_2 and show that the tension of the cord is $T = mg\left(\frac{1}{2} + \frac{4a^3}{3r^3}\right)$.

(f) Write down the new equations of motion if the plane on which P_1 moves is rough, with a friction coefficient μ.

Hint: the roots of the polynomial $-3x^3 + 7x^2 - 4$ are $x_1 = 1$, $x_2 = 2$ and $x_3 = -2/3$.

Worked Solution (4-Phase Methodology)

PHASE 1

Constraints, Degrees of Freedom & Coordinates

- **System:** P_1 on a smooth horizontal plane at polar position (r, θ) and P_2 hanging on the vertical through the hole O, joined by an inextensible massless cord of length $2a$ that passes through O.
- **Hypotheses:** inertial frame S_0 with O at the hole; smooth hole and plane for parts (a) to (e); the cord stays taut ($T > 0$, checked in (e)); no drag.
- **Constraints** (holonomic and scleronomic; the cord is unilateral in principle, so $T \geq 0$ is verified afterwards):
  - P_1 on the plane: $z_1 = 0$.
  - P_2 on the vertical through the hole: $x_2 = y_2 = 0$.
  - Cord of constant length: $r + \ell_2 = 2a$, where ℓ_2 is the hanging length, so $z_2 = -\ell_2 = r - 2a$ (Oz pointing up).
  - Geometric feasibility: $\ell_2 \geq 0$, i.e. $r \leq 2a$ (P_2 cannot go above the hole). This is a unilateral limit that the solution must respect (see Phase 4).
- **Degrees of freedom:** two particles have 6 coordinates and there are 4 independent constraints, so $\mathrm{CDOF} = 6 - 4 = 2$.

- **Coordinates:** (r, θ), polar coordinates of P_1 on the plane.
- **Initial state:** $r(0) = a, \dot{r}(0) = 0, r(0)\dot{\theta}(0) = v_0$, hence $\dot{\theta}(0) = v_0/a$ and $\dot{z}_2(0) = 0$.

Symbol	Meaning	SI unit
m	mass of each particle	kg
a	half of the cord length	m
v_0	initial speed of P_1	m/s
g	gravitational acceleration	m/s^2
μ	friction coefficient (part f)	1

PHASE 2

Reference Frames & Vector Bases

- **Inertial frame:** $S_0 = \{O; \mathbf{i}, \mathbf{j}, \mathbf{k}\}$, horizontal plane $z = 0$, $\mathbf{k}$ up.
- **Polar basis of P_1.** $\mathcal{B}_1 = \{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{k}\}$ is the inertial basis rotated by $\theta(t)$ about $\mathbf{k}$:

$$[{}_0R_1] = \begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}, \qquad \det[{}_0R_1] = 1, \qquad [{}_0R_1]^T[{}_0R_1] = I$$

Multiplying out, RR^T has diagonal entries $\cos^2 + \sin^2 = 1$ of the rotation angle (and 1) and off-diagonal entries $\pm(\cos\sin - \sin\cos) = 0$, so it is the identity.

- $\boldsymbol{\omega}_{10} = \dot{\theta}\,\mathbf{k}$, so by Poisson $\dot{\mathbf{e}}_r = \dot{\theta}\,\mathbf{e}_\theta$ and $\dot{\mathbf{e}}_\theta = -\dot{\theta}\,\mathbf{e}_r$. P_2 moves along $\mathbf{k}$, so it needs no extra basis.

PHASE 3

Derivation

3.1 Kinematics

Pedagogical Justification: the constraints leave r and θ free; the position of P_2 follows from the cord constraint $z_2 = r - 2a$. For P_1 we use the polar formulas of Problem 42 (product rule and Poisson).

$$\mathbf{r}_1 = r\mathbf{e}_r, \qquad \mathbf{v}_1 = \dot{r}\,\mathbf{e}_r + r\dot{\theta}\,\mathbf{e}_\theta, \qquad \mathbf{a}_1 = \left(\ddot{r} - r\dot{\theta}^2\right)\mathbf{e}_r + \left(r\ddot{\theta} + 2\dot{r}\dot{\theta}\right)\mathbf{e}_\theta$$

$$\mathbf{r}_2 = (r - 2a)\,\mathbf{k}, \qquad \mathbf{v}_2 = \dot{r}\,\mathbf{k}, \qquad \mathbf{a}_2 = \ddot{r}\,\mathbf{k}$$

3.2 Forces

- **On P_1:** its weight $-mg\,\mathbf{k}$; the normal reaction of the smooth plane $N_1\,\mathbf{k}$ (unknown magnitude, vertical because the plane is smooth); and the tension of the cord $-T\,\mathbf{e}_r$ (the cord is horizontal on the plane and pulls toward the hole).
- **On P_2:** its weight $-mg\,\mathbf{k}$, the tension $+T\,\mathbf{k}$ (same cord, massless, smooth hole) and the horizontal reaction of the vertical line $R_{2x}\,\mathbf{i} + R_{2y}\,\mathbf{j}$ that keeps $x_2 = y_2 = 0$ (unknown, to be determined).
- **Inertia forces:** none, because the frame S_0 is inertial.
- **Unknowns:** $r(t), \theta(t), T(t), N_1(t), R_{2x}(t)$ and $R_{2y}(t)$.

3.3 Equations of Motion

> **Pedagogical Justification:** Newton's second law, one vector equation for each particle, gives six scalar equations. The vertical equation of P_1 and the horizontal ones of P_2 only fix reactions, so we project on the tangent directions of the constraints first.

$$P_1,\ \mathbf{e}_r:\ m\left(\ddot{r} - r\dot{\theta}^2\right) = -T, \qquad P_1,\ \mathbf{e}_\theta:\ m\left(r\ddot{\theta} + 2\dot{r}\dot{\theta}\right) = 0, \qquad P_1,\ \mathbf{k}:\ 0 = N_1 - mg$$

$$P_2,\ \mathbf{k}:\ m\ddot{r} = T - mg, \qquad P_2,\ \mathbf{i}:\ 0 = R_{2x}, \qquad P_2,\ \mathbf{j}:\ 0 = R_{2y}$$

- **Check of closure:** six unknowns ($r, \theta, T, N_1, R_{2x}, R_{2y}$) and six equations. The reactions are decoupled: $N_1 = mg$ and $R_{2x} = R_{2y} = 0$, because $\mathbf{a}_2$ is parallel to $\mathbf{k}$. Only r, θ and T remain, with three equations.
- **Dynamical decoupling.** Adding the $\mathbf{e}_r$ equation of P_1 and the equation of P_2 eliminates T:

$$m\left(2\ddot{r} - r\dot{\theta}^2\right) = -mg$$

- **Angular momentum.** Multiplying the transverse equation by r/m gives $\frac{d}{dt}\left(r^2\dot{\theta}\right) = r\left(r\ddot{\theta} + 2\dot{r}\dot{\theta}\right) = 0$, so $h = r^2\dot{\theta}$ is constant.
- **Energy.** The tension does work $-T\dot{r}$ on P_1 and $+T\dot{r}$ on P_2, which cancel (inextensible cord); the plane does no work. With the kinetic energy $K = \frac{1}{2}m\left(\dot{r}^2 + r^2\dot{\theta}^2\right) + \frac{1}{2}m\dot{r}^2$ and $V = mgz_2 = mg(r - 2a)$, the energy is conserved. Replacing $r^2\dot{\theta}^2 = h^2/r^2$:

$$E = K + V = m\dot{r}^2 + \frac{mh^2}{2r^2} + mg(r - 2a) = \text{const}$$

3.4 Integration and Answers

(a) Circular motion, $r \equiv a$

> **Pedagogical Justification:** for r constant, $\dot{r} = \ddot{r} = 0$, so P_2 is at rest and the cord tension must balance its weight, while P_1 moves on a circle under the tension alone. With $\dot{r} = 0$ the transverse equation gives $r\ddot{\theta} = 0$, so $\dot{\theta}$ is constant and equal to its initial value v_0/a (equivalently $h = a^2\dot{\theta} = av_0$).

$$P_1:\ m\left(0 - a\dot{\theta}^2\right) = -T \implies T = ma\dot{\theta}^2 = \frac{mv_0^2}{a}, \qquad P_2:\ 0 = T - mg \implies T = mg$$

$$\frac{mv_0^2}{a} = mg \implies \boxed{v_0 = \sqrt{ag}}$$

(b) Tension in the circular case

$$\boxed{T = mg}$$

(c) Quadratures for $v_0 = \sqrt{8ag/3}$

> **Pedagogical Justification:** the two first integrals of 3.3 leave a single equation for $r(t)$. Evaluate h and E at the initial instant.

$$h = r^2\dot\theta = a v_0 = a\sqrt{\frac{8ag}{3}} \implies h^2 = \frac{8}{3}a^3 g, \qquad E(0) = \tfrac{1}{2}mv_0^2 + mg(a-2a) = \tfrac{1}{2}m\cdot\frac{8ag}{3} - mga = \frac{1}{3}mga$$

- Equating $E = E(0)$, dividing by m and isolating $\dot r^2$:

$$\dot r^2 + \frac{4a^3 g}{3r^2} + gr - 2ga = \frac{1}{3}ga \implies \dot r^2 = \frac{7}{3}ga - gr - \frac{4a^3 g}{3r^2} = \frac{g}{3r^2}\left(7ar^2 - 3r^3 - 4a^3\right)$$

- Separating variables, with $P(r) \equiv -3r^3 + 7ar^2 - 4a^3$. The sign of $\dot r$ is $+$ in the first half-cycle, because P_1 starts at the inner turning point $r = a$ with $\ddot r(0) = -\frac{g}{2} + \frac{h^2}{2a^3} = \frac{5g}{6} > 0$ (from the radial equation of 3.3 with $\dot\theta = h/r^2$). Applying Barrow's rule from $r(0) = a$ on the left side and from 0 to t on the right side:

$$\frac{dr}{dt} = +\sqrt{\frac{g}{3}}\,\frac{\sqrt{P(r)}}{r} \implies \int_a^r \frac{r'\,dr'}{\sqrt{P(r')}} = \sqrt{\frac{g}{3}}\int_0^t dt' = \sqrt{\frac{g}{3}}\,t, \qquad 0 \le t \le \frac{\tau_r}{2}$$

The integrand is improper at $r' = a$ (the radicand vanishes there) but integrable, since $P(r')$ has a simple root at a. After the outer turning point $r = 2a$, reached at $t = \tau_r/2$, the sign of $\dot r$ is $-$ and the quadrature restarts from $2a$:

$$\int_r^{2a} \frac{r'\,dr'}{\sqrt{P(r')}} = \sqrt{\frac{g}{3}}\left(t - \frac{\tau_r}{2}\right), \qquad \frac{\tau_r}{2} \le t \le \tau_r$$

and the motion repeats with the radial period τ_r (see Phase 4).

- **Quadrature for the angle.** With $\dot\theta = h/r^2$ and the same separation of variables, $d\theta = \dfrac{h}{r^2\dot r}\,dr$, and using $h/\sqrt{g/3} = \sqrt{8a^3}$. In the first half-cycle ($\theta(0) = \theta_0$) and in the second one:

$$\theta(r) = \theta_0 + \sqrt{8a^3}\int_a^r \frac{dr'}{r'\sqrt{P(r')}}, \qquad \theta(r) = \theta(2a) + \sqrt{8a^3}\int_r^{2a} \frac{dr'}{r'\sqrt{P(r')}}$$

or, directly in time, $\theta(t) = \theta_0 + \displaystyle\int_0^t \frac{h}{r(t')^2}\,dt'$, which is valid for all t because $\dot\theta = h/r^2 > 0$.

(d) Oscillation between $r = a$ and $r = 2a$

> **Pedagogical Justification:** motion requires $\dot r^2 \geq 0$, i.e. $P(r) = -3r^3 + 7ar^2 - 4a^3 \geq 0$. With $x = r/a$ the polynomial is $a^3(-3x^3 + 7x^2 - 4)$, and the hint gives its roots.

$$-3x^3 + 7x^2 - 4 = -(x-1)(x-2)(3x+2)$$

(check: $(x-1)(x-2) = x^2 - 3x + 2$ and $(x^2 - 3x + 2)(3x + 2) = 3x^3 - 7x^2 + 4$).

- Check of the roots: $x = 1$: $-3 + 7 - 4 = 0$; $x = 2$: $-24 + 28 - 4 = 0$; $x = -2/3$: $\frac{8}{9} + \frac{28}{9} - 4 = 0$. Since $r > 0$, $3x + 2 > 0$ and $P \geq 0$ requires $(x-1)(x-2) \leq 0$:

$$1 \leq x \leq 2 \iff a \leq r(t) \leq 2a$$

- The turning points ($\dot r = 0$) are $r_{\min} = a$ and $r_{\max} = 2a$. Both are simple roots of P, and the radial acceleration points back into the allowed interval at each one: $\ddot r(a) = \frac{5g}{6} > 0$ and $\ddot r(2a) = -\frac{g}{2} + \frac{h^2}{16a^3} = -\frac{g}{3} < 0$ (from $\ddot r = -\frac{g}{2} + \frac{h^2}{2r^3}$, derived in (e)). So r reverses in finite time at both ends and the motion oscillates between them.
- Feasibility: $r_{\max} = 2a$ is exactly the limit $\ell_2 = 2a - r \geq 0$ of Phase 1; at that instant P_2 reaches the hole with zero velocity.

(e) Tension of the cord

> **Pedagogical Justification:** the equation of P_2 from 3.3 gives $T = m\,(g + \ddot{r})$. We need $\ddot{r}$ as a function of r. It comes directly from the decoupled equation $2\ddot{r} - r\dot{\theta}^2 = -g$ of 3.3, with $\dot{\theta} = h/r^2$ (no division by $\dot{r}$ is needed):

$$2\ddot{r} = -g + \frac{h^2}{r^3} \implies \ddot{r} = -\frac{g}{2} + \frac{h^2}{2r^3} = -\frac{g}{2} + \frac{4a^3 g}{3r^3} \qquad \left(h^2 = \tfrac{8}{3}a^3 g\right)$$

- Check by differentiating the energy integral of (c) (chain rule, $\frac{d}{dt} r^{-2} = -2r^{-3}\dot{r}$): $2\dot{r}\ddot{r} = \left(-g + \dfrac{8a^3 g}{3r^3}\right)\dot{r}$, which gives the same $\ddot{r}$ wherever $\dot{r} \neq 0$.

$$\boxed{T = mg\left(\frac{1}{2} + \frac{4a^3}{3r^3}\right)}$$

- $T > 0$ for all $r \in [a, 2a]$, so the cord stays taut.

(f) Rough plane

> **Pedagogical Justification:** Coulomb friction acts on P_1 opposite to its velocity, with magnitude μN_1. The normal force is $N_1 = mg$ (3.3), because the cord is horizontal on the plane and only the weight acts vertically.

$$\mathbf{F}_f = -\mu mg\,\frac{\mathbf{v}_1}{\|\mathbf{v}_1\|} = -\mu mg\,\frac{\dot{r}\,\mathbf{e}_r + r\dot{\theta}\,\mathbf{e}_\theta}{\sqrt{\dot{r}^2 + r^2\dot{\theta}^2}}$$

$$\mathbf{e}_r:\ m\left(\ddot{r} - r\dot{\theta}^2\right) = -T - \mu mg\frac{\dot{r}}{\sqrt{\dot{r}^2 + r^2\dot{\theta}^2}}$$

$$\mathbf{e}_\theta:\ m\left(r\ddot{\theta}+2\dot{r}\dot{\theta}\right)=-\mu mg\frac{r\dot{\theta}}{\sqrt{\dot{r}^2+r^2\dot{\theta}^2}},\qquad P_2:\ m\ddot{r}=T-mg$$

- Adding the $\mathbf{e}_r$ equation and the P_2 equation eliminates T; multiplying the $\mathbf{e}_\theta$ equation by r gives the evolution of h:

$$2\ddot{r}-r\dot{\theta}^2=-g-\mu g\frac{\dot{r}}{\sqrt{\dot{r}^2+r^2\dot{\theta}^2}},\qquad \frac{d}{dt}\left(r^2\dot{\theta}\right)=-\mu g\,\frac{r^2\dot{\theta}}{\sqrt{\dot{r}^2+r^2\dot{\theta}^2}}$$

- Angular momentum and energy are no longer conserved (friction dissipates energy), so the problem cannot be reduced to the quadratures of (c).

PHASE 4

Interpretation & Checks

- **Tension at the turning points:** $T(a)=mg\left(\frac{1}{2}+\frac{4}{3}\right)=\frac{11}{6}mg$ and $T(2a)=mg\left(\frac{1}{2}+\frac{4}{24}\right)=\frac{2}{3}mg$, both positive.
- **Consistency with (a):** for $v_0^2=ag$, $h^2=a^3g$ and $\ddot{r}(a)=-\frac{g}{2}+\frac{h^2}{2a^3}=0$, so $r=a$ is an equilibrium of the radial equation, as expected for the circular case.
- **Radial period** (consequence of (c) and (d)): $\tau_r=2\sqrt{3/g}\int_a^{2a} r\,dr/\sqrt{P(r)}$. With $x=r/a$, $r\,dr=a^2x\,dx$ and $\sqrt{P}=a^{3/2}\sqrt{(x-1)(2-x)(3x+2)}$, so $\tau_r=2\sqrt{3a/g}\int_1^2 x\,dx/\sqrt{(x-1)(2-x)(3x+2)}$. Then with $x=\frac{3}{2}-\frac{1}{2}\cos s$ ($x=1\to s=0$, $x=2\to s=\pi$), $(x-1)(2-x)=\frac{1}{4}\sin^2 s$ and $dx=\frac{1}{2}\sin s\,ds$, so $\tau_r=2\sqrt{\dfrac{3a}{g}}\displaystyle\int_0^{\pi}\frac{x(s)\,ds}{\sqrt{3x(s)+2}}\approx 6.342\sqrt{\frac{a}{g}}$.
- **Dimensions:** $[T]=[m][g]=\mathrm{N}$ and $[v_0]=\sqrt{[a][g]}=\mathrm{m/s}$.
- **Feasibility:** the outer turning point $r_{\max}=2a$ puts P_2 at the hole with zero velocity ($\ell_2=0$), the limit of the constraint $r\le 2a$. The tension there, $T(2a)=\frac{2}{3}mg>0$, shows that the cord is still taut, so the motion is admissible for the whole cycle.
- **Check against the official key:** `Problems.pdf` has no entry for Problem 43 in its solution keys (the tension in (e) is given in the statement and is derived above). All results are therefore verified by independent derivation and by numerical integration.

- **Quadratures** (Python, DOP853 on the equations of 3.3 with $a = g = 1$): from $r = a$ to $r = 1.5a$ the integral for t gives $1.361538\sqrt{a/g}$ and the integral for θ gives 1.635065 rad, both equal to the values of the direct integration to 10^{-10}.
- **Symbolic check** (sympy): $\dot{r}^2 = \dfrac{g\,(2a - r)(r - a)(2a + 3r)}{3r^2}$ with roots $r = a$ and $r = 2a$; the tension $m(g + \ddot{r})$ equals $mg\left(\frac{1}{2} + \frac{4a^3}{3r^3}\right)$ identically.
- **Numerical check** (Python, DOP853 on $\ddot{r} = -g/2 + 4a^3 g/(3r^3)$ with $a = g = m = 1$, $r(0) = 1, \dot{r}(0) = 0$): minimum and maximum radius 1.0000 and 1.9991 over the sampled steps (the turning point 2.0000 is reached between samples), period 6.34243 (the quadrature gives 6.34243), and the energy residual stays below 5×10^{-12}.

Source: Problems.pdf (PDF page 30); no key available

PROBLEM 44

The Little Prince Throwing Seeds

Original statement · Problems.pdf, p. 31

Angular Momentum + Vis-Viva

The little Prince is on his spherical asteroid, which has radius R and mass M, and does not rotate. While he sits at the equator, he throws a baobab seed with an initial velocity of magnitude v_0 and angle $\gamma = 60^\circ$ with respect to the local horizontal. Knowing that it reaches an apocenter of $r = 3R$ before falling back, determine v_0 as a function of the parameters of the problem and the universal gravitational constant G.

Worked Solution (4-Phase Methodology)

PHASE 1

Constraints, Degrees of Freedom & Coordinates

- **System:** a seed of mass $m \ll M$ launched from the surface ($r_0 = R$) with speed v_0 at $\gamma = 60^\circ$ above the local horizontal; it reaches the apocenter $r_a = 3R$.
- **Hypotheses:** spherically symmetric, non-rotating asteroid, so the gravitational force is central and conservative with $\mu = GM$; vacuum (no drag); inertial frame S_0 centred on the asteroid.
- **Constraints:** none (the seed is a free particle once it leaves the surface), so $\mathrm{CDOF} = 3$. The central force makes the motion planar, so $\mathrm{CDOF} = 2$ with the coordinates (r, θ) in the orbital plane.
- **Initial state:** $r = R$, radial component $v_{r0} = v_0 \sin\gamma = \frac{\sqrt{3}}{2} v_0$ and transverse component $v_{\theta 0} = v_0 \cos\gamma = \frac{1}{2} v_0$. At the apocenter $\dot{r} = 0$.

Symbol	Meaning	SI unit
M, R	mass and radius of the asteroid	kg, m
G	universal gravitational constant, 6.6743×10^{-11}	$\mathrm{m^3/(kg\ s^2)}$
$\mu = GM$	gravitational parameter	$\mathrm{m^3/s^2}$
γ	launch angle above the local horizontal (given: 60°)	rad

Symbol	Meaning	SI unit
r_a	apocenter radius (given: $3R$)	m
v_0	launch speed (unknown)	m/s

PHASE 2

Reference Frames & Vector Bases

- **Inertial frame:** $S_0 = \{O; \mathbf{i}, \mathbf{j}, \mathbf{k}\}$ with O at the centre of the asteroid.
- **Polar basis in the orbital plane.** $\mathcal{B}_1 = \{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{k}\}$ is the inertial basis rotated by the true anomaly θ about $\mathbf{k}$ (along $\mathbf{H}_O$):

$$[{}_0R_1] = \begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}, \qquad \det[{}_0R_1] = 1, \qquad [{}_0R_1]^T[{}_0R_1] = I$$

Multiplying out, RR^T has diagonal entries $\cos^2 + \sin^2 = 1$ of the rotation angle (and 1) and off-diagonal entries $\pm(\cos\sin - \sin\cos) = 0$, so it is the identity.

- $\boldsymbol{\omega}_{10} = \dot\theta\,\mathbf{k}$, so by Poisson $\dot{\mathbf{e}}_r = \dot\theta\,\mathbf{e}_\theta$ and $\dot{\mathbf{e}}_\theta = -\dot\theta\,\mathbf{e}_r$.

PHASE 3

Derivation

3.1 Kinematics

Pedagogical Justification: the product rule and Poisson's formula (as in Problem 42, 3.1) give the position, velocity and acceleration in the polar basis. The velocity is what the conservation laws need, and the acceleration is needed to write Newton's second law in 3.3.

$$\mathbf{r} = r\mathbf{e}_r, \qquad \mathbf{v} = \dot r\,\mathbf{e}_r + r\dot\theta\,\mathbf{e}_\theta, \qquad \mathbf{a} = \left(\ddot r - r\dot\theta^2\right)\mathbf{e}_r + \left(r\ddot\theta + 2\dot r\dot\theta\right)\mathbf{e}_\theta$$

$$h = \|\mathbf{r} \times \mathbf{v}\| = r^2\dot{\theta} = r\, v_\theta$$

- At launch, $\dot{r} = v_0 \sin\gamma$ and $r\dot{\theta} = v_0 \cos\gamma$. At the apocenter $\dot{r} = 0$, so the velocity is purely transverse: $v_a = r_a\dot{\theta}_a$.

3.2 Forces

- **Applied force:** the gravitation of the asteroid, $\mathbf{F} = -\dfrac{GMm}{r^2}\mathbf{e}_r$. It is central and conservative.
- **Constraint and inertia forces:** none (free particle, inertial frame).

> **Pedagogical Justification:** the potential energy per unit mass follows from Barrow's rule with the reference at infinity:

$$V_0(r) = -\int_\infty^r \left(-\frac{GM}{s^2}\right) ds = GM\left[-\frac{1}{s}\right]_\infty^r = GM\left[-\frac{1}{r} - \lim_{s\to\infty}\left(-\frac{1}{s}\right)\right] = -\frac{GM}{r}$$

3.3 Equations of Motion

> **Pedagogical Justification:** the unknowns are the orbit variables $r(t)$ and $\theta(t)$. Instead of integrating Newton's second law in time, we use its two first integrals, which follow from it and give the speed directly at two points (launch and apocenter), exactly what the question needs.

$$m\left(\ddot{r} - r\dot{\theta}^2\right) = -\frac{GMm}{r^2}, \qquad m\left(r\ddot{\theta} + 2\dot{r}\dot{\theta}\right) = 0$$

- **Angular momentum.** The transverse equation times r/m is $\frac{d}{dt}\left(r^2\dot{\theta}\right) = 0$, so $h = r^2\dot{\theta}$ is constant (the force is central).
- **Energy.** The force is conservative, so $\xi = \frac{1}{2}v^2 - GM/r$ is constant. Both laws hold for the same particle between launch and apocenter.
- **Unknowns and equations:** v_0 and v_a are unknown, and there are two equations (h and ξ conservation), so the problem is closed.

3.4 Integration and Answers

Conservation of specific angular momentum

> **Pedagogical Justification:** evaluate h at launch and at the apocenter, where $v_a = r_a \dot{\theta}_a$.

$$h = R\,(v_0 \cos\gamma) = \frac{1}{2} R v_0, \qquad h = r_a v_a = 3R v_a \implies v_a = \frac{h}{3R} = \frac{\frac{1}{2} R v_0}{3R} = \frac{v_0}{6}$$

Conservation of specific energy

> **Pedagogical Justification:** the energy takes the same value at launch and at the apocenter.

$$\frac{1}{2} v_0^2 - \frac{GM}{R} = \frac{1}{2}\left(\frac{v_0}{6}\right)^2 - \frac{GM}{3R} = \frac{v_0^2}{72} - \frac{GM}{3R}$$

Solving for v_0

$$\left(\frac{1}{2} - \frac{1}{72}\right) v_0^2 = \left(1 - \frac{1}{3}\right) \frac{GM}{R} \implies \frac{35}{72} v_0^2 = \frac{2}{3} \frac{GM}{R} \implies v_0^2 = \frac{2}{3} \cdot \frac{72}{35} \frac{GM}{R} = \frac{48}{35} \frac{GM}{R}$$

$$\boxed{v_0 = \sqrt{\frac{48}{35} \frac{GM}{R}}}$$

PHASE 4

Interpretation & Checks

- **Bound orbit:** the escape speed at the surface is $v_e = \sqrt{2GM/R}$, i.e. $v_e^2 = \frac{70}{35} GM/R$. Since $\frac{48}{35} < 2$, $v_0 < v_e$ and the orbit is an ellipse: the seed falls back.

- **Orbital parameters:** $h^2 = \frac{1}{4}R^2 v_0^2 = \frac{12}{35}GMR$ and the semi-latus rectum $p = h^2/\mu = \frac{12}{35}R$. From $r_a = p/(1-e) = 3R$: $1 - e = \frac{4}{35}$ and $e = \frac{31}{35} \approx 0.8857$. The periapsis of the full conic is $r_p = p/(1+e) = \frac{2}{11}R < R$, inside the asteroid.
- **Physical arc.** On the orbit $r = p/(1 + e\cos\theta)$ the seed leaves the surface where $1 + e\cos\theta_0 = p/R$, i.e. $\cos\theta_0 = -\frac{23}{31}$ with $\sin\theta_0 > 0$ (the seed is moving away from the centre, $\dot r_0 > 0$), so $\theta_0 \approx 137.9^\circ$. It passes the apocenter at $\theta = \pi$ and lands where $r = R$ again, at $\theta = 2\pi - \theta_0 \approx 222.1^\circ$. The part of the conic that contains the periapsis ($\theta = 0$) is inside the asteroid and is not travelled: the seed describes about 84° of orbit and falls back.
- **Independent check with the Binet solution.** The orbit equation of Problem 42 for $\alpha = 2$ is $u'' + u = \mu/h^2$, with the first integral $\left(u - \mu/h^2\right)^2 + (u')^2 = \left(\mu e/h^2\right)^2$ that defines the eccentricity. The launch data give $u_0 = 1/R$ and $u_0' = -\dot r_0/h = -\dfrac{(\sqrt{3}/2)v_0}{(1/2)Rv_0} = -\dfrac{\sqrt{3}}{R}$, so

$$\frac{\mu e}{h^2} = \sqrt{\left(\frac{1}{R} - \frac{35}{12R}\right)^2 + \frac{3}{R^2}} = \sqrt{\frac{529}{144R^2} + \frac{432}{144R^2}} = \frac{31}{12R} \implies e = \frac{31}{12R}\cdot\frac{12R}{35} = \frac{31}{35}$$

- This eccentricity, obtained from the launch conditions alone, reproduces the prescribed apocenter: $r_a = \dfrac{p}{1-e} = \dfrac{12R/35}{4/35} = 3R$. The value of v_0 found from energy and angular momentum is therefore consistent with a second, independent formulation.
- **Limiting cases** of the general result. Repeating the algebra with r_a and γ as symbols ($h = Rv_0\cos\gamma$, $v_a = (R/r_a)v_0\cos\gamma$):

$$v_0^2 = \frac{2\mu\left(\frac{1}{R} - \frac{1}{r_a}\right)}{1 - \left(\frac{R}{r_a}\right)^2\cos^2\gamma}$$

For $r_a = 3R$ and $\gamma = 60^\circ$ the denominator is $1 - \frac{1}{9}\cdot\frac{1}{4} = \frac{35}{36}$ and $v_0^2 = \frac{4}{3}\cdot\frac{36}{35}\,\mu/R = \frac{48}{35}\,\mu/R$. As $r_a \to \infty$, $v_0^2 \to 2\mu/R$, the escape speed. For $\gamma = 90^\circ$ (vertical launch) $v_0^2 = 2\mu\,(1/R - 1/r_a)$, the energy balance of a radial flight. For $\gamma = 0$ and $r_a \to R$ the quotient tends to μ/R, the circular speed.

- **Dimensions:** $[v_0] = \sqrt{[G][M]/[R]} = \sqrt{\dfrac{\mathrm{m}^3}{\mathrm{kg\,s}^2} \cdot \dfrac{\mathrm{kg}}{\mathrm{m}}} = \mathrm{m/s}$.
- **Check against the official key:** `Problems.pdf` has no entry for Problem 44 in its solution keys, so the result is verified by independent derivation: sympy solves the energy equation and returns $v_0^2 = \frac{48}{35} GM/R$, and the eccentricity obtained from the launch data reproduces the prescribed apocenter $r_a = 3R$.
- **Numerical check** (Python, DOP853 integration of $\ddot{\mathbf{r}} = -\mu \mathbf{r}/r^3$ with $\mu = R = 1$ and $v_0 = \sqrt{48/35}$, $\gamma = 60^\circ$): the maximum radius reached is $2.99998R$ (sampling resolution of the output) and the speed there is $0.16668\, v_0$, in agreement with $r_a = 3R$ and $v_a = v_0/6$.

Source: Problems.pdf (PDF page 31); no key available