PROBLEM NS15

Moving Porous Wall with Suction

Original statement · NS15.pdf

Asymptotic suction profile | Wall shear and heat flux | Integral balances | Viscous dissipation

OFFICIAL PROBLEM STATEMENT

Problem 2: Consider a buoyancy-free, steady planar motion occurring in a semi-infinite space filled with a perfect liquid of density ρ, viscosity μ, thermal conductivity k, and specific heat c. The liquid is bounded by an infinitely long porous wall that moves parallel to itself with velocity U_w while removing the liquid with a normal suction velocity V_w. Far from the wall, the horizontal velocity component is zero and the pressure is $p = p_\infty$. The ambient value of the temperature $T = T_\infty$ is higher than the value T_w at the wall.

1. Determine the velocity components $v_x(y)$ and $v_y(y)$ and well as the pressure field $p(x, y)$.


2. Obtain the temperature distribution $T(y)$.

3. Compute the viscous force acting on the wall per unit surface $\tau_w \bar{e}_x = \bar{\bar{\tau}}' \cdot \bar{n}_w$, where $\bar{n}_w$ is the unit vector normal to the wall.

4. Determine the heat flux from the fluid to the wall $q_w = k(\nabla T) \cdot \bar{n}_w$.

5. For an alternative computation procedure for τ_w and q_w, apply the momentum and energy conservation equations to the control volume indicated in the figure. In dealing with the balance equations, evaluate explicitly the contribution of each term, stating clearly the reasons justifying any simplifications introduced.

The sheet is headed "INTRODUCTION TO FLUID MECHANICS, FINAL (Jan 21, 2014)". Transcribed as printed, including "and well as" in item 1.



Statement figure (redrawn from NS15.pdf, p. 1): porous wall at temperature T_w moving with U_w and sucking with V_w, axes x, y, normals $\bar{n}$ and $\bar{n}_w$, far field p_∞, T_∞ and the fixed control volume V_c of unit length ($\delta x = 1$)

`Source: NS15.pdf (page 1). Notes.pdf, Chapter 4: continuity Eq. 4.40, momentum Eq. 4.41, energy Eq. 4.42, integral balances Eqs. 4.2 and 4.3.`

Worked solution

Hypotheses, Data and Unknowns

- Steady planar flow of a perfect liquid (constant ρ, μ, k, c), buoyancy-free (mass forces neglected), in the half space $y > 0$ above a porous wall. The fields depend only on the distance y to the wall (the wall is infinitely long and the flow is the same at every x).
- The wall at $y = 0$ moves in its own plane with U_w and removes the liquid with the suction velocity $V_w > 0$: $v_y(0) = -V_w$. No chemical reaction and no radiation.
- Far from the wall ($y \to \infty$): $v_x \to 0, p \to p_\infty, T \to T_\infty$, with $T_\infty > T_w$.
- Data: $[\rho,\ \mu,\ k,\ c,\ U_w,\ V_w,\ p_\infty,\ T_\infty,\ T_w]$. Unknowns: v_x, v_y, p, T, τ_w and q_w.
- Notation: $\nu = \mu/\rho, \alpha = k/(\rho c), \mathrm{Pr} = \nu/\alpha = \mu c/k$.

Symbol	Meaning	SI unit
U_w, V_w	wall velocity along itself, suction velocity	m/s
p_∞, T_∞, T_w	far-field pressure and temperature, wall temperature	Pa, K, K

Symbol	Meaning	SI unit
τ_w	viscous force per unit area on the wall, along x	Pa
q_w	heat flux from the liquid to the wall	W/m^2
Pr	Prandtl number	1

Frames, Field Form and Boundary Conditions

- Cartesian frame (x, y, z) attached to the wall: x along the wall in the direction of U_w, y normal to the wall and into the liquid, z out of the plane; the basis is orthonormal and right-handed. The normal $\bar{n}_w = +\bar{e}_y$ points from the wall into the liquid (figure).
- Field form: $\bar{v} = v_x(y)\,\bar{e}_x + v_y(y)\,\bar{e}_y, p = p(x, y), T = T(y)$.
- Control volume V_c of the figure: fixed, of unit length in x ($\delta x = 1$) and unit width, from the wall to a plane $y = Y$ far from it; surfaces: the wall Σ_w ($\bar{n} = -\bar{e}_y$), the top Σ_t ($\bar{n} = +\bar{e}_y$) and the two vertical faces Σ_1 ($\bar{n} = -\bar{e}_x$) and Σ_2 ($\bar{n} = +\bar{e}_x$).

Location	Condition	Origin
$y = 0$	$v_x = U_w, v_y = -V_w, T = T_w$	moving porous wall, suction
$y \to \infty$	$v_x \to 0, p \to p_\infty, T \to T_\infty$	liquid at rest far from the wall

Step-by-Step Derivation

3.1 Velocity and pressure (item 1)

$$\frac{\partial v_x}{\partial x} + \frac{dv_y}{dy} = \underbrace{\frac{\partial v_x}{\partial x}}_{v_x = v_x(y)} + \frac{dv_y}{dy} = 0 \implies v_y = \text{const} = -V_w \tag{1}$$

The y component of the momentum equation (no mass force, $dv_y/dy = 0, d^2v_y/dy^2 = 0$) gives $0 = -\partial p/\partial y$, so $p = p(x)$, and the far-field condition $p \to p_\infty$ for every x gives $\partial p/\partial x = 0$:

$$\boxed{v_y(y) = -V_w, \qquad p(x, y) = p_\infty} \tag{2}$$

The x component:

$$\rho\Big(\underbrace{v_x\frac{\partial v_x}{\partial x}}_{\partial_x=0}+v_y\frac{dv_x}{dy}\Big)=-\underbrace{\frac{\partial p}{\partial x}}_{=0}+\mu\frac{d^2v_x}{dy^2}\;\Longrightarrow\;\frac{d^2v_x}{dy^2}+\frac{V_w}{\nu}\frac{dv_x}{dy}=0 \tag{3}$$

Trying $e^{\lambda y}$: $\lambda(\lambda+V_w/\nu)=0$, so $v_x=C_1+C_2e^{-V_wy/\nu}$. The condition $v_x\to 0$ at infinity gives $C_1=0$ (the exponential decays because $V_w>0$), and $v_x(0)=U_w$ gives $C_2=U_w$:

$$\boxed{v_x(y)=U_w\,e^{-V_wy/\nu}} \tag{4}$$

3.2 Temperature (item 2)

With $v_y=-V_w$, $\partial_x=0$ and $\phi_v=\mu\,(dv_x/dy)^2$, equation (4.42) reads $-\rho c V_w\,dT/dy=\phi_v+k\,d^2T/dy^2$. From (4), $dv_x/dy=-(V_wU_w/\nu)e^{-V_wy/\nu}$, so

$$\frac{d^2T}{dy^2}+\frac{V_w}{\alpha}\frac{dT}{dy}=-\frac{\mu U_w^2V_w^2}{k\,\nu^2}\,e^{-2V_wy/\nu} \tag{5}$$

The homogeneous solution is $B_1+B_2e^{-V_wy/\alpha}$. A particular solution $A\,e^{-2V_wy/\nu}$ requires (substituting $T_p'=-(2V_w/\nu)A\,e^{-2V_wy/\nu}$ and $T_p''=(4V_w^2/\nu^2)A\,e^{-2V_wy/\nu}$ and using $\nu/\alpha=\mathrm{Pr}$):

$$A\,(4-2\,\mathrm{Pr})=-\frac{\mu U_w^2}{k}=-\frac{\mathrm{Pr}\,U_w^2}{c}\;\Longrightarrow\;A=\frac{\mathrm{Pr}}{2(\mathrm{Pr}-2)}\frac{U_w^2}{c} \tag{6}$$

for $\mathrm{Pr}\neq 2$. (For $\mathrm{Pr}=2$ the exponents of the homogeneous and the particular solution coincide and the particular solution is $D\,y\,e^{-2V_wy/\nu}$. With $\lambda=2V_w/\nu$, $T_p'=D(1-\lambda y)e^{-\lambda y}$ and $T_p''=D(\lambda^2y-2\lambda)e^{-\lambda y}$, so $T_p''+\lambda T_p'=-D\lambda\,e^{-\lambda y}$; matching the right-hand side of (5), $D\lambda=\mu U_w^2V_w^2/(k\nu^2)$, that is $D=\mu U_w^2V_w/(2k\nu)$. The results (8) and (10) do not depend on Pr.) The conditions $T(\infty)=T_\infty$ and $T(0)=T_w$ give $B_1=T_\infty$ and $B_2=T_w-T_\infty-A$:

$$\boxed{T(y) = T_\infty + \left(T_w - T_\infty - \frac{\mathrm{Pr}\, U_w^2}{2(\mathrm{Pr}-2)\, c}\right) e^{-\mathrm{Pr}\, V_w y/\nu} + \frac{\mathrm{Pr}\, U_w^2}{2(\mathrm{Pr}-2)\, c}\, e^{-2V_w y/\nu}} \quad (7)$$

since $V_w y/\alpha = \mathrm{Pr}\, V_w y/\nu$.

3.3 Viscous force on the wall (item 3)

With $\bar{n}_w = \bar{e}_y$, the vector $\bar{\bar{\tau}}' \cdot \bar{n}_w$ is the viscous force per unit area that the liquid exerts on the wall: $\tau'_{xy}\, \bar{e}_x + \tau'_{yy}\, \bar{e}_y$ with $\tau'_{xy} = \mu\, dv_x/dy$ and $\tau'_{yy} = 2\mu\, dv_y/dy = 0$. At $y = 0$, from (4):

$$\boxed{\tau_w = \mu \frac{dv_x}{dy}\Big|_0 = -\rho\, V_w\, U_w} \quad (8)$$

The liquid pulls the wall back, against its motion.

3.4 Heat flux to the wall (item 4)

With $\bar{n}_w = \bar{e}_y$, $q_w = k\, dT/dy\big|_0$. Differentiating (7) at $y = 0$, with $B_2 = T_w - T_\infty - A$:

$$\frac{dT}{dy}\Big|_0 = -\frac{V_w}{\nu}\left(\mathrm{Pr}\, B_2 + 2A\right) \implies q_w = -\rho c V_w \left(B_2 + \frac{2A}{\mathrm{Pr}}\right) = -\rho c V_w \left[T_w - T_\infty - \frac{(\mathrm{Pr}-2)A}{\mathrm{Pr}}\right] \quad (9)$$

using $k/\nu = \rho c/\mathrm{Pr}$ and $(\mathrm{Pr}-2)A/\mathrm{Pr} = U_w^2/(2c)$:

$$\boxed{q_w = \rho c V_w \left[T_\infty - T_w + \frac{U_w^2}{2c}\right] = \frac{1}{2}\rho V_w U_w^2 + \rho c V_w \left(T_\infty - T_w\right)} \quad (10)$$

3.5 Alternative computation with the control volume V_c (item 5)

Momentum, x component (steady, fixed volume, Notes.pdf Eq. 4.2 in integral form; no mass force):

$$\int_{\Sigma_c} \rho\, v_x\, (\bar{v}\cdot\bar{n})\, d\sigma = -\int_{\Sigma_c} p\, n_x\, d\sigma + \int_{\Sigma_c} (\bar{\bar{\tau}}'\cdot\bar{n})_x\, d\sigma \tag{11}$$

Surface	$\int \rho v_x\, \bar{v}\cdot\bar{n}\, d\sigma$	$-\int p\, n_x\, d\sigma$	$\int (\bar{\bar{\tau}}'\cdot\bar{n})_x\, d\sigma$
Σ_w ($\bar{n} = -\bar{e}_y$, $\bar{v}\cdot\bar{n} = V_w$)	$\rho\, U_w V_w$	0 ($n_x = 0$)	$-\tau'_{xy}(0) = -\tau_w$
Σ_t ($\bar{n} = +\bar{e}_y$)	0 ($v_x \to 0$ far from the wall)	0 ($n_x = 0$)	0 ($dv_x/dy \to 0$)
$\Sigma_1 + \Sigma_2$	cancel (profile independent of x, opposite normals)	cancel (p uniform)	cancel ($\tau'_{xx} = 0$)

Therefore $\rho\, U_w V_w = -\tau_w$, that is $\tau_w = -\rho V_w U_w$, in agreement with (8): the wall must supply the momentum ρU_w per unit mass to the liquid it sucks, since the liquid at infinity has none.

Total energy (Notes.pdf, Eq. 4.3 for a fixed volume, steady, no mass force):

$$\int_{\Sigma_c} \rho \left(e + \frac{|\bar{v}|^2}{2}\right) \bar{v}\cdot\bar{n}\, d\sigma + \int_{\Sigma_c} p\, \bar{v}\cdot\bar{n}\, d\sigma = \int_{\Sigma_c} \bar{v}\cdot\bar{\bar{\tau}}'\cdot\bar{n}\, d\sigma - \int_{\Sigma_c} \bar{q}\cdot\bar{n}\, d\sigma \tag{12}$$

Surface	**Convective energy flux**	**Pressure work**	**Viscous work** $\bar{v}\cdot\bar{\bar{\tau}}'\cdot\bar{n}$	**Conduction** $\bar{q}\cdot\bar{n}$
Σ_w	$\rho\left[cT_w + \frac{1}{2}(U_w^2 + V_w^2)\right] V_w$	$p_\infty V_w$	$-U_w\tau_w = \rho V_w U_w^2$	$k\, dT/dy\big\vert_0 = q_w$
Σ_t	$-\rho\left[cT_\infty + \frac{1}{2}V_w^2\right] V_w$	$-p_\infty V_w$	0 (no shear far away)	0 ($dT/dy \to 0$)
$\Sigma_1 + \Sigma_2$	cancel	cancel	cancel	0 (T independent of x)

On Σ_w, $\bar{v}\cdot\bar{n} = V_w$, $\bar{v} = U_w\bar{e}_x - V_w\bar{e}_y$ and $\bar{v}\cdot\bar{\bar{\tau}}'\cdot\bar{n} = -(v_x\tau'_{xy} + v_y\tau'_{yy}) = -U_w\tau_w$; on Σ_t, $\bar{v} = -V_w\bar{e}_y$ and $T = T_\infty$. The pressure is uniform (p_∞) so its work cancels between Σ_w and Σ_t. Adding the surfaces,

$$\rho V_w\left[c\,(T_w - T_\infty) + \frac{U_w^2}{2}\right] = \rho V_w U_w^2 - q_w \implies \boxed{q_w = \frac{1}{2}\rho V_w U_w^2 + \rho c V_w\,(T_\infty - T_w)} \tag{13}$$

which is (10). The simplifications used are justified by the fact that all the fields are independent of x (lateral faces), that the shear and the temperature gradient decay exponentially (top surface, placed at $Y \gg \nu/V_w, \alpha/V_w$), and that the liquid is at rest and at p_∞ far away.

Interpretation, Limits and Dimensional Check

- **Physical meaning.** Suction holds the moving layer of thickness ν/V_w (momentum) and α/V_w (thermal) against the wall. The wall pays for the momentum of the entrained liquid ((8)), and receives the enthalpy, the kinetic energy and the viscous work ((10)).
- **Limits.** For $U_w = 0$: no shear, no dissipation, $q_w = \rho c V_w (T_\infty - T_w)$ (pure advection-conduction). For $V_w \to 0$ the layer thickens and there is no steady solution. For $T_\infty = T_w$ the heat flux is $\frac{1}{2}\rho V_w U_w^2 > 0$: the wall must remove the kinetic energy of the entrained liquid even when the temperatures are equal.
- **Dimensional check.** $V_w y/\nu$ and $\mathrm{Pr}\, V_w y/\nu$ are dimensionless. $\rho V_w U_w$ has units $\mathrm{N/m^2}$. $\rho V_w U_w^2$ and $\rho c V_w \Delta T$ have units $\mathrm{W/m^2}$.
- **Relation to NS1.** The problem is that of NS1 with the wall moving instead of the free stream: the profiles have the same form, and (10) is (23) of NS1 with $U_\infty \to U_w$.