MECHANICS APPLIED TO AEROSPACE ENGINEERING - PART I

Topic 3: Constraints and Reaction Forces - Problem Sets

Department of Continuum Mechanics and Aeronautical Engineering • BSc in Aerospace Engineering, UC3M

Ground Truth: sources/cuatrimestre-1/03-engineering-mechanics/problemas/Problems.pdf (2026 Edition)

OFFICIAL MATERIAL Problems.pdf · p. 10

Verbatim Problem Statements: All problem statements below are transcribed with 100% fidelity from the official UC3M problem collection. Solutions will be added in subsequent analytical development phases.

PROBLEM 18 Conical Surface

Heavy Particle on a Cone

Original statement · Problems.pdf, p. 10

A heavy particle of mass m is moving without friction on a cone which is described as:

$$z^2 = x^2 + y^2$$

The frame of reference $Oxyz$ is inertial and Oz is the ascending vertical. The initial coordinates of the particle are $(a, 0, a)$ and its velocity is $ag\mathbf{j}$. Reduce the problem to integral equations and determine the maximum and minimum value of z along the motion.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** A point particle of mass m moves without friction on the interior surface of an inverted cone given by $z^2 = x^2 + y^2$ with $z > 0$.
- **Configuration Degrees of Freedom (CDOFs):**
- Ambient space: 3 Cartesian coordinates (x, y, z).
- Holonomic geometric constraint: $\Phi(x, y, z) = x^2 + y^2 - z^2 = 0$.
- Number of CDOFs: $3 - 1 = 2$. We choose cylindrical coordinates (r, θ) with $z = r$.
- **Hypotheses:**

1. Constraint is smooth (frictionless): the reaction force $\mathbf{N}$ is strictly orthogonal to the tangent space of the cone ($W_{\mathbf{N}} = 0$).

2. Inertial frame with gravity acting along $-Oz$: $\mathbf{g} = -g\mathbf{k}$.

- **Initial State ($t = 0$):**
- Position: $(x_0, y_0, z_0) = (a, 0, a) \implies r(0) = a, \theta(0) = 0, z(0) = a$.
- Velocity: $\mathbf{v}_0 = \quad ag\,\mathbf{j} \implies v_r(0) = 0, v_\theta(0) = r(0)\dot{\theta}(0) = \quad ag, v_z(0) = 0$.
- **Parameters:** $m > 0$ [kg], $g > 0$ [m/s^2], $a > 0$ [m].

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- **Inertial Reference Frame:** $\mathcal{F}_0 = \{O; \mathbf{i}, \mathbf{j}, \mathbf{k}\}$.
- **Cylindrical Vector Basis:** $\mathcal{B}_1 = \{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{k}\}$, with:

$$\mathbf{e}_r = \cos\theta\,\mathbf{i} + \sin\theta\,\mathbf{j}, \qquad \mathbf{e}_\theta = -\sin\theta\,\mathbf{i} + \cos\theta\,\mathbf{j}, \qquad \mathbf{k} = \mathbf{k}$$

- **Kinematics with Constraint $z(t) = r(t)$:**
- Position: $\mathbf{r}(t) = r\mathbf{e}_r + r\mathbf{k}$.
- Velocity: Differentiating with respect to time using Poisson's rule $\dot{\mathbf{e}}_r = \dot{\theta}\mathbf{e}_\theta$:

$$\mathbf{v}(t) = \dot{r}\mathbf{e}_r + r\dot{\theta}\mathbf{e}_\theta + \dot{r}\mathbf{k}$$

- Modulus of velocity squared:

$$v^2 = \dot{r}^2 + r^2\dot{\theta}^2 + \dot{r}^2 = 2\dot{r}^2 + r^2\dot{\theta}^2$$

- **Change of basis (cylindrical basis).** $\mathcal{B}_1 = \{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{k}\}$ is the inertial basis $\mathcal{B}_0 = \{\mathbf{i}, \mathbf{j}, \mathbf{k}\}$ rotated by $\theta(t)$ about $\mathbf{k}$; the columns are the components of $\mathbf{e}_r$, $\mathbf{e}_\theta$, $\mathbf{k}$ in $\mathcal{B}_0$:

$$[{}_0R_1] = \begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}, \qquad \det[{}_0R_1] = \cos^2\theta + \sin^2\theta = 1, \qquad [{}_0R_1][{}_0R_1]^T = I$$

- The angular velocity of $\mathcal{B}_1$ is $\boldsymbol{\omega}_{10} = \dot{\theta}\,\mathbf{k}$, so Poisson's formula gives $\dot{\mathbf{e}}_r = \dot{\theta}\,\mathbf{e}_\theta$ and $\dot{\mathbf{e}}_\theta = -\dot{\theta}\,\mathbf{e}_r$, as used above.
- **Surface-adapted basis.** On the cone $z = r$ (slope 45°) the unit generator is $\mathbf{e}_g = (\mathbf{e}_r + \mathbf{k})/\sqrt{2}$ and the unit normal pointing into the cone, where the particle lies, is $\mathbf{n}_{in} = (\mathbf{k} - \mathbf{e}_r)/\sqrt{2}$. The triple $\{\mathbf{e}_g, \mathbf{e}_\theta, \mathbf{n}_{in}\}$ is right-handed ($\mathbf{e}_g \times \mathbf{e}_\theta = \mathbf{n}_{in}$) and its components in $\mathcal{B}_1$ are the columns of

$$[{}_1R_2] = \begin{pmatrix} 1/\sqrt{2} & 0 & -1/\sqrt{2} \\ 0 & 1 & 0 \\ 1/\sqrt{2} & 0 & 1/\sqrt{2} \end{pmatrix}, \qquad \det[{}_1R_2] = \tfrac{1}{2} + \tfrac{1}{2} = 1, \qquad [{}_1R_2][{}_1R_2]^T = I$$

- Both matrices were checked symbolically with sympy.

PHASE 3

Step-by-Step Mathematical Deduction

1. Conservation of Angular Momentum about Oz

Pedagogical Justification: The forces acting on the particle are gravity $\mathbf{F}_g = -mg\mathbf{k}$ and the constraint reaction $\mathbf{N}$. Gravity is parallel to Oz, so its torque about O has no z-component. The normal to the cone $f(r, z) = r - z = 0$ is $\mathbf{n} = \frac{1}{\sqrt{2}}(\mathbf{e}_r - \mathbf{k})$, which lies entirely in the meridian plane $\operatorname{span}\{\mathbf{e}_r, \mathbf{k}\}$ and intersects the Oz axis. Thus, $\mathbf{N}$ exerts zero torque about the vertical axis Oz. By the angular momentum theorem (Notes.pdf Section 4.8), L_z is an invariant of motion.

$$L_z = [\mathbf{r} \times m\mathbf{v}] \cdot \mathbf{k} = mr^2\dot{\theta} = \text{constant} = C_z$$

Evaluate C_z at $t = 0$:

$$C_z = m[r(0)]^2\dot{\theta}(0) = ma(a\dot{\theta}_0) = ma(\quad ag) = ma\quad ga$$

Therefore:

$$\dot{\theta}(t) = \frac{a\quad ga}{r^2(t)}$$

2. Conservation of Mechanical Energy

> **Pedagogical Justification:** Because the constraint is frictionless (bilateral holonomic), the reaction force $\mathbf{N}$ does no work ($\mathbf{N} \cdot \mathbf{v} = 0$). Gravity is conservative with potential energy $V = mgz = mgr$. Hence, total mechanical energy $E = T + V$ is strictly conserved.

Initial energy at $t = 0$:

$$T(0) = \frac{1}{2}mv_0^2 = \frac{1}{2}m(ag)$$

$$V(0) = mgz(0) = mga$$

$$E = T(0) + V(0) = \frac{1}{2}mga + mga = \frac{3}{2}mga$$

Energy at any subsequent time:

$$E = \frac{1}{2}m\left(2\dot{r}^2 + r^2\dot{\theta}^2\right) + mgr = \frac{3}{2}mga$$

Substitute $\dot{\theta} = \frac{a\sqrt{ga}}{r^2}$:

$$\frac{1}{2}m\left(2\dot{r}^2 + r^2\frac{a^3 g}{r^4}\right) + mgr = \frac{3}{2}mga$$

$$m\dot{r}^2 + \frac{1}{2}mg\frac{a^3}{r^2} + mgr = \frac{3}{2}mga$$

Divide through by m:

$$\dot{r}^2 + \frac{ga^3}{2r^2} + gr = \frac{3}{2}ga$$

3. Reduction to Quadratures (Integral Equation)

Isolate $\dot{r}^2$:

$$\dot{r}^2 = \frac{3}{2}ga - gr - \frac{ga^3}{2r^2} = \frac{g}{2r^2}\left(3ar^2 - 2r^3 - a^3\right)$$

Taking the square root:

$$\frac{dr}{dt} = \pm\sqrt{\frac{g}{2}\frac{-2r^3 + 3ar^2 - a^3}{r}}$$

Separating variables yields the integral equation:

$$\int_a^r \frac{r'\,dr'}{-2r'^3+3ar'^2-a^3} = \pm \quad \frac{g}{2}\,t$$

4. Determination of Maximum and Minimum of z (r)

Pedagogical Justification: The turning points of the radial motion occur when the radial velocity vanishes, $\dot{r}=0$, which corresponds to the roots of the cubic polynomial $P(r) = -2r^3+3ar^2-a^3=0$.

Rewrite $P(r)=0$:

$$2r^3-3ar^2+a^3=0$$

Since the particle starts at $r=a$, $r=a$ must be a root:

$$2(a)^3-3a(a)^2+a^3=2a^3-3a^3+a^3=0$$

Divide $2r^3-3ar^2+a^3$ by $(r-a)$:

$$2r^3-3ar^2+a^3=(r-a)(2r^2-ar-a^2)$$

Factor the quadratic factor:

$$2r^2-ar-a^2=(r-a)(2r+a)$$

Therefore, the polynomial factors completely as:

$$2r^3-3ar^2+a^3=(r-a)^2(2r+a)$$

Substituting back into the expression for $\dot{r}^2$:

$$\dot{r}^2 = -\frac{g}{2r^2}(r-a)^2(2r+a)$$

Since $r > 0$ and $a > 0$, the factor $(2r + a) > 0$.

The square $(r-a)^2 \geq 0$, which implies:

$$\dot{r}^2 = -\frac{g(2r+a)}{2r^2}(r-a)^2 \leq 0, \qquad \forall r > 0$$

Because $\dot{r}^2$ is a squared real quantity, it must satisfy $\dot{r}^2 \geq 0$.

The only physically possible solution for all time is:

$$\dot{r}^2 = 0 \iff r(t) = a = \text{constant}$$

PHASE 4

Physical Interpretation & Dimensional Verification

- **Steady Circular Orbit:** The particle is placed exactly at the minimum of the effective potential $V_{eff}(r) = mgr + \frac{ma^3g}{2r^2}$. The initial tangential velocity $v_0 = \quad ag$ provides precisely the centripetal acceleration required to balance the inward horizontal component of the normal reaction force $\mathbf{N}$.
- **Extremal Heights:**

$$z_{min} = z_{max} = a$$

The particle maintains a constant altitude $z = a$ for all time, executing uniform circular motion with orbital frequency $\omega = \dot{\theta} = \quad g/a$.

- **Dimensional check:** $[C_z] = [m\,a \quad g a] = \mathrm{kg}\cdot\mathrm{m}^2\cdot\mathrm{s}^{-1}$ (angular momentum); $[\dot r^2] = \mathrm{m}^2/\mathrm{s}^2$ and $[g\,a^3/r^2] = (\mathrm{m}/\mathrm{s}^2)\,\mathrm{m} = \mathrm{m}^2/\mathrm{s}^2$, so every term of the energy equation has the same units.
- **Reaction on the steady orbit (sympy force balance):** with $\dot\theta^2 = g/a$ the horizontal acceleration is $-g\,\mathbf{e}_r$. Requiring $N\,\mathbf{n}_{in} - mg\,\mathbf{k} = -mg\,\mathbf{e}_r$ gives $\mathbf{N} = mg(\mathbf{k} - \mathbf{e}_r) = \quad 2\,mg\,\mathbf{n}_{in}$, so $\|\mathbf{N}\| = \quad 2\,mg$ [N], pointing into the cone, which is physically admissible (it presses the particle against the surface).
- **Stability (small radial oscillations):** the effective inertia of the r-motion is $2m$ (the kinetic energy has $2\dot r^2$) and $V_{eff}''(a) = 3mg/a$, hence $\omega_r^2 = 3g/(2a)$. An RK4 integration (step 10^{-4}, $g = a = 1$) of $2\ddot r = r\dot\theta^2 - g$ with $r(0) = 1.001$, $\dot r(0) = 0$ and $r^2\dot\theta = a \quad g a$ has period 5.1304 against $2\pi/ \quad 3/2 = 5.1302$ (in units of $\quad a/g$), confirming that the circular orbit is a stable minimum of V_{eff}.

`Complete Step-by-Step Solution`

Source: Problems.pdf (Page 10)

PROBLEM 19 | Paraboloid Surface

Heavy Particle on a Paraboloid

Original statement · Problems.pdf, p. 10

A heavy particle of mass m is moving without friction on the paraboloid which is described as:

$$az = r^2$$

where a is a positive constant and r is the distance to the Oz vertical axis. If $r = a$ initially, and the particle is released with a velocity v_0 tangent to the local parallel, reduce the problem to integrals of the form $\int [...] dr = \int [...] dt$. Determine the maximum and minimum of r along the motion.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** A particle of mass m moves without friction on the paraboloid of revolution $az = r^2$, where $a > 0$ and $r = \quad x^2 + y^2$.
- **Degrees of Freedom:** 3 coordinates minus 1 constraint $\implies$ 2 CDOFs. We parametrize using cylindrical coordinates (r, θ) with $z = r^2/a$.
- **Initial State ($t = 0$):**
- Radius: $r(0) = a \implies z(0) = a^2/a = a$.
- Velocity: Launched tangent to the local parallel (pure azimuthal velocity):

$$\mathbf{v}_0 = v_0 \mathbf{e}_\theta \implies \dot{r}(0) = 0, \quad \dot{\theta}(0) = \frac{v_0}{a}, \quad \dot{z}(0) = 0$$

- **Parameters:** $m > 0$ [kg], $a > 0$ [m], $g > 0$ [m/s^2], $v_0 > 0$ [m/s].

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- **Inertial Frame:** $\mathcal{F}_0 = \{O; \mathbf{i}, \mathbf{j}, \mathbf{k}\}$.
- **Kinematics with $z = r^2/a$:**

$$\dot{z} = \frac{d}{dt}\left(\frac{r^2}{a}\right) = \frac{2r\dot{r}}{a}$$

Velocity vector:

$$\mathbf{v} = \dot{r}\mathbf{e}_r + r\dot{\theta}\mathbf{e}_\theta + \frac{2r\dot{r}}{a}\mathbf{k}$$

Velocity squared:

$$v^2 = \dot{r}^2\left(1 + \frac{4r^2}{a^2}\right) + r^2\dot{\theta}^2$$

- **Change of basis (cylindrical basis).** $\mathcal{B}_1 = \{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{k}\}$ is obtained from $\mathcal{B}_0 = \{\mathbf{i}, \mathbf{j}, \mathbf{k}\}$ by a rotation $\theta(t)$ about $\mathbf{k}$:

$$[{}_0R_1] = \begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}, \qquad \det[{}_0R_1] = 1, \qquad [{}_0R_1][{}_0R_1]^T = I$$

- **Surface-adapted basis.** With $s = \sqrt{1 + 4r^2/a^2}$, the unit tangent along the meridian is $\mathbf{e}_g = (\mathbf{e}_r + \frac{2r}{a}\mathbf{k})/s$ and the unit normal pointing into the bowl is $\mathbf{n}_{in} = (\mathbf{k} - \frac{2r}{a}\mathbf{e}_r)/s$, proportional to $-\boldsymbol{\nabla} f$ of Phase 3. Since $\mathbf{e}_g \times \mathbf{e}_\theta = \mathbf{n}_{in}$ the triple is right-handed, and

$$[{}_1R_2] = \begin{pmatrix} 1/s & 0 & -2r/(as) \\ 0 & 1 & 0 \\ 2r/(as) & 0 & 1/s \end{pmatrix}, \qquad \det[{}_1R_2] = \frac{1}{s^2} + \frac{4r^2}{a^2 s^2} = 1, \qquad [{}_1R_2][{}_1R_2]^T = I$$

- The determinants and products RR^T were verified symbolically with sympy.

PHASE 3

Step-by-Step Mathematical Deduction

1. Conservation of Angular Momentum about Oz

Pedagogical Justification: The normal to the surface of revolution $f(r,z) = r^2 - az = 0$ is $\boldsymbol{\nabla} f = 2r\mathbf{e}_r - a\mathbf{k}$, which has no azimuthal component ($\mathbf{n} \cdot \mathbf{e}_\theta = 0$). Gravity also acts along $-\mathbf{k}$. Consequently, there is no torque about the vertical Oz axis, and L_z is conserved.

$$L_z = mr^2\dot{\theta} = m[r(0)]^2\dot{\theta}(0) = ma^2\left(\frac{v_0}{a}\right) = mav_0$$

$$r^2\dot{\theta} = av_0 \implies \dot{\theta} = \frac{av_0}{r^2}$$

2. Conservation of Mechanical Energy

Pedagogical Justification: The constraint is frictionless (bilateral holonomic), so the normal reaction does zero work. Gravity is conservative with potential $V = mgz = mg\frac{r^2}{a}$.

Initial energy:

$$E = \frac{1}{2}mv_0^2 + mgz(0) = \frac{1}{2}mv_0^2 + mga$$

Energy at time t:

$$E = \frac{1}{2}m\left[\dot{r}^2\left(1+\frac{4r^2}{a^2}\right)+r^2\dot{\theta}^2\right]+mg\frac{r^2}{a} = \frac{1}{2}mv_0^2+mga$$

Multiply by $\frac{2}{m}$:

$$\dot{r}^2\left(1+\frac{4r^2}{a^2}\right)+r^2\left(\frac{av_0}{r^2}\right)^2+\frac{2gr^2}{a} = v_0^2+2ga$$

$$\dot{r}^2\left(1+\frac{4r^2}{a^2}\right)+\frac{a^2v_0^2}{r^2}+\frac{2gr^2}{a} = v_0^2+2ga$$

Grouping terms:

$$\dot{r}^2\left(1+\frac{4r^2}{a^2}\right)+r^2\left(\dot{\theta}^2+\frac{2g}{a}\right) = v_0^2+2ga$$

Compare with the quadrature formula in the official solution key (Problems.pdf, Solution keys section).

3. Reduction to Quadratures

Isolating $\dot{r}$:

$$\dot{r}^2 = \frac{v_0^2+2ga-\frac{a^2v_0^2}{r^2}-\frac{2gr^2}{a}}{1+\frac{4r^2}{a^2}} = \frac{r^2(v_0^2+2ga)-a^2v_0^2-\frac{2g}{a}r^4}{r^2\left(1+\frac{4r^2}{a^2}\right)}$$

Taking the square root and separating variables:

$$\int \frac{1 + 4r^2/a^2}{v_0^2 + 2ga - a^2v_0^2/r^2 - 2gr^2/a}\,dr = \pm \int dt$$

4. Determination of Maximum and Minimum of r

Setting $\dot{r} = 0$:

$$v_0^2 + 2ga - \frac{a^2v_0^2}{r^2} - \frac{2gr^2}{a} = 0$$

Multiply by ar^2:

$$ar^2(v_0^2 + 2ga) - a^3v_0^2 - 2gr^4 = 0$$

$$2gr^4 - a(v_0^2 + 2ga)r^2 + a^3v_0^2 = 0$$

Let $u = r^2$. The quadratic in u is:

$$2gu^2 - a(v_0^2 + 2ga)u + a^3v_0^2 = 0$$

Since $r = a \implies u = a^2$ must be a root:

$$2g(a^2)^2 - a(v_0^2 + 2ga)(a^2) + a^3v_0^2 = 2ga^4 - a^3v_0^2 - 2ga^4 + a^3v_0^2 = 0$$

Factorizing $(u - a^2)$:

$$2gu^2 - a(v_0^2 + 2ga)u + a^3v_0^2 = (u - a^2)(2gu - av_0^2) = 0$$

The two roots for $u = r^2$ are:

$$u_1 = a^2 \implies r_1 = a$$

$$u_2 = \frac{av_0^2}{2g} \implies r_2 = v_0 \quad \frac{a}{2g}$$

PHASE 4

Physical Interpretation & Dimensional Verification

- **Case 1:** $v_0 < \quad 2ga$

$r_2 = v_0 \quad \frac{a}{2g} < a.$

$$r_{max} = a, \qquad r_{min} = v_0 \quad \frac{a}{2g}$$

The particle falls inwards towards the vertex, reaches r_{min}, and climbs back to a.

- **Case 2:** $v_0 = \quad 2ga$

$r_2 = a$. Both roots coincide:

$$r_{min} = r_{max} = a$$

The particle moves on a horizontal circular orbit of constant radius $r = a$.

- **Case 3:** $v_0 > \quad 2ga$

$r_2 = v_0 \quad \frac{a}{2g} > a.$

$$r_{min} = a, \qquad r_{max} = v_0 \quad \frac{a}{2g}$$

The particle climbs up the paraboloid to r_{max}, then falls back to a.

- Compare with the official solution key (Problems.pdf, Solution keys section).
- **Dimensional check:** $[v_0^2 + 2ga] = \mathrm{m}^2/\mathrm{s}^2$, $[a^2 v_0^2 / r^2] = \mathrm{m}^2/\mathrm{s}^2$ and $[2gr^2/a] = \mathrm{m}^2/\mathrm{s}^2$; the roots $r_2 = v_0 \quad a/(2g)$ have units $(\mathrm{m/s}) \quad \mathrm{m}/(\mathrm{m/s}^2) = \mathrm{m}$.
- **Circular orbit (Case 2):** for $v_0^2 = 2ga$ the quadratic of Phase 3 becomes $2g\,u^2 - 4ga^2 u + 2ga^4 = 2g\,(u - a^2)^2$, a double root at $u = a^2$, so $\dot{r} \equiv 0$. This agrees with the circular-orbit condition $v^2 = g\,r\tan\gamma$ with $\tan\gamma = dz/dr = 2r/a = 2$ at $r = a$.
- **Limit $v_0 \to 0$:** $r_{min} = v_0 \quad a/(2g) \to 0$, the particle drops to the vertex, as expected for a body released at rest.
- **Numerical check ($g = a = v_0 = 1$, case 1):** the turning points are the roots of $v_0^2 + 2ga - a^2 v_0^2/r^2 - 2gr^2/a = 0$; bisection gives $r_{min} = 0.707107$ against $v_0 \quad a/(2g) = 0.707107$, and $r_{max} = a = 1$.

`Complete Step-by-Step Solution`

Source: Problems.pdf (Page 10)

PROBLEM 20 | Rotating Curve & Energy Conservation

Heavy Particle on a Rotating Circumference

Original statement · Problems.pdf, p. 10

A heavy particle is moving along a smooth circumference of radius R and center O. One of the diameters of the circumference is along the local vertical, and the circumference is rotating with constant angular velocity ω about it. The position of the particle with respect to the circumference is described by the angle θ between the particle and the lowest point of the circumference.

(a) Discuss the conservation of mechanical energy in the moving reference frame and compute its value.

(b) Compute the reaction of the circumference in the direction normal to its plane, as a function of θ.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** A particle of mass m slides smoothly along a circular wire of radius R rotating with constant angular velocity ω about its vertical diameter.
- **CDOFs:** 1 degree of freedom, described by angle $\theta(t)$ from the lowest point of the circumference.
- **Hypotheses:** Frictionless wire, steady rotation $\boldsymbol{\omega} = \omega \mathbf{k}$.
- **Parameters:** $m > 0$ [kg], $R > 0$ [m], $\omega > 0$ [rad/s], $g > 0$ [m/s^2].

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- **Inertial Frame:** $\mathcal{F}_0 = \{O; \mathbf{i}_0, \mathbf{j}_0, \mathbf{k}\}$.
- **Rotating Frame:** $\mathcal{F}_1 = \{O; \mathbf{e}_\rho, \mathbf{e}_\phi, \mathbf{k}\}$ rotating with angular velocity $\boldsymbol{\omega}_{1/0} = \omega \mathbf{k}$.
- **Polar Basis on the Wire:** $\mathcal{B}_w = \{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{e}_\phi\}$ where:

$$\mathbf{r} = R\sin\theta\,\mathbf{e}_\rho - R\cos\theta\,\mathbf{k} = R\mathbf{e}_r$$

$$\mathbf{e}_\theta = \cos\theta\,\mathbf{e}_\rho + \sin\theta\,\mathbf{k}$$

- **Relative Velocity in $\mathcal{F}_1$:**

$$\mathbf{v}' = R\dot{\theta}\mathbf{e}_\theta$$

- **Change of basis $\mathcal{B}_0 \to \mathcal{B}_1$ (rotating frame).** With the wire plane at azimuth ωt, $\mathbf{e}_\rho = \cos\omega t\,\mathbf{i}_0 + \sin\omega t\,\mathbf{j}_0$, $\mathbf{e}_\phi = -\sin\omega t\,\mathbf{i}_0 + \cos\omega t\,\mathbf{j}_0$:

$$[{}_0R_1] = \begin{pmatrix} \cos\omega t & -\sin\omega t & 0 \\ \sin\omega t & \cos\omega t & 0 \\ 0 & 0 & 1 \end{pmatrix}, \qquad \det[{}_0R_1] = 1, \qquad [{}_0R_1][{}_0R_1]^T = I$$

- **Change of basis $\mathcal{B}_1 \to \mathcal{B}_w$ (wire basis).** Since $\mathbf{e}_r \times \mathbf{e}_\theta = -\mathbf{e}_\phi$, the right-handed wire triple is $\{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{e}_n\}$ with $\mathbf{e}_n = -\mathbf{e}_\phi$ (the ordering $\{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{e}_\phi\}$ listed above has determinant -1; only the sign of the third vector is affected, and N_ϕ below is defined along $\mathbf{e}_\phi$). The columns are the components in $\{\mathbf{e}_\rho, \mathbf{e}_\phi, \mathbf{k}\}$:

$$[{}_1R_w] = \begin{pmatrix} \sin\theta & \cos\theta & 0 \\ 0 & 0 & -1 \\ -\cos\theta & \sin\theta & 0 \end{pmatrix}, \qquad \det[{}_1R_w] = 1, \qquad [{}_1R_w][{}_1R_w]^T = I$$

- Determinants and products RR^T were verified symbolically with sympy.

PHASE 3

Step-by-Step Mathematical Deduction

Part (a): Conservation of Mechanical Energy in the Moving Frame

Pedagogical Justification: In the rotating frame $\mathcal{F}_1$, fictitious forces appear: centrifugal force $\mathbf{F}_{cf} = m\omega^2\rho\mathbf{e}_\rho$ and Coriolis force $\mathbf{F}_{Cor} = -2m\boldsymbol{\omega} \times \mathbf{v}'$.

1. The centrifugal force is conservative, derived from potential $V_{cf} = -\frac{1}{2}m\omega^2\rho^2 = -\frac{1}{2}m\omega^2 R^2 \sin^2\theta$.

2. The Coriolis force is always perpendicular to velocity ($\mathbf{F}_{Cor} \cdot \mathbf{v}' = 0$), doing strictly zero power.

3. The constraint reaction $\mathbf{N}$ is perpendicular to the wire ($\mathbf{N} \cdot \mathbf{e}_\theta = 0$), so $W_{\mathbf{N}} = 0$.

Therefore, the effective mechanical energy E' in the rotating frame is conserved.

Expressions for energies:

$$T' = \frac{1}{2}m|\mathbf{v}'|^2 = \frac{1}{2}mR^2\dot{\theta}^2$$

$$V_g(\theta) = -mgR\cos\theta \quad (\text{with reference datum } V_g(\pi/2) = 0)$$

$$V_{cf}(\theta) = -\frac{1}{2}m\omega^2 R^2 \sin^2\theta$$

Total effective mechanical energy:

$$E' = T' + V_g + V_{cf} = \frac{1}{2}mR^2\dot{\theta}^2 - mgR\cos\theta - \frac{1}{2}m\omega^2 R^2\sin^2\theta = \text{constant}$$

Part (b): Reaction Normal to the Plane of the Circumference

> **Pedagogical Justification:** The unit vector normal to the plane of the circumference is $\mathbf{e}_\phi$. Applying Newton's second law in the rotating frame along $\mathbf{e}_\phi$ isolates the out-of-plane reaction force N_ϕ.

Dynamic equilibrium in $\mathcal{F}_1$:

$$m\mathbf{a}' = \mathbf{F}_g + \mathbf{F}_{cf} + \mathbf{F}_{Cor} + \mathbf{N}$$

Since the particle is constrained to the planar wire, $a'_\phi = 0$.

Project forces along $\mathbf{e}_\phi$:

1. Gravity: $\mathbf{F}_g \cdot \mathbf{e}_\phi = (-mg\mathbf{k}) \cdot \mathbf{e}_\phi = 0$.

2. Centrifugal: $\mathbf{F}_{cf} \cdot \mathbf{e}_\phi = (m\omega^2 R \sin\theta \mathbf{e}_\rho) \cdot \mathbf{e}_\phi = 0$.

3. Coriolis:

$$\mathbf{F}_{Cor} = -2m(\omega\mathbf{k}) \times (R\dot{\theta}\mathbf{e}_\theta) = -2m\omega R\dot{\theta}(\mathbf{k} \times (\cos\theta\,\mathbf{e}_\rho + \sin\theta\,\mathbf{k}))$$

Since $\mathbf{k} \times \mathbf{e}_\rho = \mathbf{e}_\phi$ and $\mathbf{k} \times \mathbf{k} = \mathbf{0}$:

$$\mathbf{F}_{Cor} = -2m\omega R\dot{\theta}\cos\theta\,\mathbf{e}_\phi$$

4. Reaction: $\mathbf{N} \cdot \mathbf{e}_\phi = N_\phi$.

Equating components:

$$0 = -2m\omega R\dot{\theta}\cos\theta + N_\phi \implies N_\phi = 2m\omega R\dot{\theta}\cos\theta$$

Using energy conservation to express $\dot{\theta}$ as a function of θ:

$$\dot{\theta} = \pm \sqrt{\frac{2}{mR^2}\left(E' + mgR\cos\theta + \frac{1}{2}m\omega^2 R^2 \sin^2\theta\right)}$$

$$N_\phi(\theta) = \pm 2m\omega\cos\theta \sqrt{\frac{2}{m}\left(E' + mgR\cos\theta + \frac{1}{2}m\omega^2 R^2 \sin^2\theta\right)}$$

PHASE 4

Physical Interpretation & Dimensional Verification

- The out-of-plane reaction N_ϕ is purely generated by the Coriolis acceleration: to keep the particle moving along the rotating meridian, the wire must exert a lateral force balancing the Coriolis effect.
- At the equator ($\theta = \pi/2$), $\cos(\pi/2) = 0 \implies N_\phi = 0$. At this point, the velocity $\mathbf{v}'$ is parallel to $\boldsymbol{\omega}$, so the cross product $\boldsymbol{\omega} \times \mathbf{v}'$ vanishes.
- **Dimensional check:** $[N_\phi] = [m\,\omega\,R\,\dot{\theta}] = \mathrm{kg}\cdot\mathrm{s}^{-1}\cdot\mathrm{m}\cdot\mathrm{s}^{-1} = \mathrm{N}$; in E' each of $\frac{1}{2}mR^2\dot{\theta}^2$, $mgR\cos\theta$ and $\frac{1}{2}m\omega^2R^2\sin^2\theta$ has units of joule.
- **Limit $\omega \to 0$:** the wire is at rest, $N_\phi \to 0$ and $E' \to \frac{1}{2}mR^2\dot{\theta}^2 - mgR\cos\theta$, the energy of the simple pendulum.
- **Independent check of N_ϕ (sympy, inertial frame):** differentiating twice $\mathbf{r} = R\sin\theta\,\mathbf{e}_\rho(\omega t) - R\cos\theta\,\mathbf{k}$ in the inertial frame gives $\mathbf{a}\cdot\mathbf{e}_\phi = 2\omega R\dot{\theta}\cos\theta$; since only N_ϕ acts along $\mathbf{e}_\phi$, $N_\phi = 2m\omega R\dot{\theta}\cos\theta$, identical to the rotating-frame result.
- **Numerical check of E' (RK4, step 10^{-3}, $R = 1$ m, $\omega = 1.3$ rad/s, $g = 9.81$ m/s^2):** integrating $\ddot{\theta} = -(g/R)\sin\theta + \omega^2\sin\theta\cos\theta$ for 20 s from $\theta = 0.4$, $\dot{\theta} = 0.3$, E'/m stays at -9.118750 with a drift of 9×10^{-14}.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 10)

PROBLEM 22 | 1D Curve Constraint

Particle on a Curve

Original statement · Problems.pdf, p. 10

A heavy point particle P of mass m is constrained to move without friction along the curve:

$$y = a\left(1 - \cos\frac{x}{a}\right) \tag{4}$$

in the range $-\pi a \leq x \leq \pi a$, where a is a positive constant. Initially, the particle is located at $x = 0$ with velocity v_0 along the positive x axis.

(a) Reduce the problem to integrals.

(b) If $v_0 = \quad ga$, determine the minimum and maximum value of x along the motion.

(c) What should be the minimum value of v_0 in order to reach $x = \pi a$?

Extended Section (Moving Reference Frame):
Let's assume now that the curve containing the point particle rotates around the OY axis with constant angular velocity $\boldsymbol{\omega} = \Omega\mathbf{j}$.

(d) Define a convenient moving reference frame with origin in O, $OX_1Y_1Z_1$. Determine the inertia force that acts on the particle in this moving reference frame as a function of m, Ω, x_1 and $\dot{x}_1$, where x_1 represents the position coordinate of P along OX_1.

(e) Reduce the problem to quadratures and determine the value of the reaction force.

(f) Find out a transcendental equation whose solutions are the equilibrium positions of the point particle in $OX_1Y_1Z_1$.

(g) If Ω were a function of time, would it be possible to use the energy equation in the same way as before? Justify your answer.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** A particle of mass m is constrained to move without friction along the smooth planar curve:

$$y = a\left(1 - \cos\frac{x}{a}\right), \qquad x \in [-\pi a, \pi a]$$

in a vertical plane under uniform downward gravity $\mathbf{g} = -g\mathbf{j}$.

- **CDOFs:** 1 degree of freedom, parametrized by Cartesian abscissa $x(t)$.
- **Initial State ($t = 0$):** $x(0) = 0 \implies y(0) = a(1 - \cos 0) = 0$, with initial velocity $\mathbf{v}_0 = v_0\mathbf{i}$ ($v_0 > 0$).
- **Parameters:** $m > 0$ [kg], $a > 0$ [m], $g > 0$ [m/s^2], $v_0 > 0$ [m/s].

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- **Inertial Frame:** $\mathcal{F}_0 = \{O; \mathbf{i}, \mathbf{j}, \mathbf{k}\}$.
- **Curve Differential Elements:**

$$\frac{dy}{dx} = \frac{d}{dx}\left[a\left(1 - \cos\frac{x}{a}\right)\right] = \sin\left(\frac{x}{a}\right)$$

Differential arc-length:

$$ds^2 = dx^2 + dy^2 = dx^2 + \sin^2\left(\frac{x}{a}\right)dx^2 = \left[1 + \sin^2\left(\frac{x}{a}\right)\right]dx^2$$

$$ds = \sqrt{1 + \sin^2\left(\frac{x}{a}\right)}\,dx$$

- **Velocity:**

$$v = \frac{ds}{dt} = \sqrt{1 + \sin^2\left(\frac{x}{a}\right)}\,\dot{x}$$

PHASE 3

Step-by-Step Mathematical Deduction

Part (a): Reduction of Motion to Integrals

Pedagogical Justification: The frictionless constraint does zero work ($W_N = 0$). Gravity is conservative with potential energy $V(y) = mgy = mga(1 - \cos(x/a))$. Total mechanical energy is constant.

$$E = \frac{1}{2}mv^2 + mgy = \frac{1}{2}mv_0^2 + mg(0) = \frac{1}{2}mv_0^2$$

$$\frac{1}{2}m\left[1 + \sin^2\left(\frac{x}{a}\right)\right]\dot{x}^2 + mga\left(1 - \cos\frac{x}{a}\right) = \frac{1}{2}mv_0^2$$

Multiply by $2/m$:

$$\left[1 + \sin^2\left(\frac{x}{a}\right)\right]\dot{x}^2 = v_0^2 - 2ga\left(1 - \cos\frac{x}{a}\right)$$

Isolate $\dot{x} = \frac{dx}{dt}$:

$$\frac{dx}{dt} = \pm\sqrt{\frac{v_0^2 - 2ga(1 - \cos(x/a))}{1 + \sin^2(x/a)}}$$

Separation of variables yields the quadrature:

$$\int_0^{x(t)} \sqrt{\frac{1 + \sin^2(x'/a)}{v_0^2 - 2ga(1 - \cos(x'/a))}}\,dx' = \pm t$$

Part (b): Turning Points for $v_0 = \quad ga$

> **Pedagogical Justification:** Turning points occur where the velocity vanishes ($v = 0 \iff \dot{x} = 0$).

$$v_0^2 - 2ga\left(1 - \cos\frac{x}{a}\right) = 0$$

Substitute $v_0^2 = ga$:

$$ga - 2ga\left(1 - \cos\frac{x}{a}\right) = 0$$

Divide by ga:

$$1 - 2\left(1 - \cos\frac{x}{a}\right) = 0 \implies 2\cos\frac{x}{a} = 1 \implies \cos\frac{x}{a} = \frac{1}{2}$$

In the domain $x/a \in [-\pi, \pi]$:

$$\frac{x}{a} = \pm\frac{\pi}{3} \implies x_{min} = -\frac{\pi}{3}a, \qquad x_{max} = +\frac{\pi}{3}a$$

Part (c): Minimum Velocity v_0 to Reach $x = \pi a$

> **Pedagogical Justification:** At the crest $x = \pi a$, the height is $y(\pi a) = a(1 - \cos\pi) = a(1 - (-1)) = 2a$. For the particle to reach this crest, its kinetic energy at the peak must be non-negative ($T(\pi a) \geq 0$).

$$E \geq V(\pi a) \implies \frac{1}{2}mv_0^2 \geq mg(2a) = 2mga$$

$$v_0^2 \geq 4ga \implies v_{0,min} = \sqrt{4ga} = 2\sqrt{ga}$$

Part (d): Moving Reference Frame with Rotation $\boldsymbol{\omega} = \Omega\mathbf{j}$

- Frame $\mathcal{F}_1 = \{O; \mathbf{i}_1, \mathbf{j}, \mathbf{k}_1\}$ rotating with $\boldsymbol{\Omega} = \Omega\mathbf{j}$.
- Particle position: $\mathbf{r}' = x_1\mathbf{i}_1 + y(x_1)\mathbf{j}$.
- Relative velocity: $\mathbf{v}' = \dot{x}_1\mathbf{i}_1 + \sin(x_1/a)\dot{x}_1\mathbf{j}$.
- Inertia forces in $\mathcal{F}_1$:

1. Centrifugal Force:

$$\mathbf{F}_{cf} = -m\boldsymbol{\Omega} \times (\boldsymbol{\Omega} \times \mathbf{r}') = m\Omega^2 x_1 \mathbf{i}_1$$

2. Coriolis Force:

$$\mathbf{F}_{Cor} = -2m\boldsymbol{\Omega} \times \mathbf{v}' = -2m(\Omega \mathbf{j}) \times (\dot{x}_1 \mathbf{i}_1 + \dot{y}_1 \mathbf{j}) = 2m\Omega \dot{x}_1 \, \mathbf{k}_1$$

Part (e): Quadratures and Reaction Force in the Moving Frame

- Effective potential in $\mathcal{F}_1$:

$$V_{eff}(x_1) = mgy(x_1) - \frac{1}{2}m\Omega^2 x_1^2 = mga\left(1 - \cos\frac{x_1}{a}\right) - \frac{1}{2}m\Omega^2 x_1^2$$

- Energy conservation in $\mathcal{F}_1$:

$$E' = \frac{1}{2}m\left[1 + \sin^2(x_1/a)\right]\dot{x}_1^2 + mga\left(1 - \cos\frac{x_1}{a}\right) - \frac{1}{2}m\Omega^2 x_1^2 = \text{constant}$$

- Reaction force: $\mathbf{N} = N_n \mathbf{n} + N_z \mathbf{k}_1$.

Along the binormal $\mathbf{k}_1$: $N_z = -F_{Cor,z} = -2m\Omega\dot{x}_1$.

Part (f): Transcendental Equilibrium Equation

Equilibrium occurs where $\frac{dV_{eff}}{dx_1} = 0$:

$$\frac{dV_{eff}}{dx_1} = mg\sin\left(\frac{x_1}{a}\right) - m\Omega^2 x_1 = 0 \implies g\sin\left(\frac{x_1}{a}\right) - \Omega^2 x_1 = 0$$

Part (g): Case $\Omega = \Omega(t)$

If Ω varies with time, the centrifugal potential becomes explicitly time-dependent ($\frac{\partial V_{cf}}{\partial t} = -m\Omega\dot{\Omega}x_1^2 \neq 0$) and an Euler inertia force $\mathbf{F}_{Euler} = -m\dot{\boldsymbol{\Omega}} \times \mathbf{r}'$ appears, which does non-zero work. Thus, mechanical energy in $\mathcal{F}_1$ is **not** conserved.

PHASE 4

Physical Interpretation & Dimensional Verification

- The potential well has width $2\pi a$ and barrier height $2ga$. Rotation creates a centrifugal destabilizing potential $-\frac{1}{2}m\Omega^2 x_1^2$ so that the origin loses stability for $\Omega^2 > g/a$. Off-centre equilibria satisfy $\sin u = \lambda u$ with $u = x_1/a$ and $\lambda = \Omega^2 a/g$; since $\sin u/u$ decreases monotonically from 1 to 0 on $(0, \pi]$, they exist (one pair $\pm u^*$ with $0 < u^* < \pi$) only for $\lambda < 1$, i.e. $\Omega^2 < g/a$, and there they are unstable ($V''_{eff} = (mg/a)(\cos u^* - \lambda) < 0$).

> **Erratum:** The first version stated that off-centre equilibria appear for $\Omega^2 > g/a$; they exist only for $\Omega^2 < g/a$ (subcritical case) and are unstable. Numeric check: a scan of $\sin u = \lambda u$ on $(0, \pi]$ finds one root for $\lambda = 0.5$ ($u^* = 1.8955$) and for 0.9, and none for $\lambda = 1, 1.1, 2$.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 11)

Particle on a Circumference with a Spring

Original statement · Problems.pdf, p. 12

A heavy particle P is constrained to move along a circumference and it is attached to a spring as shown in the figure. The mass of the particle is m, and the radius of the circumference is a. The other end of the spring is attached to a point of the y axis with coordinates $(0, \beta a)$ and the constant of the spring is equal to k.

(a) Compute the potential of the forces acting on the particle as a function of the angle θ (shown in the figure).

(b) Identify the equilibrium positions.

The particle departs from the point $(a, 0)$ of the circumference with an initial velocity $\mathbf{v}_0 = v_0\mathbf{j}$.

(c) Reduce the motion to integrals (i.e., quadratures).

(d) If $\beta = \frac{mg}{ka}$, obtain the position of the particle as a function of time.

Viscous Damping Case:
Consider now the situation in which an additional force acts on the particle. The force is proportional to, and in the same direction as, the instantaneous velocity. The constant of proportionality is $2m\mu$. The initial conditions are the same as before.

(e) Obtain the position of the particle as a function of time.

(f) Obtain the reaction of the circumference.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** A particle of mass m slides along a vertical circular wire of radius a centered at O. A linear spring of stiffness k and zero natural length connects the particle P to anchor point $A(0, \beta a)$ on the vertical axis.
- **CDOFs:** 1 degree of freedom, angle θ measured counterclockwise from the positive x-axis.
- **Forces:**

1. Gravity: $-mg\mathbf{j}$.

2. Spring force: $\mathbf{F}_s = -k\mathbf{AP}$.

3. Constraint reaction $\mathbf{N}$ normal to the wire.

- **Initial State ($t = 0$):** Released from $(a, 0) \implies \theta(0) = 0$ with $\mathbf{v}_0 = v_0\mathbf{j} \implies \dot{\theta}(0) = v_0/a$.
- **Parameters:** $m, a, k, g, \beta, v_0 > 0$.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Position of anchor A: $\mathbf{r}_A = \beta a\mathbf{j}$.
- Position of particle P: $\mathbf{r}_P = a\cos\theta\,\mathbf{i} + a\sin\theta\,\mathbf{j}$.
- Spring elongation vector:

$$\mathbf{AP} = \mathbf{r}_P - \mathbf{r}_A = a\cos\theta\,\mathbf{i} + a(\sin\theta - \beta)\,\mathbf{j}$$

- Length squared of spring:

$$|\mathbf{AP}|^2 = a^2\cos^2\theta + a^2(\sin\theta - \beta)^2 = a^2\left[\cos^2\theta + \sin^2\theta - 2\beta\sin\theta + \beta^2\right] = a^2(1 + \beta^2 - 2\beta\sin\theta)$$

PHASE 3

Step-by-Step Mathematical Deduction

Part (a): Total Potential Energy Function $V(\theta)$

> **Pedagogical Justification:** Both gravity and the linear spring are conservative forces. The total potential energy is the sum of gravitational and elastic potentials.

$$V_g(\theta) = mgy = mga\sin\theta$$

$$V_s(\theta) = \frac{1}{2}k|\mathbf{AP}|^2 = \frac{1}{2}ka^2(1+\beta^2-2\beta\sin\theta)$$

Summing both contributions:

$$V(\theta) = mga\sin\theta + \frac{1}{2}ka^2(1+\beta^2) - k\beta a^2\sin\theta = \frac{1}{2}ka^2(1+\beta^2) + (mg-k\beta a)a\sin\theta$$

Part (b): Identification of Equilibrium Positions

Equilibrium requires $\frac{dV}{d\theta} = 0$:

$$\frac{dV}{d\theta} = (mg - k\beta a)a\cos\theta = 0$$

Two cases emerge:

1. If $mg - k\beta a \neq 0$: $\cos\theta = 0 \implies \theta_1 = \frac{\pi}{2}$ (top) and $\theta_2 = -\frac{\pi}{2}$ (bottom).

2. If $\beta = \frac{mg}{ka}$: $\frac{dV}{d\theta} \equiv 0$ for **all** θ. Every point along the circumference is an equilibrium position (neutral equilibrium)!

Part (c): Reduction of Motion to Quadratures

Conservation of mechanical energy:

$$E = \frac{1}{2}ma^2\dot{\theta}^2 + V(\theta) = \frac{1}{2}mv_0^2 + V(0) = \frac{1}{2}mv_0^2 + \frac{1}{2}ka^2(1+\beta^2)$$

$$\dot{\theta} = \pm \sqrt{\frac{v_0^2}{a^2} - \frac{2(mg - k\beta a)}{ma}\sin\theta}$$

$$\int_0^{\theta(t)} \frac{d\theta'}{\sqrt{\frac{v_0^2}{a^2} - \frac{2(mg-k\beta a)}{ma}\sin\theta'}} = t$$

Part (d): Case $\beta = \frac{mg}{ka}$

When $\beta = \frac{mg}{ka}$, the coefficient $(mg - k\beta a) = 0$.

The potential energy is strictly constant: $V(\theta) = \text{constant}$.

The equation of motion reduces to:

$$\ddot{\theta} = 0 \implies \dot{\theta}(t) = \dot{\theta}(0) = \frac{v_0}{a}$$

Integrating with $\theta(0) = 0$:

$$\theta(t) = \frac{v_0}{a}t$$

The particle circles the wire with strictly uniform angular speed!

Part (e): Viscous Damping Case (Damping force $\mathbf{F}_d = -2m\mu\mathbf{v}$)

With $\beta = \frac{mg}{ka}$, the tangential equation of motion is:

$$ma\ddot{\theta} = F_{d,\theta} = -2m\mu(a\dot{\theta})$$

Divide by ma:

$$\ddot{\theta} + 2\mu\dot{\theta} = 0$$

Let $\omega(t) = \dot{\theta}(t)$:

$$\dot{\omega} + 2\mu\omega = 0 \implies \omega(t) = \omega(0)e^{-2\mu t} = \frac{v_0}{a}e^{-2\mu t}$$

Integrate for position $\theta(t) = \int_0^t \omega(t')dt'$ with $\theta(0) = 0$:

$$\theta(t) = \frac{v_0}{a}\int_0^t e^{-2\mu t'}dt' = \frac{v_0}{a}\left[-\frac{1}{2\mu}e^{-2\mu t'}\right]_0^t = \frac{v_0}{2\mu a}\left(1 - e^{-2\mu t}\right)$$

Part (f): Reaction of the Circumference

Radial Newton's second law, with N the component of the reaction along $+\mathbf{e}_r$ (outward), $\mathbf{F}_g \cdot \mathbf{e}_r = -mg\sin\theta$ and $\mathbf{F}_s \cdot \mathbf{e}_r = -ka(1 - \beta\sin\theta)$:

$$-ma\dot{\theta}^2 = N + \mathbf{F}_g \cdot \mathbf{e}_r + \mathbf{F}_s \cdot \mathbf{e}_r$$

$$N(t) = -ma[\dot{\theta}(t)]^2 + mg\sin\theta(t) + ka(1 - \beta\sin\theta(t))$$

Substitute $\beta = \frac{mg}{ka}$:

$$N(t) = ka - ma\left(\frac{v_0}{a}\right)^2 e^{-4\mu t} = ka - \frac{mv_0^2}{a}e^{-4\mu t}$$

Erratum: The first version of part (f) had the sign of the reaction wrong ($N = ma\dot{\theta}^2 + mg\sin\theta + ka(1 - \beta\sin\theta)$, which follows from no sign convention). With N the outward component, $N = -ma\dot{\theta}^2 + mg\sin\theta + ka(1 - \beta\sin\theta)$, i.e. $N\,\mathbf{e}_r = ka - (mv_0^2/a)e^{-4\mu t}$ for $\beta = mg/(ka)$ (inward component $-N$). Numeric check: sympy solving $m\mathbf{a} = \mathbf{F}_g + \mathbf{F}_s + N\mathbf{e}_r$ reproduces the general expression with zero residual.

PHASE 4

Physical Interpretation & Dimensional Verification

- As $t \to \infty$, the particle comes to rest asymptotically at $\theta_\infty = \frac{v_0}{2\mu a}$, and the reaction force approaches the static spring preload ka.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 12)

PROBLEM 26 | Semicircular Rotating Wire

Heavy Particle on a Rotating Half-Circumference

Original statement · Problems.pdf, p. 14

A heavy point particle P of mass m is constrained to move without friction along the half-circumference wire of radius a shown in the figure. The wire containing the point particle rotates around the OY axis with constant angular velocity $\omega = \Omega\mathbf{j}$. Initially, the particle is located at $x = 0$ with velocity v_0 along the positive x axis.

(a) Determine the number of degrees of freedom of the problem.

(b) Define a convenient moving reference frame with origin in O, $OX_1Y_1Z_1$. Express the inertia force that acts on the particle in this moving reference frame.

(c) Express also the components of the weight of the particle with respect to $OX_1Y_1Z_1$.

(d) Determine if there are any equilibrium points.

(e) Reduce the problem to integrals (i.e. quadratures) and determine the value of the reaction force.

(f) Is it possible to use the energy equation? If Ω were a function of time, would it be possible to use the energy equation? Justify your answer.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** A particle of mass m slides smoothly along a half-circumference wire of radius a lying in the X_1Y_1 plane, which rotates around the vertical OY axis with constant angular velocity $\boldsymbol{\omega} = \Omega\mathbf{j}$.
- **CDOFs:** 1 degree of freedom ($\theta \in [0, \pi]$).
- **Initial State:** At $t = 0, x_1(0) = 0, \theta(0) = 0$, velocity $\mathbf{v}_0 = v_0\mathbf{i}_1$.
- **Parameters:** $m, a, \Omega, g, v_0 > 0$.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Moving frame $\mathcal{F}_1 = \{O; \mathbf{i}_1, \mathbf{j}, \mathbf{k}_1\}$ rotating with $\boldsymbol{\omega}_{1/0} = \Omega\mathbf{j}$.
- Position on half-circle: $\mathbf{r}' = a\sin\theta\,\mathbf{i}_1 - a\cos\theta\,\mathbf{j}$.
- Polar tangent on wire: $\mathbf{e}_\theta = \cos\theta\,\mathbf{i}_1 + \sin\theta\,\mathbf{j}$.
- Relative velocity: $\mathbf{v}' = a\dot{\theta}\mathbf{e}_\theta$.
- **Change of basis $\mathcal{B}_0 \to \mathcal{B}_1$ (rotation about j).** $\mathcal{B}_1 = \{\mathbf{i}_1, \mathbf{j}, \mathbf{k}_1\}$ is the inertial basis $\{\mathbf{i}, \mathbf{j}, \mathbf{k}\}$ rotated by Ωt about $\mathbf{j}$, so $\mathbf{i}_1 = \cos\Omega t\,\mathbf{i} - \sin\Omega t\,\mathbf{k}$ and $\mathbf{k}_1 = \sin\Omega t\,\mathbf{i} + \cos\Omega t\,\mathbf{k}$:

$$[{}_0R_1] = \begin{pmatrix} \cos\Omega t & 0 & \sin\Omega t \\ 0 & 1 & 0 \\ -\sin\Omega t & 0 & \cos\Omega t \end{pmatrix}, \qquad \det[{}_0R_1] = \cos^2\Omega t + \sin^2\Omega t = 1, \qquad [{}_0R_1][{}_0R_1]^T = I$$

- **Change of basis $\mathcal{B}_1 \to \mathcal{B}_w$ (wire basis).** With $\mathbf{e}_r = \sin\theta\,\mathbf{i}_1 - \cos\theta\,\mathbf{j}$, $\mathbf{e}_\theta = \cos\theta\,\mathbf{i}_1 + \sin\theta\,\mathbf{j}$ and $\mathbf{e}_r \times \mathbf{e}_\theta = \mathbf{k}_1$, the triple $\{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{k}_1\}$ is right-handed:

$$[{}_1R_w] = \begin{pmatrix} \sin\theta & \cos\theta & 0 \\ -\cos\theta & \sin\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}, \qquad \det[{}_1R_w] = \sin^2\theta + \cos^2\theta = 1, \qquad [{}_1R_w][{}_1R_w]^T = I$$

- Both matrices were checked symbolically with sympy ($\mathbf{i}_1 \times \mathbf{j} = \mathbf{k}_1$ included).

PHASE 3

Step-by-Step Mathematical Deduction

Part (a): Degrees of Freedom

- Ambient space: 3 coordinates. Two constraints: wire geometry ($r = a, z_1 = 0$).
- Total CDOFs: $3 - 2 = 1$.

Part (b): Inertia Forces in $\mathcal{F}_1$

1. Centrifugal Force:

$$\mathbf{F}_{cf} = m\Omega^2 x_1 \mathbf{i}_1 = m\Omega^2 a \sin\theta \, \mathbf{i}_1$$

2. Coriolis Force:

$$\mathbf{F}_{Cor} = -2m(\Omega \mathbf{j}) \times (a\dot{\theta}\mathbf{e}_\theta) = 2m\Omega a\dot{\theta} \cos\theta \, \mathbf{k}_1$$

Part (c): Components of Weight

$$\mathbf{F}_g = -mg\mathbf{j}$$

Part (d): Equilibrium Points in $\mathcal{F}_1$

Project equation of motion along the wire tangent $\mathbf{e}_\theta$:

$$ma\ddot{\theta} = (\mathbf{F}_g + \mathbf{F}_{cf}) \cdot \mathbf{e}_\theta = (-mg\mathbf{j} + m\Omega^2 a \sin\theta \mathbf{i}_1) \cdot (\cos\theta \, \mathbf{i}_1 + \sin\theta \, \mathbf{j})$$

$$ma\ddot{\theta} = m\Omega^2 a \sin\theta\cos\theta - mg\sin\theta = ma\left(\Omega^2\cos\theta - \frac{g}{a}\right)\sin\theta$$

Equilibria ($\ddot{\theta} = 0$):

1. $\sin\theta = 0 \implies \theta = 0$ (lowest point, stable if $\Omega^2 < g/a$).

2. $\cos\theta = \frac{g}{\Omega^2 a}$. This requires $\Omega^2 > g/a$, yielding the stable equilibrium $\theta_0 = \arccos\left(\frac{g}{\Omega^2 a}\right)$.

Part (e): Reduction to Quadratures & Reaction Force

Effective potential:

$$V_{eff}(\theta) = -mga\cos\theta - \frac{1}{2}m\Omega^2 a^2 \sin^2\theta$$

Energy conservation:

$$\frac{1}{2}ma^2\dot{\theta}^2 + V_{eff}(\theta) = E' = \frac{1}{2}mv_0^2 - mga$$

$$\dot{\theta} = \pm \sqrt{\frac{v_0^2}{a^2} + \frac{2g}{a}(\cos\theta - 1) + \Omega^2 \sin^2\theta}$$

Out-of-plane reaction:

$$N_z = -F_{Cor,z} = -2m\Omega a\dot{\theta}\cos\theta$$

Part (f): Energy Equation Validity

Energy is conserved in $\mathcal{F}_1$ because the rotation rate Ω is constant. If $\Omega = \Omega(t)$, Euler forces do work and $\partial V_{eff}/\partial t \neq 0$, breaking energy conservation.

PHASE 4

Physical Interpretation & Dimensional Verification

- Supercritical pitchfork bifurcation at $\Omega_c = \sqrt{g/a}$.
- **Dimensional check:** $[m\Omega^2 a] = \text{kg}\cdot\text{s}^{-2}\cdot\text{m} = \text{N}$ (centrifugal force); $[\Omega^2\cos\theta - g/a] = \text{s}^{-2}$; $[N_z] = [m\,\Omega\,a\,\dot{\theta}] = \text{N}$; in the expression of $\dot{\theta}$ every term has units s^{-2} under the root.
- **Limits:** for $\Omega \to 0$ the effective potential reduces to $-mga\cos\theta$ (simple pendulum with a single stable equilibrium at $\theta = 0$) and $N_z \to 0$; at $\Omega = \Omega_c = \sqrt{g/a}$ the off-axis equilibrium $\cos\theta_0 = g/(\Omega^2 a) \to 1$ merges with $\theta = 0$; for $\Omega \to \infty$, $\theta_0 \to \pi/2$.

- **Numerical check ($\Omega^2 = 2g/a$):** $\cos\theta_0 = 1/2$, $\theta_0 = 60^\circ$; $V''_{eff}(\theta_0) = mga\cos\theta_0 - m\Omega^2 a^2\cos 2\theta_0 = 1.5\,mga > 0$ (stable) and the small-oscillation frequency is $\omega^2 = V''_{eff}/(ma^2) = 1.5\,g/a = \Omega^2\sin^2\theta_0$, which agree.

`Complete Step-by-Step Solution`

Source: Problems.pdf (Page 14)

PROBLEM 29 | Unilateral Liftoff

Heavy Particle on a Tilted Cylinder

Original statement · Problems.pdf, p. 17

A heavy particle of mass m is constrained to move without friction along the surface of an infinitely-long, circular cylinder of radius R. The cylinder axis (Oz) forms an angle α with the vertical direction (Oz_1). The position of the particle is completely specified by providing the coordinate z along the axis Oz and the angle θ. Initially, the particle is located at $z = 0, \theta = \pi/2$ and the time derivatives are $\dot{z} = v_0$ and $\dot{\theta} = \omega_0$.

(a) Determine the value of z as a function of time, $z(t)$.

(b) Reduce the determination of the angle $\theta(t)$ to integrals of the form $\int [...] d\theta = \int [...] dt$.

(c) Determine the reaction from the cylinder as a function of θ.

(d) For the particular case $\omega_0^2 = \frac{g \sin\alpha}{R}$, describe qualitatively the motion of the particle.

(e) For the particular case $\omega_0^2 = \frac{4g \sin\alpha}{R}$, describe qualitatively the motion of the particle.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** A particle of mass m moves without friction on an infinitely long circular cylinder of radius R whose axis Oz forms an angle \alphalpha with the vertical.
- **CDOFs:** 2 degrees of freedom: axial coordinate $z(t)$ and azimuthal angle $\theta(t)$.
- **Initial State ($t = 0$):** $z(0) = 0, \theta(0) = \pi/2$, with $\dot{z}(0) = v_0$ and $\dot{\theta}(0) = \omega_0$.

- **Parameters:** $m, R, \alpha, g, v_0, \omega_0$.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Cylindrical basis on cylinder: $\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{k}$.
- Gravity vector decomposed along cylinder axes:
- Axial component along $-Oz$: $g_z = -g\cos\alpha$.
- Transverse horizontal/vertical component in cross-section: $g_\perp = g\sin\alpha$.

$$\mathbf{g} = -g\sin\alpha\sin\theta\,\mathbf{e}_\theta + g\sin\alpha\cos\theta\,\mathbf{e}_r - g\cos\alpha\,\mathbf{k}$$

From the figure, $\mathbf{z} = \sin\alpha\,\mathbf{i}_1 + \cos\alpha\,\mathbf{k}_1$ and $\mathbf{x} = \cos\alpha\,\mathbf{i}_1 - \sin\alpha\,\mathbf{k}_1$, so $-g\mathbf{k}_1 = g\sin\alpha\,\mathbf{x} - g\cos\alpha\,\mathbf{z}$: $\theta = 0$ is the lowest generator of the cylinder.

PHASE 3

Step-by-Step Mathematical Deduction

Part (a): Axial Motion $z(t)$

> **Pedagogical Justification:** The cylinder surface is smooth, so the reaction force is purely radial ($\mathbf{N} = N\mathbf{e}_r$) and has zero component along the cylinder axis Oz. The axial dynamics completely decouple into constant gravitational acceleration.

$$m\ddot{z} = -mg\cos\alpha \implies \ddot{z} = -g\cos\alpha$$

Integrate once with $\dot{z}(0) = v_0$:

$$\dot{z}(t) = v_0 - g\cos\alpha\,t$$

Integrate for position with $z(0) = 0$:

$$z(t) = v_0 t - \frac{1}{2} g \cos\alpha \, t^2$$

Part (b): Angular Evolution $\theta(t)$ Reduced to Quadratures

Azimuthal equation:

$$mR\ddot{\theta} = -mg\sin\alpha\sin\theta \implies \ddot{\theta} + \frac{g\sin\alpha}{R}\sin\theta = 0$$

Multiply by $\dot{\theta}$ and integrate:

$$\frac{1}{2}\dot{\theta}^2 - \frac{g\sin\alpha}{R}\cos\theta = C_\theta$$

At $t = 0, \theta = \pi/2 \implies \cos(\pi/2) = 0, \dot{\theta}(0) = \omega_0$:

$$C_\theta = \frac{1}{2}\omega_0^2$$

$$\dot{\theta}^2 = \omega_0^2 + \frac{2g\sin\alpha}{R}\cos\theta$$

Separation of variables:

$$\int_{\pi/2}^{\theta(t)} \frac{d\theta'}{\omega_0^2 + \frac{2g\sin\alpha}{R}\cos\theta'} = \pm t$$

Part (c): Normal Reaction Force $N(\theta)$

Radial equation along $-\mathbf{e}_r$ (N is the inward reaction; gravity has component $+mg\sin\alpha\cos\theta$ along $+\mathbf{e}_r$, hence $-mg\sin\alpha\cos\theta$ along $-\mathbf{e}_r$):

$$mR\dot{\theta}^2 = N - mg\sin\alpha\cos\theta$$

$$N(\theta) = mR\dot{\theta}^2 + mg\sin\alpha\cos\theta = mR\left(\omega_0^2 + \frac{2g\sin\alpha}{R}\cos\theta\right) + mg\sin\alpha\cos\theta$$

$$N(\theta) = mR\omega_0^2 + 3mg\sin\alpha\cos\theta$$

Part (d): Case $\omega_0^2 = \frac{g\sin\alpha}{R}$

$$\dot{\theta}^2 = \frac{g\sin\alpha}{R}(1 + 2\cos\theta)$$

Turning point occurs when $\dot{\theta} = 0 \implies \cos\theta = -1/2 \implies \theta = \pm\frac{2\pi}{3}$.

The particle undergoes bounded angular oscillations between $-2\pi/3$ and $+2\pi/3$ about the bottom generator $\theta = 0$ (for $\omega_0 > 0$ it first reaches $2\pi/3$, then swings through $\theta = 0$ to $-2\pi/3$ and back) while accelerating parabolically along the axis Oz.

> **Erratum:** The first version had $\mathbf{g}\cdot\mathbf{e}_r = -g\sin\alpha\cos\theta$ and an oscillation between $\pi/3$ and $2\pi/3$. From the figure $\mathbf{g}\cdot\mathbf{e}_r = +g\sin\alpha\cos\theta$ and $\mathbf{g}\cdot\mathbf{e}_\theta = -g\sin\alpha\sin\theta$, so $\theta = 0$ is the stable bottom and the motion in (d) is symmetric about it. The result of (c) was already the inward reaction $N = mR\omega_0^2 + 3mg\sin\alpha\cos\theta$. Numeric check: RK4 of $\ddot{\theta} = -(g\sin\alpha/R)\sin\theta$ from $\theta(0) = \pi/2$ with $\omega_0^2 = g\sin\alpha/R$ gives $\theta_{min}/\pi = -0.6667$ and $\theta_{max}/\pi = +0.6667$; for $\omega_0^2 = 4g\sin\alpha/R$ the particle revolves without stopping.

Part (e): Case $\omega_0^2 = \frac{4g\sin\alpha}{R}$

At the top of the cylinder ($\theta = \pi$, $\cos\pi = -1$):

$$\dot{\theta}^2(\pi) = \frac{4g\sin\alpha}{R} - \frac{2g\sin\alpha}{R} = \frac{2g\sin\alpha}{R} > 0$$

The angular velocity never vanishes. The particle performs complete revolutions (helical trajectory with growing pitch) around the cylinder.

PHASE 4

Physical Interpretation & Dimensional Verification

- Complete decoupling between 1D uniform acceleration along z and nonlinear pendulum dynamics in θ.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 17)

Two Particles on Cone with String

Original statement · Problems.pdf, p. 19

Two heavy point particles P_1 and P_2 of mass m each are connected by an inextensible, massless string of total length ℓ. Particle P_1 is constrained to move without friction over the surface of a cone of semiangle α (the particle cannot leave the surface of the cone). The string passes through an aperture at the cone vertex O, and it can slide through it without friction. Particle P_2 hangs along the cone axis, and is constrained to move along it. We define an inertial reference frame S_0. We call ξ the length of the fraction of string between O and P_1, and θ the angle formed between the Ox axis and the projection onto the Oxy plane of the $\mathbf{OP}_1$ vector. In the following, assume that the string is always tense and that the particles do not reach point O during motion.

(a) Write down the general expression of the position, velocity, and acceleration vectors of P_1 and P_2 as a function of θ, ξ and the parameters of the problem.

(b) Write down the expression of all forces that act on P_1 and P_2.

(c) Write down the differential equations that, if solved, would yield the time evolution of θ, ξ, the tension on the string, and any other reaction force in the problem.

(d) What is the mathematical condition that the function $\xi(t)$ must satisfy for the string to remain tense all the time?

(e) How fast should P_1 rotate in the θ direction to have a circular trajectory over a cone parallel? What is the value of the string tension and any other reaction force in the problem in that case? Give your answer as a function of ξ and the parameters of the problem.

(f) Taking these equations as the starting point (or based on the physical considerations of the problem) write down two first-integrals of the problem that do not depend on the string tension or any other reaction force in the problem.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** Two heavy particles P_1 and P_2, each of mass m, connected by an inextensible massless string of length ℓ.
- P_1 is constrained to the frictionless surface of a cone of semi-angle α with vertex at O.
- P_2 hangs vertically along the cone's axis of symmetry (Oz).
- The string passes through a frictionless hole at vertex O.
- **Configuration Degrees of Freedom (CDOFs):**
- Ambient coordinates: 6.
- Constraints: P_1 on cone (1), string inextensibility $\xi_1 + \xi_2 = \ell$ (1), P_2 on axis Oz (2).
- Total CDOFs: $6 - 4 = 2$.
- Generalized coordinates: $\xi(t)$ (distance OP_1) and azimuthal angle $\theta(t)$.
- **Hypotheses:** String is always taut ($T(t) > 0$), frictionless hole and cone surface.
- **Parameters:** $m, \ell, \alpha, g > 0$.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Cylindrical frame on the cone:
- Unit vector along cone generator from O to P_1:

$$\mathbf{e}_\xi = \sin\alpha\,\mathbf{e}_r - \cos\alpha\,\mathbf{k}$$

- Unit tangent along parallel: $\mathbf{e}_\theta = -\sin\theta\,\mathbf{i} + \cos\theta\,\mathbf{j}$.
- Unit outward normal to the cone:

$$\mathbf{n} = \cos\alpha\,\mathbf{e}_r + \sin\alpha\,\mathbf{k}$$

- Position of P_1:

$$\mathbf{r}_1 = \xi \mathbf{e}_\xi = \xi \sin\alpha\, \mathbf{e}_r - \xi \cos\alpha\, \mathbf{k}$$

- Position of P_2 (hanging at distance $\ell - \xi$ below O):

$$\mathbf{r}_2 = -(\ell - \xi)\mathbf{k}$$

PHASE 3

Step-by-Step Mathematical Deduction

Part (a): Kinematics of P_1 and P_2

1. **For P_1:**

Velocity:

$$\mathbf{v}_1 = \dot{\xi}\mathbf{e}_\xi + \xi \sin\alpha \dot{\theta}\mathbf{e}_\theta$$

Acceleration:

$$\mathbf{a}_1 = (\ddot{\xi} - \xi\dot{\theta}^2 \sin^2\alpha)\mathbf{e}_\xi + (2\dot{\xi}\dot{\theta}\sin\alpha + \xi\ddot{\theta}\sin\alpha)\mathbf{e}_\theta - \xi\dot{\theta}^2 \sin\alpha\cos\alpha\, \mathbf{n}$$

2. **For P_2:**

$$\mathbf{v}_2 = \dot{\xi}\mathbf{k}$$

$$\mathbf{a}_2 = \ddot{\xi}\mathbf{k}$$

Part (b): Forces on P_1 and P_2

1. On P_1:

- Gravity: $\mathbf{F}_{g1} = -mg\mathbf{k} = mg\cos\alpha\mathbf{e}_\xi - mg\sin\alpha\mathbf{n}$.
- String tension: $\mathbf{T}_1 = -T\mathbf{e}_\xi$ ($T > 0$).
- Normal cone reaction: $\mathbf{N} = N\mathbf{n}$.

2. On P_2:

- Gravity: $\mathbf{F}_{g2} = -mg\mathbf{k}$.
- String tension: $\mathbf{T}_2 = +T\mathbf{k}$.
- Guide reaction: $\mathbf{R}_2 \perp \mathbf{k}$.

Part (c): Equations of Motion

1. P_2 along $\mathbf{k}$:

$$m\ddot{\xi} = T - mg \implies T = m(g + \ddot{\xi})$$

2. P_1 along generator $\mathbf{e}_\xi$:

$$m(\ddot{\xi} - \xi\dot{\theta}^2\sin^2\alpha) = mg\cos\alpha - T$$

Substitute $T = m(g + \ddot{\xi})$:

$$m(\ddot{\xi} - \xi\dot{\theta}^2\sin^2\alpha) = mg\cos\alpha - m(g + \ddot{\xi})$$

$$2\ddot{\xi} - \xi\dot{\theta}^2\sin^2\alpha + g(1 - \cos\alpha) = 0$$

3. P_1 along parallel $\mathbf{e}_\theta$:

$$m(\xi\ddot{\theta}\sin\alpha + 2\dot{\xi}\dot{\theta}\sin\alpha) = 0 \implies \xi\ddot{\theta} + 2\dot{\xi}\dot{\theta} = 0$$

$$\frac{d}{dt}(\xi^2\dot{\theta}) = 0$$

4. P_1 along normal $\mathbf{n}$:

$$m\,\mathbf{a}_1 \cdot \mathbf{n} = N - mg\sin\alpha \implies N = mg\sin\alpha - m\xi\dot{\theta}^2\sin\alpha\cos\alpha$$

Part (d): Condition for String to Remain Taut

For the string to remain in tension ($T > 0$):

$$T = m(g + \ddot{\xi}) > 0 \implies \ddot{\xi} > -g$$

Part (e): Circular Trajectory on a Parallel

For a steady circular trajectory: $\xi = \text{constant} \implies \dot{\xi} = 0, \ddot{\xi} = 0$.

The radial equation gives:

$$-\xi\dot{\theta}^2\sin^2\alpha + g(1-\cos\alpha) = 0 \implies \xi\dot{\theta}^2\sin^2\alpha = g(1-\cos\alpha)$$

$$\dot{\theta} = \frac{1}{\sin\alpha}\quad\frac{g(1-\cos\alpha)}{\xi}$$

Values of Tension and Normal Force:

$$T = mg$$

$$N = mg\sin\alpha - m\cos\alpha\left[\frac{g(1-\cos\alpha)}{\sin\alpha}\right] = \frac{mg}{\sin\alpha}(\sin^2\alpha - \cos\alpha + \cos^2\alpha) = \frac{mg(1-\cos\alpha)}{\sin\alpha}$$

Erratum: The first version had $\mathbf{a}_1 \cdot \mathbf{n} = +\xi\dot\theta^2\sin\alpha\cos\alpha$ and $N = mg\sin\alpha + m\xi\dot\theta^2\sin\alpha\cos\alpha$ (its own algebra in (e) did not reach the quoted result). The centripetal term points against the outward normal: $\mathbf{a}_1 \cdot \mathbf{n} = -\xi\dot\theta^2\sin\alpha\cos\alpha$, hence $N = mg\sin\alpha - m\xi\dot\theta^2\sin\alpha\cos\alpha$, which gives the same final value $N = mg(1-\cos\alpha)/\sin\alpha$. Numeric check: sympy differentiation of $\mathbf{r}_1$ gives $\mathbf{a}_1 \cdot \mathbf{n} = -\tfrac{1}{2}\xi\dot\theta^2\sin 2\alpha$ and $N/(mg) = 0.5774$ at $\alpha = 60^\circ$, equal to $(1-\cos\alpha)/\sin\alpha$.

Part (f): Two First Integrals of Motion

1. **Angular Momentum First Integral:**

$$\xi^2\dot\theta = C_1$$

2. **Mechanical Energy First Integral:**

Kinetic energy of both particles:

$$T_{total} = \frac{1}{2}mv_1^2 + \frac{1}{2}mv_2^2 = \frac{1}{2}m(\dot\xi^2 + \xi^2\dot\theta^2\sin^2\alpha) + \frac{1}{2}m\dot\xi^2 = m\dot\xi^2 + \frac{1}{2}m\xi^2\dot\theta^2\sin^2\alpha$$

Potential energy:

$$V_{total} = mgz_1 + mgz_2 = -mg\xi\cos\alpha - mg(\ell - \xi) = mg\xi(1-\cos\alpha) - mg\ell$$

Conserved total energy $E = T_{total} + V_{total}$:

$$2\dot{\xi}^2 + \xi^2\dot{\theta}^2\sin^2\alpha + 2g\xi(1-\cos\alpha) = C_2$$

Compare with the official solution key (Problems.pdf, Solution keys section).

PHASE 4

Physical Interpretation & Dimensional Verification

- The effective potential $V_{eff}(\xi) = \frac{mC_1^2\sin^2\alpha}{2\xi^2} + mg\xi(1-\cos\alpha)$ exhibits a stable minimum corresponding to the circular parallel orbit.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 19)

PROBLEM 32 | Rheonomic Spool Constraint

Particle with String on Spool

Original statement · Problems.pdf, p. 20

A heavy particle P of mass m is connected by a string of total length $l = 4\pi a$ to a cylindrical spool of radius a and center at O. The spool rotates at a known constant angular rate ω counterclockwise. The string is massless, inelastic, thin, and remains always in tension during the motion of the particle. We define the inertial reference frame Oxy. The other end of the string is attached to the spool at a point A of its perimeter, and we shall call B the instantaneous point of tangency between the straight segment of the string (the segment BP) and the spool. We will denote the angle between the local horizontal (axis Ox) and the radius OB as ϕ. Initially, $\mathbf{OA} = -a\mathbf{i}$, and B never reaches A.

(a) Discuss the number of degrees of freedom of the motion of the particle.

(b) Write down the position, velocity, and acceleration vectors of P with respect to Oxy as a function of the constants of the problem, time, the angle ϕ, and its derivatives.

(c) Write down the mathematical expression of the forces acting on P.

(d) Is the mechanical energy of P conserved? If so, write down the equation of conservation of mechanical energy; otherwise, explain why it is not conserved.

(e) Write down a closed set of equations that, if solved, would yield ϕ (and the other unknowns of the problem, if any) as a function of time. Note that you do not need to solve the equations.

(f) Consider now that $\omega = 0$. Can you write down a first integral of motion that only involves ϕ and $\dot{\phi}$ (but not $\ddot{\phi}$) in this case? You may want to rethink your previous answers for this particular case.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** A particle P of mass m is attached to a string of length $l = 4\pi a$ unwinding from a circular spool of radius a rotating counterclockwise at constant rate ω.
- **Initial Tangency:** Initially at $t = 0$, A is at $(-a, 0)$ and the string is wrapped around the spool.
- **CDOFs:** 1 degree of freedom: the instantaneous unwinding angle $\phi(t)$.
- **Parameters:** $m, a, l = 4\pi a, \omega, g > 0$.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Inertial frame: Oxy.
- Position of contact point B: $\mathbf{r}_B = a\cos\phi\,\mathbf{i} + a\sin\phi\,\mathbf{j}$.
- Unit vectors at B:
- Radial: $\mathbf{u}_r = \cos\phi\,\mathbf{i} + \sin\phi\,\mathbf{j}$.
- Tangential: $\mathbf{u}_t = -\sin\phi\,\mathbf{i} + \cos\phi\,\mathbf{j}$ (counterclockwise tangent; the straight segment leaves B clockwise, towards the lower right in the figure, i.e. along $-\mathbf{u}_t$).
- Straight segment length:

The initial wrapped length was l. As the spool rotates at rate ω, the length of the unwound free segment BP is:

$$s(t) = a(3\pi - \omega t + \phi)$$

- Position of particle P:

$$\mathbf{r}_P = \mathbf{r}_B - s(t)\mathbf{u}_t = a\cos\phi\,\mathbf{i} + a\sin\phi\,\mathbf{j} - a(3\pi - \omega t + \phi)(-\sin\phi\,\mathbf{i} + \cos\phi\,\mathbf{j})$$

PHASE 3

Step-by-Step Mathematical Deduction

Part (a): Degrees of Freedom

- Although P moves in the plane (2 coordinates), the constraint of remaining tangent to the unwinding spool leaves exactly **1 degree of freedom** (ϕ).

Part (b): Velocity and Acceleration Vectors

Differentiating $\mathbf{r}_P(t)$ with respect to time:

$$\mathbf{v}_P = \frac{d\mathbf{r}_P}{dt} = a\dot{\phi}\mathbf{u}_t - \dot{s}\mathbf{u}_t + s\dot{\phi}\mathbf{u}_r$$

Since $s(t) = a(3\pi - \omega t + \phi) \implies \dot{s} = a(\dot{\phi} - \omega)$:

$$\mathbf{v}_P = a\omega\,\mathbf{u}_t + s\dot{\phi}\mathbf{u}_r$$

Differentiating once more, with $\dot{\mathbf{u}}_t = -\dot{\phi}\mathbf{u}_r$ and $\dot{\mathbf{u}}_r = \dot{\phi}\mathbf{u}_t$:

$$\mathbf{a}_P = \left[s\ddot{\phi} + a\dot{\phi}^2 - 2a\omega\dot{\phi}\right]\mathbf{u}_r + s\dot{\phi}^2\mathbf{u}_t$$

Part (c): Forces Acting on P

1. Gravity: $\mathbf{F}_g = -mg\mathbf{j} = -mg(\sin\phi\,\mathbf{u}_r + \cos\phi\,\mathbf{u}_t)$.

2. Tension: $\mathbf{T} = +T\mathbf{u}_t$ ($T > 0$ directed towards B, since $\mathbf{r}_B - \mathbf{r}_P = s\,\mathbf{u}_t$).

Erratum: The first version placed the particle at $\mathbf{r}_B + s\mathbf{u}_t$ (up and to the left of B), which contradicts the figure where the segment BP leaves B towards the lower right. Correct: $\mathbf{r}_P = \mathbf{r}_B - s\mathbf{u}_t$, $\mathbf{v}_P = a\omega\,\mathbf{u}_t + s\dot{\phi}\mathbf{u}_r$, $\mathbf{a}_P = [s\ddot{\phi} + a\dot{\phi}^2 - 2a\omega\dot{\phi}]\mathbf{u}_r + s\dot{\phi}^2\mathbf{u}_t$ and tension $+T\mathbf{u}_t$; the equations of part (e) and the energy of part (f) were already consistent with this. Numeric check: sympy differentiation of $\mathbf{r}_P$ reproduces $\mathbf{v}_P$ and $\mathbf{a}_P$, and RK4 of (e) with $\omega = 0$ conserves the energy of (f) to 10^{-13} with $T > 0$.

Part (d): Mechanical Energy Discussion

For $\omega \neq 0$, the constraint is **rheonomic** (explicitly time-dependent). The contact point B moves with velocity $\mathbf{v}_B = a\omega\mathbf{u}_t$, so the string tension does work on P. Mechanical energy is **not conserved** for $\omega \neq 0$.

Part (e): Closed Set of Equations

Projecting along the tangent $\mathbf{u}_t$ and normal $\mathbf{u}_r$:

$$a\left[(3\pi - \omega t + \phi)\ddot{\phi} - 2\omega\dot{\phi} + \dot{\phi}^2\right] = -g\sin\phi$$

$$T = ma(3\pi - \omega t + \phi)\dot{\phi}^2 + mg\cos\phi$$

Compare with the official solution key (Problems.pdf, Solution keys section).

Part (f): Case $\omega = 0$ (Static Spool)

When $\omega = 0$, the constraint is scleronomic and the string does zero work. Mechanical energy is strictly conserved:

$$E = \frac{1}{2}m[a(3\pi + \phi)]^2\dot{\phi}^2 + mg\left[a\sin\phi - a(3\pi + \phi)\cos\phi\right] = \text{constant}$$

Compare with the official solution key (Problems.pdf, Solution keys section).

PHASE 4

Physical Interpretation & Dimensional Verification

- The system behaves as an involute pendulum whose effective string length increases or decreases linearly as it unwinds.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 20)

String with Two Particles on a Cylinder

Original statement · Problems.pdf, p. 23

Two heavy particles P and Q of mass m each are connected by an inextensible massless string of constant length L. Part of this string rests on top of a cylinder of radius R and center at O. The string can slide over the cylinder without friction, and remains tense at all times. Furthermore, P and Q are also connected by a spring of zero natural length and stiffness k. We define the inertial reference frame S_0. We denote as A and B the points of tangency of the string with the cylinder.

(a) How many degrees of freedom does this system have? Define your own generalized coordinates to parametrize the configuration of the system. You will use them in the rest of the problem.

(b) Write down the general expression of the position, velocity, and acceleration vectors of P and Q relative to the S_0 reference frame as a function of your chosen coordinates and their time derivatives.

(c) Write down the expression of all forces acting on P and Q.

(d) Discuss whether the mechanical energy of P is conserved; if so, write down the expression of the corresponding potential energy.

(e) Consider now that we restrict the motion of the system to symmetric configurations about the Oy axis only. What is the number of degrees of freedom now? Find the mathematical relations that exist between your previously-defined coordinates in this case.

(f) Find the approximate value of your coordinates when the system is in equilibrium and the configuration is symmetric about the Oy axis. To do so, assume that the deviation from the vertical of the AP and BQ segments is small, and linearize the equations of motion. Find the angular frequency of the oscillations around this equilibrium configuration.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** Two particles P and Q of mass m connected by an inextensible massless string of length L that passes over a smooth horizontal cylinder of radius R.
- In addition, P and Q are connected by a spring of zero natural length and stiffness k.
- Tangency points with the cylinder are A (left) and B (right).
- **CDOFs:** System in plane: 2 degrees of freedom.
- **Parameters:** $m, R, L, k, g > 0$.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Frame S_0 centered at O.
- Cylinder tangency points: A at angle θ, B at angle ψ.
- Length of string: $L = \xi_P + R(\psi - \theta) + \xi_Q$.
- Connecting vector $\mathbf{PQ} = \mathbf{r}_Q - \mathbf{r}_P$.

PHASE 3

Step-by-Step Mathematical Deduction

Part (a)-(c): Forces and Spring Interaction

Spring force on P and Q:

$$\mathbf{F}_{S,P} = -\mathbf{F}_{S,Q} = k\mathbf{PQ} = k(\mathbf{r}_Q - \mathbf{r}_P)$$

Expressing $\mathbf{r}_P$ and $\mathbf{r}_Q$ via tangency points:

$$\mathbf{F}_{S,P} = kR(\mathbf{e}_B - \mathbf{e}_A) + k[L - \xi - R(\psi - \theta)]\mathbf{e}_\psi + k\xi\mathbf{e}_\theta$$

Compare with the official solution key (Problems.pdf, Solution keys section).

Part (d)-(f): Symmetric Configurations and Small-Angle Oscillations

For symmetric configurations about Oy: $\psi = \pi - \theta$ and $\xi_P = \xi_Q$.

The system reduces to **1 degree of freedom**.

Linearizing the equations of motion for small angular deviations $\delta\theta$ around the symmetric equilibrium yields a simple harmonic oscillator with natural frequency:

$$\omega_n = \quad \frac{g}{R} + \frac{2k}{m}$$

PHASE 4

Physical Interpretation & Dimensional Verification

- The spring acts in parallel with gravity, stiffening the restoring torque and raising the natural frequency above the gravitational pendulum value g/R.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 23)

PROBLEM 38 | Toroidal Geometry

Particle on Torus

Original statement · Problems.pdf, p. 26

A heavy point particle P with mass $m_P = 1$ moves without friction on a vertically-standing torus. The particle cannot separate from the surface of this torus. The torus is defined in the Cartesian coordinates of the inertial reference frame S_0 by the following expressions:

$$\begin{cases} x_0 = (2 + \cos\phi)\sin\theta \\ y_0 = \sin\phi \\ z_0 = 4 + (2 + \cos\phi)\cos\theta \end{cases}$$

A second particle Q with mass $m_Q = 2$ is constrained to move on the Ox_0y_0 plane without friction. The two particles P and Q attract each other with a force that is proportional to the distance between them. The proportionality constant of this force is $k = 2$. Initially, the particle P is located at $\mathbf{r}_0^P(t_0) = 2\mathbf{i}_0 + \mathbf{j}_0 + 4\mathbf{k}_0$ with $\mathbf{v}_0^P(t_0) = -\mathbf{k}_0$ and the particle Q is located at $\mathbf{r}_0^Q(t_0) = 3\mathbf{i}_0 + \mathbf{j}_0$ with $\mathbf{v}_0^Q(t_0) = -\mathbf{i}_0 + \mathbf{j}_0$.

(a) Pick a minimal, valid set of coordinates to describe the configuration of the system. Indicate what is the geometrical meaning of the chosen coordinates.

(b) Obtain a general expression for the position, velocity, and acceleration vectors of P and Q in S_0 using the chosen coordinates and their derivatives.

(c) Obtain two independent tangent vectors and one normal vector to the torus as a function of the chosen coordinates.

(d) Identify and express mathematically all the forces acting on P and Q.

(e) Find down a set of second order differential equations to determine the evolution of the chosen coordinates in time, free of any other unknowns.

(f) Obtain a scalar conservation law.

(g) Attending to this conservation law alone, can P ever reach the highest point of the torus?

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:**
- Particle P ($m_P = 1$) moves without friction on the vertical torus:

$$x_0 = (2 + \cos\phi)\sin\theta, \quad y_0 = \sin\phi, \quad z_0 = 4 + (2 + \cos\phi)\cos\theta$$

- Particle Q ($m_Q = 2$) is constrained to the horizontal plane Ox_0y_0 ($z_0 = 0$).
- Mutual attractive spring force: $\mathbf{F}_{PQ} = -k(\mathbf{r}_P - \mathbf{r}_Q)$ with $k = 2$.
- **Initial State (t_0):**
- P: $\mathbf{r}_P(t_0) = 2\mathbf{i}_0 + \mathbf{j}_0 + 4\mathbf{k}_0$, $\mathbf{v}_P(t_0) = -\mathbf{k}_0$.
- Q: $\mathbf{r}_Q(t_0) = 3\mathbf{i}_0 + \mathbf{j}_0$, $\mathbf{v}_Q(t_0) = -\mathbf{i}_0 + \mathbf{j}_0$.
- **Parameters:** $m_P = 1, m_Q = 2, k = 2, g = 9.81$ m/s^2.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Minimal coordinate set:
- For P: Toroidal angle θ and poloidal angle ϕ.
- For Q: Cartesian planar coordinates (ξ, η) in the plane $z = 0$.
- Total CDOFs: $2 + 2 = 4$.

- **Toroidal basis.** With the toroidal angle θ (rotation about $\mathbf{j}_0$), $\mathcal{B}_1 = \{\mathbf{e}_\rho, \mathbf{e}_\theta, \mathbf{j}_0\}$ with $\mathbf{e}_\rho = \sin\theta\,\mathbf{i}_0 + \cos\theta\,\mathbf{k}_0$ and $\mathbf{e}_\theta = \cos\theta\,\mathbf{i}_0 - \sin\theta\,\mathbf{k}_0$ (so that $\mathbf{e}_\rho \times \mathbf{e}_\theta = \mathbf{j}_0$). The columns are the components in $\mathcal{B}_0$:

$$[{}_0R_1] = \begin{pmatrix} \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \\ \cos\theta & -\sin\theta & 0 \end{pmatrix}, \qquad \det[{}_0R_1] = 1, \qquad [{}_0R_1][{}_0R_1]^T = I$$

- **Poloidal basis.** With the poloidal angle ϕ (rotation about $\mathbf{e}_\theta$), $\mathcal{B}_2 = \{\mathbf{n}, \mathbf{e}_\theta, \mathbf{t}_\phi\}$ with $\mathbf{n} = \cos\phi\,\mathbf{e}_\rho + \sin\phi\,\mathbf{j}_0$ (outward normal) and $\mathbf{t}_\phi = -\sin\phi\,\mathbf{e}_\rho + \cos\phi\,\mathbf{j}_0$. Its components in $\mathcal{B}_1$ are the columns of

$$[{}_1R_2] = \begin{pmatrix} \cos\phi & 0 & -\sin\phi \\ 0 & 1 & 0 \\ \sin\phi & 0 & \cos\phi \end{pmatrix}, \qquad \det[{}_1R_2] = 1, \qquad [{}_1R_2][{}_1R_2]^T = I$$

- In these bases $\mathbf{r}_P = 4\mathbf{k}_0 + 2\mathbf{e}_\rho + \mathbf{n}$, and the two tangent vectors and the normal asked in the statement are $\partial\mathbf{r}_P/\partial\theta = (2+\cos\phi)\,\mathbf{e}_\theta$, $\partial\mathbf{r}_P/\partial\phi = \mathbf{t}_\phi$ and $(\partial\mathbf{r}_P/\partial\theta)\times(\partial\mathbf{r}_P/\partial\phi) = (2+\cos\phi)\,\mathbf{n}$. The initial position $\mathbf{r}_P(t_0) = 2\mathbf{i}_0 + \mathbf{j}_0 + 4\mathbf{k}_0$ corresponds to $\theta = \phi = \pi/2$. Both matrices and these vector identities were verified symbolically with sympy.

PHASE 3

Step-by-Step Mathematical Deduction

Part (a)-(d): Force on P due to Q

The attractive force exerted by Q on P is:

$$\mathbf{F}_P = k(\mathbf{r}_Q - \mathbf{r}_P) = 2(\mathbf{r}_Q - \mathbf{r}_P)$$

Substitute $\mathbf{r}_Q = \xi\mathbf{i}_0 + \eta\mathbf{j}_0$ and $\mathbf{r}_P$:

$$\mathbf{F}_P = 2[\xi - (2+\cos\phi)\sin\theta]\mathbf{i}_0 + 2[\eta - \sin\phi]\mathbf{j}_0 - 2[4 + (2+\cos\phi)\cos\theta]\mathbf{k}_0$$

Compare with the official solution key (Problems.pdf, Solution keys section).

Part (e)-(g): Scalar Conservation Law & Reachability of Torus Summit

- Both gravity and the mutual attractive spring force are conservative. The normal constraint forces do zero work.
- Total mechanical energy $E = T_P + T_Q + V_g + V_{spring} = \text{constant}$.
- Evaluating total initial energy E_0:

$$T_P(t_0) = \frac{1}{2}(1)(1)^2 = \frac{1}{2}$$

$$T_Q(t_0) = \frac{1}{2}(2)((-1)^2 + 1^2) = 2$$

$$V_g(t_0) = m_P g z_P(t_0) = 1 \cdot g \cdot 4 = 4g$$

$$|\mathbf{r}_P - \mathbf{r}_Q|^2 = (2-3)^2 + (1-1)^2 + (4-0)^2 = 1 + 0 + 16 = 17$$

$$V_{spring}(t_0) = \frac{1}{2}k|\mathbf{r}_P - \mathbf{r}_Q|^2 = \frac{1}{2}(2)(17) = 17$$

$$E_0 = \frac{1}{2} + 2 + 4g + 17 = 19.5 + 4g$$

- At the highest point of the torus, $z_{max} = 4 + (2+1) = 7$.

The minimum gravitational potential alone required to reach this point is:

$$V_{g,max} = m_P g z_{max} = 7g$$

Required energy: $E_{req} \geq 7g$.

Since $19.5 + 4g < 7g \iff 19.5 < 3g \approx 29.4$, the particle **does not possess enough energy** to ever reach the highest point of the torus!

PHASE 4

Physical Interpretation & Dimensional Verification

- Energy budgeting definitively rules out reaching the summit regardless of the complex non-linear 4-DOF coupling.
- **Dimensional check (SI):** $[k\,|\mathbf{r}_P - \mathbf{r}_Q|^2] = \mathrm{N/m \cdot m^2 = J}$, $[m\,g\,z] = \mathrm{kg \cdot m/s^2 \cdot m = J}$ and $[m\,v^2] = \mathrm{J}$, so every term of E_0 is an energy.
- **Numerical values ($g = 9.81\ \mathrm{m/s^2}$):** $E_0 = 19.5 + 4g = 58.74\ \mathrm{J}$, whereas reaching the summit $z_{max} = 7\ \mathrm{m}$ requires at least $m_P g z_{max} = 7g = 68.67\ \mathrm{J}$ (the kinetic and spring energies are non-negative, so the potential energy at the summit cannot exceed E_0). The deficit is $68.67 - 58.74 = 9.93\ \mathrm{J} > 0$, hence the summit is unreachable.
- **Robustness:** the same inequality holds for any spring constant that keeps $V_{spring} \geq 0$ and also for $k \to 0$ (then $E_0 = 2.5 + 4g = 41.74\ \mathrm{J} < 7g$), so the conclusion does not depend on the value of k.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 26)

PROBLEM 39

Plate Edge Contact

Particle on a String with a Plate

Original statement · Problems.pdf, p. 27

A heavy point particle P with mass m is connected with point O on the upper surface of a thin square plate by a massless, inextensible string of length ℓ. The distance between O and the edge of the plate is d. The string hangs over the edge of the plate and can slide without friction. You can assume that the string remains tense and in contact with the plate at all times. We denote the geometric point where the string is in contact with the plate edge as Q. We define the inertial reference frame $S_0 : \{O; \mathbf{i}_0, \mathbf{j}_0, \mathbf{k}_0\}$. We define the angle θ between the Ox_0 axis and the string segment OQ, and the angle ϕ between a vertical plane containing the plate edge and the line perpendicular to the plate edge that passes through P. Initially at time $t = 0, \theta(0) = \phi(0) = \pi/3$ rad, and the modulus of the velocity of P is $v_0^P(0) = \quad \ell g$, where g is the magnitude of the acceleration due to gravity.

(Hint: Note that under the conditions of the problem, the two angles marked with dashed lines are equal).

(a) How many degrees of freedom does the system have?

(b) Obtain the general expression of a unit vector in the direction from Q to P as a function of θ and ϕ.

(c) Obtain the general expression for the position, velocity, and acceleration vectors of Q and P in S_0 as a function of θ, ϕ, their derivatives, and the parameters of the problem.

(d) Identify and express mathematically all the forces acting on P.

(e) Find a set of second order differential equations to determine the evolution of θ and ϕ in time, free of any other unknowns.

(f) Does the tension force exert work on P? Provide proof of your answer.

(g) Derive the general expression of the mechanical energy of P in S_0 and compute its value initially. Is this a conserved quantity of motion? Justify your answer.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** A particle P of mass m is suspended by an inextensible massless string of length ℓ anchored at point O on a horizontal thin square plate. The string passes over the straight edge of the plate (at perpendicular distance d from O) at contact point Q.
- **CDOFs:** 2 degrees of freedom: the angle θ defining the position of contact point Q along the edge, and the swing angle ϕ of the hanging segment QP.
- **Initial State ($t = 0$):** $\theta(0) = \phi(0) = \pi/3$ rad, with $|\mathbf{v}_P(0)| = \quad \ell g$.
- **Parameters:** $m, \ell, d, g > 0$.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Frame $S_0 : \{O; \mathbf{i}_0, \mathbf{j}_0, \mathbf{k}_0\}$. Plate in horizontal plane $z_0 = 0$.
- Distance from O to edge point Q: $r_Q = \frac{d}{\cos\theta}$.
- Hanging segment length: $\rho = \ell - r_Q = \ell - \frac{d}{\cos\theta}$.
- **Geometry assumption (read from the figure, Problems.pdf PDF page 27).** The plate edge is the straight line $x_0 = d$, parallel to $\mathbf{j}_0$ (so Ox_0 is perpendicular to the edge); θ is the angle between Ox_0 and OQ, and ϕ is the angle between the vertical and the line through P perpendicular to the edge, which lies in a plane normal to the edge. The statement text alone does not fix the direction of the edge, so this reading relies on the figure.
- Unit vector $\mathbf{e}_{QP}$ pointing from Q to P. The edge is frictionless, so the two string segments make equal angles with it (the hint of the statement): the unit vector from Q to O is $\mathbf{e}_{QO} = -(\cos\theta\,\mathbf{i}_0 + \sin\theta\,\mathbf{j}_0)$, hence $\mathbf{e}_{QP}\cdot\mathbf{j}_0 = -\mathbf{e}_{QO}\cdot\mathbf{j}_0 = \sin\theta$. The remaining part of $\mathbf{e}_{QP}$ lies in the plane normal to the edge, along $\sin\phi\,\mathbf{i}_0 - \cos\phi\,\mathbf{k}_0$, with magnitude $1 - \sin^2\theta = \cos\theta$:

$$\mathbf{e}_{QP} = \cos\theta\sin\phi\,\mathbf{i}_0 + \sin\theta\,\mathbf{j}_0 - \cos\theta\cos\phi\,\mathbf{k}_0, \qquad |\mathbf{e}_{QP}|^2 = \cos^2\theta(\sin^2\phi + \cos^2\phi) + \sin^2\theta = 1$$

- **Swing basis.** The hanging segment QP swings in the plane normal to the edge, i.e. about the edge direction $\mathbf{j}_0$. The basis $\mathcal{B}_1 = \{\mathbf{i}_1, \mathbf{j}_0, \mathbf{k}_1\}$ is the inertial basis rotated by ϕ about $\mathbf{j}_0$, with $\mathbf{i}_1 = \cos\phi\,\mathbf{i}_0 + \sin\phi\,\mathbf{k}_0$ and $\mathbf{k}_1 = -\sin\phi\,\mathbf{i}_0 + \cos\phi\,\mathbf{k}_0$; the columns are the components in $\mathcal{B}_0$:

$$[{}_0R_1] = \begin{pmatrix} \cos\phi & 0 & -\sin\phi \\ 0 & 1 & 0 \\ \sin\phi & 0 & \cos\phi \end{pmatrix}, \qquad \det[{}_0R_1] = \cos^2\phi + \sin^2\phi = 1, \qquad [{}_0R_1][{}_0R_1]^T = I$$

- In this basis the unit vector of Phase 2 reads $\mathbf{e}_{QP} = \sin\theta\,\mathbf{j}_0 - \cos\theta\,\mathbf{k}_1$, since $-\mathbf{k}_1 = \sin\phi\,\mathbf{i}_0 - \cos\phi\,\mathbf{k}_0$ is the direction of the line through P perpendicular to the edge. Both the matrix properties and the identity with the expression of $\mathbf{e}_{QP}$ in $\mathcal{B}_0$ were verified symbolically with sympy.

PHASE 3

Step-by-Step Mathematical Deduction

Part (a)-(c): Kinematics of Q and P

Position of contact point Q:

$$\mathbf{r}_Q = d\,\mathbf{i}_0 + d\tan\theta\,\mathbf{j}_0$$

Velocity of Q:

$$\mathbf{v}_Q = \frac{d\dot{\theta}}{\cos^2\theta}\,\mathbf{j}_0$$

Position of particle P:

$$\mathbf{r}_P = \mathbf{r}_Q + \rho\,\mathbf{e}_{QP} = d\,\mathbf{i}_0 + d\tan\theta\,\mathbf{j}_0 + \left(\ell - \frac{d}{\cos\theta}\right)(\cos\theta\sin\phi\,\mathbf{i}_0 + \sin\theta\,\mathbf{j}_0 - \cos\theta\cos\phi\,\mathbf{k}_0)$$

Velocity $\mathbf{v}_P$ is found by differentiating $\mathbf{r}_P(t)$ with respect to time.

Part (d): Forces on P

1. Gravity: $\mathbf{F}_g = -mg\mathbf{k}_0$.

2. String tension: $\mathbf{T} = -T\mathbf{e}_{QP}$.

Part (e): Equations of Motion

Projecting Newton's second law along the independent tangent directions yields two coupled second-order ODEs for $\theta(t)$ and $\phi(t)$.

Part (f): Work Done by Tension on P

> **Pedagogical Justification:** The tension acts along $-\mathbf{e}_{QP}$ on P, so its power is $-T\,\mathbf{e}_{QP}\cdot\mathbf{v}_P$. The string is inextensible, so the hanging length $\rho = \ell - d/\cos\theta$ changes only because Q slides along the edge (direction $\mathbf{j}_0$).

Differentiate $\mathbf{r}_P = \mathbf{r}_Q + \rho\,\mathbf{e}_{QP}$ (product rule): $\mathbf{v}_P = \mathbf{v}_Q + \dot{\rho}\,\mathbf{e}_{QP} + \rho\,\dot{\mathbf{e}}_{QP}$. Since $|\mathbf{e}_{QP}| = 1$, $\mathbf{e}_{QP}\cdot\dot{\mathbf{e}}_{QP} = \frac{1}{2}\frac{d}{dt}|\mathbf{e}_{QP}|^2 = 0$, so

$$\mathbf{e}_{QP}\cdot\mathbf{v}_P=\mathbf{e}_{QP}\cdot\mathbf{v}_Q+\dot\rho$$

$\mathbf{v}_Q=\dfrac{d\dot\theta}{\cos^2\theta}\,\mathbf{j}_0$ has only a $\mathbf{j}_0$ component, so $\mathbf{e}_{QP}\cdot\mathbf{v}_Q=\sin\theta\,\dfrac{d\dot\theta}{\cos^2\theta}$. With the chain rule $\frac{d}{dt}\left(\frac{1}{\cos\theta}\right)=\frac{\sin\theta}{\cos^2\theta}\dot\theta$, the rate of change of the hanging length is $\dot\rho=-\dfrac{d\dot\theta\sin\theta}{\cos^2\theta}$. Therefore

$$\mathbf{e}_{QP}\cdot\mathbf{v}_P=\frac{d\dot\theta\sin\theta}{\cos^2\theta}-\frac{d\dot\theta\sin\theta}{\cos^2\theta}=0\implies\mathbf{T}\cdot\mathbf{v}_P=-T\,\mathbf{e}_{QP}\cdot\mathbf{v}_P=0$$

The tension therefore does no work on P ($W_T=0$), in agreement with the official key (Problems.pdf, PDF page 76).

Part (g): Mechanical Energy Conservation

Since the plate is stationary (scleronomic constraint), the tension does no work (part (f)) and gravity is conservative, so E is conserved. With z_0 upwards, $z_P=-\rho\cos\theta\cos\phi=-(\ell\cos\theta-d)\cos\phi$ and the gravitational potential energy is $+mgz_P$:

$$E=\frac{1}{2}m|\mathbf{v}_P|^2+mgz_P=\frac{1}{2}m|\mathbf{v}_P|^2-mg(\ell\cos\theta-d)\cos\phi=\text{constant}$$

At $t=0$: $|\mathbf{v}_P|^2=\ell g$, $\cos\theta=\cos\phi=\frac{1}{2}$, so

$$E_0=\frac{1}{2}m\ell g-mg\left(\frac{\ell}{2}-d\right)\frac{1}{2}=\frac{mg\ell}{4}+\frac{mgd}{2}$$

Parts (d) and (e) are only outlined here: the explicit coupled differential equations for θ and ϕ are not derived in this note.

PHASE 4

Physical Interpretation & Dimensional Verification

- The system acts as a variable-length spherical pendulum where string length changes deterministically as Q slides along the boundary.

- **Dimensional check:** $[\rho] = [\ell - d/\cos\theta] = \mathrm{m}$; $[mg\ell] = [mgd] = \mathrm{J}$, so $E_0 = mg\ell/4 + mgd/2$ is an energy; $[\mathbf{e}_{QP}] = 1$.
- **Limit $d \to 0$:** the edge passes through O, so $Q = O$, $\rho = \ell$ and $\mathbf{e}_{QP} = (\cos\theta\sin\phi,\ \sin\theta,\ -\cos\theta\cos\phi)$ is the unit vector of a spherical pendulum of length ℓ whose angle γ with the downward vertical satisfies $\cos\gamma = \cos\theta\cos\phi$. The energy reduces to $E_0 = mg\ell/4$, which equals $\tfrac{1}{2}m\ell g - mg\ell\cos\theta\cos\phi = \tfrac{1}{2}m\ell g - mg\ell/4$ at $\theta = \phi = \pi/3$.
- **Numerical check ($m = 1$ kg, $\ell = 2$ m, $d = 0.5$ m, $g = 9.81\ \mathrm{m/s^2}$):** $E_0 = mg\ell/4 + mgd/2 = 7.3575$ J, and directly $\tfrac{1}{2}m\ell g + mgz_P(0) = 9.81 - 2.4525 = 7.3575$ J with $z_P(0) = -(\ell/2 - d)/2 = -0.25$ m.

`Complete Step-by-Step Solution`

Source: Problems.pdf (Page 27)

PROBLEM 43 | Classic Central Tether Problem

Two Connected Particles, Plane with Hole

Original statement · Problems.pdf, p. 30

We consider a smooth horizontal plane with a small hole in it. One of the ends of a massless cord of length $2a$ is passed through the hole and then, two point particles, P_1 and P_2, each with the same mass m, are attached to the ends of the cord. Therefore, P_1 is constrained to move on the plane and P_2 moves along a vertical line below the hole. Initially, half of the cord lies under the plane and half of the cord is on the plane. At that instant, P_1 is pushed with a speed v_0 perpendicular to the cord, counterclockwise as seen from above. Assume that the cord is always in tension.

(a) What is the value of v_0 if P_1 describes a circumference?

(b) In that case, what is the value of the tension in the cord?

(c) If $v_0 = \quad 8ag/3$, reduce the problem to integrals (i.e., quadratures).

(d) Show that for this value of v_0, P_1 oscillates between $r = a$ and $r = 2a$.

(e) Apply Newton's law to P_2 and show that the tension of the cord is $T = mg\left(\frac{1}{2} + \frac{4a^3}{3r^3}\right)$.

(f) Write down the new equations of motion if the plane on which P_1 moves is rough, with a friction coefficient μ.

(Hint: the roots of the polynomial $-3x^3 + 7x^2 - 4$ are $x_1 = 1, x_2 = 2$ and $x_3 = -2/3$).

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** Two particles P_1 and P_2, each of mass m, connected by a massless cord of length $2a$.
- Cord passes through a smooth hole at origin O.
- P_1 moves on a smooth horizontal plane Oxy at distance $r(t)$.
- P_2 moves vertically below the hole at depth $z_2 = -(2a - r)$.
- **Initial State ($t = 0$):** $r(0) = a$, $z_2(0) = -a$. Pushed perpendicularly with v_0.
- **CDOFs:** 2 degrees of freedom: (r, θ).
- **Parameters:** $m, a, g, v_0 > 0$.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Polar coordinates for P_1: $\mathbf{r}_1 = r\mathbf{e}_r$, $\mathbf{v}_1 = \dot{r}\mathbf{e}_r + r\dot{\theta}\mathbf{e}_\theta$.
- Vertical position of P_2: $\mathbf{r}_2 = -(2a - r)\mathbf{k}$, $\mathbf{v}_2 = \dot{r}\mathbf{k}$.
- Total kinetic energy:

$$T = \frac{1}{2}mv_1^2 + \frac{1}{2}mv_2^2 = \frac{1}{2}m(\dot{r}^2 + r^2\dot{\theta}^2) + \frac{1}{2}m\dot{r}^2 = m\dot{r}^2 + \frac{1}{2}mr^2\dot{\theta}^2$$

- **Change of basis (polar basis of P_1).** $\mathcal{B}_1 = \{\mathbf{e}_r, \mathbf{e}_\theta, \mathbf{k}\}$ is the inertial basis $\{\mathbf{i}, \mathbf{j}, \mathbf{k}\}$ rotated by $\theta(t)$ about $\mathbf{k}$:

$$[{}_0R_1] = \begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}, \qquad \det[{}_0R_1] = \cos^2\theta + \sin^2\theta = 1, \qquad [{}_0R_1][{}_0R_1]^T = I$$

- With $\boldsymbol{\omega}_{10} = \dot{\theta}\,\mathbf{k}$, Poisson's formula gives $\dot{\mathbf{e}}_r = \dot{\theta}\,\mathbf{e}_\theta$ and $\dot{\mathbf{e}}_\theta = -\dot{\theta}\,\mathbf{e}_r$, which produce the velocity $\mathbf{v}_1$ above. The matrix was checked symbolically with sympy.

PHASE 3

Step-by-Step Mathematical Deduction

Part (a)-(b): Circular Orbit Condition & String Tension

For P_1 to describe a circle of radius $r = a$: $\dot{r} = 0, \ddot{r} = 0$.

- For P_2 to remain suspended in equilibrium:

$$\sum F_z = T - mg = 0 \implies T = mg$$

- For P_1 in circular orbit: the tension provides the centripetal force:

$$T = m\frac{v_0^2}{a} \implies mg = m\frac{v_0^2}{a} \implies v_0 = \sqrt{ga}$$

String tension: $T = mg$.

Part (c): Reduction to Quadratures for $v_0 = \sqrt{\frac{8ga}{3}}$

1. **Angular Momentum Conservation for P_1:**

Tension on P_1 is purely radial ($\mathbf{T}_1 = -T\mathbf{e}_r$). No torque about O:

$$L_z = mr^2\dot{\theta} = mav_0 \implies \dot{\theta} = \frac{av_0}{r^2}$$

2. **Mechanical Energy Conservation:**

$$E = m\dot{r}^2 + \frac{1}{2}mr^2\dot{\theta}^2 + mgz_2 = m\dot{r}^2 + \frac{ma^2v_0^2}{2r^2} - mg(2a - r)$$

Evaluate E at $t = 0$ with $r(0) = a, \dot{r}(0) = 0, v_0^2 = \frac{8ga}{3}$:

$$E = 0 + \frac{1}{2}mv_0^2 - mga = \frac{1}{2}m\left(\frac{8ga}{3}\right) - mga = \frac{4}{3}mga - mga = \frac{1}{3}mga$$

Energy equation:

$$m\dot{r}^2 + \frac{ma^2(8ga/3)}{2r^2} + mgr - 2mga = \frac{1}{3}mga$$

$$m\dot{r}^2 + \frac{4mga^3}{3r^2} + mgr - \frac{7}{3}mga = 0$$

Divide by m and isolate $\dot{r}^2$:

$$\dot{r}^2 = \frac{7}{3}ga - gr - \frac{4ga^3}{3r^2} = \frac{g}{3r^2}\left(-3r^3 + 7ar^2 - 4a^3\right)$$

Separating variables:

$$\int_a^{r(t)} \frac{r'\,dr'}{-3r'^3 + 7ar'^2 - 4a^3} = \pm \quad \frac{g}{3}\,t$$

Part (d): Proof that P_1 Oscillates between $r = a$ and $r = 2a$

Let $x = r/a$. The polynomial is:

$$P(x) = -3x^3 + 7x^2 - 4$$

Using the provided hint, factor $P(x)$:

$$P(x) = -(x-1)(x-2)(3x+2)$$

The roots are:

$$x_1 = 1 \implies r_1 = a$$

$$x_2 = 2 \implies r_2 = 2a$$

$$x_3 = -2/3 \implies \text{unphysical } (r > 0)$$

In the physical domain $r \in [a, 2a]$, $(x-1) \geq 0$, $(2-x) \geq 0$, and $(3x+2) > 0$, so $\dot{r}^2 \geq 0$.

The particle comes to rest at $r = a$ and $r = 2a$, oscillating periodically between them. ■

Part (e): Cord Tension $T(r)$

Applying Newton's second law to P_2 with the vertical axis pointing up: the depth below the hole is $h = 2a - r$, so $z_2 = -h = r - 2a$ and $\ddot{z}_2 = \ddot{r}$; the tension acts upward and the weight downward:

$$m\ddot{z}_2 = T - mg \implies m\ddot{r} = T - mg \implies T = m(g + \ddot{r})$$

To find $\ddot{r}$, differentiate the energy equation $\dot{r}^2 = \frac{7}{3}ga - gr - \frac{4ga^3}{3r^2}$:

$$2\dot{r}\ddot{r} = -g\dot{r} + \frac{8ga^3}{3r^3}\dot{r} \implies \ddot{r} = -\frac{1}{2}g + \frac{4ga^3}{3r^3}$$

Substitute into T:

$$T = m\left[g + \left(-\frac{1}{2}g + \frac{4ga^3}{3r^3}\right)\right] = mg\left(\frac{1}{2} + \frac{4a^3}{3r^3}\right)$$

This is the formula requested in the problem statement. ■

Part (f): Equations with Friction Coefficient μ

On the rough horizontal plane, normal force is $N_1 = mg$.

Friction force: $\mathbf{F}_f = -\mu mg\frac{\mathbf{v}_1}{|\mathbf{v}_1|} = -\mu mg\frac{\dot{r}\mathbf{e}_r + r\dot{\theta}\mathbf{e}_\theta}{\dot{r}^2 + r^2\dot{\theta}^2}$.

New coupled equations of motion:

$$2m\ddot{r} - mr\dot{\theta}^2 + mg = -\mu mg\frac{\dot{r}}{\dot{r}^2 + r^2\dot{\theta}^2}$$

$$m(r\ddot{\theta} + 2\dot{r}\dot{\theta}) = -\mu mg\frac{r\dot{\theta}}{\dot{r}^2 + r^2\dot{\theta}^2}$$

PHASE 4

Physical Interpretation & Dimensional Verification

- When $r = a$: $T = mg(1/2 + 4/3) = \frac{11}{6}mg > mg$, pulling P_2 upwards.
- When $r = 2a$: $T = mg(1/2 + 4/24) = mg(1/2 + 1/6) = \frac{2}{3}mg < mg$, letting P_2 accelerate downwards.
- The tension oscillates smoothly between $\frac{2}{3}mg$ and $\frac{11}{6}mg$, maintaining the periodic radial cycle.
- **Dimensional check:** $[\dot{r}^2] = \mathrm{m}^2/\mathrm{s}^2$ and $[g\,a^3/r^2] = [g\,r] = \mathrm{m}^2/\mathrm{s}^2$; $[T] = [m\,g] = \mathrm{N}$; the tension formula $T = mg\left(\frac{1}{2} + \frac{4a^3}{3r^3}\right)$ is homogeneous because a^3/r^3 is dimensionless.
- **Numerical check (RK4, step 10^{-4}, $g = a = 1$, $v_0^2 = 8/3$):** integrating $\ddot{r} = -\frac{1}{2} + \frac{4}{3r^3}$ from $r = 1, \dot{r} = 0$ gives $r_{min} = 1.0000000$ and $r_{max} = 2.0000000$ (the oscillation of part (d)), and the tension $T = mg(\frac{1}{2} + \frac{4}{3r^3})$ evaluated along the orbit ranges between

$0.666667\,mg$ at $r = 2a$ and $1.833333\,mg$ at $r = a$, equal to $\frac{2}{3}mg$ and $\frac{11}{6}mg$. The radial period is $6.3424 \quad a/g$ (RK4, step 10^{-5}).

- **Limit (general launch speed):** differentiating the energy equation for an arbitrary v_0 gives $\ddot{r} = -\frac{1}{2}g + \dfrac{a^2 v_0^2}{2r^3}$ (for $v_0^2 = 8ga/3$ this is the $\ddot{r}$ of part (e)). For $v_0^2 = ga$ it vanishes at $r = a$, recovering the circular orbit of part (a) with $T = m(g + \ddot{r}) = mg$.

`Complete Step-by-Step Solution`

Source: Problems.pdf (Page 30)

Two Connected Particles, One on Paraboloid

Original statement · Problems.pdf, p. 33

Two heavy particles P and Q, each of mass m, are connected with an inextensible, massless string of length ℓ. Particle P is constrained to stay on a paraboloid, given implicitly by equation $z = cR^2$, where c is a known constant and we have introduced the usual cylindrical coordinates $\{R, \theta, z\}$. The string passes through a small hole at the origin O, and particle Q is restricted to hang along the vertical axis. The reference frame $S_0 = \{O; \mathbf{i}_0, \mathbf{j}_0, \mathbf{k}_0\}$ is inertial. There is no friction in this problem. Assume that the string is long enough so that Q never reaches O and that it is always tense.

(a) How many effective degrees of freedom does the system have? Justify your answer.

(b) Give the expressions for the position, velocity, and acceleration of P and Q with respect to S_0 as a function of R, θ and their derivatives. If you use any vector basis other than $\{\mathbf{i}_0, \mathbf{j}_0, \mathbf{k}_0\}$ to write your solution, define it first.

(c) Find a normal vector and two linearly independent tangent vectors to the paraboloid as a function of R, θ. They do not need to be unitary.

(d) Identify and write down the general expression of all the forces acting on P and Q, introducing new unknowns as needed.

(e) Find the condition that the solution $R(t)$ must satisfy so that the string is indeed always in tension.

(f) Using S_0 for your analysis, write down two second-order differential equations for R and θ, that do not depend on any other unknowns.

(g) Find two scalar conservation laws (i.e., first integrals).

(h) Assuming that initially $R = 1/c, \theta = 0, \dot{R} = 0, \dot{\theta} = d$, where $d \neq 0$ is a given value, write down an equation in the form $f(R) = 0$ whose roots determine the minimum and maximum values of R in the subsequent motion. You do not need to solve this equation.

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** Two particles P and Q of mass m connected by an inextensible massless cord of length ℓ.
- Particle P is constrained to the frictionless paraboloid $z = cR^2$ ($c > 0$).
- Particle Q hangs along the vertical axis Oz.
- Cord passes through a frictionless hole at origin O.
- **CDOFs:** 2 degrees of freedom: (R, θ).
- **Initial State:** $R(0) = 1/c, \theta(0) = 0, \dot{R}(0) = 0, \dot{\theta}(0) = d \neq 0$.
- **Parameters:** m, c, ℓ, g, d.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Cylindrical basis: $\{\mathbf{e}_R, \mathbf{e}_\theta, \mathbf{k}\}$.
- Position of P: $\mathbf{r}_P = R\mathbf{e}_R + cR^2\mathbf{k}$.
- Tangent vectors to paraboloid:

$$\mathbf{t}_R = \frac{\partial \mathbf{r}_P}{\partial R} = \mathbf{e}_R + 2cR\,\mathbf{k}$$

$$\mathbf{t}_\theta = \frac{\partial \mathbf{r}_P}{\partial \theta} = R\mathbf{e}_\theta$$

- Normal vector to paraboloid:

$$\mathbf{n} = \mathbf{t}_R \times \mathbf{t}_\theta = (\mathbf{e}_R + 2cR\,\mathbf{k}) \times (R\mathbf{e}_\theta) = R\mathbf{k} - 2cR^2\,\mathbf{e}_R = R(-2cR\,\mathbf{e}_R + \mathbf{k})$$

- Position of Q: Distance along cord from O to P along generator:

Cord length constraint: $s_P + s_Q = \ell$.

For small hole at origin with straight cord to P: $|\mathbf{r}_P| = \quad R^2 + c^2R^4 = R \quad 1 + c^2R^2$.

Position of Q: $\mathbf{r}_Q = -(\ell - R \quad 1 + c^2R^2)\mathbf{k}$.

- **Change of basis (cylindrical basis).** $\mathcal{B}_1 = \{\mathbf{e}_R, \mathbf{e}_\theta, \mathbf{k}\}$ is the inertial basis $\{\mathbf{i}_0, \mathbf{j}_0, \mathbf{k}_0\}$ rotated by $\theta(t)$ about $\mathbf{k}$ ($\mathbf{k} = \mathbf{k}_0$):

$$[{}_0R_1] = \begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}, \qquad \det[{}_0R_1] = 1, \qquad [{}_0R_1][{}_0R_1]^T = I$$

- **Surface-adapted basis.** With $s = \quad 1 + 4c^2R^2$, the unit meridian tangent is $\mathbf{e}_g = (\mathbf{e}_R + 2cR\,\mathbf{k})/s$ (proportional to $\mathbf{t}_R$), the unit normal is $\hat{\mathbf{n}} = (-2cR\,\mathbf{e}_R + \mathbf{k})/s$ (proportional to $\mathbf{n}$ above) and $\mathbf{e}_g \times \mathbf{e}_\theta = \hat{\mathbf{n}}$, so $\{\mathbf{e}_g, \mathbf{e}_\theta, \hat{\mathbf{n}}\}$ is right-handed and

$$[{}_1R_2] = \begin{pmatrix} 1/s & 0 & -2cR/s \\ 0 & 1 & 0 \\ 2cR/s & 0 & 1/s \end{pmatrix}, \qquad \det[{}_1R_2] = \frac{1 + 4c^2R^2}{s^2} = 1, \qquad [{}_1R_2][{}_1R_2]^T = I$$

- Both determinants and products RR^T were verified symbolically with sympy.

PHASE 3

Step-by-Step Mathematical Deduction

Part (a)-(d): Forces and Vectors

1. Forces on P: Gravity $-mg\mathbf{k}$, normal reaction $\mathbf{N} = N\frac{-2cR\mathbf{e}_R + \mathbf{k}}{1+4c^2R^2}$, cord tension $\mathbf{T}_P = -T\frac{\mathbf{r}_P}{|\mathbf{r}_P|}$
.

2. Forces on Q: Gravity $-mg\mathbf{k}$, cord tension $\mathbf{T}_Q = +T\mathbf{k}$.

Part (e): Tension Condition

The string remains in tension as long as $T(t) > 0$.

For Q, $m\ddot{z}_Q = T - mg \implies T = m(g + \ddot{z}_Q) > 0 \iff \ddot{z}_Q > -g$.

Part (f)-(g): Two First Integrals of Motion

1. **Angular Momentum Conservation:**

The surface is axisymmetric and the cord tension is central (directed towards O). Neither exerts torque about Oz:

$$L_z = mR^2\dot{\theta} = \text{constant} = m[R(0)]^2 d = m\frac{d}{c^2}$$

$$\dot{\theta}(t) = \frac{d}{c^2 R^2}$$

2. **Total Mechanical Energy Conservation:**

Constraints are frictionless and scleronomic:

$$E = T_P + T_Q + V_{g,P} + V_{g,Q} = \text{constant}$$

$$T_P = \frac{1}{2}m\left[\dot{R}^2(1 + 4c^2R^2) + R^2\dot{\theta}^2\right]$$

$$T_Q = \frac{1}{2}m\dot{z}_Q^2$$

$$V = mg(cR^2) + mgz_Q$$

Part (h): Turning Point Equation $f(R) = 0$

Setting $\dot{R} = 0$ in the conserved energy equation $E(R, \dot{R} = 0) = E_0$ yields the implicit algebraic equation $f(R) = 0$ whose positive roots define the minimum and maximum radii R_{min} and R_{max}.

PHASE 4

Physical Interpretation & Dimensional Verification

- The particle executes bounded precessing orbits on the paraboloid, bounded between two parallel circles R_{min} and R_{max}.
- **Dimensional check:** $[c] = \mathrm{m}^{-1}$, $[d] = \mathrm{s}^{-1}$, $R(0) = 1/c$ is a length; $[cR^2] = \mathrm{m}$ and $[c\,R] = 1$, so $\quad 1 + c^2R^2$ is dimensionless.
- **Explicit turning-point equation (part (h)).** At $\dot{R} = 0$ the kinetic energy reduces to $\frac{1}{2}mR^2\dot{\theta}^2$ with $R^2\dot{\theta}^2 = d^2/(c^4R^2)$ (from L_z), and the potential energy is $mg\,[cR^2 + R \quad 1 + c^2R^2] - mg\ell$ (the term $-mg\ell$ cancels in $E - E_0$). Equating with the initial energy at $R(0) = 1/c$ (where $R \quad 1 + c^2R^2 = \quad 2/c$), per unit mass:

$$f(R) = \frac{d^2}{2c^4R^2} + g\left(cR^2 + R \quad 1 + c^2R^2\right) - \frac{d^2}{2c^2} - \frac{(1 + \quad 2)\,g}{c} = 0$$

Each term has units $\mathrm{m}^2/\mathrm{s}^2$. The allowed radii are those with $f(R) \le 0$, and $R = 1/c$ is a root (sympy: $f(1/c) = 0$).

- **Numerical example ($c = d = g = 1$):** the roots of f are $R = 0.4828$ and $R = 1$ (the launch point is the outer turning point), $f(0.7) = -0.549$ and $f(0.9) = -0.276$ are negative (allowed band between the roots), and $f(0.4) = 0.802$, $f(1.2) = 0.747$ are positive (forbidden), so the orbit is bounded between $R_{min} = 0.4828/c$ and $R_{max} = 1/c$.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 33)

Double Pendulum

Original statement · Problems.pdf, p. 35

A double pendulum consists of two heavy point masses P and Q, each of mass m, connected to the origin O and to each other by two rigid, massless bars of length ℓ. We define the inertial frame S_0 with origin O and vector basis $\mathcal{B}_0$. We define the two angles θ and ϕ to describe the configuration of the system.

(a) Write down the general expressions of the position, velocity, and acceleration vectors of P and Q, using θ, ϕ and their derivatives.

(b) Write down all forces acting on P and Q, introducing new unknowns as needed.

(c) Write down the equations of motion for θ and ϕ, free of other unknowns.

(d) Find and write down one conservation law of this problem.

(e) If the initial conditions are $\theta = \phi = \pi/4, \dot{\theta} = \dot{\phi} = 0$, will Q ever cross the Ox axis? Justify your answer.

(f) Consider now that we impose the additional constraint $\phi = 2\theta$. Compute the natural frequency of oscillation of the system under the assumption of small angles.

(Hint: The mechanical energy of an ideal harmonic oscillator of natural frequency ω_0 and mass m can be written as $\frac{1}{2}m(\dot{x}^2 + \omega_0^2 x^2)$).

Full Analytical Solution (4-Phase Methodology)

PHASE 1

Physical Statement, Hypotheses & Parameters

- **Physical System:** Two point masses P and Q, each of mass m, connected by two rigid massless bars of length ℓ.
- First bar connects origin O to P, making angle θ with downward vertical.
- Second bar connects P to Q, making angle ϕ with downward vertical.
- **CDOFs:** 2 degrees of freedom: (θ, ϕ).
- **Parameters:** $m, \ell, g > 0$.

PHASE 2

Reference Frames, Vector Bases & Coordinate Geometry

- Coordinate axes: Ox horizontal to the right, Oz vertically upwards (downward vertical is $-\mathbf{k}$).
- Position of P:

$$\mathbf{r}_P = \ell \sin\theta\, \mathbf{i} - \ell \cos\theta\, \mathbf{k}$$

- Position of Q:

$$\mathbf{r}_Q = \mathbf{r}_P + \ell \sin\phi\, \mathbf{i} - \ell \cos\phi\, \mathbf{k} = \ell(\sin\theta + \sin\phi)\, \mathbf{i} - \ell(\cos\theta + \cos\phi)\, \mathbf{k}$$

PHASE 3

Step-by-Step Mathematical Deduction

Part (a): Velocity and Acceleration Vectors

1. Velocity of P:

$$\mathbf{v}_P = \ell\dot{\theta}\cos\theta\,\mathbf{i} + \ell\dot{\theta}\sin\theta\,\mathbf{k}$$

$$v_P^2 = \ell^2\dot{\theta}^2$$

2. Velocity of Q:

$$\mathbf{v}_Q = \ell(\dot{\theta}\cos\theta + \dot{\phi}\cos\phi)\,\mathbf{i} + \ell(\dot{\theta}\sin\theta + \dot{\phi}\sin\phi)\,\mathbf{k}$$

$$v_Q^2 = \ell^2\left[\dot{\theta}^2 + \dot{\phi}^2 + 2\dot{\theta}\dot{\phi}(\cos\theta\cos\phi + \sin\theta\sin\phi)\right] = \ell^2\left[\dot{\theta}^2 + \dot{\phi}^2 + 2\dot{\theta}\dot{\phi}\cos(\theta-\phi)\right]$$

Part (b)-(c): Equations of Motion

Total Kinetic Energy:

$$T = \frac{1}{2}mv_P^2 + \frac{1}{2}mv_Q^2 = \frac{1}{2}m\ell^2\left[2\dot{\theta}^2 + \dot{\phi}^2 + 2\dot{\theta}\dot{\phi}\cos(\theta-\phi)\right]$$

Total Potential Energy (taking datum at $z=0$):

$$V = mgz_P + mgz_Q = -mg\ell\cos\theta - mg\ell(\cos\theta + \cos\phi) = -mg\ell(2\cos\theta + \cos\phi)$$

Lagrange's equations $\frac{d}{dt}\left(\frac{\partial T}{\partial \dot{q}}\right) - \frac{\partial T}{\partial q} = -\frac{\partial V}{\partial q}$:

1. For θ:

$$2\ell\ddot{\theta} + \ell\ddot{\phi}\cos(\theta-\phi) + \ell\dot{\phi}^2\sin(\theta-\phi) + 2g\sin\theta = 0$$

2. For ϕ:

$$\ell\ddot{\phi} + \ell\ddot{\theta}\cos(\theta - \phi) - \ell\dot{\theta}^2\sin(\theta - \phi) + g\sin\phi = 0$$

Part (d): Conservation Law

The system is conservative with scleronomic constraints. Total mechanical energy is constant:

$$E = \frac{1}{2}m\ell^2\left[2\dot{\theta}^2 + \dot{\phi}^2 + 2\dot{\theta}\dot{\phi}\cos(\theta - \phi)\right] - mg\ell(2\cos\theta + \cos\phi) = \text{constant}$$

Part (e): Will Q Ever Cross the Ox Axis?

- Given initial state: $\theta(0) = \phi(0) = \pi/4$, released from rest ($\dot{\theta}(0) = \dot{\phi}(0) = 0$).
- Initial energy:

$$E_0 = -mg\ell\left(2\cos\frac{\pi}{4} + \cos\frac{\pi}{4}\right) = -3mg\ell\frac{2}{2} = -\frac{3\sqrt{2}}{2}mg\ell \approx -2.121\,mg\ell$$

- For Q to cross the Ox axis, its vertical coordinate z_Q must reach 0:

$$z_Q = -\ell(\cos\theta + \cos\phi) = 0 \implies \cos\theta + \cos\phi = 0$$

At that instant, the minimum potential energy of the system is:

$$V = -mg\ell(2\cos\theta + \cos\phi) = -mg\ell(\cos\theta + (\cos\theta + \cos\phi)) = -mg\ell\cos\theta$$

Since $\cos\theta \leq 1, V \geq -mg\ell$.

The required energy to cross the axis would be:

$$E_{req} \geq V \geq -mg\ell$$

However, the initial energy is $E_0 = -2.121\, mg\ell < -mg\ell$.

Because $E_0 < E_{req}$, the kinetic energy would have to be negative, which is physically impossible!

Conclusion: Q can **never** cross the Ox axis.

Part (f): Imposed Constraint $\phi = 2\theta$ and Small-Angle Natural Frequency

When $\phi = 2\theta$, $\dot{\phi} = 2\dot{\theta}$.

For small angles $\theta \ll 1$:

$$\cos(\theta - \phi) = \cos(-\theta) = \cos\theta \approx 1$$

Kinetic energy:

$$T = \frac{1}{2}m\ell^2\left[2\dot{\theta}^2 + (2\dot{\theta})^2 + 2\dot{\theta}(2\dot{\theta})(1)\right] = \frac{1}{2}m\ell^2[2+4+4]\dot{\theta}^2 = 5m\ell^2\dot{\theta}^2$$

Potential energy with $\cos u \approx 1 - \frac{u^2}{2}$:

$$V = -mg\ell(2\cos\theta + \cos(2\theta)) \approx -mg\ell\left[2\left(1 - \frac{\theta^2}{2}\right) + \left(1 - \frac{4\theta^2}{2}\right)\right]$$

$$V \approx -mg\ell[3 - 3\theta^2] = \text{const} + 3mg\ell\theta^2$$

Total energy of the equivalent oscillator:

$$E = 5m\ell^2\dot{\theta}^2 + 3mg\ell\theta^2 = \text{constant}$$

Differentiating with respect to time:

$$10m\ell^2\dot{\theta}\ddot{\theta} + 6mg\ell\theta\dot{\theta} = 0$$

Divide by $10m\ell^2\dot{\theta}$:

$$\ddot{\theta} + \frac{6g}{10\ell}\theta = 0 \implies \ddot{\theta} + \frac{3g}{5\ell}\theta = 0$$

The natural frequency of oscillation is:

$$\omega_0 = \sqrt{\frac{3g}{5\ell}}$$

PHASE 4

Physical Interpretation & Dimensional Verification

- The mechanical coupling $\phi = 2\theta$ acts as an internal kinematic constraint that stiffens the double pendulum into an equivalent single degree of freedom harmonic oscillator with effective mass $10m$ and effective restoring stiffness $6mg/\ell$, yielding the frequency $\omega_0 = \sqrt{3g/(5\ell)}$.
- **Dimensional check:** $[T] = [m\ell^2\dot{\theta}^2] = \mathrm{kg}\cdot\mathrm{m}^2\cdot\mathrm{s}^{-2} = \mathrm{J}$, $[V] = [mg\ell] = \mathrm{J}$, and $[\omega_0] = \sqrt{[g]/[\ell]} = \mathrm{s}^{-1}$ (the effective inertia $10m\ell^2$ and stiffness $6mg\ell$ are expressed in the coordinate θ; with $x = \ell\theta$ they become $10m$ and $6mg/\ell$).
- **Numerical check of part (e) (RK4, step 10^{-3}, $g = 9.81\ \mathrm{m/s^2}$, $m = \ell = 1$, 60 s from $\theta = \phi = \pi/4$ at rest):** the full nonlinear equations of part (c) give a maximum of $z_Q/\ell = -1.3375$, always negative, so Q never reaches the Ox axis, consistent with the energy bound $V \geq -mg\ell$ against $E_0 = -2.121\,mg\ell$.

- **Numerical check of part (f):** the exact one-degree-of-freedom Lagrangian with $\phi = 2\theta$ (without the small-angle approximation) integrated by RK4 from $\theta = 10^{-3}$ rad has half-period 1.2950 s, against $\pi/\omega_0 = \pi \quad 5\ell/(3g) = 1.2949$ s.

Complete Step-by-Step Solution

Source: Problems.pdf (Page 35)

← Previous Topic
Topic 2: Particle Dynamics

Theory Reference
Review Topic Theory →

Back to Syllabus →
Problems Hub

Study notes written from the official course material (Problems.pdf · p. 10). Online version: subjects/engineering-mechanics/problemas/topic-3.html