



You make **possible**



I want to code

But what language should I use

Patrick Riel – Software Engineer



Barcelona | January 27-31, 2020



Session ID

Agenda

- Introduction
- Navigating the Programming Landscape
- Trends in Open Source
- Languages
- Developer Tools
- Conclusion

Introduction

Introduction

- Software Engineer with Cisco DevNet
- Enjoys writing code in a variety of programming languages
- Believes coding should be fun (love what you do)
- Have had the opportunity to present at multiple Cisco Live events
- Luckily enough to work on quite some interesting projects over the course of 3+ years at Cisco

Navigating the Programming Landscape

Filters

Clear

DevNet x

Programmability x

Search



86 sessions

Learning Paths



Session Type



Technology



Solutions



Technical Level



Day



Accelerate Cisco DNA SD-Access deployments through Business API orchestration - DEVNET-2412



API Metadata Why You Should Care! - DEVLIT-4012



Automate Your Network with Nornir Python Automation Framework - DEVNET-2192



Automating Your Cisco UCS with Python - Managing Your Infrastructure as Code - DEVNET-1611



Behind the scenes of the IOS XE Programmability Lab - DEVLIT-4010



Cisco DNA Center Platform - Real time notifications via webhooks - DEVNET-2225



Cisco UCS & Cisco Intersight - Programmability Automation & Orchestration Overview - DEVNET-1481



Cloud 101: When it rains it pours; An 45-minute bootcamp to everything cloud - DEVNET-1233



Coding 1001 - Intro to APIs and REST - DEVNET-1897.d



Coding 1001 - Intro to APIs and REST - DEVNET-1897.b



*There are only two kinds of
programming languages: those
people always _____ about and
those nobody uses.*

Bjarne Stroustrup

C++

Descriptions of Languages

- Functional
- Imperative
- Declarative
- Compiled
- Interpreted



Functional

- Higher Order Functions
- Immutable Data
- Lisp, Haskell, Clojure, Erlang

Imperative


- Statements to change state
- Focuses on describing *HOW* a program operates

Declarative

- Contrasts with Imperative
- *WHAT* the program must accomplish

Compiled

- In theory, all languages can be compiled.
- Source Code -> Machine Code
- Typically faster to execute
- Catching errors at compile time



hello.go

go > hello > hello.go > ...

1

package main

2

3

import "fmt"

4

5

func main() {

6

fmt.Println("Hello World!")

7

}

8

OUTPUTDEBUG CONSOLETERMINAL

2: zsh

→ hello go build .

→ hello ll

total 4144

-rwxr-xr-x 1 localadmin staff 2.0M Jan 30 04:44 hello

-rw-r--r-- 1 localadmin staff 73B Jan 24 19:10 hello.go

→ hello ./hello

Hello World!

→ hello

Interpreted

- Executes code directly
- Software processed (Virtual Machine or emulator)
- Can have smaller execution binary



→ **hello** python

Python 2.7.16 (default, Oct 16 2019, 00:34:56)

[GCC 4.2.1 Compatible Apple LLVM 10.0.1 (clang-1001.0.37.14)] on darwin

Type "help", "copyright", "credits" or "license" for more information.

>>> print("welcome to Cisco DevNet")

welcome to Cisco DevNet

>>> █

Trends in Open Source

Trends in Open Source

NUMBER OF CONTRIBUTORS TO OPEN SOURCE PROJECTS		
01	microsoft/vscode	19.1k
02	MicrosoftDocs/azure-docs	14k
03	flutter/flutter	13k
04	firstcontributions/first-contributions	11.6k
05	tensorflow/tensorflow	9.9k
06	facebook/react-native	9.1k
07	kubernetes/kubernetes	6.9k
08	DefinitelyTyped/DefinitelyTyped	6.9k
09	ansible/ansible	6.8k
10	home-assistant/home-assistant	6.3k

TypeScript

Powershell

Dart

Markdown

C++/Python

JavaScript, Java, Objective C, C++

Go

TypeScript

Python

Python

<https://octoverse.github.com/>

Trends in Open Source

CHANGE IN CONTRIBUTIONS TO OPEN SOURCE PROJECTS		
01	aspnet/AspNetCore	346%
02	flutter/flutter	279%
03	MicrosoftDocs/vsts-docs	264%
04	istio/istio	194%
05	aws-amplify/amplify-js	188%
06	helm/charts	184%
07	ValveSoftware/Proton	182%
08	gatsbyjs/gatsby	179%
09	storybookjs/storybook	178%
10	cypress-io/cypress	178%

C#

Dart

Markdown

Go

TypeScript

Go

C++/Scala


JavaScript

TypeScript

JavaScript / CoffeeScript

<https://octoverse.github.com/>

Trends in Open Source



Trends in Open Source

CHANGE IN PROGRAMMING LANGUAGE USE,
2018-2019

01	Dart	532%
02	Rust	235%
03	HCL	213%
04	Kotlin	182%
05	TypeScript	161%
06	PowerShell	154%
07	Apex	154%
08	Python	151%
09	Assembly	149%
10	Go	147%

<https://octoverse.github.com/>

Languages

Rust - Hello World

```
fn main() {  
    println!("Hello World!");  
}
```



```
for x in 0..10 {  
    println!("{}", x); // x: i32  
}
```

```
/// Returns the relevant CPU features enabled at compile time.
fn compile_cpu_features() -> Vec<&'static str> {
    let mut features = vec![];
    if cfg!(feature = "simd-accel") {
        features.push("+SIMD");
    } else {
        features.push("-SIMD");
    }
    if cfg!(feature = "avx-accel") {
        features.push("+AVX");
    } else {
        features.push("-AVX");
    }
    features
}
```

Rust – Why?

- Performance
- Reliability
- Productivity
- Memory Safety

Rust – Good Use Cases

- Command Line Tools
- WebAssembly
- Networking
- Embedded
- <https://github.com/rust-unofficial/awesome-rust>

Python – Hello World

```
print("Hello World!")
```

```
def hello_world(count):
```

```
    for i in range(count):
```

```
        print("hello world")
```

```
hello_world(5)
```

```
class Channel(ClosingContextManager):
```

```
    """
```

```
    A secure tunnel across an SSH .Transport. A Channel is meant to behave...
```

```
    """
```

```
    def __init__(self, chanid):
```

```
        #: Channel ID
```

```
        self.chanid = chanid
```

```
        #: Remote channel ID
```

```
        self.remote_chanid = 0
```

Python – Why?

- Friendly and Easy to Learn
- Powerful
- Fast
- Expressive
- Great Libraries

Python – Good Use Cases

- Web and Internet Development
- Scientific and Numeric computing
- Education, great for teaching programming
- DevOps Tools
- Networking

Go – Hello World

```
package main
```

```
import "fmt"
```

```
func main() {  
    fmt.Println("Hello World!")  
}
```

```
import "fmt"

func main() {

    kvs := map[string]string{"a": "apple", "b": "banana"}
    for k, v := range kvs {
        fmt.Printf("%s -> %s\n", k, v)
    }
}
```

// TODO: Unit tests for this code, we can spin up a test SSH server with instructions here:

// <https://godoc.org/golang.org/x/crypto/ssh#ServerConn>

```
type sshTunnel struct {
```

```
    Config *ssh.ClientConfig
```

```
    Host string
```

```
    SSHPort string
```

```
    client *ssh.Client
```

```
}
```

```
func makeSSHTunnel(user string, signer ssh.Signer, host string) (*sshTunnel, error) {
```

```
    config := ssh.ClientConfig{
```

```
        User:      user,
```

```
        Auth:      []ssh.AuthMethod{ssh.PublicKeys(signer)},
```

```
        HostKeyCallback: ssh.InsecureIgnoreHostKey(),
```

```
    }
```

```
    return &sshTunnel{
```

```
        Config: &config,
```

```
        Host: host,
```

```
        SSHPort: "22",
```

```
    }, nil
```

```
}
```

Go – Why?

- Productivity
- Portable
- Performance
- Concise
- Concurrency
- Compile Time!

Go – Good Use Cases

- Server/Web Development
- Command Line Tools
- Networking
- Databases

JavaScript – Hello World

```
console.log('Hello World!');
```

```
// First one is the good old forEach loop  
const array = [1, 3, 5, 8, 12];  
  
array.forEach(number => {  
  console.log(number);  
});
```



```

/**
 * @param {object} nativeEvent Native browser event.
 * @return {string} Normalized `key` property.
 */
function getEventKey(nativeEvent: KeyboardEvent): string {
  if (nativeEvent.key) {
    // Normalize inconsistent values reported by browsers due to
    // implementations of a working draft specification.

    // FireFox implements `key` but returns `MozPrintableKey` for all
    // printable characters (normalized to `Unidentified`), ignore it.
    const key = normalizeKey[nativeEvent.key] || nativeEvent.key;
    if (key !== 'Unidentified') {
      return key;
    }
  }

  // Browser does not implement `key`, polyfill as much of it as we can.
  if (nativeEvent.type === 'keypress') {
    const charCode = getEventCharCode(nativeEvent);

    // The enter-key is technically both printable and non-printable and can
    // thus be captured by `keypress`, no other non-printable key should.
    return charCode === 13 ? 'Enter' : String.fromCharCode(charCode);
  }
  if (nativeEvent.type === 'keydown' || nativeEvent.type === 'keyup') {
    // While user keyboard layout determines the actual meaning of each
    // `keyCode` value, almost all function keys have a universal value.
    return translateToKey[nativeEvent.keyCode] || 'Unidentified';
  }
  return '';
}

```

JavaScript – Why?

- Productivity
- The Scripting Language for the Web
- Fast
- Frontend/Backend
- It's everywhere
- Expressive

JavaScript – Good Use Cases

- Visualizations
- Server/Web Development
- GUIs
- Mobile Development

C – Hello World

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    printf("Hello World!");
```

```
}
```

```
#include <stdio.h>
int main() {
    int i;
    for (i = 1; i < 11; ++i)
    {
        printf("%d ", i);
    }
    return 0;
}
```

```
#include <linux/completion.h>
#include "internal.h"

LIST_HEAD(crypto_alg_list);
EXPORT_SYMBOL_GPL(crypto_alg_list);
DECLARE_RWSEM(crypto_alg_sem);
EXPORT_SYMBOL_GPL(crypto_alg_sem);

BLOCKING_NOTIFIER_HEAD(crypto_chain);
EXPORT_SYMBOL_GPL(crypto_chain);

static struct crypto_alg *crypto_larval_wait(struct crypto_alg *alg);

struct crypto_alg *crypto_mod_get(struct crypto_alg *alg)
{
    return try_module_get(alg->cra_module) ? crypto_alg_get(alg) : NULL;
}
```

C – Why?

- Performance (FAST!)
- Highly Portable
- System Programming
- Closer to the Hardware
- Direct access to memory

C – Good Use Cases

- Embedded
- Operating Systems
- Networking
- Anything where performance is a top priority

Java – Hello World

```
class HelloWorld {  
  
    public static void main(String args[])  
    {  
        System.out.println("Hello, World");  
    }  
}
```

```
class HelloWorld {  
    public static void main(String args[])  
    {  
        printHelloWorld(5);  
    }  
    public static void printHelloWorld(Integer count) {  
        for (int i = 0; i < count; i++) {  
            System.out.println(i);  
        }  
    }  
}
```

```

@Override
public Generator opts(ClientOptInput opts) {
    this.opts = opts;
    this.openAPI = opts.getOpenAPI();
    this.config = opts.getConfig();
    this.templatingEngine = this.config.getTemplatingEngine();

    String ignoreFileLocation = this.config.getIgnoreFilePathOverride();
    if (ignoreFileLocation != null) {
        final File ignoreFile = new File(ignoreFileLocation);
        if (ignoreFile.exists() && ignoreFile.canRead()) {
            this.ignoreProcessor = new CodegenIgnoreProcessor(ignoreFile);
        } else {
            LOGGER.warn("Ignore...file");
        }
    }

    if (this.ignoreProcessor == null) {
        this.ignoreProcessor = new CodegenIgnoreProcessor(this.config.getOutputDir());
    }

    return this;
}

```

Java – Why?

- Highly Portable
- Flexible
- Good community support
- Teaching/Education
- Android

Java – Good Use Cases

- Big Data
- Enterprise Applications
- Android
- Web/Server Programming

Data Transports

Data Interchange Formats

- JSON
- XML
- Protobuf

JSON

- Built to be human readable...
- Built on two primary structures...
- A collection of name/value pairs (an object, record, struct, dictionary, hash table)
- An ordered list of values (array, vector, list, or sequence)
- MOST general-purpose programming languages provide DEFAULT standard libraries and tools for interacting and using JSON within that programming language.


```
{  
  "id": "",  
  "emails": [  
    "priel@cisco.com"  
  ],  
  "phoneNumbers": [  
  ],  
  "displayName": "Patrick Riel",  
  "nickName": "Patrick",  
  "firstName": "Patrick",  
  "lastName": "Riel",  
  "orgId": "",  
  "created": "",  
  "lastActivity": "",  
  "status": "active",  
  "type": "person"  
}
```

XML

- Built to be human readable...]
- Extensible Markup Language that also functions as a *data interchange format*.
- MOST general-purpose programming languages provide DEFAULT standard libraries and tools for interacting and using XML within that programming language.

```
<?xml version="1.0" encoding="UTF-8"?>

<serv:message

  xmlns:serv="http://www.webex.com/schemas/2002/06/service"

  xmlns:com="http://www.webex.com/schemas/2002/06/common"

  xmlns:ep="http://www.webex.com/schemas/2002/06/service/ep"

  xmlns:meet="http://www.webex.com/schemas/2002/06/service/meeting">

  <serv:header>

    <serv:response>

      <serv:result>SUCCESS</serv:result>

      <serv:gsbStatus>PRIMARY</serv:gsbStatus>

    </serv:response>

  </serv:header>

  <serv:body>

    <serv:bodyContent xsi:type="ep:getAPIVersionResponse"

      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">

      <ep:apiVersion>WebEx XML API V11.0.0</ep:apiVersion>

    </serv:bodyContent>

  </serv:body>

</serv:message>
```

Protobuf

- Mechanism for serializing structured data – SIMILAR to XML
- Support generated code in Java, Python, Objective-C and C++
- Proto3 (latest version of the protocol) also supports Dart, Go, Ruby, and C#

```
syntax = "proto2";

package tutorial;

option java_package = "com.example.tutorial";
option java_outer_classname = "AddressBookProtos";

message Person {
    required string name = 1;
    required int32 id = 2;
    optional string email = 3;

    enum PhoneType {
        MOBILE = 0;
        HOME = 1;
        WORK = 2;
    }

    message PhoneNumber {
        required string number = 1;
        optional PhoneType type = 2 [default = HOME];
    }

    repeated PhoneNumber phones = 4;
}
```

<https://developers.google.com/protocol-buffers/docs/javatutorial>

Developer Tools

Developer Tools

- Developer tools are an integral part of Software Development
- Makes our lives as software developers EASIER

Developer Tools - IDEs

- Visual Studio Code <https://code.visualstudio.com/>
- Atom <https://atom.io/>
- Android Studio <https://developer.android.com/studio>
- Xcode <https://developer.apple.com/xcode/>
- Eclipse <https://www.eclipse.org/ide/>

Developer Tools – The Terminal

- iTerm 2
- terminal
- cmd
- Powershell



images



dmz.txt



old



cleur2020



googleglass-
demo.mov



cleur2020.pptx

terminal

TOP HITS

Terminal

terminal-notifier — ibm-openhorizon

APPLICATIONS

terminal-notifier — meraki

DEFINITION

terminal

OTHER

terminal

terminal_windows.go

terminal_test.go


terminal_other.go

terminal.go

DEVELOPER

terminal.py

terminal_server.py



Terminal

Version: 2.9.5

	Kind	Application
Size	10.1 MB	
Created	10/4/18	
Modified	8/22/19	
Last opened	11/22/19	

```
Terminal  Shell  Edit  View  Window  Help
localadmin — localadmin@PRIEL-M-84RQ — ~ — zsh — 80x24
Last login: Tue Jan 28 20:44:18 on ttys001
l='ls -lah'
➔ ~ pwd
/Users/localadmin
➔ ~ date
Thu Jan 30 09:45:27 CET 2020
➔ ~
```



Developer Tools - Debuggers

- Great tool to understand the flow of programs
- Help find bugs in your code
- Extremely useful
- Most languages come with debuggers

DEBUG AND RUNLaunch

VARIABLES

Local

kvs: <map[string]string> (length: 2)

"a": "apple"

"b": "banana"

v: "apple"

k: "a"

Global

> .inittask: <runtime.initTask>

WATCH

CALL STACK

main.mainPAUSED ON BREAKPOINT

main.mainmain.go

runtime.mainproc.go 203

runtime.goexitasm_amd64.s 1357

> runtime.goparkPAUSED

> runtime.goparkPAUSED

> runtime.goparkPAUSED

> runtime.goparkPAUSED

client_test.gociscolive_test.go

cleur2020 > demo > main.go > main

1package main

2

3import "fmt"

4

5func main() {

6

7kvs := map[string]string{"a": "apple", "b": "banana"}

8for k, v := range kvs {

9fmt.Printf("%s -> %s\n", k, v)

10}

11

12

OUTPUTDEBUG CONSOLETERMINAL

API server listening at: 127.0.0.1:14952

Developer Tools - Containers

- Lighter than VMs
- Docker - <https://www.docker.com/>
- Additional Learning <https://developer.cisco.com/learning/lab/containers-101/step/1>

→ **cleur2020** docker ps

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
f90d23d7d392	chrono_config	"/entrypoint.sh chro..."	7 days ago	Up 7 days	0.0.0.0:8888->8888/tcp	icube-release_chronograf_1
9ba9720d4f56	telegraf	"/entrypoint.sh --de..."	7 days ago	Up 7 days	8092/udp, 8125/udp, 8094/tcp, 0.0.0.0:9273->9273/tcp	icube-release_telegraf_1
43b3fb6a4815	kapacitor	"/entrypoint.sh kapa..."	7 days ago	Up 7 days	0.0.0.0:9092->9092/tcp	icube-release_kapacitor_1
fe2e9873a10e	icube-release_icube	"/scripts/wait-for.s..."	7 days ago	Up 7 days	0.0.0.0:8100-8101->8100-8101/tcp, 0.0.0.0:8103->8103/tcp	icube-release_icube_1
21cfb4811c2d	cassandra:3.10	"/docker-entrypoint.s..."	7 days ago	Up 7 days	7000-7001/tcp, 0.0.0.0:9042->9042/tcp, 7199/tcp, 0.0.0.0:9160->9160/tcp	icube-release_cassandra_1
514547ee48f1	influxdb	"/entrypoint.sh infl..."	7 days ago	Up 7 days	0.0.0.0:8082->8082/tcp, 0.0.0.0:8086->8086/tcp, 0.0.0.0:8089->8089/udp	icube-release_influxdb_1
eb3085d479b2	icube-release_scripts	"tail -f /scripts/wa..."	7 days ago	Up 7 days		icube-release_scripts_1
2732ad6a68ea	nrf-journey_backend	"docker-entrypoint.s..."	2 weeks ago	Up 2 weeks	4001/tcp, 0.0.0.0:4001->80/tcp	nrf-journey_backend_1
86f2844bc6cf	nrf-journey_mongodb	"docker-entrypoint.s..."	2 weeks ago	Up 2 weeks	27017/tcp	nrf-journey_mongodb_1
fb445e2a7b61	redis	"docker-entrypoint.s..."	3 weeks ago	Up 12 days	0.0.0.0:6379->6379/tcp	webexglass_redis_1

→ **cleur2020** █

Developer Tools - curl

- Command Line Tool for transferring DATA <https://curl.haxx.se/>
- It supports a LONG list of protocols

DICT, FILE, FTP, FTPS, Gopher, HTTP, HTTPS, IMAP, IMAPS, LDAP, LDAPS, POP3, POP3S, RTMP, RTSP, SCP, SFTP, SMB, SMBS, SMTP, SMTPS, Telnet and TFTP. curl supports SSL certificates, HTTP POST, HTTP PUT, FTP uploading, HTTP form based upload, proxies, HTTP/2, cookies, user+password authentication (Basic, Plain, Digest, CRAM-MD5, NTLM, Negotiate and Kerberos), file transfer resume, proxy tunneling and more.


```
curl --location \  
  --request POST 'https://devnetml.cisco.com/api/v1/jobs/listing' \  
  --header 'Content-Type: application/json' \  
  --header $DEVNET_ML_AUTH_HEADER \  
  --data-raw '{  
    "data": "software engineer"  
  }'
```

Developer Tools - Postman

- A collaboration platform for API development. <https://www.getpostman.com/>
- But primarily an API Client, which allows you to quickly and easily send REST, SOAP, and GraphQL directly within Postman

New

Import

Runner

My Workspace

Invite

Sign In

Filter

History

Collections

APIs BETA

+ New API

Sign in to create APIs

APIs define related collections and environments under a consistent schema.

Sign in to create APIs

POST https://devnetml.cisco.com/ap...

POST https://events.rainfocus.com/...

+

...

No Environment

Untitled Request

Comments (0)

POST

https://events.rainfocus.com/api/search

Send

Save

Params

Authorization

Headers (12)

Body

Pre-request Script

Tests

Settings

Cookies

Code

none

form-data

x-www-form-urlencoded

raw

binary

GraphQL BETA

KEY	VALUE	DESCRIPTION	...	Bulk Edit
<input checked="" type="checkbox"/> search.sessiontype	DevNet			
<input checked="" type="checkbox"/> type	session			
<input checked="" type="checkbox"/> size	50			
<input checked="" type="checkbox"/> from	50			
Key	Value	Description		

Body

Cookies

Headers (13)

Test Results

Status: 200 OK

Time: 1574ms

Size: 1.23 MB

Save Response

Pretty

Raw

Preview

Visualize BETA

JSON

```

12     "code": "DEVWKS-2690",
13     "abbreviation": "DEVWKS-2690",
14     "title": "DevNet Workshop: ACI Telemetry REST APIs",
15     "abstract": "<p><strong><em>Please Note: There are only 8 laptops available for this session. Seating
is available on a first come, first serve basis. Registering for this session does not guarantee
you a seat, please plan accordingly.</em></strong></p><p>Learn how ACI provides stats and
anomalies that can help with network troubleshooting via the NIR application. We will walk you
through the app features, and how to access the information programmatically via APIC REST APIs.
In addition, we will also show you a demo of how you can consume the stats which are written to a
"

```

Bootcamp

Developer Tools - Packer

- Tool for creating identical machine images for multiple platforms from a single source configuration.
- Not a configuration management tool (Like Ansible, Chef, Puppet)
- Able to create machine images for a variety of formats
 - AMIs, VMDK/VMX , OVF etc.
- <https://www.packer.io/>

Developer Tools - Ansible

- App deployment, Configuration management, Workflow orchestration tool
- <https://www.ansible.com/>
- Additional Learning - https://developer.cisco.com/learning/lab/ansible-03_ansible-hands-on/step/1

Developer Tools – Draw.io

- Open source Diagramming Tool. <https://www.draw.io/>
- Great for Mockups and Diagrams

Untitled Diagram

File Edit View Arrange Extras Help

Unsaved changes. Click here to save.

100%

Search Shapes

Scratchpad

General

Misc

Diagram

View

Options

Paper Size

Edit Data

Clear Default Style

Page-1

Developer Tools – Browsers!

- Browsers have built in developer tools
- Great for building and debugging Web Applications
- <https://developer.mozilla.org/en-US/docs/Tools>

▶ Debugging the browser

Extending the devtools

Settings


Tips

Release notes

The Core Tools

You can open the Firefox Developer Tools from the menu by selecting *Tools > Web Developer* > *Toggle Tools* or use the keyboard shortcut **Ctrl** + **Shift** + **I** or **F12** on Windows and Linux, or **Cmd** + **Opt** + **I** on macOS.

The ellipsis menu on the right-hand side of Developer Tools contains several commands that let you perform actions or change tool settings.



This button only appears when there are multiple iframes on a page. Click it to display a list of the iframes on

Inspector Console Debugger Network Style Editor Performance Memory Storage Accessibility What's New Components Profiler

Search HTML

```
<!DOCTYPE html>
<html class="" dir="ltr" lang="en">
  <head prefix="og: http://ogp.me/ns#">
    <body>
      <script></script>
      <div id="react-container" data-component-name="SPA">
      </div>
      <script></script>
      <!--site js-->
      <script defer="" type="text/javascript" src="/static/build/js/react-main.20ac4d089bb0.js" charset="utf-8"></script>
      <script defer="" type="text/javascript" src="/static/build/js/react-bcd-signal.089b16e429d6.js" charset="utf-8"></script>
    </body>
  </html>
```

Filter Styles

```
element {
}
body {
  line-height: 1.6;
  font-family: Arial,x-locale-body,sans-serif;
  letter-spacing: -.00278rem;
  font-size: 18px;
  font-size: 1rem;
  -webkit-font-smoothing: antialiased;
  -moz-osx-font-smoothing: grayscale;
}
```

a, abbr, address, article, aside, audio, b, blockquote, body, canvas, caption, cite, code, dd, del, details, dfn, div, dl, dt, em, fieldset, figcaption, figure, footer, form, h1, h2, h3, h4, h5, h6, header, hgroup, hr, html, i, iframe, img, ins, kbd, label, legend, li, mark, menu, nav, object, ol, p, pre, q, samp, section, small, span, strong, sub, summary, sup, table, tbody, td, tfoot, th, thead, time, tr, ul, var, video

Conclusion

- There are many languages out there, learn multiple
- Languages are not inherently bad
- <https://developer.cisco.com/startnow/>
- <https://developer.cisco.com/learning/devnet-express/dnav3-track/dev-setup/dev-what/step/1>

Complete your online session survey



- Please complete your session survey after each session. Your feedback is very important.
- Complete a minimum of 4 session surveys and the Overall Conference survey (starting on Thursday) to receive your Cisco Live t-shirt.
- All surveys can be taken in the Cisco Events Mobile App or by logging in to the Content Catalog on ciscolive.com/emea.

Cisco Live sessions will be available for viewing on demand after the event at ciscolive.com.


Cisco Webex Teams

Questions?

Use Cisco Webex Teams to chat with the speaker after the session

How

- 1 Find this session in the Cisco Events Mobile App
- 2 Click “Join the Discussion”
- 3 Install Webex Teams or go directly to the team space
- 4 Enter messages/questions in the team space



cs.co/ciscolivebot#

Continue your education



Demos in the
Cisco Showcase



Walk-In Labs



Meet the Engineer
1:1 meetings



Related sessions



Thank you





You make **possible**