

The background is a vibrant, abstract composition of numerous overlapping, elongated, teardrop-like shapes in various colors including dark blue, light blue, green, yellow, orange, and red. These shapes radiate from a central point, creating a starburst or sunburst effect. Some shapes have white circular cutouts. Scattered around the main burst are several small, solid-colored circles in blue, yellow, and red.

TURN IT UP

CISCO *Live!*

#CiscoLive



The bridge to possible

Cisco Optics Applications in Optical Transport

Ray Nering, Sr. Product Line Manager MIG
Maurizio Gazzola, Sr. Product Line Manager MIG
BRKOPT-2011

CISCO *Live!*

#CiscoLive





Agenda

- Why Cisco Optics?
- QSFP DD Grey optics solutions
- 400G upgrade solutions
- QSFP DD Grey optics roadmap
- Pluggable DCO WDM Overview
- Router Interconnect
- QDD vs. CFP2 vs. TXP
- Conclusion

Why Cisco Optics? Pain Free Sourcing

CISCO *Live!*



Pain Free Sourcing

Breadth
of
portfolio



1G to 400G
Standard and
non-standard
devices

Breadth
of
suppliers



Single point of
access to breadth
of suppliers

High
volume



>10 million
transceivers
shipped per year

Change
Management



Manage supplier
changes, requalify,
secure supply

Cisco Optics Supply Chain Offers Unmatched Benefits

Supplier Management

- Ensure security of supply
- PCN/MCN management
- Audit suppliers
- Audit suppliers' critical subcomponent suppliers

Gold standard for Quality

- Validate early stage quality
- Active quality monitoring
- Ongoing quality assurance testing

Delivery

- Regional fulfillment sites
- Global service depots
- Industry leading lead times

Gartner

Cisco Supply Chain team consistently ranked in top 10 of Gartner's annual global *Supply Chain Top 25* and #1 for 2020


cisco *Live!*

QSFP DD Grey optic solutions




Introducing Cisco QSFP DD Portfolio

QSFP-DD



- QSFP-DD MSA has very broad industry support
- MSA has over 60 member companies
- Port is backward compatible to QSFP+, QSFP28, QSFP56
 - Ease migration to 400G
- Leverages industry cost structure and production capability of QSFP
 - Over 70M QSFP ports have been deployed to date
 - Industry has invested in roughly 40M QSFP modules
- Support 2x100G designs
- QSFP-DD will support over 20W of power dissipation
 - Supports pluggable coherent modules (ZR & ZR+)
- Broad product offering from copper cable to coherent
- Evolving to 800G in future (QSFP-DD800 MSA)

Why is Backward Compatibility Important



40G QSFP+

100G QSFP28

2x 100G QSFP-DD

200G QSFP56

400G QSFPDD




Platform with QSFP-DD Ports

Allows customers to buy the latest platforms with the latest features while managing their speed migration over time on a per port basis

Recipe for Success – Why will QSFP-DD succeed?

QSFP-DD positively checks out on all the 4 pillars necessary for a pluggable module to succeed



Compatibility

Alignment with ASIC IO (8x 50G PAM4 necessary)




Investment Protection

Backwards compatibility enables smooth network transition allowing reuse of the \$9B investment the industry has already made in QSFP modules



System Density

Support network requirements for system density: 32 & 36 ports




Superior Performance

Support necessary thermal/SI for implementation
All optical and copper reaches supportable incl. 400ZR

400GBASE-DR4 & 4x100G to 100GBASE-DR/FR/LR Breakout

- QSFP-DD provides the industry's highest density 100G interface
- Module in breakout is a high density 100G interface for 500m, 2km or 10km reach
- MPO-12 SMF connector
- Module provides breakouts to 4 lanes of 100GE
- Three reaches: 400G-DR4 – 500m; 4X100G-FR – 2km; 4X100G-LR – 10km
- QSFP-100G-DR/FR/LR provide low cost 100G to QSFP28 port



Single-Wavelength QSFP100 Portfolio

Cisco Silicon Photonics




Orderable


Orderable

Orderable


Q1 CY21




DR (500m)



FR (2km)



LR (10km)



ER-Lite (25km)

Data Center:


- Leaf switch connectivity to high density spine switch
- Nexus bundles

- Alternative to CWDM4
- 400G compatibility for incremental upgrade

- Alternative to LR4
- 400G compatibility for full utilization of port bandwidth


- Low-cost alternative to ER4-Lite, CFP2-DCO
- Cisco Silicon Photonics performance advantage

Single-Wavelength 100G Optics



400G MMF Solution (QDD-400G-SR4-BD)


- Provides 400GE connectivity over 4 prs. of MMF
 - Same cable infrastructure as 100G-SR4
- Ease speed migration from 100G to 400G with 4x 100G breakouts
- Reach target is 100m



2X100G QSFP-DD to 100G QSFP28 Breakout

- QSFP-DD 2X100G Modules connect legacy 100G modules to QSFP-DD ports
- Available in for the most common legacy module types
- Higher density 100G connectivity

Module Type	Optical Connector
2X 100G-LR4	Dual Duplex CS Connector
2X 100G-CWDM4	Dual Duplex CS Connector
2X 100G-SR4	MMF MPO-24 Connector



2X 100G-LR4 Breakout Example

400G upgrade solutions

CISCO *Live!*



DC Topology - Scale

Today

Next Gen

100G-DCO

400G-ZR/ZR+

100G-LR4

400G-LR4
400G-FR4

100G-CWDM4
100G-PSM4


400G-FR4
400G-DR4

100G-AOC
100G-BiDi

400G-AOC
400G-SR8
400G-SR4.2

100G-CR4
4x25G-CR

400G-CR8
8x50G-CR



cisco Live!

How to Transition from 100G to 400G Optics

400G optics on both ends of the link

Reach	Optic today	Next Gen	Media
100m MMF	100G SR4	400G SR4.2	Parallel fiber; supports breakout
500m SMF	100G PSM4	400G DR4 (500m) 4x100G FR (2km)	Parallel fiber; supports breakout
500m/2km SMF	100G SM-SR 100G CWDM4	400G FR4	Duplex fiber, no breakout
10km SMF	100G LR4	400G LR4	Duplex fiber, no breakout
80km SMF	100G DCO	400G ZR	Duplex fiber, no breakout
<30m	100G AOC	400G AOC	
<3m	100G DAC	400G DAC	

Cisco's portfolio of QSFP-DD modules makes it easy to upgrade to 400G in many cases with the current fiber infrastructure

Upgrading only one end of the link to QSFP-DD?

QSFP-DD breakout options provide backwards optical compatibility to QSFP28

Reach	QSFP 100G end	QSFP-DD end	
100m MMF	100G SR4	2x100G SR4	Connect up to TWO 100G-SR4 modules to a QSFP-DD port with a QDD-2X100-SR4-S module
2km SMF	100G CWDM4	2x100G CWDM4	Connect up to TWO 100G-CWDM4 modules to a QSFP-DD port with QDD-2X100-CWDM4-S modules
10km SMF	100G LR4	2x100G LR4	Connect up TWO 100G-LR4 modules to a QSFP-DD port with QDD-2x100-LR4-S modules
500m	100G-DR	400G DR4 (500m)	Connect up to FOUR 100G-DR modules to a QSFP-DD port with QDD-400G-DR4-S modules
2km SMF	100G FR	4x100G FR (2km)	Connect up to FOUR 100G-FR modules to a QSFP-DD port with QDD-4x100G-FR-S modules
10km SMF	100G LR	4x100G LR	Connect up to FOUR 100G-LR modules to a QSFP-DD port with QDD-4x100G-LR-S modules
100m MMF	100G BiDi	400G SR4.2	Connect up to FOUR 100G-BiDi modules to a QSFP-DD port with QDD-400G-SR4-BD


Cisco's portfolio of QSFP-DD modules provides efficient connectivity solutions between platforms for almost any interface

QSFP DD Grey optics roadmap




QSFP56-DD 400G Roadmap



CABLES



MULTIMODE OPTICS




SINGLE MODE OPTICS



Plan – Technology under evaluation

QSFP28-DD 2x100G Programs



MULTIMODE OPTICS

2x100G SR4

Available

100m

SINGLE MODE OPTICS

2x100G CWDM4

Available

2x100G CWDM4,
2 x TX and 2 x RX fibers

2x100G LR4

Roadmap

FCS: Q1CY21

2x100G LR4,
2x TX and 2 x RX fibers

500m

2km

10km

- QSFP28-DD optics enables high-density 100G backward compatibility with current gen100G optics

Optics support

- Compatibility matrix (platform to optics): <https://tmgmatrix.cisco.com/>
- Interoperability matrix (optics to optics): <https://tmgmatrix.cisco.com/iop>
- Cisco Optics Blog Site: <https://blogs.cisco.com/tag/ciscooptics>
- Transceiver Datasheets: <https://www.cisco.com/c/en/us/products/interfaces-modules/transceiver-modules/index.html>


Pluggable DCO WDM Overview



What is a DCO transceiver ?

DCO = Digital Coherent Optic

Cisco 100G Transponder line card for 300x300mm layouts




150W

Discrete Photonic Elements



Digital Signal Processor



28nm

Silicon Photonics Integration
Advanced packaging Integration



QSFP-DD 400G DCO




PIC with Multi Chip Packaging



Moore's Law



7nm



15W

Coherent 400G Product variants

- 3 Mechanical format will be available on the market:
 - CFP2 DCO
 - QSFP-DD
 - O-SFP
- CFP2 DCO is a larger form factor that allows to integrate a Mini-EDFA in the Optical Frontend. CFP2 DCO key different will be Tx Power about 0dBm that will allow full compatibility with current MCS Optical Add/Drop structure
- QSFP-DD and OSFP shows smaller footprint but QSFP-DD is smaller providing moreover full back-compatibility with QSFP+ and QSFP28.
- Cisco will productize QSFP-DD and CFP2-DCO
- Cisco proved that QSFP-DD, even with small power envelop can support maximum scale number in term of ports per RU

What are the Cisco 400G DCO variants ?

400GE, 4x100GE



400G

-10dBm Passive Fixed Filter



P2P metro line system

120km

cisco Live!

400GE, 4x100GE




openZR+

Improved FEC performance

100G/200G/300G/400G

-10dBm Passive Fixed Filter



P2P line system for long haul

1500km

400GE, 4x 100GE/OTU4, 40x 10GE/OTU2/OTU2e/STM64/16GFC




Open ROADMs

Improved FEC performance

100G/200G/300G/400G

+1dBm Contention-less Direction-less



Brown-field line system

1500km

Router Interconnect

CISCO *Live!*



Remote Routers – Symmetric solution

- In case of symmetric 400G routers interconnect multiple option can be considered:
- Assuming a WDM system in the middle 3 major use cases are possible

1. WDM ZR/ZR+ optics embedded on the router

- a) Sub case 1: Cisco WDM system
- b) Sub case 2: Third part WDM system



2. 400GE Interconnection with a 400GE capable TXP




3. 4x100GE fan out with a 100GE capable TXP



Remote Routers – Asymmetric solution

- The best option to interconnect a 400G router to a legacy 100G router is leverage on 400G ZR+ optics embedded in the router (also ZR is OK if distance is less than 120km)
- Router 400G port is configured as 4x 100G fanout mode as ZR+ pluggable will transport those 100GE streams onto a single wavelength at 400G
- On the remote location an interoperable Muxponder will break out 4 individual 100G interfaces to the 100G router




- Two Muxponder solution are planned to be interoperable with ZR+:
 1. NCS 2000 1.2T Muxponder Line Card (Titano6 program) – Q2CY2021 Rel 12.2
 2. NCS 1004 OTN-Xponder Line card (Bo program)
 1. Q1CY2021 IOS-XR 7.3.x (ZR)
 2. Q3CY2021 IOS-XR 7.4.x (ZR+)

QDD vs. CFP2 vs. TXP



DCO vs. TXP


- If the Router supports DCO capable the choice is intuitively to use the pluggables in place of a TXP
 - Much better Density (no need of external TXP shelf)
 - Better power consumption
 - Cost optimized solution (no need of 2 client optics, the connection cable, the transponder electronics etc.)




BUT.....

TXPs use cases

- There are still use cases when TXPs will be needed:
 - Submarine Applications
 - ULH network where there is no space for regeneration
 - The flexibility and the performance benefits that high-end optics mounted on the TXPs can not be matched by the DCO pluggable due to the power constraint driven by specific real-estate
- A second case is when there is not a match between the router capacity and the lambda capacity on the WDM system
 - Typical use case when one router has 400G WDM DCO and the router on the other side is 100G capable
 - A Muxponder on one side interoperating with direct wavelength from the router is expected



What about QDD vs CFP2



- TX Power Range:
 - -10 dBm, (ZR or ZR+ w/o Nyquist Shaping)
 - ~13dBm (ZR+ w/Nyquist shaping)

- TX Power Range:
 - -10 to +1dBm (SW Configurable)



- The 10dB of delta Tx Power will have a deep implication about which Add/Drop structure can be supported:
 - Unamplified passive coupler, MCS and CCOFS:
 - They require high input power and so **CFP2 DCO** shall be used
 - CFP2 DCO is compatible with any existing ADD/drop config
 - Amplified Passive coupler, Passive AWG
 - System can tolerate low Input Power and so **QDD DCO** shall be used

“Cisco is now all-in when it comes to the optics business.”

Optical technology has become an increasingly larger percentage of a communications system's bill of materials, and the purchase gives Cisco more direct control of those costs.

Andrew Schmitt

Founder and Directing Analyst, Signal AI



The bridge to possible

Thank you

CISCO *Live!*

#CiscoLive



The background is a vibrant, abstract composition of numerous overlapping, elongated, teardrop-like shapes in various colors including dark blue, light blue, green, yellow, orange, and red. These shapes radiate from a central point, creating a starburst or sunburst effect. Some shapes have white circular cutouts. Scattered around the main burst are several small, solid-colored circles in blue, yellow, and red.

TURN IT UP

CISCO *Live!*

#CiscoLive