

Developing multi-product show tech consolidation application with Kubernetes

Tomonobu Okada – Principal Engineer
DEVNET-2966



Cisco Webex App

Questions?

Use Cisco Webex App to chat with the speaker after the session

How

- 1 Find this session in the Cisco Live Mobile App
- 2 Click "Join the Discussion"
- 3 Install the Webex App or go directly to the Webex space
- 4 Enter messages/questions in the Webex space

Webex spaces will be moderated by the speaker until June 17, 2022.



https://ciscolive.ciscoevents.com/ciscolivebot/#DEVNET-2966





Agenda

- Introduction
- Challenges to solve
- LokiGO Overview
- Development Principles
- Run and use LokiGO (Demo1)
- Kubernetesize (Demo2)
- Case Study

Introduction









Tomonobu Okada


Principal Engineer, TAC Based in Tokyo, Japan Tech: 4G/5G mobile packet core



Challenges to solve




Technology Evolution vs Complexity





Challenges to support complex solution

- All hardware & software component is tightly integrated to form service
- High dependency between components
- Need basic understanding of the entire solution
- Difficulity to isolate a faulty component






DEVNET-2966

LokiGO Overview



LokiGO Overview

Multi-product show tech consolidation application



LokiGO Use-cases

Complex Solution

LokiGO can consolidate show tech file from different products and most important logging messages will be presented.

Multiple Devices

When there is a need to troubleshoot multiple routers for a routing protocol issue, LokiGO can combine them.

Single Device

Even for single device, LokiGO can consolidate different types of logging in a show tech so easy to troubleshoot.



LokiGO Architecture

- Frontend UI(React)
- Backend App(Golang)
- Parse the data generated by LokiGO
- Send to Loki

- Store the data sent by Promtail
- Process query from Grafana
- Dashboard based on Loki as data source
- Provide clean up function

LokiGO

Promtail

Grafana Loki

Grafana

Log Cleaner

Docker / Kubernetes















Development Principles



Development Principle - Why Golang?

Golang vs Python

- Parse 10 show support detail files
- Extract each tar.gz file
- Fetch "show logging" output
- Write it to a file
- Basic code, no performance optimization

Python

> time python staros_log_test.py python staros_log_test.py 54.36s user 2.89s system 98% cpu 57.953 total

Golang

> time ./main ./main 7.11s user 2.04s system 103% cpu 8.828 total

> Is -Ih | awk '{print \$9,\$5}'

ssd0.tar.gz 12M ssd1.tar.gz 12M

ssd2.tar.gz 12M ssd3.tar.gz 12M

ssd4.tar.gz 12M

ssd5.tar.gz 12M

ssd6.tar.gz 12M

ssd7.tar.gz 12M

ssd8.tar.gz 12M

ssd9.tar.gz 12M


Go is faster than Python!!



DEVNET-2966

Development Principle - Why Grafana Loki?

- Grafana Loki is developed and released by Grafana Labs
- Loki is a horizontally-scalable, highly-available, multi-tenant log aggregation system inspired by Prometheus
- https://grafana.com/oss/loki/
- 3 components, Promtail, Loki, Grafana





Promtail Log Scraping

Logging file generated by LokiGO

```
4e22f491-df0a-47d7-b676-2efcd8f0ea12---test-cimc--- +0000 ---2021-Apr-13+20:19:19

UUID Hostname Timestamp

| CIMC | Watchdog 2 BMC_WATCHDOG #0xf4 | Hard reset. |

Loggin

g

expression: ^(?P<uuid>.*)---(?P<hostname>.*)--- (?P<time>(?:-|\+[0-9]{4}) ---[0-9]{4}-[a-zA-Z]{3}-[0-9]{2}\+[0-9]{2}:[0-9]{2}) (?P<message>.*$)
```

Promtail Scraping Config

Data on Grafana



Run and use LokiGO



Run with Docker

- git clone https://github.com/tookada/ciscolokigo.git
- · cd ciscolokigo
- docker run -v \$(pwd):/mnt/config --name promtail -d -v \$(pwd)/log:/var/log grafana/promtail:1.6.0 -config.file=/mnt/config/promtail-config.yaml
- docker run -d -v \$(pwd):/mnt/config -p 3100:3100 --name loki grafana/loki:1.6.0 config.file=/mnt/config/loki-config.yaml
- docker run -p 8089:8089 -d --name lokigo -v \$(pwd)/log:/var/log tookadacisco/lokigo:prod
- docker run -d -p 3000:3000 -v \$(pwd)/datastore:/etc/grafana/provisioning/datasources -v \$(pwd)/dashboard:/etc/grafana/provisioning/dashboards -v \$(pwd)/json-config:/etc/dashboards --name grafana -e "GF_INSTALL_PLUGINS=grafana-piechart-panel" grafana/grafana:7.5.7
- The application can be accessed on http://127.0.0.1:8089
- The default username and password for Grafana is admin/admin (You will be requested to change it).




LokiGO Frontend UI

http://127.0.0.1:8089/

LokiGo - Multi product log consolidation and visualization

Supported Products






LokiGO Dashboard

Data can be filtered by product and/or logtype

Search keyword / Ignore keyword





DEVNET-2966

Demo 1 Run LokiGO with Docker



Kubernetesize



Kubernetesized LokiGO - Infrastructure as Code

Container deployment automation


kubectl create -f https://raw.githubusercontent.com/tookada/ciscolokigo/main/lokigo.yaml

Infrastructure as Code

```
apiVersion: apps/v1
kind: Deployment
metadata:
  labels:
    app: lokigo
    tier: frontend
    name: lokigo
    namespace: Grafana
---
spec:
    containers:
    - image: tookadacisco/lokigo:prod
    name: lokigo-react
```

```
apiVersion: v1
kind: Service
metadata:
  labels:
    app: lokiqo
    tier: frontend
  name: lokigo-service
  namespace: grafana
spec:
  ports:
  - port: 8089
    protocol: TCP
    targetPort: react-http
    nodePort: 30089
```

Kubernetesized LokiGO Overview





Kubernetesized LokiGO Readiness & Liveness Probe

- Deployment lokigo (similar policy is applied on other deployment too)
 - Monitor TCP port 8089 with readinessProbe, start monitoring after the first 5 seconds and monitor at 5 second intervals
 - Monitor TCP port 8089 with livenessProbe, start monitoring after the first 30 seconds, and monitor at 30 second intervals

```
readinessProbe:
  tcpSocket:
    port: 8089
  initialDelaySeconds: 5
 periodSeconds: 5
livenessProbe:
  tcpSocket:
    port: 8089
  initialDelaySeconds: 30
 periodSeconds: 30
```



Demo 2 Run LokiGO with Kubernetes



Run with Kubernetes (cont.)

```
stack@pod47-master:~$ kubectl create -f lokigo_proxy.yaml
namespace/grafana created
configmap/promtail-config created
configmap/loki-config created
deployment.apps/lokigo created
service/lokigo-service created
deployment.apps/loki created
service/loki-service created
configmap/loki-datastore created
configmap/dashboard-config created
configmap/dashboard-json created
deployment.apps/grafana created
service/grafana-service created
```



Run with Kubernetes

```
stack@pod47-master:~$ kubectl get deploy -n grafana
NAME
         READY
                 UP-TO-DATE
                             AVAILABLE
                                        AGE
         1/1
                                        5m18s
grafana
         1/1
loki
                                        5m18s
lokigo
      1/1
                                        5m18s
stack@pod47-master:~$ kubectl get pod -n grafana
                                 STATUS
                                          RESTARTS
NAME
                         READY
                                                    AGE
grafana-6dfdc6797b-jdp5c 1/1
                                 Running
                                                     62.s
loki-6c5cc4d487-qsfwp 1/1
                                 Running
                                                     62s
lokigo-65ff5d7bfc-6wc5w 3/3
                                 Running
                                                     62s
```

http://<IP address of your Kubernetes cluster>:30089/



Case Study



Case Study 1

BFD Down detected at StarOS running on CVIM/UCS

ECC error is the trigger of BFD down and this is the problem we need to investigate.

BFD down is detected at StarOS and this is customer visible

```
| 2021-06-23 22:37:50 staros | Internal trap notification 1277 (BFDSessionDown) vpn | 2021-06-23 22:37:50 staros | Internal trap notification 1277 (BFDSessionDown) vpn | 2021-06-23 22:37:50 staros | Internal trap notification 1277 (BFDSessionDown) vpn |
```

Right before the BFD down, ECC errors are reported at

```
2021-05-23 22:34:21 ucs
                                                CIMC | Memory DDR4_P2_H1_ECC #0xb4 | read 1 correctable ECC errors on CPU2 DIMM H1 |
2021-36-23 22:34:12 cvim
                                               root: [check_mlom_port.sh] Ping OK!!
2021-06-23 22:33:12 cvim
                                               root: [check_mlom_port.sh] Ping OK!!
                                               .0(4i):selparser:1318: [[xxxCVxxx]]:selparser.c:727: # 54 04 00 00 01 02 00 00 0C 38 D3
2021-06-23 22:33:01 ucs
2021-06-23 22:33:00 ucs
                                                CIMC | Memory DDR4_P2_H1_ECC #0xb4 | read 1 correctable ECC errors on CPU2 DIMM H1 |
                                               systemd-logind: Removed session 229224.
2021-06-23 22:32:54 cvim
2021-06-23 22:32:24 cvim
                                               systemd-logind: Removed session 229223.
                                                CIMC | Memory DDR4_P2_H1_ECC #0xb4 | read 1 correctable ECC errors on CPU2_DIMM_H1 |
2021-06-23 22:32:20 ucs
2021-06-23 22:32:20 ucs
                                                .0(4i):selparser:1318: [[xxxCVxxx]]:selparser.c:727: # 53 04 00 00 01 02 00 00 E4 37 D3
```


Single bit ECC is reported at CVIM also



Case Study 2 (cont.)

L2VPN traffic outage with IOS-XR

Various type of service traffic over SR with L3/L2 VPN technologies



Service traffic stopped suddenly

- The service runs on L2 VPN
- The outage started from Sep 28 23:19:26 to Sep 28 23:19:50
- No issue is seen on other service
- There were several operations on the day over metro network
- The metro network consists of over 20 PE/CE/P routers



Case Study 2

L2VPN traffic outage with IOS-XR

- Zoom in the timestamp which the outage happened
- There was an ISSU SW upgrade on one PE router
- Narrow down to one router and keep debugging

```
2021 Sep 28 23:19:26.648 +0900 ios_xr | RP/0/RP1/CPU0 ospf[1010]: %ROUTING-OSPF-5-HA NOTICE : Process 500: Starting NSR-enabled recovery procedures
2021 Sep 28 23:19:26.670 +0900 ios_xr RP/0/RP1/CPU0 ospf[1009]: %ROUTING-OSPF-5-HA_NOTICE : Process 101: Starting NSR-enabled recovery procedures
2021 Sep 28 23:19:26.674 +0900 ios_xr RP/0/RP1/CPU0 bpm[1080]: %ROUTING-BGP-5-ASYNC_IPC_STATUS : bpm-active:(bgp-bpm-active)inst-id 0, Service Published
2021 Sep 28 23:19:26.674 +0900 ios_xr RP/0/RP1/CPU0 ospf[1010]: %ROUTING-OSPF-5-HA_NOTICE: Process 500: Signaled PROC_AVAILABLE
2021 Sep 28 23:19:26.678 +0900 ios_xr RP/0/RP1/CPU0 ospf[1010]: %ROUTING-OSPF-5-HA_NOTICE : Process 500: Completed NSR-enabled activation procedures
2021 Sep 28 23:19:26.685 +0900 ios_xr RP/0/RP1/CPU0 imfpga[196] Change ISSU Node State from [Secondary] to [Primary]
2021 Sep 28 23:19:26.686 +0900 ios_xr RP/0/RP1/CPU0 imfpga[194]
                                                                 Change ISSU Node State from [Secondary] to [Primary]
                                                                 ISSU Phase Change Notification [Phase Run Exec], changing IM PLLs now
2021 Sep 28 23:19:26.687 +0900 ios xr RP/0/RP1/CPU0 imfpga[194]
2021 Sep 28 23:19:26.687 +0900 ios xr RP/0/RP1/CPU0 imfpga[197]
                                                                 Change ISSU Node State from [Secondary] to [Primary]
2021 Sep 28 23:19:26.689 +0900 ios xr RP/0/RP1/CPU0 imfpga[199]
                                                                 Change ISSU Node State from [Secondary] to [Primary]
                                                                 ISSU Phase Change Notification [Phase Run Exec], changing IM PLLs now
2021 Sep 28 23:19:26.690 +0900 ios xr RP/0/RP1/CPU0 imfpga[199]
2021 Sep 28 23:19:26.692 +0900 ios_xr RP/0/RP1/CPU0 ospf[1009]: %ROUTING-OSPF-5-HA_NOTICE : Process 101: Signaled PROC_AVAILABLE
2021 Sep 28 23:19:26.693 +0900 ios_xr RP/0/RP1/CPU0 imfpga[198]: Change ISSU Node State from [Secondary] to [Primary]
2021 Sep 28 23:19:26.693 +0900 ios_xr RP/0/RP1/CPU0 ospf[1009]: %ROUTING-OSPF-5-HA NOTICE : Process 101: Completed NSR-enabled activation procedures
2021 Sep 28 23:19:26.693 +0900 ios_xr RP/0/RP1/CPU0 imfpga[195]: ISSU Phase Change Notification [Phase Run Exec], changing IM PLLs now
> 2021 Sep 28 23:19:26.695 +0900 ios_xr RP/0/RP1/CPU0 imfpga[198]: ISSU Phase Change Notification [Phase Run Exec], changing IM PLLs now
2021 Sep 28 23:19:26.695 +0900 ios_xr RP/0/RP1/CPU0 imfpqa[197]: ISSU Phase Change Notification [Phase Run Exec], changing IM PLLs now
2021 Sep 28 23:19:26.697 +0900 ios_xr RP/0/RP1/CPU0 imfpga[196]: ISSU Phase Change Notification [Phase Run Exec], changing IM PLLs now
2021 Sep 28 23:19:26.706 +0900 ios_xr RP/0/RP1/CPU0 issudir[227]: %PKT_INFRA-FM-6-FAULT_INFO : ISSU-IN-PROGRESS :DECLARE :0/RP1/CPU0: ISSU_IN_PROGRESS Alarm : being DECLARED for the system
2021 Sep 28 23:19:26.715 +0900 ios_xr RP/0/RP1/CPU0 tmgctrl[276]: ISSU Phase Change Notification [Phase Run Exec]
2021 Sep 28 23:19:26.715 +0900 ios_xr RP/0/RP1/CPU0 tmgctrl[276]: ISSU Phase Change issu_phase:8
2021 Sep 28 23:19:26.715 +0900 ios_xr RP/0/RP1/CPU0 tmgctrl[276]: issul phase nfn received : 8 1 1
2021 Sep 28 23:19:26.715 +0900 ios_xr RP/0/RP1/CPU0 tmgctrl[276]: ISSU Node Role Change Notification [Primary]
2021 Sep 28 23:19:26.813 +0900 ios xr RP/0/RP1/CPU0 bpm[1080]: %ROUTING-BGP-5-ASYNC IPC STATUS : bpm-default:(A)inst-id 0. Connection Closed
                                      RP/0/RP1/CPU0 bgp[1065]: %ROUTING-BGP-5-ASYNC IPC STATUS : default:(A)inst-id 0. Connection Close
```



References

Cisco Code Exchange
 https://developer.cisco.com/codeexchange/github/repo/tookada/ciscolokigo

Git Repogitory
 https://github.com/tookada/ciscolokigo

Docker Hub

https://hub.docker.com/r/tookadacisco/lokigo



Technical Session Surveys

- Attendees who fill out a minimum of four session surveys and the overall event survey will get Cisco Live branded socks!
- Attendees will also earn 100 points in the Cisco Live Game for every survey completed.
- These points help you get on the leaderboard and increase your chances of winning daily and grand prizes.



Cisco Learning and Certifications

From technology training and team development to Cisco certifications and learning plans, let us help you empower your business and career. www.cisco.com/go/certs



(CLCs) are prepaid training vouchers redeemed directly with Cisco.



Learn



Train



Certify



Cisco U.

IT learning hub that guides teams and learners toward their goals

Cisco Digital Learning

Subscription-based product, technology, and certification training

Cisco Modeling Labs

Network simulation platform for design, testing, and troubleshooting

Cisco Learning Network

Resource community portal for certifications and learning



Cisco Training Bootcamps

Intensive team & individual automation and technology training programs

Cisco Learning Partner Program

Authorized training partners supporting Cisco technology and career certifications

Cisco Instructor-led and Virtual Instructor-led training

Accelerated curriculum of product, technology, and certification courses



Cisco Certifications and Specialist Certifications

Award-winning certification program empowers students and IT Professionals to advance their technical careers

Cisco Guided Study Groups

180-day certification prep program with learning and support

Cisco Continuing Education Program

Recertification training options for Cisco certified individuals

Here at the event? Visit us at The Learning and Certifications lounge at the World of Solutions





Continue your education

- Visit the Cisco Showcase for related demos
- Book your one-on-one Meet the Engineer meeting
- Attend the interactive education with DevNet, Capture the Flag, and Walk-in Labs
- Visit the On-Demand Library for more sessions at www.CiscoLive.com/on-demand



Thank you



cisco Live!



