



You make **possible**



Customizing Cisco Collaboration Devices

Stève Sfartz, stsfartz@cisco.com
API Architect, DevNet

DEVNET-2071

CISCO *Live!*

Barcelona | January 27-31, 2020




Cisco Webex Teams

Questions?

Use Cisco Webex Teams to chat with the speaker after the session

How

- 1 Find this session in the Cisco Events Mobile App
- 2 Click “Join the Discussion”
- 3 Install Webex Teams or go directly to the team space
- 4 Enter messages/questions in the team space



/Cisco/DevNet/SteveSfartz

- API Architect at Cisco DevNet
- Working to deliver the greatest API Experience for Cisco's developer community
- Technical Lead for Cisco's API Style Guide
- Webex Teams & Devices APIs
- Contributor to DevNet Code & Automation Exchange
 - postman collections for Webex Teams & Devices APIs
 - awesome-webex, awesome-xapi
 - code samples & dev tools



webex: stsfartz@cisco.com
github: [ObjectIsAdvantag](#)
twitter: [@SteveSfartz](#)

“vision without
execution is
hallucination”

Agenda

- CE programmability - xAPI
- Interacting with SSH, HTTP, Websockets
- Embedding code as JavaScript Macros
- Building and deploying UI Interactions
- Latest features



<https://projectworkplace.cisco.com>

7 participants, video call & presentation in progress





Demo
[OnAir]

In-Room Controls and UI Extensions





Demo [Enhanced Meeting Rooms]

In-Room Controls for Philips Hue

Network Topology



Hue Bulb

zigbee



172.17.101.71



172.17.101.83




172.17.101.69

Hue Controls

<http://bit.ly/ObjectIsAdvantag-HueDisco>



HTTP Put




Hue Controls

<http://bit.ly/ObjectIsAdvantag-HueDisco>



HTTP Put



API Reference Guide

xCommand Dial

Applies to: All products

Requires user role: ADMIN, INTEGRATOR, USER

Dial out from the device. Returns information about the CallId and Conferenceld, which are required for some of the other commands.


USAGE:

```
xCommand Dial Number: "Number" [Protocol: Protocol] [CallRate: CallRate]  
[CallType: CallType] [BookingId: "BookingId"] [Appearance: Appearance]  
[DisplayName: "DisplayName"] [TrackingData: "TrackingData"]
```

Dial (command)

- from t-shell

```
xcommand Dial Number: stsfarmz@cisco.com  
*r DialResult CallId: 2  
*r DialResult ConferenceId: 1
```



/!\ Look for tests
SIP addresses in
'awesome-xapi'

Awesome xAPI



awesome



DEVNET

published

<https://github.com/CiscoDevNet/awesome-xapi>

A curated list of developer resources for **Webex Room and Desk Devices** inspired by awesome-go and awesome-python.

Looking for developer resources for **Webex Teams**? check [awesome-webex](#).

Developer Tools

Handy tools to build, test and deploy applications.

- Sandbox - Reserve a CE device and code for up to a week (by DevNet).
 - [CE 9.9 Sandbox](#) - RoomKit Sandbox equipped with CE 9.9.
 - [CE 9.7 Sandbox](#) - RoomKit Sandbox equipped with CE 9.7.
 - Test
 - [Playground](#) - Launch the UI Extensions Editor straight from Chrome, no codec (by ObjectIsAdvantag).
- ➡ SIP test addresses - [111@bjn.vc](#), [fireplace@ivr.vc](#), [goldfish@selfie.vc](#), [halloween@ivr.vc](#), [havnen@expressway.dk](#).
- Deploy
 - [CE-Deploy](#) - Desktop application for deploying features (by voipnorm).
 - [CiscoTPCustomXML](#) - Deploy packages to Cisco Telepresence apps (by vipnorm).

Dial (command)

- from t-shell

```
xcommand Dial Number: stsfurtz@cisco.com
*r DialResult CallId: 2
*r DialResult ConferenceId: 1
```

- from code

```
xapi.command('Dial', { Number: 'stsfurtz@cisco.com' })
  .then((call) => {
    console.log(`Started call with status: ${call.status},
                id: ${call.CallId}`);
  })
```

Dial (command)

```
xapi.command('Dial', { Number: '206844539@cisco.webex.com' })
  .then((call) => {
    console.log(`Started call with status: ${call.status}, id: ${call.id}`);

    // Stop call after delay
    const delay = 30;
    console.log(`Call will be disconnected in ${delay} seconds...`);

    setTimeout(() => {
      console.log('Disconnecting');
      xapi.command('Call Disconnect', { CallId: call.CallId })
    }, delay * 1000);
  })
```

Changing Color of a Philips Hue bulb

Hue bridge IP

Hue user

light number

PUT

`http://172.17.201.69/api/SECRET/lights/4/state`

`{ "hue": 25500 }`

color



200 OK

`[{ "success": { "/lights/4/state/hue": 25500 } }]`

Awesome xAPI



awesome



DEVNET

published

<https://github.com/CiscoDevNet/awesome-xapi>


A curated list of developer resources for **Webex Room and Desk Devices** inspired by awesome-go and awesome-python.

Looking for developer resources for **Webex Teams**? check [awesome-webex](#).

Reference Guides

API Reference, Configuration and Administration guide for specific versions of CE and RoomOS.

- CE 9.10

 [API Reference Guide](#), [Administrator Guide \(CodecPro\)](#), and [\(RoomKit\)](#), [Customization Guide \(coming\)](#)

- CE 9.9

- [Blog: WebEngine and new UI Extensions Editor](#)

- [API Reference Guide](#), [Administrator Guide \(CodecPro\)](#), and [\(RoomKit\)](#), [Customization Guide](#)



- CE 9.8

- [Blog: New features,](#)

- [API Reference Guide](#), [Administrator Guide \(CodecPro\)](#), and [\(RoomKit\)](#), [Customization Guide](#)

xCommand HttpClient Put

Applies to: All products

Requires user role: ADMIN

Sends an HTTP(S) Put request to the server that is specified in the Url parameter.

You can use the AllowInsecureHTTPS parameter to specify whether or not to validate the server's certificate before sending data over HTTPS. This parameter has no effect unless the xConfiguration HttpClient AllowInsecureHTTPS is set to On.

This is a multiline command, so the payload (data) follows after the parameters.

USAGE:

```
xCommand HttpClient Put [AllowInsecureHTTPS: AllowInsecureHTTPS] [Header:  
"Header"] [Timeout: Timeout] Url: "Url"
```

```
xConfiguration HttpClient Mode: On  
xConfiguration HttpClient AllowInsecureHTTPS: True
```



Required

HttpClient command

- from t-shell


```
xcommand HttpClient Put
  Header: "Content-Type: application/json"
  Url: " http://192.168.1.33/api/SECRET/lights/1/state"
{ "hue": 25500, "sat" : 255, "on" : true }
.
```

- from code

```
xapi.command("HttpClient Put", {
  Url: `http://${BRIDGE_IP}/api/${BRIDGE_USER}/lights/${LIGHT_ID}/state`,
  Header: [ "Content-Type: application/json" ],
  AllowInsecureHTTPS: "True"
},
JSON.stringify({ "hue": 25500, "sat" : 255, "on" : false }));
```


Embedded JavaScript Macros

CE & RoomOS Programmability (xAPI)



Launch the Macro Editor

<https://10.10.20.17X/web>



The screenshot displays the Cisco Webex Room Kit configuration interface. The top navigation bar is blue with the Cisco logo on the left and the IP address 192.168.1.34 and 'Cisco Webex Room Kit' on the right. Below this is a horizontal menu with tabs: Home, Call Control, Setup, Security, Maintenance, and Integration. The Integration tab is selected, and a dropdown menu is open, showing 'UI Extensions Editor', 'Macro Editor' (highlighted with a green arrow), and 'Developer API'. On the left side, there is a search bar and a list of configuration categories: Audio, CallHistory, Cameras, Conference, FacilityService, HttpClient (highlighted in blue), and HttpFeedback. The main content area is titled 'Configuration' and shows the 'HttpClient' section. It contains three settings: 'AllowHTTP' set to 'True', 'AllowInsecureHTTPS' set to 'True', and 'Mode' set to 'On'. Each setting has a dropdown arrow next to its value.

Cisco 192.168.1.34
Cisco Webex Room Kit

Home Call Control **Setup** Security Maintenance Integration localadmin

Search...

Configuration

HttpClient

AllowHTTP True

AllowInsecureHTTPS True

Mode On

Macro Editor



Runtime ▾

Preferences

Import from file...

Create new macro

peoplecount



```
1 const xapi = require('xapi');
2
3 xapi.status
4   .get('RoomAnalytics PeopleCount')
5   .then((count) => {
6     console.log(`Initial count is: ${count.Current}`);
7   })
```

Severity ▾

Enter filter

☐ Show history

2019-01-20 20:38:02 peoplecount > Loading...

2019-01-20 20:38:02 [system] > Starting macros...


2019-01-20 20:38:02 [system] > Macros ready.

2019-01-20 20:38:02 peoplecount > 'Initial count is: 4'



Demo [HttpClient command]

Macro runtime



Configuration

Macros

AutoStart	<input type="text" value="On"/>	
Mode	<input type="text" value="On"/>	
UnresponsiveTimeout	<input type="text" value="5"/>	(0 to 65535)
XAPI Transport	<input type="text" value="TSH"/>	

- Maximum number of macros (10 currently)
- CE & RoomOS devices (but SX10)
- Run as 'Admin' role by default
- Duktape JavaScript runtime (version 2.2+) with Babel
 - 'babel-preset-latest' is specified to support latest ES6+ features
 - async/await is supported
- `/!\` Macro tutorial accessible from the codec



Demo [Disco Macro]

HttpClient command

ChatOps – posting to a Webex Teams space

```
xapi.command("HttpClient Post", {
  Header: ["Content-Type: application/json",
           "Authorization: Bearer " + token],
  Url: "https://api.ciscospark.com/v1/messages",
  AllowInsecureHTTPS: "True"
},
JSON.stringify({
  "markdown": "_Your RoomKit says_\n>'hi **Everybody**'",
  "roomId": roomId
})))
.then((result) => console.log('message pushed to Webex Teams'))
```





CiscoLive 11:15

Your RoomKit says

| 'hi Everybody'


Creating UI Extensions





Launch the UI Extensions Editor

<https://10.10.20.17X/web>



The screenshot displays the Cisco Webex Room Kit configuration interface. At the top, a blue header bar contains the Cisco logo on the left and the IP address 192.168.1.34 and the text 'Cisco Webex Room Kit' on the right. Below the header is a navigation bar with tabs: Home, Call Control, Setup, Security, Maintenance, and Integration. The Integration tab is selected, and a dropdown menu is open, showing three options: 'UI Extensions Editor' (highlighted with a green arrow), 'Macro Editor', and 'Developer API'. To the right of the dropdown are minus and plus buttons. On the left side of the page is a sidebar with a search bar and a list of configuration categories: Audio, CallHistory, Cameras, Conference, FacilityService, HttpClient (highlighted in blue), and HttpFeedback. The main content area is titled 'Configuration' and shows the 'HttpClient' section. It contains three settings, each with a label and a dropdown menu: 'AllowHTTP' set to 'True', 'AllowInsecureHTTPS' set to 'True', and 'Mode' set to 'On'.

Configuration

HttpClient

AllowHTTP	True
AllowInsecureHTTPS	True
Mode	On

UI Extensions Editor

The screenshot displays the Cisco UI Extensions Editor interface. At the top left is the Cisco logo. The main title bar reads "UI Extensions configuration - Edited". On the right side of the title bar are navigation icons: a blue up arrow, a grey eye, a grey left arrow, a grey right arrow, and a grey menu icon.


The interface is divided into three main sections:

- Extensions Panel (Left):** Contains a "Disco Custom" button with a lightbulb icon and a "New" button.
- Configuration Panel (Center):** Shows a configuration area with a "Disco" label and a "+" button. Below this is a "Blink" label and a slider widget. The slider has a blue track and a white knob. Below the slider is another "+" button. At the bottom of this panel is a toolbar with icons for: a toggle switch, a slider, a range slider, a plus button, up/down arrows, a text input, a resize handle, and a delete handle. Below the toolbar is the text "Drag widgets to the panel to add them".
- Properties Panel (Right):** Titled "Properties", it shows the "Widget id" as "DISCO_slider" and the "Widget width" as "4". There are minus and plus buttons for adjusting the width. At the bottom is a red "Delete widget" button.



Demo [UI Extensions Editor]

Listening to events



```
xapi.event.on('UserInterface Extensions Widget Action', (event) => {  
  if ((event.WidgetId == 'DISCO_slider') && (event.Type == 'released')) {  
    console.log(`updated slider↑: ${event.Value}`);  
    // Change bulb color  
  }  
});
```

Macro Editor




Demo

[Connecting the dots]

xAPI protocols & formats

CE & RoomOS Programmability (xAPI)



protocols

serial port

ssh

websocket

HTTP

formats

text

XML

JSON

Terminal Mode: t-shell



```
xconfiguration ?
- User Configurations -

Audio          Logging      Proximity     UserInterface
CallHistory    Macros       RoomAnalytics  UserManagement
Cameras        Network     SerialPort    Video
Conference     NetworkServices SIP            WebEngine
GPIO           Peripherals Standby
H323           Phonebook   SystemUnit
HttpClient     Provisioning Time

OK
xstatus ?
- Status -

Audio          GPIO         Peripherals   Standby
Bookings       H320        Provisioning   SystemUnit
Call           H323        Proximity     Time
Cameras        HttpFeedback RoomAnalytics  UserInterface
Capabilities    MediaChannels RoomPreset     Video
Conference     Network     Security
Diagnostics    NetworkServices SIP

OK
```

serial port

ssh

websocket

HTTP

text

XML

JSON

Terminal Mode: t-shell



```
xcommand ?
- User Commands -

Audio          Diagnostics    Peripherals    Standby
Bookings       Dial           Phonebook       SystemUnit
Call           GPIO           Presentation    Time
CallHistory    HttpClient     Provisioning    UserInterface
Camera         HttpFeedback   Proximity       UserManagement
Cameras        Macros         RoomPreset      Video
Conference     Message        Security
```

OK

```
xFeedback help:
xFeedback register XPathExpression[1..200]
xFeedback deregister XPathExpression[1..200]
xFeedback deregisterall
xFeedback list
```

serial port

ssh

websocket


HTTP

text

XML

JSON

CE & RoomOS Programmability (xAPI)



serial port
ssh
websocket*
HTTP

text
XML
JSON

HTTP



POST

https://192.168.1.26/putxml

Params

Authorization

Headers (2)

Body ●

Pre-request Script

Tests

☐ none

☐ form-data

☐ x-www-form-urlencoded

☒ raw

☐ binary

XML (text/xml)

1

<Command>

2

<Macros>

3

<Macro>

4

<Save>

5

<Name>HelloWorld</Name>

6

<OverWrite>True</OverWrite>

7

<body>console.log("hello world")</body>

8

</Save>

9

</Macro>

10

</Macros>

11

</Command>

12

serial port
ssh
webSocket
HTTP

text
XML
JSON

Cisco CE xAPI (as admin)

Send commands, update configuration and request status for on-premises Collaboration Devices, and cloud-registered Webex Devices

xAPI is the Application Programming Interface (API) for Collaboration Endpoint software(Cisco CE and RoomOS), for both on-premise registered video conferencing devices (CUCM, VCS) as well as devices registered to Cisco's cloud service (Cisco Webex Devices).

This collection gathers commands accessible to an 'Admin' user, and local to the collaboration device.

Which commands are available depends on the product, the back-end (on-premise, cloud), and the user role of the local user (admin, audit, integrator, roomcontrol, user). To get an overview of the commands, check the reference guide for the version of CE or RoomOS you are running. Here is a link to the guide for CE 9.8 and RoomOS as of September 2019:

<https://www.cisco.com/c/dam/en/us/td/docs/telepresence/endpoint/ce98/collaboration-endpoint-software-api-reference-guide-ce98.pdf>

CHECK all collections for Cisco APIs:

<https://explore.postman.com/team/ciscodevnet>



Run in Postman

View Documentation

PUBLISHER



Cisco DevNet

Cisco's developer program - developer.cisco.com - helps developers and IT professionals write applications and develop integrations.

CATEGORIES

BUSINESS SOLUTIONS

IMPORTS


400+

CE & RoomOS Programmability (xAPI)

<https://github.com/cisco-ce/jsxapi>



*Events, Status,
Configuration, Commands*



serial port
ssh
websocket
HTTP

text
XML
JSON


```
15  const jsxapi = require('jsxapi');
16  const xapi = jsxapi.connect("ssh://10.10.20.153", {
17      username: 'admin',
18      password: 'ciscopsdt'
19  });
20
21  xapi.on('error', (err) => { ...
39  });
40
41  xapi.on('ready', () => {
42      console.log("connexion successful");
43
44      // Display current audio volume
45      xapi.status
46          .get('Audio Volume')
47          .then((level) => {
48              console.log(`Current volume level: ${level}`);
49          });
```

CE & RoomOS Programmability (xAPI)

<https://github.com/cisco-ce/pyxows>




*Events, Status,
Configuration, Commands*



serial port
ssh
websocket
HTTP

text
XML
JSON

Macros and/or Standalone applications



Embedded macro or standalone app?

Macros

- Status, configuration, commands, events
- Invoke HTTP-based APIs
- Limited number of macros (currently 10)
- Stateless only (no db persistence)*
- No macro to macro communication**

Use cases

- ⇒ Custom behaviors
- ⇒ Interact with IoT exposing HTTP APIs

Standalone Apps

- Status, configuration, commands, events
- Interact with legacy APIs (beyond REST)
- Server-side limitations only (memory, disk)
- Stateful with data persistence

Use cases

- ⇒ Manage / Automate multiple devices
- ⇒ Integrate with Process or 3rd party product

Accessing your Collaboration Device's API

on-prem devices


Webex Room Kit

<https://projectworkplace.cisco.com/#/en-us/product/webexroomkit/0/0>



CE devices are API-native

<https://<device-ip>/config/NetworkServices>

192.168.1.26
Cisco Webex Room Kit

HomeCall ControlSetupSecurityMaintenanceIntegrationlocaladmin

Search...

Configuration

Audio

CallHistory

Cameras

Conference

FacilityService

HttpClient

Logging

Macros

Network

NetworkServices

Peripherals

NetworkServices

General Settings

HTTP

ModeHTTPS

Proxy

LoginName(0 to 80 characters)

ModeOff

PACUrl(0 to 255 characters)

Devices

CL19B

3

DEVICES FOUND

Online, With Issues 0
Expired 0
Offline 2
Online 1

Add Device

Type	Status	Belongs to
Cisco Webex Codec Plus	Offline	CL19B RoomKit1
Cisco Webex Room Kit Plus	Offline	CL19B Classroom
Cisco Webex Room Kit Plus	Online	CL19B Workshop

<https://admin.webex.com>

Admin UI for cloud-registered Webex Devices

<https://admin.webex.com/devices>



Cisco Webex Room Kit Plus

● Online

Settings

Lines	None
IP Address	172.17.201.69
Network Connectivity	Wired
MAC Address	B0:26:80:64:2B:A9
SIP Address	theater@devnetzone.room.ciscospark.com
Serial Number	FOC2216NSC1
Software	Stable RoomOS 2019-06-03 ccc122100bb

Device Access

Advanced Settings	Open the web interface of the device
Cisco Support	Remote Access Key



REQUIREMENT: local connectivity to the device


<https://admin.webex.com/devices>  <https://<device-ip>/cloud-login>

 Cisco Webex Room Kit Plus
● Online


Settings

Lines	None
IP Address	172.17.201.69
Network Connectivity	Wired
MAC Address	B0:26:80:64:2B:A9
SIP Address	theater@devnetzone.room.ciscospark.com
Serial Number	FOC2216NSC1
Software	Stable RoomOS 2019-06-03 ccc122100bb

Device Access

Advanced Settings [Open the web interface of the device](#) 

Cisco Support [Remote Access Key](#)




The screenshot shows the Cisco Spark Room Kit web interface. At the top is a blue header with the Cisco logo. Below it is a navigation bar with tabs: Home (selected), Setup, Security, Maintenance, and Integration. The main content area is titled 'System Information' and contains a 'General' section. This section lists various system details in a two-column format.

Product:	Cisco Spark Room Kit
Last boot:	2017-12-23
Serial number:	FOC2111N3TK
Software version:	Spark Room OS 2017-11-21 d31e4c18
Installed options:	Encryption RemoteMonitoring
System name:	-
IPv4:	192.168.1.34
IPv6:	2a01:cb05:857a:c500:a96:adff:fe60:9d04
MAC address:	08:96:AD:60:9D:04
Temperature:	Normal

Adding user roles to access your device

<https://<device-ip>/web/localusers>

- Create a local user: 'Control', 'Integrator' or 'Admin' role



The screenshot displays the Cisco Collaboration Endpoint web interface. The top navigation bar is blue with the Cisco logo on the left and the IP address 192.168.1.34 and device name Cisco Collaboration Endpoint on the right. Below this is a grey navigation bar with tabs for Home, Setup, Security, Maintenance, and Integration. The Security tab is active, and a dropdown menu is open, showing options for Local Users, Service Certificates, and Certificate Authorities. The Local Users page shows a table with two users: 'control' (RoomControl User) and 'integrator' (Integrator User). Each user has a red 'Delete user' button next to it.

Username	Role	Action
control	RoomControl User	Delete user
integrator	Integrator User	Delete user

User Roles

<https://collaborationhelp.cisco.com/article/en-us/jkhs20>

Admin	Have unrestricted access to the device's local web interface. Access the API over SSH, serial connection, or HTTP(S). Create and manage users with the <i>Integrator</i> and <i>RoomControl</i> roles.
Integrator	Access the device's local web interface. <i>Integrator</i> has the same access as an <i>Admin</i> user, except creation of new users. Access the API over SSH, serial connection, or HTTP(S).
RoomControl	Access the In-Room Control editor and corresponding development tools on the web interface, to create touch interface extensions (in-room controls). Access the API commands that are required to create touch interface extensions.
User	Make calls and search the People lists. Modify a few settings, for example adjust the ringtone volume and set the time and date format.



<https://developer.cisco.com/site/sandbox/>

Experiment with a DevNet Sandbox

Version CE 9.9



Room Kit

WebEx Device

WINDOW: INSTRUCTIONS COMMANDS ACTIVITY OUTPUT NAVIGATOR STYLE: BEHAVIOUR: 100% More

INSTRUCTIONS

Room Kit

DevBox

VPN

Overview:

This sandbox is provided for the purpose of discovering Cisco Collaboration Software - CE9.2+ programmability for Room Devices (MX, SX, DX and Room Kit series). It comes with a Room Kit device and a developer box.


Integrators, IT engineers and application developers can discover the extensibility of Cisco Collaboration Endpoints, and learn to code for Room Devices by getting hands-on with In-Room Controls and Macros, but also checking status, changing configuration and sending commands through xAPI.

Roomkit:

Once you have created a VPN session to the sandbox, you can:


- Discover the admin interface from your laptops Web browser
- Open a ssh session to the Room Kit and enter t-shell

SANDBOX




Latest Features

CE Programmability (xAPI)




CE Programmability at a glance

- Enhance the User eXperience of your meetings
 - add UI Extensions to Room/Desk/Boards devices
 - interact with IoT devices
 - customized behaviors as macros
 - Integrate with enterprise process
- Automate your devices from code
 - initiate calls, fetch history
 - collect room analytics
 - apply branding across devices
 - deploy UI Extensions & macros



Locked down interface

- 'Kiosk-like' User experience, no settings menu and standard buttons
- Example: Speed dial to experts via a custom button



```
xConfiguration UserInterface Features HideAll: True  
xConfiguration UserInterface SettingsMenu Visibility: Hidden
```


Cisco Collaboration Devices Programmability

Available on all devices running CE & RoomOS



Room Kit standard, pro, mini




*no Macros on SX10




Complete programmability

DX, DeskPro




cisco *Live!*

CE and RoomOS



CE and RoomOS



What's new with Webex Devices APIs

- Recently added and New Features
 - CE feature-parity for Webex Boards
 - **Web Applications** for Webex Boards, Room Series and Desks Pro
 - Cloud xAPI for cloud and linked Devices
- Coming
 - REST APIs to configure Webex Devices
 - Webhook events for Webex Devices



Cloud xAPI with Webex Edge for Devices

Cloud access and control of on-prem Collaboration Devices linked via Webex Edge for Devices

POST


<https://<webex>/v1/xapi/command/standby.activate>

200 OK


```
{  
  "deviceId": "{{_deviceId}}"  
}
```

CE Programmability & Webex Devices APIs

- **Tuesday, 10:00 – ‘Meet DevNet’ podium – DEVNET-3010.f**
 - Learn how to make Network Automation Simple with the Community
- **Wednesday, 12:15 – Hall 8, C128 – BRKDEV-3244**
 - Advanced coding for Cisco Video devices
- **Wednesday, 15:00 – Classroom 3 – DEVNET-2071**
 - Customizing Cisco Collaboration Devices

 **Thursday, 10:00 – DevNet Theater – DEVNET-1462**

- Webex Room Device APIs (latest and new features)

 **Friday, 11:30 – BRKCOL-3008**

- Customization and Integrations of Cisco Video Room Devices

Awesome xAPI



awesome



DEVNET

published

<https://github.com/CiscoDevNet/awesome-xapi>

A curated list of developer resources for **Webex Room and Desk Devices** inspired by awesome-go and awesome-python.

Looking for developer resources for **Webex Teams**? check [awesome-webex](#).

Contents

DISCLAIMER: Cisco does not make any commitments about the resources listed in this document, nor the accuracy of the third party resources and any content accessible via the links below.


- [!Get Started!](#)
- [Articles and Blogs](#)
- [Building Blocks](#)
- [Code samples](#)
- [Developer Tools](#)
 - [DevNet Sandbox](#)
- [Reference](#)
 - [PDF Guides](#)
- [3rd Party Hardware](#)

Join the 'xAPI Devs'
Teams Space

<http://bit.ly/join-xapi-devs>

Ultrasound

<https://github.com/ObjectIsAdvantag/xapi-samples/tree/master/controls/ultrasound>



Give users control to your devices' Ultrasound MaxVolume

- In-Room Control
- Macro-compatible

/!\ Pairing is disabled


custom message pushed to your devices' Touch10/DX interface as pairing is enabled / disabled.

Maze Game

<https://github.com/ObjectIsAdvantag/xapi-samples/tree/master/controls/maze-scores>

*End-to-end enriched
User Experience for
Meeting Rooms*


- In-Room Control
- macro



Play the Maze	Rules	Options
Score	1050	restart
Instructions	nothing here, let's continue exploring.	
Pick a direction	<div><div><</div><div>help</div><div>></div><div>^</div><div>v</div></div>	

Agenda with notifications

https://github.com/ObjectsAdvantag/xapi-samples/tree/master/controls/agenda_push



	Monday	Tuesday	Wednesday
11:30AM Classroom 2		ChatBots 101: design, code, deploy [DEVNET-2896]	push
12:30PM Classroom 2		Golang 101 for ITPros [DEVNET-1808]	push
03:30PM Workshop 5		Enhancing Meeting Rooms UX with xAPIs [DEVNET-2074]	push



Pushes session details to a Webex Teams space

- In-Room Control
- Javascript Macro
- HttpClient command
- Webex Bot account



Survey 06:42


Monday, 3:30PM: **Enhancing Meeting Rooms User Experience with xAPIs - DEVNET-2074** at Workshop 5
Join this workshop to go hands-on with CE - Cisco Collaboration Endpoint System - programmability. You'll learn to interact with a Spark-registered Collaboration device from the xAPI, and then implement an end-to-end application that will leverage the Room Analytics capability of RoomKit devices.

Interactive Live Map

<https://github.com/ObjectIsAdvantag/roomkit-react-map>

*Interactive map showing
PeopleCount analytics
from a set of Room Kits*

- React
- Node.js
- 'jsxapi'



xAPI module at DevNet

<https://developer.cisco.com/learning/modules/xapi-intro>

Introduction to Webex Devices Programmability

Discover how to customize and extend Webex Devices through xAPI – the API exposed by Cisco Collaboration Endpoint CE software. Learn to configure your device, start video calls from code, add Branding but also how to create custom In-Room Controls and deploy Macros on your devices. Go hands-on with a CE-capable device or a provided RoomKit sandbox. This module assumes you have some basic programming experience.

🕒 1 Hour 20 Minutes



💡 Introduction to xAPI for Cisco Collaboration Devices

Explore the programmability of Cisco Collaboration Devices and understand xAPI – the API exposed by Cisco TelePresence CE software.

💡 Creating Custom In-Room Controls and Macros

Learn how to create custom controls for Cisco Collaboration Devices, using the on-board control simulator tool and the in-room control editor. Then make those controls interactive via a server-based Node.js script, or an on-board JavaScript macro.

💡 Customizing Collaboration Devices from Code

Learn to customize display logos, signage and custom messages for Cisco Collaboration Devices via SSH, HTTP and Node.js/JavaScript.

Learn more about the new DevNet Certifications and how you can prepare now!

Associate Level

Specialist Level

Professional Level

Expert Level

Engineering



Software



Future
Offering

Complete your online session survey



- Please complete your session survey after each session. Your feedback is very important.
- Complete a minimum of 4 session surveys and the Overall Conference survey (starting on Thursday) to receive your Cisco Live t-shirt.
- All surveys can be taken in the Cisco Events Mobile App or by logging in to the Content Catalog on ciscolive.com/emea.

Cisco Live sessions will be available for viewing on demand after the event at ciscolive.com.

Continue your education



Demos in the
Cisco Showcase



Walk-In Labs



Meet the Engineer
1:1 meetings



Related sessions



Thank you





You make **possible**