

SOCKET_SERVER.c

```
GNU nano 8.7.1 SOCKET_PATH.c
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main(){
int server_fd, client_fd;
struct sockaddr_un address;
char buffer[100];

//create socket
server_fd = socket(AF_UNIX, SOCK_STREAM, 0);

//set socket address
address.sun_family = AF_UNIX;
strcpy(address.sun_path, SOCKET_PATH);

//Remove old path
unlink(SOCKET_PATH);

//Bind socket to path
bind(server_fd, (struct sockaddr *)&address, sizeof(address));

//Wait for client
listen(server_fd, 5);
printf("Server waiting...\n");

//Accept client
client_fd = accept(server_fd, NULL, NULL);

//Recieve Client
read(client_fd, buffer, sizeof(buffer));

printf("Message from client: %s\n", buffer);

close(client_fd);
close(server_fd);

unlink(SOCKET_PATH);

return 0;
}
```

Output:

```

nction it appears in
crazyguy64@CrazyGuy64:~$ nano SOCKET_PATH.c
crazyguy64@CrazyGuy64:~$ gcc SOCKET_PATH.c -o SOCKET_PATH
crazyguy64@CrazyGuy64:~$ ./SOCKET_PATH
Server waiting...
hello
Message from client: Hello Server
crazyguy64@CrazyGuy64:~$ hello
Command 'hello' not found, but can be installed with:
sudo snap install hello # version 2.10, or
sudo apt install hello # version 2.10-5build1
See 'snap info hello' for additional versions.
crazyguy64@CrazyGuy64:~$ ./SOCKET_PATH
Server waiting...
Message from client: Hello Server
crazyguy64@CrazyGuy64:~$
```

SOCKET_CLIENT.c

```
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main(){
int client_fd;
struct sockaddr_un address;

//Create Socket
client_fd = socket(AF_UNIX, SOCK_STREAM, 0);

//set socket address
address.sun_family = AF_UNIX;
strcpy(address.sun_path, SOCKET_PATH);

//Connect to server
connect(client_fd, (struct sockaddr *)&address, sizeof(address));

//send message
write(client_fd, "Hello Server", 12);

printf("Message sent to sever.\n");

close(client_fd);

return 0;
}
```

Output:

```
crazyguy64@CrazyGuy64:~$ nano SOCKET_CLIENT.c
crazyguy64@CrazyGuy64:~$ gcc SOCKET_CLIENT.c -o SOCKET_CLIENT
crazyguy64@CrazyGuy64:~$ ./SOCKET_CLIENT
Message sent to sever.
crazyguy64@CrazyGuy64:~$ ./SOCKET_CLIENT
Message sent to sever.
```