

# ACMT Example: Population density over distance (advanced)

Weipeng Zhou

2/22/2021

## Introduction

Automatic Context Measurement Tool (ACMT) is a convenient tool for studying neighbourhoods in the United States. Based on the user-provided address and radius, ACMT locates a geographical area and outputs context measurements (population, education level, commute time, etc.) for the area. ACMT is easy to install, highly reproducible and works consistently across computer platforms.

There are various ways of using ACMT and here we show one example – 5-city comparison of population density decay as function of distance from City Hall.

We use ACMT to get population densities for 5 cities (Seattle, Los Angeles, Chicago, New York and Boston) over 5 radiuses (1000, 2000, 3000, 4000, 5000). We consider the center of a city to be the location of its City Hall. We compute the density using the land area within a region only. After getting the densities, we make a plot of density over radius, categorized by cities; and we will be able to tell which city is the most populated across space. We also explore the relationship between population density and national walkability index.

We take the following steps:

1. Find the addresses of each city's City Hall
2. Use ACMT's geocoder to convert the addresses to coordinates
3. Use ACMT to get the population, land area and national walkability index measurement for each coordinate over 5 radiuses (1000, 2000, 3000, 4000, 5000)
4. Calculate population density
5. Plot density vs. radius, categorized by cities, as well as vs. walkability index.

## Example

### 1. Find the addresses of each city's City Hall

We have gathered the City Hall addresses for Seattle, Los Angeles, Chicago, New York and Boston from Google.

```
source("setup-acmt.R")

library(ggplot2)
city_hall_to_address_list <- list(
  seattle_city_hall="600 4th Ave, Seattle, WA 98104",
  los_angeles_city_hall="200 N Spring St, Los Angeles, CA 90012",
  chicago_city_hall="121 N LaSalle St, Chicago, IL 60602",
  new_york_city_hall="City Hall Park, New York, NY 10007",
```

```
boston_city_hall="1 City Hall Square #500, Boston, MA 02201"
)
```

## 2. Use ACMT's geocoder to convert the addresses to coordinates

ACMT comes with a handy geocoder that converts addresses to latitude/longitude coordinates. We check if geocoder is available in the version of ACMT you installed; if it is not available, we use the pre-computed coordinates.

```
convert_address_to_lat_long <- function (city_hall_to_address_list) { # function to get get lat/long for
  city_hall_to_lat_long_list <- vector(mode="list", length=length(city_hall_to_address_list))
  names(city_hall_to_lat_long_list) <- names(city_hall_to_address_list)
  for (name in names(city_hall_to_address_list)){
    city_hall_to_lat_long_list[[name]] <- geocode(city_hall_to_address_list[[name]])
  }
  return(city_hall_to_lat_long_list)
}
```

```
# is geocoder available?
geocoder_is_available <- FALSE
tryCatch({ # note that codes in try is not inside a new function, just treat it as normal R code
  geocode("1 City Hall Square #500, Boston, MA 02201")
  geocoder_is_available <- TRUE
}, error = function(condition) { # note that in error handler, the codes is inside a new function; thi
  print(condition$message)
  print("Geocoder not available: using stored address to lat/long mappings instead")
})
```

```
city_hall_to_lat_long_list <- NULL
# call geocoder if available, use hard coded info otherwise
if (geocoder_is_available) {
  city_hall_to_lat_long_list <- convert_address_to_lat_long(city_hall_to_address_list)
} else {
  city_hall_to_lat_long_list <- list(
    seattle_city_hall=list(latitude=47.60328, longitude=-122.3302),
    los_angeles_city_hall=list(latitude=34.05397, longitude=-118.2436),
    chicago_city_hall=list(latitude=41.88334, longitude=-87.63229),
    new_york_city_hall=list(latitude=40.66392, longitude=-73.93835),
    boston_city_hall=list(latitude=42.35773, longitude=-71.05919)
  )
}
```

```
print(city_hall_to_lat_long_list[1])
```

```
## $seattle_city_hall
## $seattle_city_hall$latitude
## [1] 47.60328
##
## $seattle_city_hall$longitude
## [1] -122.3302
```

### 3. Use ACMT to get the population measurement for each coordinate over 5 radiuses (1000, 2000, 3000, 4000, 5000)

We create a function for querying ACMT measurements for a list of coordinates and radiuses. We are interested in the variable `total_pop_count`.

```
# function to get the environmental measures for the variables we are intersted
get_variable_measures_from_acmt <- function (city_hall_to_lat_long_list, radius_vector, year, names_of_variable_to_get) {
  city_hall_to_radius_to_variable_to_measures_list <- vector(mode="list", length=length(city_hall_to_lat_long_list))
  names(city_hall_to_radius_to_variable_to_measures_list) <- names(city_hall_to_lat_long_list)

  for(city_hall in names(city_hall_to_radius_to_variable_to_measures_list)) {
    radius_to_variable_to_measures_list <- vector(mode="list", length=length(radius_vector))
    names(radius_to_variable_to_measures_list) <- as.character(radius_vector)
    for (radius in radius_vector) {
      print(city_hall)
      print(radius)
      # get lat/long
      latitude <- city_hall_to_lat_long_list[[city_hall]]$latitude
      longitude <- city_hall_to_lat_long_list[[city_hall]]$longitude

      # get environmental measures for all variables
      environmental_measures <- get_acmt_standard_array(long=longitude, lat=latitude, radius_meters = radius)

      # get environmental measures for the variables are intersted
      variable_to_measures_list <- vector(mode="list", length=length(names_of_variable_to_get))
      names(variable_to_measures_list) <- names_of_variable_to_get
      for (name_of_variable in names_of_variable_to_get) {
        value_of_variable <- environmental_measures[environmental_measures$names == name_of_variable, ]
        variable_to_measures_list[[name_of_variable]] <- value_of_variable
      }
      #radius_to_variable_to_measures_list[[which(radius == radius_vector)]] <- variable_to_measures_list
      radius_to_variable_to_measures_list[[as.character(radius)]] <- variable_to_measures_list
    }
    city_hall_to_radius_to_variable_to_measures_list[[city_hall]] <- radius_to_variable_to_measures_list
  }
  return(city_hall_to_radius_to_variable_to_measures_list)
}

city_hall_to_lat_long_list <- city_hall_to_lat_long_list
radius_vector <- c(1000, 2000, 3000, 4000, 5000)
year <- 2017
names_of_variable_to_get <- c("total_pop_count", "AC_UNPR", "NatWalkInd") # population, land area in a
codes_of_acs_variables_to_get <- c("B01001_001") # speed up; ask ACMT to only query this variable from
external_data_name_to_info_list <- list(# provide info for getting walkability data; we took a shortc
  walkability=list(vector_of_expected_downloaded_file_name=NULL,
    download_file=NULL,
    process_file=NULL,
    geoid_type="Block Group",
    variable_name_to_interpolate_by_sum_boolean_mapping=walkability_variable_name_

  )
)

start_time_get_variable_measures_from_acmt <- Sys.time()
```

```
city_hall_to_radius_to_variable_to_measures_list <- get_variable_measures_from_acmt(city_hall_to_lat_lon)
end_time_get_variable_measures_from_acmt <- Sys.time()
```

```
print(city_hall_to_radius_to_variable_to_measures_list[1])
```

```
## $seattle_city_hall
## $seattle_city_hall$`1000`
## $seattle_city_hall$`1000`$total_pop_count
## [1] 20044.58
##
## $seattle_city_hall$`1000`$AC_UNPR
## [1] 702.2545
##
## $seattle_city_hall$`1000`$NatWalkInd
## [1] 17.84299
##
##
## $seattle_city_hall$`2000`
## $seattle_city_hall$`2000`$total_pop_count
## [1] 65731.66
##
## $seattle_city_hall$`2000`$AC_UNPR
## [1] 2419.356
##
## $seattle_city_hall$`2000`$NatWalkInd
## [1] 17.54651
##
##
## $seattle_city_hall$`3000`
## $seattle_city_hall$`3000`$total_pop_count
## [1] 124582.8
##
## $seattle_city_hall$`3000`$AC_UNPR
## [1] 5253.051
##
## $seattle_city_hall$`3000`$NatWalkInd
## [1] 17.03588
##
##
## $seattle_city_hall$`4000`
## $seattle_city_hall$`4000`$total_pop_count
## [1] 171717.8
##
## $seattle_city_hall$`4000`$AC_UNPR
## [1] 8532.673
##
## $seattle_city_hall$`4000`$NatWalkInd
## [1] 16.73855
##
##
## $seattle_city_hall$`5000`
## $seattle_city_hall$`5000`$total_pop_count
## [1] 212564.4
##
```

```
## $seattle_city_hall$`5000`$AC_UNPR
## [1] 12280.61
##
## $seattle_city_hall$`5000`$NatWalkInd
## [1] 16.5113
print("Between start and end of getting ACMT measures: ")

## [1] "Between start and end of getting ACMT measures: "
print(end_time_get_variable_measures_from_acmt - start_time_get_variable_measures_from_acmt)

## Time difference of 39.61673 mins
```

#### 4. Calculate population density

We create a function for computing population density for the given radiues.

```
add_density_measures <- function(city_hall_to_radius_to_variable_to_measures_list) {
  city_hall_to_radius_to_variable_to_measures_with_population_density_list <- city_hall_to_radius_to_variable_to_measures_list
  for (city_hall in names(city_hall_to_radius_to_variable_to_measures_with_population_density_list)){
    for(radius_character in names(city_hall_to_radius_to_variable_to_measures_with_population_density_list[[city_hall]])){
      for(variable in names(city_hall_to_radius_to_variable_to_measures_with_population_density_list[[city_hall]][radius_character])){
        if(variable == "total_pop_count"){ # add other "if" statements if you want to compute other measures
          total_pop_count <- city_hall_to_radius_to_variable_to_measures_with_population_density_list[[city_hall]][radius_character][variable]
          #radius_numeric <- as.numeric(radius_character) # do not use radius
          population_density <- total_pop_count/(city_hall_to_radius_to_variable_to_measures_with_population_density_list[[city_hall]][radius_character][variable])
          city_hall_to_radius_to_variable_to_measures_with_population_density_list[[city_hall]][radius_character][variable] <- population_density
        }
      }
    }
  }
  return(city_hall_to_radius_to_variable_to_measures_with_population_density_list)
}
```

```
city_hall_to_radius_to_variable_to_measures_with_population_density_list <- add_density_measures(city_hall_to_radius_to_variable_to_measures_list)
print(city_hall_to_radius_to_variable_to_measures_with_population_density_list[1:2])
```

```
## $seattle_city_hall
## $seattle_city_hall$`1000`
## $seattle_city_hall$`1000`$total_pop_count
## [1] 20044.58
##
## $seattle_city_hall$`1000`$AC_UNPR
## [1] 702.2545
##
## $seattle_city_hall$`1000`$NatWalkInd
## [1] 17.84299
##
## $seattle_city_hall$`1000`$population_density
## [1] 0.00705316
##
##
## $seattle_city_hall$`2000`
## $seattle_city_hall$`2000`$total_pop_count
```

```

## [1] 65731.66
##
## $seattle_city_hall$`2000`$AC_UNPR
## [1] 2419.356
##
## $seattle_city_hall$`2000`$NatWalkInd
## [1] 17.54651
##
## $seattle_city_hall$`2000`$population_density
## [1] 0.00671361
##
##
## $seattle_city_hall$`3000`
## $seattle_city_hall$`3000`$total_pop_count
## [1] 124582.8
##
## $seattle_city_hall$`3000`$AC_UNPR
## [1] 5253.051
##
## $seattle_city_hall$`3000`$NatWalkInd
## [1] 17.03588
##
## $seattle_city_hall$`3000`$population_density
## [1] 0.005860405
##
##
## $seattle_city_hall$`4000`
## $seattle_city_hall$`4000`$total_pop_count
## [1] 171717.8
##
## $seattle_city_hall$`4000`$AC_UNPR
## [1] 8532.673
##
## $seattle_city_hall$`4000`$NatWalkInd
## [1] 16.73855
##
## $seattle_city_hall$`4000`$population_density
## [1] 0.004972921
##
##
## $seattle_city_hall$`5000`
## $seattle_city_hall$`5000`$total_pop_count
## [1] 212564.4
##
## $seattle_city_hall$`5000`$AC_UNPR
## [1] 12280.61
##
## $seattle_city_hall$`5000`$NatWalkInd
## [1] 16.5113
##
## $seattle_city_hall$`5000`$population_density
## [1] 0.004277123
##
##

```

```

##
## $los_angeles_city_hall
## $los_angeles_city_hall$`1000`
## $los_angeles_city_hall$`1000`$total_pop_count
## [1] 20247.35
##
## $los_angeles_city_hall$`1000`$AC_UNPR
## [1] 761.6894
##
## $los_angeles_city_hall$`1000`$NatWalkInd
## [1] 16.64763
##
## $los_angeles_city_hall$`1000`$population_density
## [1] 0.006568582
##
##
## $los_angeles_city_hall$`2000`
## $los_angeles_city_hall$`2000`$total_pop_count
## [1] 75624.11
##
## $los_angeles_city_hall$`2000`$AC_UNPR
## [1] 2973.994
##
## $los_angeles_city_hall$`2000`$NatWalkInd
## [1] 15.82125
##
## $los_angeles_city_hall$`2000`$population_density
## [1] 0.006283499
##
##
## $los_angeles_city_hall$`3000`
## $los_angeles_city_hall$`3000`$total_pop_count
## [1] 157247.2
##
## $los_angeles_city_hall$`3000`$AC_UNPR
## [1] 6435.669
##
## $los_angeles_city_hall$`3000`$NatWalkInd
## [1] 15.59502
##
## $los_angeles_city_hall$`3000`$population_density
## [1] 0.006037686
##
##
## $los_angeles_city_hall$`4000`
## $los_angeles_city_hall$`4000`$total_pop_count
## [1] 303410.8
##
## $los_angeles_city_hall$`4000`$AC_UNPR
## [1] 11442.5
##
## $los_angeles_city_hall$`4000`$NatWalkInd
## [1] 15.48465
##

```

```
## $los_angeles_city_hall$`4000`$population_density
## [1] 0.006552263
##
##
## $los_angeles_city_hall$`5000`
## $los_angeles_city_hall$`5000`$total_pop_count
## [1] 490979.8
##
## $los_angeles_city_hall$`5000`$AC_UNPR
## [1] 18032.81
##
## $los_angeles_city_hall$`5000`$NatWalkInd
## [1] 15.23306
##
## $los_angeles_city_hall$`5000`$population_density
## [1] 0.006727933
```

## 5. Plot density vs. radius, categorized by cities

We create a function for converting the data we have so far to `ggplot` friendly format. We then use `ggplot` to create our plot.

```
convert_to_dataframe_for_plotting <- function (city_hall_to_radius_to_variable_to_measures_with_population_density_list){
  city_hall_vector <- c()
  radius_vector <- c()
  variable_vector <- c()
  value_vector <- c()

  for(city_hall in names(city_hall_to_radius_to_variable_to_measures_with_population_density_list)){
    for(radius_character in names(city_hall_to_radius_to_variable_to_measures_with_population_density_list[[city_hall]])){
      for(variable in names(city_hall_to_radius_to_variable_to_measures_with_population_density_list[[city_hall]][[radius_character]])){
        city_hall_vector <- c(city_hall_vector, city_hall)
        radius_vector <- c(radius_vector, as.numeric(radius_character))
        variable_vector <- c(variable_vector, variable)
        value_vector <- c(value_vector, city_hall_to_radius_to_variable_to_measures_with_population_density_list[[city_hall]][[radius_character]][[variable]])
      }
    }
  }

  dataframe_for_plotting <- data.frame(city_hall_vector, radius_vector, variable_vector, value_vector, stringsAsFactors = FALSE)
  names(dataframe_for_plotting) <- c("city_hall", "radius", "variable", "value")
  return(dataframe_for_plotting)
}
```


```
dataframe_for_plotting <- convert_to_dataframe_for_plotting(city_hall_to_radius_to_variable_to_measures_with_population_density_list)
```

```
print(head(dataframe_for_plotting))
```


```
##           city_hall radius      variable      value
## 1 seattle_city_hall  1000    total_pop_count 2.004458e+04
## 2 seattle_city_hall  1000         AC_UNPR 7.022545e+02
## 3 seattle_city_hall  1000      NatWalkInd 1.784299e+01
## 4 seattle_city_hall  1000 population_density 7.053160e-03
## 5 seattle_city_hall  2000    total_pop_count 6.573166e+04
## 6 seattle_city_hall  2000         AC_UNPR 2.419356e+03
```



```
ggplot(dataframe_for_plotting[dataframe_for_plotting$variable == "population_density", ], aes(x=radius)) +
  geom_line(aes(y=value, col=city_hall)) +
  labs(y="population density (people/m^2)",
       x="radius (m)")
```



```
ggplot(dataframe_for_plotting[dataframe_for_plotting$variable == "NatWalkInd", ], aes(x=radius)) +
  geom_line(aes(y=value, col=city_hall)) +
  labs(y="national walkability index",
       x="radius (m)")
```



## Results

We see that New York City still has a much higher population density than others, but its density reduction is less drastic than we saw when not using land area to calculate population density. Also, because of the use of land area as denominator, the population density of all cities all increased, and LA increased the least because other cities have a higher proportion of water and thus benefits more from switching from using a circular area as denominator to using land area.

Regarding to the walkability index, we see New York City is again at the top. According to the definition of walkability index, New York City has high mix of employment types and occupied housing, mix of employment types, street intersection density, and proportion of carpool workers (<https://www.epa.gov/smartgrowth/smart-location-mapping#:~:text=National%20Walkability%20Index%20score.,results%20of%20indicator%20rank%20scores.&text=>