


Recap and biological replicates

Sandra Cortijo sandra.cortijo@slcu.cam.ac.uk

Sergio Martinez Cuesta sermarcue@gmail.com

Ashley Sawle Ashley.Sawle@cruk.cam.ac.uk

Denis Seyres Denis.seyres@bioresource.nihr.ac.uk



- Quality check
- Alignment
- Filtering
- Peak calling
- Peak annotation
- Sequence motif discovery
- Signal (non-peak) analysis
- Visualisation

fastqc

bwa, bowtie

samtools

macs2

ChIPseeker

MEME tools

deepTools

IGV


Do we need replicates?

To ensure that ChIP-seq experiments are reproducible and to test their validity we need **at least 2 replicates**

Do we need replicates?

To ensure that ChIP-seq experiments are reproducible and to test their validity we need **at least 2 replicates**


Technical vs. biological replicates



Do we need replicates?

To ensure that ChIP-seq experiments are reproducible and to test their validity we need **at least 2 replicates**

Technical vs. biological replicates



Increase the significance of peaks by using more replicates

Do we need replicates?

In ChIP-seq, what is the overlap between replicate peaks?

Do we need replicates?

In ChIP-seq, what is the overlap between replicate peaks?

To investigate the agreement between replicates: you can also use the method known as **Irreproducible Discovery Rate (IDR) analysis**

Do we need replicates?

In ChIP-seq, what is the overlap between replicate peaks?

To investigate the agreement between replicates: you can also use the method known as **Irreproducible Discovery Rate (IDR) analysis**

- Two replicates are similar if the ranking of significant peaks (by p-value) is consistent between the two replicates in comparison to the ranking of less significant peaks (noise)

Do we need replicates?




In ChIP-seq, what is the overlap between replicate peaks?

To investigate the agreement between replicates: you can also use the method known as **Irreproducible Discovery Rate (IDR) analysis**

- Two replicates are similar if the ranking of significant peaks (by p-value) is consistent between the two replicates in comparison to the ranking of less significant peaks (noise)




Developed in Qunhua Li and Peter Bickel as part of the ENCODE project

IDR




reasonable
consistency

IDR



reasonable
consistency

IDR






The IDR score represents the *probability of a peak to belong to the irreproducible group*



consistency

IDR



poor
consistency

IDR

The method compares two lists of ChIP-seq peaks, and statistically assesses the point where the ranking in the list is no longer conserved between the replicates (**decay point**).

IDR

The method compares two lists of ChIP-seq peaks, and statistically assesses the point where the ranking in the list is no longer conserved between the replicates (**decay point**).

Li and Bickel have used this principle to define numerical cutoffs on peaks called after merging the replicates (**IDR thresholds**) where an IDR of 0.05 means that there is a 5% chance that a called peak is irreproducible.