

Binary search

```
#include <iostream>
```

```
using namespace std;
```

```
int main()
```

```
{
```

```
    int a[20], n, key, low, high, mid;
```

```
    bool found = false;
```

```
    cout << "Enter number of elements: ";
```

```
    cin >> n;
```

```
    cout << "Enter elements in sorted order:\n";
```

```
    for(int i = 0; i < n; i++)
```

```
        cin >> a[i];
```

```
    cout << "Enter key to search: ";
```

```
    cin >> key;
```

```
    low = 0;
```

```
    high = n - 1;
```

```
    while(low <= high)
```

```
    {
```

```
        mid = (low + high) / 2;
```

```

    if(a[mid] == key)
    {
        cout << "Key found at position " << mid + 1;

        found = true;

        break;
    }

    else if(key < a[mid])

        high = mid - 1;

    else

        low = mid + 1;
}

if(!found)

    cout << "Key not found";

return 0;
}

```

Linear search

```
#include<iostream>
```

```
using namespace std;
```

```

int main() {

    int i, n, key, sk, a[20];

    bool status = false;

```

```
cout << "Enter number of array elements and search key: ";
```

```
cin >> n >> sk;
```

```
cout << "Enter elements:\n";
```

```
for (i = 0; i < n; i++) {
```

```
    cin >> a[i];
```

```
}
```

```
for (i = 0; i < n; i++) {
```

```
    if (a[i] == sk) {
```

```
        cout << "sk found at " << i + 1 << endl;
```

```
        status = true;
```

```
        break;
```

```
    }
```

```
}
```

```
if (!status) {
```

```
    cout << "Key not found" << endl;
```

```
}
```

```
return 0;
```

```
}
```

Selection sort

```
#include <iostream>
```

```
using namespace std;
```

```
int main() {
```

```
    int n;
```

```
    cout << "Enter number of elements: ";
```

```
    cin >> n;
```

```
    int arr[n];
```

```
    cout << "Enter elements:\n";
```

```
    for (int i = 0; i < n; i++) {
```

```
        cin >> arr[i];
```

```
    }
```

```
    // Selection sort using nested loops
```

```
    for (int i = 0; i < n; i++) {
```

```
        for (int j = i + 1; j < n; j++) {
```

```
            if (arr[i] > arr[j]) {
```

```
                // Swap immediately
```

```
                int temp = arr[i];
```

```
                arr[i] = arr[j];
```

```
                arr[j] = temp;
```

```
            }
```

```
        }
```

```
    }
```

```

    cout << "Sorted array:\n";

    for (int i = 0; i < n; i++) {

        cout << arr[i] << " ";

    }

    cout << endl;


    return 0;

}

Insertion sort

#include <iostream>

using namespace std;

int main() {

    int n;

    cout << "Enter number of elements: ";

    cin >> n;


    int arr[n];

    cout << "Enter elements:\n";

    for (int i = 0; i < n; i++) {

        cin >> arr[i];

    }


    // Insertion Sort using nested loops

    for (int i = 1; i < n; i++) {

```

```

    for (int j = i; j > 0; j--) {
        if (arr[j] < arr[j - 1]) {
            // Swap elements

            int temp = arr[j];

            arr[j] = arr[j - 1];

            arr[j - 1] = temp;
        }
    }
}

```

```

cout << "Sorted array:\n";
for (int i = 0; i < n; i++) {
    cout << arr[i] << " ";
}

cout << endl;

```

```

    return 0;
}

```

Singlr ll-insertion

```
#include <iostream>
```

```
using namespace std;
```

```
class node {
```

```
public:
```

```
    int data;
```

```

    node *link;

};

int main() {

    node *h = NULL, *cn = NULL, *t = NULL;

    int val, ch;

    // Creating initial linked list

    do {

        cn = new node();

        cout << "Enter node data: ";

        cin >> val;

        cn->data = val;

        cn->link = NULL;

        if (h == NULL) {

            h = cn;

            t = cn;

        } else {

            t->link = cn;

            t = cn;

        }

        cout << "\nDo you want to continue 1/0: \n";

        cin >> ch;

    } while (ch);

```

```

// Display original linked list data

cout << "\nLinked list data:\n";

t = h;

while (t != NULL) {

    cout << t->data << " -> ";

    t = t->link;

}

cout << "NULL\n";


// Insertion at starting

t = h;

cn = new node();

cout << "\nEnter node data to insert at beginning:\n";

cin >> val;

cn->data = val;

cn->link = t;

h = cn;


// Display linked list data after insertion

cout << "\nLinked list data after insertion operation:\n";

t = h;

while (t != NULL) {

    cout << t->data << " -> ";

    t = t->link;

```



```

    }

    cout << "NULL\n";

    return 0;
}

Single ll-deletion

#include <iostream>

using namespace std;

class node {
public:
    int data;
    node *link;
};

int main() {

    node *h = NULL, *cn = NULL, *t = NULL;

    int val, ch;

    // Creating initial linked list
    do {

        cn = new node();

        cout << "Enter node data: ";

        cin >> val;

        cn->data = val;

```

```
cn->link = NULL;

if (h == NULL) {
    h = cn;
    t = cn;
} else {
    t->link = cn;
    t = cn;
}

cout << "\nDo you want to continue 1/0:\n";
cin >> ch;
} while (ch);
```

```
// Display original linked list data
```

```
cout << "\nLinked list data:\n";
```

```
t = h;
```

```
while (t != NULL) {
```

```
    cout << t->data << " -> ";
```

```
    t = t->link;
```

```
}
```

```
cout << "NULL\n";
```

```
// Deletion at starting
```

```
if (h != NULL) {
```

```
    t = h;
```

```

        h = h->link;

        t->link = NULL;

        delete t;

        cout << "\nDeletion completed at beginning.\n";
    } else {

        cout << "\nList is empty, deletion not possible.\n";

    }

    // Display linked list data after deletion

    cout << "\nLinked list data after deletion operation:\n";

    t = h;

    while (t != NULL) {

        cout << t->data << " -> ";

        t = t->link;

    }

    cout << "NULL\n";

    return 0;

}

```

Stack arrays

```
#include <iostream>
```

```
using namespace std;
```

```
int main()
```

```
{
```

```
int s[10], size, item, top = -1, op;
```

```
cout << "Enter size of the stack: ";
```

```
cin >> size;
```

```
do {
```

```
    cout << "\n1: PUSH\n2: POP\n3: PEEK\n4: DISPLAY\n5: EXIT\nCHOOSE ANY ONE OPTION: ";
```

```
    cin >> op;
```

```
    switch (op) {
```

```
        case 1:
```

```
            if (top == size - 1) {
```

```
                cout << "Stack is overflow\n";
```

```
            } else {
```

```
                top = top + 1;
```

```
                cout << "\nEnter stack elements: ";
```

```
                cin >> item;
```

```
                s[top] = item;
```

```
            }
```

```
            break;
```

```
        case 2:
```

```
            if (top == -1) {
```

```
                cout << "Stack is underflow\n";
```

```
            } else {
```

```
                cout << s[top] << " is popped\n";
```

```
    top = top - 1;
```

```
}
```

```
break;
```

case 3:

```
if (top == -1) {
```

```
    cout << "Stack is underflow\n";
```

```
} else {
```

```
    cout << s[top] << " is top element\n";
```

```
}
```

```
break;
```

case 4:

```
if (top == -1) {
```

```
    cout << "Stack is underflow\n";
```

```
} else {
```

```
    cout << "Stack Elements:\n";
```

```
    for (int i = top; i >= 0; i--) {
```

```
        cout << s[i] << " ";
```

```
    }
```

```
    cout << "\n";
```

```
}
```

```
break;
```

case 5:

```
exit(0);
```

default:

```
cout << "Invalid option\n";
```

```

    }

    cout << "Do you want to continue 1/0? ";

    cin >> op;

} while (op);

return 0;

}

```

Stack linked list

```

#include <iostream>

using namespace std;

```

```

class node {

public:

    int data;

    node *link;

};

```

```

int main() {

    node *top = NULL, *cn = NULL, *t = NULL;

    int val, op;

    do {

        cout << "\n1: PUSH\n2: POP\n3: PEEK\n4: DISPLAY\n5: EXIT\nCHOOSE ANY ONE OPTION: ";

        cin >> op;
    }
}

```

```
switch (op) {  
    case 1:  
        cn = new node();  
        cout << "\nEnter node data: ";  
        cin >> val;  
        cn->data = val;  
        cn->link = NULL;  
  
        if (top == NULL) {  
            top = cn;  
            t = cn;  
        } else {  
            cn->link = top;  
            top = cn;  
        }  
        break;  
  
    case 2:  
        if (top == NULL) {  
            cout << "Stack is underflow\n";  
        } else {  
            cout << top->data << " is popped\n";  
            t = top;  
            top = top->link;  
            t->link = NULL;  
        }  
    }  
}
```

```
        delete t;  
    }  
    break;
```

case 3:

```
    if (top == NULL) {  
        cout << "Stack is underflow\n";  
    } else {  
        cout << top->data << " is top node value\n";  
    }  
    break;
```

case 4:

```
    if (top == NULL) {  
        cout << "Stack is underflow\n";  
    } else {  
        t = top;  
        while (t != NULL) {  
            cout << t->data << " ";  
            t = t->link;  
        }  
        cout << "\n";  
    }  
    break;
```


case 5:

exit(0);

default:

cout << "Invalid option\n";

}

cout << "Do you want to continue 1/0? ";

cin >> op;

} while (op);

return 0;

}

Queue (arrays)

#include <iostream>

using namespace std;

int main() {

int q[100], item, f = -1, r = -1, size, choice, cont;

cout << "\nEnter size of Queue: ";

cin >> size;

do {

cout << "\n1: Enqueue\n2: Dequeue\n3: Peek\n4: Display\n5: Exit\n";

cout << "\nChoose any one option: ";

```
cin >> choice;
```

```
switch (choice) {
```

```
    case 1:
```

```
        if (r == size - 1) {
```

```
            cout << "\nQueue Overflow\n";
```

```
        } else {
```

```
            if (f == -1) {
```

```
                f = 0;
```

```
            }
```

```
            cout << "Enter item: ";
```

```
            cin >> item;
```

```
            r++;
```

```
            q[r] = item;
```

```
        }
```

```
        break;
```

```
    case 2:
```

```
        if (f == -1 || f > r) {
```

```
            cout << "\nQueue Underflow\n";
```

```
        } else {
```

```
            cout << "\nDeleted item: " << q[f] << endl;
```

```
            f++;
```

```
            if (f > r) { // Reset queue configuration if empty
```

```
                f = r = -1;
```

```
    }  
}  
  
break;
```

case 3:

```
if (f == -1 || f > r) {  
    cout << "\nQueue Underflow/Empty\n";  
} else {  
    cout << "\nFront element: " << q[f] << endl;  
}  
  
break;
```

case 4:

```
if (f == -1 || f > r) {  
    cout << "\nQueue Underflow\n";  
} else {  
    cout << "\nQueue elements: ";  
    for (int i = f; i <= r; i++) {  
        cout << q[i] << " ";  
    }  
    cout << "\n";  
}  
  
break;
```

case 5:

```
exit(0);
```

```
default:
```

```
cout << "\nInvalid option\n";
```

```
}
```

```
cout << "\nEnter 1 to continue OR 0 to exit: ";
```

```
cin >> cont;
```

```
} while (cont);
```

```
return 0;
```

```
}
```

```
Queue(linked list)
```

```
#include <iostream>
```

```
using namespace std;
```

```
class node {
```

```
public:
```

```
int data;
```

```
node *link;
```

```
};
```

```
int main() {
```

```
node *f = NULL, *r = NULL, *cn = NULL, *t = NULL;
```

```
int ch;
```

```

do {

    cout << "\n1: Enqueue\n2: Dequeue\n3: Peek\n4: Display\n5: Exit\n";

    cout << "\nEnter your choice: ";

    cin >> ch;

    switch (ch) {

        case 1: // Enqueue

            cn = new node();

            cout << "Enter item: ";

            cin >> cn->data;

            cn->link = NULL;

            if (f == NULL) {

                f = r = cn;

            } else {

                r->link = cn;

                r = cn;

            }

            cout << cn->data << " is inserted into Queue\n";

            break;

        case 2: // Dequeue

            if (f == NULL) {

                cout << "\nQueue Underflow\n";

```

```
} else {  
  
    t = f;  
  
    cout << "\nDeleted item: " << t->data << endl;  
  
    f = f->link;  
  
    delete t;  
  
    if (f == NULL) {  
  
        r = NULL;  
  
    }  
}  
  
break;
```

case 3: // Peek

```
if (f == NULL) {  
  
    cout << "\nQueue is empty\n";  
  
} else {  
  
    cout << "\nFront element: " << f->data << endl;  
  
}  
  
break;
```

case 4: // Display

```
if (f == NULL) {  
  
    cout << "\nQueue is empty\n";  
  
} else {  
  
    t = f;  
  
    cout << "\nQueue elements: ";
```

```
        while (t != NULL) {  
            cout << t->data << " ";  
            t = t->link;  
        }  
        cout << "\n";  
    }  
    break;  
  
    case 5:  
        cout << "\nExiting...\n";  
        exit(0);  
  
    default:  
        cout << "\nInvalid choice\n";  
    }  
  
    cout << "\nEnter 1 to continue 0 to Exit: ";  
    cin >> ch;  
} while (ch);  
  
return 0;  
}
```