

26/11/25

1. Write a function to print Sum of digits. input: 234
output: 9.

C

```
#include <stdio.h>
```

```
#include <conio.h>
```

```
void print sum of digits (int n) {
```

```
    int sum = 0;
```

```
    while (n > 0) {
```

```
        sum += n % 10;
```

```
    // get last digit.
```

```
        n /= 10;
```

```
    // remove last digit.
```

```
}
```

```
    printf("Sum of digits = %d", sum);
```

```
}
```

```
int main () {
```

```
    int num;
```

```
    printf("Enter a number: ");
```

```
    scanf("%d", &num);
```

```
    print sum of digits (num);
```

```
return 0;
```

```
}
```

Example

Input - 234

output : Sum of digits = 9.

2. Write a C program to reverse given number using functions. Input: 123, output: 321.

```
#include <stdio.h>
```

```
#include <conio.h>
```

```
// Function to reverse the number.
```

```
int reverse number (int num) {
```

```
int rev = 0, digit;
```

```
while (num != 0) {
```

```
digit = num % 10;
```

```
// extract last digit
```

```
rev = rev * 10 + digit;
```

```
// build reversed number.
```

```
num /= 10;
```

```
// remove last digit.
```

```
}
```

```
return rev;
```

```
}
```

```
int main ( ) {
```

```
int n, reversed;
```

```
printf("Enter a number:");
```

```
scanf("%d", &n);
```

```
reversed = reverse number (n);
```

```
printf("Reversed number : %d \n", reversed);
```

```
return 0;
```

```
}
```

Input :- Enter a number = 123

output :- Reversed number = 321.

3. Swap two numbers with using third variable.
Input a=10, b=20, output : a=20, b=10.

```
#include <stdio.h>
```

```
#include <conio.h>
```

```
int main ( ) {
```

```
int a, b, temp;
```

```
printf("Enter two numbers :");
```

```
scanf("%d %d", &a, &b);
```

```
temp = a;
```

```
// store a in temp
```

```
a = b;
```

```
// assign b to a.
```

b = temp;

// assign temp (old a) to b.

printf("After Swapping : a = %d, b = %d", a, b);

return 0;

}

Input :- a = 10, b = 20.

Output :- a = 20, b = 10.