

① 20 MCQs on increment/decrement.

1. What is the value of 'x' after the statement `int x=5`

`x++`?

: ?

- A. 4 B. 5 C. 6 D. 7.

Ans:- C.

2. What is the result of `++x`?

- A. increment after use. B. Increment before use.
C. Decrement before use. D. No change.

Ans:- B.

3. What is the out put?

```
C    int x=10;
```

```
     printf("%i", x++);
```

A. 10 B. 11 C. 9 D. Undefined.

Ans :- A.

4. What is the out put?

```
C int x=10;
```

```
printf("%d", ++x);
```

A. 10 B. 11 C. 9 D. Undefined.

Ans :- B.

5. What does x-- do?

A. Decrements x before use. B. Decrements x after use.

C. Increments x after use. D. Increments x before use.

Ans :- B.

6. What is the out put?

```
C int x=5;
```

```
printf("%d", --x);
```

A. 5 B. 4 C. 6 D. Undefined.

Ans :- B.

7. What is the output?

```
C int x=5;
```

```
printf("%d", x--);
```

A. 4 B. 5 C. 6 D. Undefined.

Ans :- B.

8. Which of the following modifies the variable before its value is used?

A. $x++$ B. $++x$ C. $x---$ D. (A) and (C).

Ans:- B.

9. What is the output?

```
C
int a=3, b;
b = a++ + ++a;
printf("%d", b);
```

A. 7 B. 8 C. 9 D. Undefined behaviour.

Ans:- D. (Because, a is modified twice without a sequence point).

10. What is the output?

```
C
int x=2;
int y = x++ + ++x;
printf("%d", y);
```

A. 6 B. 8 C. 4 D. Undefined behaviour.

Ans:- D.

11. Which operator has higher precedence?

A. $++$ (Post) B. $++$ (Pre) C. Both have same precedence.
D. Depends on compiler.

Ans:- C.

12. Which of the following is NOT valid?

- A. ++x B. x++ C. x++++ D. --x

Ans:- C.

13. What is the output?

```
C int i = 1;
```

```
printf("%d %d", i++, ++i);
```

- A. 12 B. 22 C. 13 D. undefined behaviour.

Ans:- D.

14. What is the result of --(--x)?

- A. valid B. Invalid C. Depends on value of x
D. performs two decrements;

Ans :- B (You cannot apply operators directly like that).

15. What is the output?

```
C int x = 4;
```

```
x = x++ + 1;
```

```
printf("%d", x);
```

- A. 4 B. 5 C. 6 D. undefined behaviour.

Ans:- C (Most compilers evaluate x++ first then add 1).

16. Which of the following correctly increments a pointer?

- A. p+ B. ++p C. p+- D. p++--

Ans:- B.

17. What is the output?

A. C

```
int x=10;
```

```
printf("%d", ++x + x++);
```

A. 21

B. 22

C. 20

D. Undefined behaviour.

Ans:- D.

18. What is the output?

C

```
int x=0;
```

```
printf("%d", x++ + ++x);
```

A. 0

B. 1

C. 2

D. Undefined behaviour.

Ans:- C

19. What is the output?

```
int x=5;
```

```
int y = --x + --x;
```

```
printf("%d", y);
```

A. 7

B. 8

C. 9

D. Undefined error.

Ans:- D.

20. Which operator decreases value before using it?

A. x--

B. --x

C. x++

D. none.

Ans:- B.