

1, write a function to print sum of digits
Input: 234, output: 9.

```
#include <stdio.h>
#include <conio.h>

void print sum of digits (int n) {
```

```
    int sum = 0;
```

```
    while (n > 0) {
```

```
        sum += n % 10;
```

```
        // get last digit
```

```
        n /= 10;
```

```
        // remove last digit
```

```
    printf ("Sum of digits = %d", sum);
```

```
    int main () {
```

```
        int num;
```

```
        printf ("Enter a number: ");
```

```
        scanf ("%d", &num);
```

```
        print sum of digits (num);
```

```
        return 0;
```

```
    }
```

Input = 234

Output = 9.

2, write a C program to reverse given number using function. Input : 123, Output : 321

```
#include <stdio.h>

int reverse (int n) {
    while
    int rev = 0;
    while (n > 0) {
        rev = rev * 10 + (n % 10);
        n = n / 10;
    }
    return rev;
}

int main () {
    int num;
    printf ("Enter a number: ");
    scanf ("%d", &num);
    printf ("Reversed number: %d",
    reverse (num));
    return 0;
}
```

Input : 123

Output : 321

2, Swap two numbers with using third variable.
Input a=10, b=20 output a=20, b=10.

```
#include <stdio.h>
```

```
int main () {
```

```
int a=10, b=20, temp;
```

```
printf("Before Swapping: a=%d, b=%d\n", a, b);
```

```
temp = a;
```

```
a = b;
```

```
b = temp;
```

```
printf("After Swapping: a=%d, b=%d\n", a, b);
```

```
return 0;
```

```
}
```

Output

Before Swapping = a=10, b=20

After Swapping = a=20, b=10.

Conclusion

0 numbers

Input: 10