

1. Which of the following is a valid C variable name?

- A) 1variable
- B) variable_1
- C) variable-1
- D) variable 1

Answer: B) variable_1

Explanation: Variable names can contain letters, digits, and underscores, but cannot start with a digit or contain spaces or hyphens.

2. Which of the following is not a valid data type in C?

- A) int
- B) float
- C) real
- D) char

Answer: C) real

Explanation: C does not have a data type called real. Use float or double for real numbers.

3. What is the size of an int in most modern C compilers?

- A) 2 bytes
- B) 4 bytes
- C) 8 bytes
- D) Depends on the compiler

Answer: D) Depends on the compiler

Explanation: The size of int can vary depending on the system architecture and compiler (usually 4 bytes).

4. What is the output of the following code?

```
int a = 5, b = 2;  
printf("%d", a / b);
```

- A) 2.5
- B) 2
- C) 3
- D) Error

Answer: B) 2

Explanation: Integer division truncates the decimal part.

5. Which of the following is the correct syntax for if statement?

- A) if condition then statement;
- B) if (condition) statement;
- C) if condition { statement; }
- D) if (condition);

Answer: B) if (condition) statement;

Explanation: The correct syntax uses parentheses around the condition.

6. Which function is used to read a single character from the user?

- A) scanf()
- B) getchar()
- C) get()
- D) gets()

Answer: B) getchar()

Explanation: getchar() reads one character from standard input

7. What is the correct syntax to declare a pointer in C?

- A) int ptr;
- B) int *ptr;
- C) int ptr;
- D) ptr int;

Answer: B) int *ptr;

Explanation: * is used to declare a pointer.

8. What will be the output of this code?

```
int a = 10;  
printf("%d", a++);
```

- A) 10
- B) 11
- C) 9
- D) Undefined

Answer: A) 10

Explanation: Post-increment prints a first, then increases its value.

9. Which of the following loops is guaranteed to execute at least once?

- A) for
- B) while
- C) do...while
- D) None

Answer: C) do...while

Explanation: do...while checks the condition after executing the loop body once.

10. What is the output of this code?

```
printf("%d", 5 == 5);
```

- A) true
- B) false
- C) 1
- D) 0

Answer: C) 1

Explanation: In C, true is represented as 1.

11. Which header file is needed for using printf() and scanf()?

- A) stdlib.h
- B) stdio.h
- C) conio.h
- D) string.h

Answer: B) stdio.h

Explanation: Input/output functions are declared in stdio.h

12. What will sizeof(char) return?

- A) 2
- B) 4
- C) 1
- D) Depends on system

Answer: C) 1

Explanation: A char always occupies 1 byte.

13. What is the output of this code?

```
int x = 10;  
int y = ++x;  
printf("%d %d", x, y);
```

- A) 10 10
- B) 11 11
- C) 10 11
- D) 11 10

Answer: B) 11 11

Explanation: Pre-increment increases the value before assignment.

14. Which operator is used to access the value at the address stored in a pointer?

- A) &
- B) *
- C) ->
- D) %

Answer: B) *

Explanation: The dereference operator * is used to access the value at the pointer's address.

15. What is the output of this code?

```
int a = 5;  
if (a = 0)  
    printf("Zero");  
else  
    printf("Non-zero");
```

- A) Zero
- B) Non-zero
- C) Error
- D) No output

Answer: B) Non-zero

Explanation: a = 0 is an assignment, not comparison. It assigns 0 to a (which is false), so the else part runs.

Would you like me to make these as a printable quiz (PDF or DOCX) with blank answer spaces for students?