

main.c

```
1
2 #include <stdio.h>
3 int main() {
4     int num, firstDigit, lastDigit;
5     printf("Enter a number: ");
6     scanf("%d", &num);
7     lastDigit = num % 10;
8     while (num >= 10) {
9         num = num / 10;
10    }
11    firstDigit = num;
12    printf("Frist digit: %d\n", firstDigit);
13    printf("Last digit: %d\n", lastDigit);
14    return 0;
15 }
```

Output

Enter a number: 4529
Frist digit: 4
Last digit: 9

=== Code Execution Successful ===



main.c

```
1
2 #include <stdio.h>
3 int main() {
4     int num;
5     unsigned long long factorial = 1;
6     printf("Enter a number: ");
7     scanf("%d", &num);
8     if (num < 0) {
9         printf("Factorial is not defined for negative numbers.\n");
10    } else {
11        for (int i = 1; i <= num; ++i) {
12            factorial *= i;
13        }
14        printf("Factorial of %d = %llu\n", num, factorial);
15    }
16    return 0;
17 }
```

Output

Enter a number: 5
Factorial of 5 = 120

=== Code Execution Successful ===





main.c

Run

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int num, i, isPrime = 1;
5     printf("Enter a number: ");
6     scanf("%d", &num);
7     if (num <= 1) {
8         printf("%d is not a prime number.\n", num);
9         return 0;
10    }
11    for (i = 2; i <= num / 2; i++) {
12        if (num % i == 0) {
13            isPrime = 0;
14            break;
15        }
16    }
17    if (isPrime)
18        printf("%d is a prime number.\n", num);
19    else
20        printf("%d is not a prime number.\n", num);
21    return 0;
22 }
```

Output

Enter a number: 7
7 is a prime number.

=== Code Execution Successful ===

Programiz PRO

Premium
Courses by
Programiz

Learn More

main.c

```
1
2 #include <stdio.h>
3 int factorial(int n) {
4     int fact = 1;
5     for (int i = 1; i <= n; i++) {
6         fact *= i;
7     }
8     return fact;
9 }
10 int main() {
11     int num, temp, digit, sum = 0;
12     printf("Enter a number: ");
13     scanf("%d", &num);
14     temp = num;
15     while (temp > 0) {
16         digit = temp % 10;
17         temp /= 10;
18     }
19     if (sum == num)
20         printf("%d is a strong number.\n", num);
21     else
22         printf("%d is not a strong number.\n", num);
23     return 0;
24 }
```

Output

Enter a number: 145
145 is not a strong number.

=== Code Execution Successful ===

main.c

```
1
2 #include <stdio.h>
3 int main() {
4     int num, sum = 0, digit;
5     printf("Enter a number: ");
6     scanf("%d", &num);
7     while (num > 0) {
8         digit = num % 10;
9         sum += digit;
10        num = num / 10;
11    }
12    printf("Sum of digits = %d\n", sum);
13    return 0;
14 }
```

Output

Enter a number: 1234
Sum of digits = 10

=== Code Execution Successful ===