

main.c

9

printf("Monday\n");

10

break;

11

case 2:

12

printf("Tuesday\n");

13

break;

14

case 3:

15

printf("Wednesday\n");

16

break;

17

case 4:

18

printf("Thursday\n");

19

break;

20

case 5:

21

printf("Friday\n");

22

break;

23

case 6:

24

printf("Saturday\n");

25

break;

26

case 7:

27

printf("Sunday\n");

28

break;

29

default:

30

printf("Invalid input! Please enter a number between 1 and 7

31

}\n");

32

return 0;

33

}

Run

Share

Clear

Output

Enter day number (1-7): 3
Wednesday

=== Code Execution Successful ===

Adobe
Creative Cloud

Better tools,
more
opportunities.

Get
Creative Cloud Pro.

Learn more



Artwork by
Srishti Gupta Roy.

main.c

```
1
2 #include <stdio.h>
3 int main() {
4     int num;
5     printf("Enter a number:");
6     scanf("%d", &num);
7     if (num < 10 && num > -10) {
8         printf("one digit\n");
9     }
10    else if (num >= 10 && num < 100 || num <= -10 && num > - 100) {
11        printf("two digits\n");
12    }
13    return 0;
14 }
```

Output

Enter a number:5
one digit

=== Code Execution Successful ===



main.c

```
1
2 #include <stdio.h>
3 int main() {
4     char ch;
5     printf("Enter a character: ");
6     scanf("%c", &ch);
7     if ((ch >= 'A' && ch <= 'Z') || (ch >= 'a' && ch <= 'z')) {
8         printf(" '%c' is an alphabet.\n", ch);
9     }
10    else if (ch >= '0' && ch <= '9') {
11        printf(" '%c' is a special character.\n", ch);
12    }
13    return 0;
14 }
```

Output

Enter a character: A
'A' is an alphabet.

=== Code Execution Successful ===



main.c

```
1
2 #include <stdio.h>
3 int main() {
4     char ch;
5     printf("Enter a character: ");
6     scanf("%c", &ch);
7     if ((ch >= 'A' && ch <= 'Z') || (ch >= 'a' && ch <= 'z')) {
8         if (ch == 'A' || ch == 'E' || ch == 'I' || ch == 'O' || ch ==
            'U' ||
9             ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch == 'u')
10            {
11                printf("%c' is a vowel.\n", ch);
12            } else {
13                printf("%c' is a consonant.\n", ch);
14            } else {
15                printf("%c' is not an alphabet.\n", ch);
16            }
17     return 0;
18 }
```

Output

Enter a character: e
'e' is a vowel.

=== Code Execution Successful ===

Clear



main.c

```
1
2 #include <stdio.h>
3 int main() {
4     int year;
5     printf("Enter a year:");
6     scanf("%d", &year);
7     if ((year % 4 == 0 && year % 100 != 0) || (year % 400 == 0)) {
8         printf("%d is a leap year.\n", year);
9     } else {
10        printf("%d is not a leap year.\n", year);
11    }
12    return 0;
13 }
```

Output

Enter a year:2024
2024 is a leap year.

=== Code Execution Successful ===



main.c

```
1
2 #include <stdio.h>
3 int main() {
4     int num, firstDigit, lastDigit;
5     printf("Enter a number: ");
6     scanf("%d", &num);
7     lastDigit = num % 10;
8     while (num >= 10) {
9         num = num / 10;
10    }
11    firstDigit = num;
12    printf("Frist digit: %d\n", firstDigit);
13    printf("Last digit: %d\n", lastDigit);
14    return 0;
15 }
```

Output

Enter a number: 4529
Frist digit: 4
Last digit: 9

=== Code Execution Successful ===



main.c

```
1
2 #include <stdio.h>
3 int main() {
4     int num, sum = 0, digit;
5     printf("Enter a number: ");
6     scanf("%d", &num);
7     while (num > 0) {
8         digit = num % 10;
9         sum += digit;
10        num = num / 10;
11    }
12    printf("Sum of digits = %d\n", sum);
13    return 0;
14 }
```

Output

Enter a number: 1234
Sum of digits = 10

=== Code Execution Successful ===

main.c

```
1
2 #include <stdio.h>
3 int factorial(int n) {
4     int fact = 1;
5     for (int i = 1; i <= n; i++) {
6         fact *= i;
7     }
8     return fact;
9 }
10 int main() {
11     int num, temp, digit, sum = 0;
12     printf("Enter a number: ");
13     scanf("%d", &num);
14     temp = num;
15     while (temp > 0) {
16         digit = temp % 10;
17         temp /= 10;
18     }
19     if (sum == num)
20         printf("%d is a strong number.\n", num);
21     else
22         printf("%d is not a strong number.\n", num);
23     return 0;
24 }
```

Output

Enter a number: 145
145 is not a strong number.

=== Code Execution Successful ===

main.c

```
1
2 #include <stdio.h>
3 int main() {
4     int num;
5     unsigned long long factorial = 1;
6     printf("Enter a number: ");
7     scanf("%d", &num);
8     if (num < 0) {
9         printf("Factorial is not defined for negative numbers.\n");
10    } else {
11        for (int i = 1; i <= num; ++i) {
12            factorial *= i;
13        }
14        printf("Factorial of %d = %llu\n", num, factorial);
15    }
16    return 0;
17 }
```

Output

Enter a number: 5
Factorial of 5 = 120

=== Code Execution Successful ===



Clear

```
Enter a number: 7
7 is a prime number.

=== Code Execution Successful ===
```