



main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int a = 4;
5     int b = 2;
6     int result = 4 >= 2;
7     printf("Result of 4 >= 2: %d", result);
8     return 0;
9 }
```

Result of 4 >= 2: 1

=== Code Execution Successful ===



main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int factorial(int n) {
4     if (n==0 || n == 1)
5         return 1;
6     else
7         return n * factorial(n - 1);
8 }
9 int main() {
10     int num = 4;
11     int fact = factorial(num);
12     printf("Factorial of %d is %d", num, fact);
13     return 0;
14 }
```

Factorial of 4 is 24

=== Code Execution Successful ===

main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int a = 4;
5     int b = 2;
6     int result = 4 == 2;
7     printf("Result of 4 == 2: %d", result);
8     return 0;
9 }
```

Result of 4 == 2: 0

=== Code Execution Successful ===



main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int a = 4;
5     int b = 2;
6     int result = 4 <= 2;
7     printf("Result of 4 <= 2: %d", result);
8     return 0;
9 }
```

Result of 4 <= 2: 0

=== Code Execution Successful ===

main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int a = 4;
5     int b = 2;
6     int result = 4 > 2;
7     printf("Result of 4 > 2: %d", result);
8     return 0;
9 }
```

Result of 4 > 2: 1

=== Code Execution Successful ===



main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int a = 4;
5     int b = 2;
6     if (a < b) {
7         printf("%d < %d is %d is true", a, b);
8     } else {
9         printf("%d < %d is false", a, b);
10    }
11    return 0;
12 }
```

4 < 2 is false

=== Code Execution Successful ===

main.c

```
1
2 #include <stdio.h>
3 int main() {
4     int a = 4;
5     int b = 2;
6     int result;
7     result = a ^ b;
8     printf("%d ^ %d is %d", a, b, result);
9     return 0;
10 }
```

Run

Output

Clear

4 ^ 2 is 6

=== Code Execution Successful ===

main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int a, b;
5     float result;
6     printf("Enter the a value: ");
7     scanf("%d", &a);
8     printf("Enter the b value: ");
9     scanf("%d", &b);
10    if (b == 0) {
11        printf("Division by zero is not allowed.");
12    } else {
13        result = (float)a / b;
14        printf("%d / %d is %.2f", a, b, result);
15    }
16    return 0;
17 }
```

```
Enter the a value: 4
Enter the b value: 2
4 / 2 is 2.00
```

```
=== Code Execution Successful ===
```


main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int a, b, result;
5     printf("Enter the a value: ");
6     scanf("%d", &a);
7     printf("Enter the b value: ");
8     scanf("%d", &b);
9     result = a & b;
10    printf("%d & %d is %d", a, b, result);
11    return 0;
12 }
```

Enter the a value: 4
Enter the b value: 2
4 & 2 is 0

=== Code Execution Successful ===

main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     float a, b, result;
5     printf("Enter the a value: ");
6     scanf("%f", &a);
7     printf("Enter the b value: ");
8     scanf("%f", &b);
9     if (b == 0) {
10         printf("Error! Division by zero is not allowed.\n");
11     } else {
12         result = a / b;
13         printf("The division of %.2f by %.2f is %.2f\n", a, b,
            result);
14     }
15     return 0;
16 }
```

Enter the a value: 20
Enter the b value: 78
The division of 20.00 by 78.00 is 0.26

=== Code Execution Successful ===

main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int a, b, product;
5     printf("Enter the a value: ");
6     scanf("%d", &a);
7     printf("Enter the b value: ");
8     scanf("%d", &b);
9     product = a * b;
10    printf("The product of %d and %d is %d\n", a, b, product);
11    return 0;
12 }
```

Enter the a value: 48
Enter the b value: 60
The product of 48 and 60 is 2880

=== Code Execution Successful ===



main.c



Share

Run

Output

Clear

```
1
2 #include <stdio.h>
3 int main() {
4     int a, b, difference;
5     printf("Enter the a value: ");
6     scanf("%d", &a);
7     printf("Enter the b value: ");
8     scanf("%d", &b);
9     difference = a - b;
10    printf("The difference between %d and %d is %d\n", a, b
        , difference);
11    return 0;
12 }
```

Enter the a value: 25
Enter the b value: 15
The difference between 25 and 15 is 10

=== Code Execution Successful ===