CISC3010 / TOPIC 14 / FINAL REPORT / 2 NOVEMBER 2026

TokenFlow: Request Routing and Iteration-Level LLM Serving

CHEONG KIN NGAI (Bankey)

ABSTRACT

Serving requests with different lengths requires decisions both between model replicas and within each replica. TokenFlow implements an HTTP gateway, two independent Qwen2.5-0.5B-Instruct workers, streamed responses, and trace-based checks on one CPU host. A controlled real-model study replays 2,880 requests across 24 trials. Least-outstanding routing lowers mean trial P95 time to first token at 1 request/s, but neither tested rate establishes a reliable throughput winner. A separate execution comparison increases throughput from 0.787 to 1.154 requests/s by sharing suitable transformer operations. A simulator isolates static versus continuous admission, while fault and cancellation tests check request cleanup. The results distinguish worker selection, admission timing, and execution, with explicit limits on shared-host and workload generalization.

1 Introduction

An LLM service must choose where a request runs and how its tokens share computation with other requests. These choices interact with variable prompt lengths, variable output lengths, and the growing key-value (KV) state used by Attention. A low request count need not mean a low remaining token workload.

Research questions. Does least-outstanding routing improve response time over round robin on a fixed mixed workload? Which benefits come from worker scheduling and shared computation? TokenFlow exposes queues, slots, execution pieces, and terminal outcomes to connect each claim to a measured mechanism.

The implementation adds gateway accounting, worker lifecycle, iteration scheduling, selective execution, and a trace checker around pretrained weights and existing tensor operations. The experiments distinguish whole-request routing from admission timing and shared computation.

Related work and scope

Orca [1] motivates admitting requests at iteration boundaries and batching selected operations. Sarathi-Serve [5] motivates bounding prompt work alongside decode. TokenFlow adapts these ideas to full CPU replicas. DistServe [6] motivates distinguishing first-token delay from streaming delay; phase disaggregation itself is outside this implementation.



Figure 1. Process architecture. The gateway routes complete requests to two independent Qwen workers, each with its own queue and KV state. All processes share one CPU host.

2 System overview

The gateway enforces local client limits (HTTP 429 with a retry hint), atomically selects a healthy worker using round robin (RR) or least outstanding (LO), and relays streamed tokens. LO counts assigned requests that are queued or running; terminal outcomes release counts. Each worker owns a FIFO queue, four active slots and request-local KV state. Continuous admission fills freed slots at iteration boundaries. Selective execution then shares compatible token-wise operations while keeping Attention separate (Figure 3). Client labels are a demo mechanism, rather than production authentication. The backend uses Qwen [2], PyTorch and Transformers [3, 4].



Figure 2. Routing on real Qwen. Points and whiskers show mean ± sample SD across six trials per policy and arrival rate (120 requests/trial). Values at right are means. P95 is computed within each trial; latency scales differ by load. RR: round robin; LO: least outstanding.

3.1 Experimental setup

Experiments use Windows, Python 3.13.9, an Intel Core Ultra 5 338H (12 logical CPUs), and 31.5 GiB RAM. Each FP32 Qwen2.5-0.5B-Instruct worker has two model threads, four slots, and a 4,096-token reservation budget. Continuous admission, selective execution, and the 128-token prefill allowance stay fixed.

Each trial replays 120 saved short/long requests at 1 or 3 requests/s, with output caps of 16 or 48 tokens. **Open-loop** arrivals do not wait for earlier completions. Workers warm up first; benchmark quotas avoid rejections. Six paired repeats per rate alternate policy order: 24 trials and 2,880 requests.

3.2 Metrics and uncertainty

Throughput divides successful requests by the interval from first scheduled dispatch to final client outcome. Time to first token (TTFT) and completion use one monotonic client clock. P95 is computed within each trial, then summarized across trials.

Variation in Figure 2 is sample SD. The reported 95% intervals instead use Student-t intervals over six **paired trial differences**. Requests and tokens are not treated as independent repetitions. With six pairs, these intervals are approximate and generalization remains limited.

3.3 Results and interpretation

At **1 request/s**, throughput is 0.964 ± 0.017 for RR and 0.971 ± 0.005 requests/s for LO. Mean trial P95 TTFT falls from 3.72 ± 1.29 to 2.37 ± 0.29 s. The paired mean reduction is 1.35 s, with an approximate 95% interval of [0.23, 2.48] s. Mean trial P95 completion falls from 13.13 to 11.53 s.

At **3 requests/s**, throughput is 1.294 ± 0.061 for RR and 1.269 ± 0.057 requests/s for LO. P95 TTFT is 45.44 ± 4.40 versus 45.69 ± 2.75 s; P95 completion is 52.63 versus 53.34 s. The paired throughput intervals include zero at both rates: the study establishes neither a reliable throughput winner nor equivalence.

At the higher load, full-slot fractions are 92.6% (RR) and 90.3% (LO). Gateway CPU is about 10.5% and 10.7% **of one logical core**. This indicates worker-side queueing pressure without observed gateway CPU overload; it does not establish whole-host CPU or memory-bandwidth saturation.

Outstanding request count does not measure remaining tokens, and RR already distributes this mix reasonably evenly. These are plausible explanations for the small throughput difference, not experimentally isolated causes. A separate constructed alternating-order diagnostic has 16 trials and 1,024 requests; it is retained in the evidence and excluded from this primary comparison.

4 Scheduling and model execution



Figure 3. Selective computation within one worker iteration (schematic). Decode pieces and a bounded prompt chunk share token-wise operations. Attention is split by request with independent histories and masks, then rows merge for shared output projection and MLP. The prefill allowance limits prompt tokens per step, not elapsed time.

4.1 Shared execution on real Qwen



Figure 4. Real Qwen execution. Three paired trials of 24 requests per mode. Bars: means; whiskers: sample SD; circles: individual trials.

Both modes use LO, continuous admission, two workers, arrivals at 6/s, and identical prompts, output caps, and bounded prefill. Both compute vocabulary logits only at output-producing positions. Only execution changes.

Throughput rises from 0.787 ± 0.008 to 1.154 ± 0.006 requests/s (**46.7%**). P95 TTFT falls from 19.18 to 11.98 s; P95 completion from 26.54 to 17.15 s. All workload-position token IDs match across six trials. This execution result is separate from the routing comparison.

4.2 Bounded prefill has a tradeoff

Holding selective execution fixed, a separate comparison changes whole-prompt prefill to a 128-token shared allowance, with three trials per setting and 24 requests per trial. Intermediate chunks update KV without producing output.

Gap	Whole prompt	128 tokens	Change
P95	544.6 ± 6.9	854.6 ± 34.2	+56.9%
P99	1,962.9 ± 27.8	913.7 ± 21.0	-53.5%

Table 1. Streaming gaps (ms). Mean ± sample SD of trial percentiles. Change compares means; lower is better.

4.3 Continuous admission in the simulator



Figure 5. Simulator admission. Three trials per setting, 48 requests/trial. Bars: means; whiskers: sample SD; circles: trials. These times describe the simulator, not real Qwen.

The simulator holds LO routing, two workers, four slots, a 32-token prefill allowance, and the same request mix and timing model fixed. Static admission waits for an active cohort to finish before admitting another; continuous admission fills freed slots at step boundaries. Each trial has 36 short and 12 long requests. The 28 October rerun contains 12 trials and 576 requests.

Decode step cost is (0.012 + 0.002 × active decode requests) s; prompt-chunk cost is (0.003 + 0.00025 × chunk tokens) s. These costs describe the simulator, rather than predicting Qwen speedup.

At 6/s, mean trial P95 TTFT drops from 7.36 to 1.29 s; at 18/s, from 11.85 to 5.12 s. Short-request mean queue wait drops from 2.96 to 0.38 s and from 5.01 to 1.99 s, respectively. The earlier 12-trial suite shows the same direction and remains separately archived.

4.4 Reading the streaming tradeoff

Chunking reduces rare long gaps while worsening P95 (Table 1). It spreads interference across iterations. P99 was inspected after P95, so these three-trial descriptive results need a larger prospective test. Token gaps are correlated.

5 Correctness and failure behavior

5.1 Trace and numerical checks

The independent checker verifies one assignment and one terminal outcome per admitted request, ordered non-duplicated token events, model-step piece accounting, and cleanup of outstanding counts, slots, and reservations. Expected fault runs can pass lifecycle checks while containing explicit failed outcomes.

Twelve actual-model reference cases match Transformers-generated token IDs, covering heterogeneous prompts, conversation context, chunk sizes, and a late arrival. An FP32 teacher-forced audit compares full-vocabulary logits and per-layer KV values. The maximum recorded absolute logit difference is 2.05×10^{-5}, within the recorded tolerances, with no argmax differences.

An earlier BF16 audit failed strict numerical agreement when changed matrix shapes rounded close logits into a tie. The failed audit is retained; the final backend and reported real-model comparisons use FP32. This correction avoids mixing development speed measurements with validated final results.

The full routing archive checks 40 trials, 3,904 requests, and 108,800 output tokens, including the separately labelled order diagnostic. On 28 October, all 32 automated tests passed, including the earlier Kafka tests. These checks validate observed cases rather than every input and failure mode.

5.2 Partial failure and cancellation

Stopping one real-model worker during a 16-request run yields nine completions and seven explicit failures. Detection takes 0.554 s in that run. New requests use the surviving worker. Restart is manual and includes model loading; an interrupted partial answer is not resumed or silently replayed.

In a separate 12-request run, nine requests complete and three are cancelled. The checker finds no remaining reservations. The recorded product demo also shows chat, both routing policies, HTTP 429 admission control, execution inspection, cancellation, and failure/recovery.

6 Limitations and implications

The study uses synthetic templates, fixed output caps, two arrival rates, and two replicas sharing one host. It is neither a representative production trace nor an answer-quality evaluation. CPU and memory interference, few repetitions, and coarse P95 estimates constrain generalization. A larger heterogeneous or multi-host workload could change the routing result.

The gateway and host are single failure points. The system does not implement model sharding, GPU kernels, PagedAttention, cross-request prefix KV reuse, phase disaggregation, or seamless output replay. Live KV tensor bytes exclude allocator overhead and process/model memory.

7 Reproducibility and contributions

The submission contains source, pinned dependencies and model revision, startup and experiment commands, sample requests, the architecture, demo video and captions, raw traces, checker, and plotting scripts. The report builder recreates vector figures directly from the submitted CSV/ZIP evidence; no local run directory or model download is needed to rebuild this PDF.

Clean-checkout checks start both the simulator and real model with two healthy workers and complete sample requests. Fresh dependency installation was checked using cached pinned model weights; the full first-time weight download was not repeated. The setup documents Windows as the verified environment.

No specific presentation feedback was received. Subsequent work audited deliverables against the assignment, packaged raw evidence and portable verification, reran the simulator comparison and automated checks, and improved the report's architecture and experimental presentation.

The project adds gateway accounting, worker lifecycle, scheduling, selective execution, observability, checks, and experiments around pretrained Qwen and PyTorch/Transformers. Codex provided substantial design, implementation, test, experiment, and documentation assistance; its use and validation are disclosed in `AI_USE.md`. Existing libraries and readings are attributed below.

8 Conclusion

TokenFlow demonstrates three distinct serving decisions with an inspectable application. LO improves first-token delay at the tested lower arrival rate, but the primary routing study does not identify a reliable throughput winner. A separate real-model experiment supports shared execution in the tested configuration, while simulation supports continuous admission under its stated timing model. Tail-gap and fault observations show why throughput alone is insufficient to judge a serving design.

References

[1] G.-I. Yu et al. **Orca: A Distributed Serving System for Transformer-Based Generative Models.** OSDI, 2022. Paper and proceedings.

[2] Qwen Team. **Qwen2.5-0.5B-Instruct.** Pretrained model and model card. Hugging Face.

[3] PyTorch contributors. **PyTorch documentation.** Tensor operations and CPU inference. Documentation.

[4] Hugging Face. **Transformers documentation.** Model loading, generation, and cache interfaces. Documentation.

[5] A. Agrawal et al. **Taming Throughput-Latency Tradeoff in LLM Inference with Sarathi-Serve.** OSDI, 2024. Paper and proceedings.

[6] Y. Zhong et al. **DistServe: Disaggregating Prefill and Decoding for Goodput-optimized Large Language Model Serving.** OSDI, 2024. Paper and proceedings.