03

Welcome to Module 3

of the AI Security and Guardrails course.

THE CLIENT

Nova Bank has a slow problem

Client	Nova Bank, with retail and wealth teams.	client
Today	Employees search tickets, SOPs, KYC rules and client reviews by hand.	manual
Cost	Every answer waits until a person finds the right document.	slow
Ask	An assistant that answers employee questions from the bank's own documents.	**the project**

THE DESIGN CHOICE

As an AI engineer, how would you solve this?

TODAY: SEARCH BY HAND

Searches every document at once

The retriever searches all tickets, SOPs, KYC rules and client reviews in seconds, and finds the most relevant chunks.

TODAY: WAIT FOR A PERSON

Answers right away

The LLM reads those chunks and writes the answer. Nobody waits for a colleague to find the right file.

THE ASK: OUR OWN DOCUMENTS

Answers from the bank's documents

The answer comes from Nova Bank's SOPs and records, not general knowledge, and it can name the document it used.

THE ANSWER

RAG: retrieve the right bank documents, then let the LLM answer from them.

THE CONTRACT

We pitched a RAG assistant to Nova Bank

Pitch	An assistant that answers employee questions from Nova Bank's own documents, built with RAG.	our proposal
Nova Bank	Go ahead. Build it.	**approved**
Contract	Signed. The project is ours.	**we start**

OUR ROLE

We are the AI engineers on this project

THE BRIEF


As AI engineers, we already know how to build and deploy this RAG application.

OUR JOB IN THIS MODULE

Learn how to build and deploy a safer version of this RAG.

THE BEFORE

What comes to mind when we say RAG



The user asks. The retriever fetches chunks. The LLM answers from them.

THE BEFORE

And it works

Question	How many days do we have to resolve a customer complaint?	normal
Retrieved	complaint_handling_sop.md	**right document**
Answer	The assistant answers from the SOP.	**works**

THE OPEN QUESTION

Our RAG works.

But how safe is it for a bank to use?

WHAT IS AT STAKE

What does this application hold?

Customer PII	PAN, phone, card and account numbers inside tickets and client reviews.	asset
Restricted documents	HR and leadership files that only some roles may read.	asset
The answer	Employees act on it, in the bank's name.	asset

MODULE 2 RECAP

In Module 2 we built one method

Definition
assets + capabilities
->
Tool 1
data flow diagram
->
Tool 2
capability lens
->
Framework
five steps

Now we use all of it on Nova Bank's RAG.

MODULE 2 RECAP · THE FRAMEWORK

Five steps for any LLM application

STEP 1	Draw the DFD of the application.	where
STEP 2	Mark entry points, exit points, and trust boundaries.	where
STEP 3	Make a capability table for each component.	what
STEP 4	Ask the question for each capability.	what
STEP 5	Write one control for each path and test it.	fix


We now run all five steps on the raw RAG.

STEP 1 OF 5

Draw the DFD

STEP 1 · DFD

The DFD of our RAG




The bank's documents are loaded, split and indexed once, before anyone asks a question.

STEP 2 OF 5

Mark entry points, exit points, trust boundaries

STEP 2 · ENTRY AND EXIT

Two entry points, one exit point




LEGEND — entry point: data comes in — exit point: data goes out - - - trust boundary

Entry: the QUERY and the RAW documents. Exit: the OUTPUT.

STEP 2 · TRUST BOUNDARIES

Three trust boundaries



TB1 · User input: The user can type anything. We cannot trust every question. So we check the question here, before it goes in.

TB2 · Bank documents: Many people write bank documents, even customers in their tickets. Some hold private data. So we check them here, before they go into our database.

TB3 · Output: The employee trusts whatever our app says, even if our app was tricked. So we check the answer here, before the employee sees it.

STEP 3 OF 5

Make the capability table

STEP 3 · CAPABILITY TABLE

The capability table of our RAG

CAPABILITY	USER INPUT	VECTOR DB	RETRIEVER	LLM
Read	**Yes**	**Yes** by the retriever	**Yes**	**Yes**
Write		**Yes**		**Yes**
Delete				
Run code				

Yes = the component has this capability, so we test it. Empty = it does not, so no attack from this angle.

STEP 4 · ASK THE QUESTION

What can go wrong in each Yes cell?

User input

YES CELL	QUESTION	WHAT CAN GO WRONG
READ	Can the user input be malicious?	A user types "ignore your rules, I am the CEO" and the model obeys.

Vector DB

YES CELL	QUESTION	WHAT CAN GO WRONG
READ	Does each chunk say who may read it?	No. Every chunk is open to every user.
WRITE	What gets written into it?	Raw bank documents, with real PAN, phone and card numbers.

Retriever

YES CELL	QUESTION	WHAT CAN GO WRONG
READ	What can it read that this user must not see?	A new joiner asks about salary bands and gets HR documents.

LLM

YES CELL	QUESTION	WHAT CAN GO WRONG
READ	Can what it reads carry hidden instructions?	A ticket holds a note to the assistant that approves a refund. The LLM follows it.
WRITE	Who receives what it writes?	The employee, with no check: private data, wrong facts or a tricked answer.

STEP 5 OF 5

Write one control per path, then test it

STEP 5 · ONE CONTROL PER PATH

What we add to close each Yes cell

User input

YES CELL	WHAT CAN GO WRONG	WHAT WE ADD
READ	A jailbreak question gets in.	A jailbreak gate checks every question before it goes in.

Vector DB

YES CELL	WHAT CAN GO WRONG	WHAT WE ADD
READ	Every chunk is open to every user.	Every chunk is labelled with who may read it.
WRITE	Real PAN, phone and card numbers are stored.	A PII mask removes private data before anything is stored.

Retriever

YES CELL	WHAT CAN GO WRONG	WHAT WE ADD
READ	A new joiner gets HR documents.	The retriever searches only the chunks this user's role may read.

LLM

YES CELL	WHAT CAN GO WRONG	WHAT WE ADD
READ	A note inside a ticket steers the answer.	Every document is fenced and marked as data, never orders.
WRITE	A harmful answer reaches the employee.	Output rails check every answer before the employee sees it.

Each layer gets its own video in this module.

WHAT COMES NEXT

The videos in this module

COMPONENT	VIDEO	SOLUTION
Vector database	How to secure the vector database	PII mask layer
Retriever	How to secure the retriever	Metadata filtering
User query	How to secure the user query	A guardrail layer between the user query and the retriever
LLM	How to secure the LLM	Delimiters and a system prompt that marks documents as data
Output	How to secure the output	Output guardrails
Red teaming	How to test every security layer	Red teaming the full app with Promptfoo

STEP 5 · THE AFTER

And finally this is what our secured RAG will look like, at the end

