

KHV SERIES

TRUCK BLOWERS WITH SECONDARY SUCTION i.e. Air Injection

- **Air Flow** - 250 CFM - 5700 CFM
- **Pressure** - 20 psi continuous
- **Vacuum** - 90%
- **Warranty** - 12/18 months

SHV SERIES

TRUCK BLOWERS WITH SECONDARY SUCTION i.e. Air Injection

- **Air Flow** - 400 CFM - 6000 CFM
- **Pressure** - 20 psi continuous
- **Vacuum** - 93%
- **Warranty** - 12/18 months

PERFORMANCE DATA FOR VACUUM OPERATION OF AIR INJECTION 3-LOBE KHV SERIES

KHV 01 Upto 450 m³/hr 85% Vacuum

KHV 02 Upto 1200 m³/hr 90% Vacuum

KHV 03 Upto 2000 m³/hr 90% Vacuum

KHV 04 Upto 3500 m³/hr @ 90% Vacuum

KHV 05 Upto 5400 m³/h @ 90% Vacuum

KHV 06 Upto 9600 m³/h @ 90% Vacuum

PERFORMANCE DATA FOR VACUUM OPERATION OF AIR INJECTION - 3 LOBE SHV SERIES

MODEL	RPM	VACUUM	VACUUM	VACUUM	VACUUM	VACUUM	VACUUM	VACUUM	VACUUM	VACUUM	VACUUM								
		20% m³/hr. KW	30% m³/hr. KW	40% m³/hr. KW	50% m³/hr. KW	60% m³/hr. KW	70% m³/hr. KW	80% m³/hr. KW	90% m³/hr. KW	93% m³/hr. KW									
SHV 30	3500	1449	12	1417	16	1383	20	1344	24	1290	28	1195	33	965	37	267	41	-	-
	3110	1275	10	1243	14	1209	18	1170	22	1116	25	1021	29	791	33	93	37	-	-
	2920	1191	10	1159	13	1125	17	1086	20	1031	24	936	27	707	31	80	34	-	-
	2840	1067	9	1035	12	1001	15	962	19	907	22	812	24	583	28	-	31	-	-
	2350	938	8	906	11	872	14	839	17	778	20	683	22	454	24	-	-	-	-
SHV 32	3300	2092	16	2029	21	1964	27	1889	34	1784	40	1602	47	1159	52	145	59	-	-
	3110	1959	15	1896	20	1832	26	1757	32	1652	38	1470	44	1026	49	80	56	-	-
	2940	1841	14	1778	19	1714	24	1639	30	1534	36	1352	41	908	47	-	53	-	-
	2740	1702	13	1639	18	1574	23	1499	28	1394	33	1212	39	769	44	-	-	-	-
	2150	1292	10	1229	14	1183	18	1088	23	983	26	801	30	359	34	-	-	-	-
SHV 35	2900	3917	26	3854	36	3788	48	3713	60	3606	71	3423	82	2977	94	1955	106	80	110
	2660	3576	24	3512	35	3446	44	3371	55	3265	65	3082	75	2635	86	1613	97	-	-
	2370	3164	22	3100	31	3034	40	2959	49	2853	58	2670	67	2223	77	1201	87	-	-
	2090	2766	19	2702	27	2636	35	2561	43	2455	51	2272	59	1825	68	802	76	-	-
	1800	2353	17	2289	24	2223	30	2148	37	2042	44	1859	51	1412	58	390	65	-	-
	1550	1993	15	1924	20	1868	26	1793	32	1687	38	1504	44	1057	50	34	56	-	-
SHV 40	2500	5817	40	5700	58	5577	75	5468	87	5278	104	4807	121	3783	138	1061	157	80	162
	2250	5190	36	5070	52	4944	68	4832	78	4639	93	4180	109	3178	125	426	141	-	-
	2090	4788	34	4667	48	4539	63	4426	72	4230	87	3778	101	2791	116	80	131	80	-
	1780	4010	29	3886	41	3754	53	3638	62	3437	74	2999	86	2040	98	-	110	-	-
	1350	2931	22	2804	31	2665	41	2546	47	2338	56	1919	66	1000	75	-	-	-	-
	1500	2426	12	2390	17	2353	22	2316	27	2279	32	2242	37	2205	42	2168	47	-	-
SHV 45	1900	7936	52	7826	71	7712	96	7585	121	7401	143	7085	165	6319	189	4559	213	80	221
	1700	7072	47	6953	66	6839	86	6712	108	6526	128	6212	148	5446	169	3686	199	-	-
	1520	6277	42	6182	59	6054	77	5927	97	5743	115	5427	132	4661	151	2901	170	-	-
	1340	5492	37	5402	52	5268	67	5141	85	4957	101	4641	117	3875	134	2116	150	-	-
	1150	4663	32	4553	45	4439	58	4312	73	4128	87	3812	100	3046	115	1287	129	-	-
	750	2918	21	2808	29	2694	37	2567	48	2383	56	2067	66	1301	75	80	84	-	-

Note : For other Models, contact H.O.

STANDARD EXECUTION

The standard unit consists of :

- Fabricated steel base frame with C.I. slide rails • Non-return valve
- Discharge silencer • V-belt and pulleys or coupling with guard • Vacuum gauge
- Flexi-mounts • Suction strainer • Silencer on main and secondary suction

OPTIONAL

- Temperature gauge and switch • Acoustic enclosure for sound reduction
- Vacuum gauge and switch • Flexible bellows • Cooler on discharge

SALIENT FEATURES

- High volumetric & mechanical efficiencies • Lower power consumption
- Lower operating costs • Absolutely dry operation • Guaranteed oil free conveying
- Reliable operation & less maintenance

Focus on Quality & Reliability

Emphasis on quality & performance is a commitment of every individual at Swam beginning at grass root level. The quality control is practiced at all levels of the organization and all its aspects are thoroughly complied with the specified standard and specification, till the product gets delivered.

The quality assurance system encompasses self quality control by each worker, supervised by quality control engineers. Each product undergoes thorough & stringent tests at different stages of manufacturing and are test run for several hours prior to despatch as per the relevant code, customers' specification & approved quality plan.

Advance Manufacturing System

Swam has the most advance manufacturing system with a large number of CNC Machines installed in our four plants. The Truck Blowers / Root Blowers & other products are manufactured with most optimum profile resulting higher efficiencies, high displacement, lower slippage. Thus our products are more energy efficient compared to other.



SWAM PNEUMATICS PVT. LTD.

(ISO-9001: 2008 Quality Certified)

C-2, Sector-3, Noida- 201301, Gautam Budh Nagar (INDIA), Tel : +91-120-4696222, Fax : +91-120-2443283, 4696200

E-mail : sales@swamatics.com, Website : www.swamatics.com

Leader in: Air-Gas Conveying, Boosting & Vacuum Technology