



about us

Swam, a leading engineering company and global leader specializing in design, engineering, manufacturing, and supply of Rotary Air and Gas Blowers, Truck Blowers, Centrifugal Fans Turbo Blowers, Liquid ring Vacuum pumps and Compressors, Dry Screw Vacuum Pumps, Vacuum Boosters, 4 Stage Hook & Claw Vacuum Pumps, Sliding vane compressors, Acoustic enclosures & related equipments.

Swam, a group known for its technology, innovation and excellence that has been acquired exceptional through product design & development capabilities to meet stringent quality and performance requirements and to confirm to the customers tough and diversified specifications. At Swam emphasis has been on innovative design, precision engineering, advanced technology, excellence in performance and quick responsiveness to customers.

With over three decades of experience the company has adequately matured to execute different project and is today represented in over 15 countries. Our quality system has been accredited with ISO-9001 quality standards and procedures. The company's head office & work are located at Noida near New Delhi, the capital city of India. The company has FOUR manufacturing plants equipped with CNC Machines and in-house testing facility upto 1000kw.

Our highly motivated engineers and work force faces, each contract with commitment to meet the client process specification and quality requirement. The company has executed many prestigious projects under the stringent quality compliance.


The company's quality system is as per ISO 9001:2008 and has very high regard for safety and environment and hence has all plants certified to ISO 14001 and OHSAS 18001.



SCVP-Series 4 Stage Hook & Claw Vacuum Pump

SCVP-Series is a Multi-stage Dry Vacuum Pump which has a pair of lobes on the top and 03 pairs of claw rotors below, all rotating in opposite directions in a synchronous way within the pump casing to form suction and discharge operation. This is totally Oil-free, non-contacting, four stage roots and hook & claw arrangement that makes it more suitable for pumping air and other suitable gases. This technology provides consistent vacuum with high efficiencies at lowest cost along reliable performance and safety standards.

The SCVP Series pumps are available in capacities 250m³/h and 350m³/h with an ultimate vacuum of less than 1mbar.



SPECIFICATIONS

Description/Frequency/Phase	Hz	50	50
Orientation	-	Vertical	Vertical
No. of stages	-	3	4
Construction	-	3 claw	1 root + 3 claw
Maximum pumping speed	m ³ /h	250	350
Ultimate pressure (total pressure)	mbar	< 0.5	0.05
Motor power	kW	11	11
Weight	kg	565	656
Noise level**	dB(A)	< 80	< 85
Inlet connection	-	125NB	125NB
Exhaust connection	-	80NB	80NB
Gearbox oil capacity	L	3.2	3.5
Recommended oil (supplied)	-	TURBO 46	TURBO 46
Cooling system type	-	Direct water-cooling	Direct water-cooling
Cooling-water flow	l/min	5 to 10	5 to 10
Supply temperature range	°C	5 to 35	5 to 35
Cooling-water supply pressure - 1/2" BSP (M)	Bar G	upto 10	upto 10
Cooling water supply	water quality: Reynar stability index	6.5 – 7	6.5 – 7
Shaft-seals air/nitrogen purge - 3/8" BSP (F)	20 LPM	0.3 to 0.5 bar g	0.3 to 0.5 bar g
N2 purge and gas ballast purge	3/8" BSP (F)	02 to 05 bar g	02 to 05 bar g
Pressure relief valve	-	Yes	Yes
Overall dimensions (Length x Width x Height)	mm	860x750x1665	980 x 890 x 1750

** 5 min solvent purge + 10 min inlet purge.

