

Spark and Druid: a suitable match

Harish Butani

August 20, 2015

Druid was designed to handle the ingest and analysis of large amounts of **Event** data. This is a key capability in the AdTech/Marketing and Internet-of-Things(IOT) spaces. In the AdTech arena events generated from human activity are analyzed for doing User targeting, Campaign attribution, Site optimization etc. In the IOT arena event streams and analysis are at the heart of myriad of Applications for Smart Cities, Smart Environment, Smart Water etc.

Event Datasets are like flattened(wide denormalized tables) multi-dimensional Cubes. Druid provides fast slice and dice capability on the raw event data by building a multi-dimensional OLAP index that is primarily partitioned on Time. OLAP indexes are a technique that is used to speed-up slice and dice queries(MDX) on traditional cubes. SAP BW Accelerator's TREX Engine(the precursor to SAP Hana) is an example of another OLAP index technology. Druid provides a REST based Query interface over its Index. This is similar to SQL and there have been efforts to provide SQL-like interfaces on top of Druid; but a full fledged SQL interface is missing.

On the other hand Apache Spark has a very rich LINQ like programming model for expressing data analysis. It has rich SQL capabilities that closely matches Hive SQL: standard join support, datatypes, analytical functions, Cubing/Rollup, jdbc/odbc access etc. The DataSources API enables federating external Datasets; enabling bridging data from disparate systems and applying the analytic capabilities of Spark on all of the data.

There are 2 scenarios where we see the combination of Druid and Spark adding a lot of value:

- For existing deployments of Druid, expose the Druid Index as a DataSource in Spark. This provides a proper SQL interface(with jdbc/odbc access) to the Druid dataset; it also enables analytics in Spark(SQL + advanced analytics) to utilize the fast navigation/aggregation capabilities of the Druid Index. The second point is the key: the goal is **fast SQL++ access on a denormalized/flat event Dataset**. One that marries the rich programming model of Spark with the fast access and aggregation capabilities of Druid. *This paper focuses on this scenario. Our initial development is for this scenario.*
- Longer term , we envision using the Druid technology as an OLAP index for Star Schemas residing in Spark. This is classic OLAP space/performance tradeoff: a specialized secondary index to speed up queries.

The rest of the paper describes the details of the Spark Druid DataSource that is built using the Spark DataSources API and a set of Plan Rewrite techniques. We demonstrate how Querying against **raw event** Datasets can be

rewritten to use the Druid Index, and that these rewritten Plan perform significantly better than the original Plans.

Brief Introduction to Spark, Druid

Druid

Apache Druid is data store designed for fast exploratory analytics on a very large wide data set(think event streams). Its key capabilities and underlying techniques are:

- a columnar storage format for partially nested data structures.
- an olap/multi-dimensional distributed indexing structure
- arbitrary exploration of billion-row tables with sub-second latencies
- realtime ingestion (ingested data is immediately available for querying)
- fault-tolerant distributed architecture that doesn't lose data.

Druid is architected as a group of services:


Historical nodes handle storage and querying on "historical" data (non-realtime).

Realtime nodes ingest data in real time. They are in charge of accepting incoming data and making it available immediately to Queries. Aged data is pushed to deep storage and picked up by Historical nodes.


Coordinator nodes monitor historical nodes and ensure that data is available, replicated and in a generally "optimal" configuration.

Broker nodes receive queries from clients and forward those queries to Realtime and Historical nodes. They merge these results before returning them to the client.

Indexer nodes form a cluster of workers to load batch and real-time data into the system



Druid Query Model



Spark

Apache Spark is an in-memory, general-purpose cluster computing system whose programming model is based on a LINQ style API on datasets. It provides a very rich Datasets API in Java, Scala, Python and R, and a runtime engine that

supports general execution graphs. On top of this core it provides several higher level components: Spark SQL for SQL and structured data processing, MLlib for machine learning, GraphX for graph processing, and Spark Streaming.

The DataSources API enables Spark to integrate natively with a large number of external sources. DataSources have been written for Cassandra, JDBC DS, CSV etc. The DataSources abstraction provides a mechanism by which processing in the form of *predicates and column pruning* can be pushed down to the external system where the Data resides.


Spark and Druid

An obvious starting point is to just expose a Druid Index as a Spark DataSource. This seems like a useful thing to do: it enables proper SQL access; deeper analytics on the Event data is enabled without having to copy of the event data (and more painful manage the copy) . But this is not a very useful solution for the following reasons:

- the DataSource mechanics only allow predicate pushdown and column pruning; so aggregations have to be done in Spark; one of the big strengths of the Druid index is nullified.
- This treats Druid as the primary source of the data. In fact in most cases this is wrong. The usual Data setup is for raw data to land in hdfs or s3, for data to be indexed and possibly aggregated to a higher time grain. For example a Druid index may have aggregated information up to an hour or day granularity.


The fundamental problem with the Datasource only approach is that it doesn't treat Druid as an Index. What we want is to *make it appear that the raw event DataSet is being accessed, and where possible to rewrite Query Plans on this DataSet to use the Druid Index*. The overall picture is:

- **raw event** data is landing in hdfs/s3, and a Druid Index is kept upto date.
- the Event data is exposed in the Spark Analytical platform as residing on the Deep Storage layer: hdfs/s3.
- We setup a DataSource that wraps (and hence exposes the schema and data) of the **raw event** DataSet, but has access to the corresponding Druid Index. A companion Planning component then tries to rewrite Plans on the **raw event** Dataset to utilize the Index where possible.



Druid DataSource for Spark

DruidDataSource is a Spark Datasource that enables users to utilize the Druid Index to accelerate OLAP style queries on the underlying **raw event** Dataset. It wraps the DataFrame that exposes the *raw* Dataset and also is provided with information about the Druid Index for this Dataset.



The DataSource is configured with the following parameters:

Name	Description
sourceDataFrame	The DataFrame that represents the raw Data
druidHost/Port	Information on how to connect to the Druid Broker
druidDatasource	Name of the Druid Index for the raw dataset
timeDimensionColumn	The column from the raw dataset that is the time dimension in the Druid Index
columnMapping	a Map for mapping raw dataset column names to column names in Druid.

Other parameters are also available/will be added to configure rewrites and Druid behavior like functionalDependencies, maxCardinalityPerQuery, maxResultCardinality etc. These will be documented in the future.

Here is a example of defining a Druid DataSource:

Listing 1: Defining a Druid DataSource

```

1 CREATE TEMPORARY TABLE orderLineItemPartSupplier
2   USING org.sparklinedata.druid
3   OPTIONS (sourceDataframe "orderLineItemPartSupplierBase",
4     timeDimensionColumn "l_shipdate",
  
```

```

5      druidDatasource "tpch",
6      druidHost "localhost",
7      druidPort "8082",
8      columnMapping '{ "l_quantity" : "sum_l_quantity",
9                      "ps_availqty" : "sum_ps_availqty"
10                      }
11 )

```

The raw dataset is exposed in the *orderLineItemPartSupplierBase* DataFrame. There is a Druid Index on this Dataset called **tpch**, the *l_shipdate* column is used as the time dimension for the index.

When Spark asks the **Druid DataSource** to create the Relation it: connects to Druid, reads the metadata about the specified Druid datasource and sets up a *DruidRelationInfo* metadata object. It returns a *DruidRelation* a *BaseRelation* to the Spark engine. The basic behavior of *DruidRelation* when asked for an RDD is to defer to the underlying *DataFrame* (*orderLineItemPartSupplierBase* in the above example). But if it has an associated *DruidQuery*, it returns a *DruidRDD*. A *DruidQuery* encapsulates a Druid Query specification, along with a List of intervals on which to apply the Query, and information on how to map the result into Spark Rows. *DruidRDD* is the bridge between Spark and Druid. It runs the *DruidQuery* on Druid for each interval (*DruidRDD* returns the results of each interval in a separate partition). For each Partition the compute call invokes the Druid Broker with the Druid Query, the results are converted into a *Iterator* of Spark Rows.

During planning, the *DruidPlanner* applies a set of rewrite rules to convert a Logical Plan on the raw dataset *DataFrame* into a *DruidQuery*.

Query Rewrites

Spark *SQLContext* allows the Spark Planner to be configured with extra physical plan generation rules. These are applied before built-in Physical transformation. We add the *DruidStrategy* to the *SparkPlanner*.

The *DruidStrategy*

This relies on the *DruidPlanner* to possibly convert a *LogicalPlan* into a *DruidQueryBuilder*. If a *LogicalPlan* has an equivalent *DruidQueryBuilder*, than this is converted into a *SparkPlan* with the following steps:

1. Setup a *DruidQuery* object: this contains the *QuerySpec* (a scala data structure that matches the Druid json information model for expressing queries), and the intervals this Query needs to run on.
2. Setup a *DruidRelation* with the the *DruidRelationInfo* metadata object and *DruidQuery* object.
3. Setup a Physical Plan that looks like

```

Project
  PhysicalRDD(druidRelation.buildScan)

```

The PhysicalRDD wraps the RDD provided by the DruidRelation. The Projection takes care of any dataType mappings and evaluating expressions on aggregation from the Aggregation Operator original Plan..

DruidPlanner

The DruidPlanner is the the entry point for the Druid rewrite functionality. It is a container of DruidTransforms. In order to enable rewrites the user needs to invoke `DruidPlanner(sqlContext)`. This registers DruidStrategy with the SparkPlanner. A DruidTransform is responsible for converting a Logical Plan into a DruidQueryBuilder. A DruidQueryBuilder is a case class that captures information about a Druid Query. It also captures mapping information from Spark Expressions to Results coming out of Druid: including dataType and column name mappings. There are several DruidTransforms to convert different Plan trees to a DruidQuery, but the Logical Plan must at least contain an Aggregation Operator. More on this in the Query Rewrite Rules section.

Mapping Druid results into Spark Rows

Query Building: Column Name, Type mapping

The DruidQueryBuilder maintains a map from the Druid Query Result column-Name to the triple: (Expression, spark DataType, druid DataType):

- Expression is the Catalyst Expression from the original Plan that the Druid column in the Result row represents.
- The DataType of the Expression in the original SQL plan.
- The DataType of the value returned by Druid.

The 2 datatypes need not match; during rewrite a check is made to see if the conversion from the Druid datatype to Spark Expression datatype is valid. If not, the rewrite doesn't happen. This map is populated as expressions from the Aggregate Operator are added to the DruidQueryBuilder.

Setting up the Output Schema of the PhysicalRDD Operator that wraps the Druid RDD

The schema for the PhysicalRDD Operator is formed by creating a StructType from each of the columns in the output Map maintained by the DruidQueryBuilder. For Grouping Expressions that were AttributeReferences in the original Plan, we reuse their ExprIds; for non AttributeReferences new ExprIds are generated. This way any resolved AttributeReferences above the replaced Plan SubTree are still valid and point to the correct child Attribute in the rewritten Plan.

Projection on top of the PhysicalRDD Operator.

A Projection Operator is added above the PhysicalRDD Operator to:

- provide the same schema as the original Aggregate Operator. (or the Ordering/Filter Operator above the Agg.Op in case of having/order/limit rewrites)

- To ensure Attribute names, ExprId and DataTypes match what was in the original Operator.

The ProjectionList is formed from the aggregation expressions of the original Agg. Operator. Any expressions that were mapped to Druid Result columns are replaced by AttributeReferences to the child PhysicalRDD Attributes. The following rules are followed:

- If needed the AttributeReference is wrapped in a cast to convert to the original Spark Plan's dataType.
- AttributeReferences in the original Plan carry the original ExprId, so that references above this Operator remain valid. Names from the original AttributeReference are also maintained by wrapping the new AttributeReference in an Alias.

TPCH Flattened Cube example

We explain the Rewrite rules by giving examples from the following setup. Consider a raw transaction log that is based on the TPCB benchmark specification

Listing 2: The TPCB denormalized DataFrame

```

1 CREATE TEMPORARY TABLE orderLineItemPartSupplierBase(
2   o_orderkey integer, o_custkey integer,
3   o_orderstatus string, o_totalprice double, o_orderdate string,
4   o_orderpriority string, o_clerk string,
5   o_shippriority integer, o_comment string, l_partkey integer,
6   l_suppkey integer, l_linenummer integer,
7   l_quantity double, l_extendedprice double, l_discount double,
8   l_tax double, l_returnflag string,
9   l_linestatus string, l_shipdate string, l_commitdate string,
10  l_receiptdate string, l_shipinstruct string,
11  l_shipmode string, l_comment string, order_year string,
12  ps_partkey integer, ps_suppkey integer,
13  ps_availqty integer, ps_supplycost double, ps_comment string,
14  s_name string, s_address string,
15  s_phone string, s_acctbal double, s_comment string,
16  s_nation string, s_region string, p_name string,
17  p_mfgr string, p_brand string, p_type string, p_size integer,
18  p_container string, p_retailprice double,
19  p_comment string, c_name string, c_address string,
20  c_phone string, c_acctbal double,
21  c_mktsegment string, c_comment string, c_nation string,
22  c_region string)
23 USING com.databricks.spark.csv
24 OPTIONS (
25   path "tpchFlattenedData_10/orderLineItemPartSupplierCustomer",
26   header "false", delimiter "|"
27 )

```

This is a single transaction table that is formed by denormalizing(flattening) the TPCB Star Schema. We have a TpchGen tool for creating a flattened transaction table from an existing Tpch Star schema.

Also assume there is a Druid Index built for this DataSet and is exposed in Spark as a DruidDataSource

Listing 3: TPCCH Druid DataSource

```

1 CREATE TEMPORARY TABLE orderLineItemPartSupplier
2   USING org.sparklinedata.druid
3   OPTIONS (sourceDataframe "orderLineItemPartSupplierBase",
4     timeDimensionColumn "l_shipdate",
5     druidDatasource "tpch",
6     druidHost "localhost",
7     druidPort "8082",
8     columnMapping '{ "l_quantity" : "sum_l_quantity",
9                      "ps_availqty" : "sum_ps_availqty"
10                    }'
11 )

```

So queries are rewritten against the 'orderLineItemPartSupplier' table. For example TPCCH Q1 is written as:

Listing 4: Sample Query

```


1 select l_returnflag, l_linestatus, count(*),
2       sum(l_extendedprice) as s, max(ps_supplycost) as m,
3       avg(ps_availqty) as a, count(distinct o_orderkey)
4 from orderLineItemPartSupplier
5 group by l_returnflag, l_linestatus

```

Without the DruidPlanner configured these queries will run as if they are issued against the underlying sourceDataFrame, in this case against the wrapped DataSource 'orderLineItemPartSupplierBase'.

Query Rewrite and Validation Rules

Plans that can be rewritten must have the following core structure.



The base of the Plan must be a Physical RDD Operator on a DruidRelation, followed by 0 or more Project/Filter criteria, followed by an Aggregation. Only plans with this core structure are considered for rewrite. On top of the Aggregation, there can optionally be a Filter(representing the SQL having clause), a Sort and a Limit.

Validation 1: Base table column validation

Columns referenced in the Project below the Aggregate must have a corresponding column in the Druid Index.

Rewrite 2: Filter Rewrite

The Filter predicates are combined into **Conjunctive Normal Form**. An attempt is made to rewrite each conjunct. If any conjunct cannot be rewritten, then the Plan is not rewritten.

Rewrite 2.1: Interval condition rewrite A predicate of the form `compOp(dateTime(timeDim), literalDateTime)` is extracted as an *time Interval* of the Druid Query.

Where 'compOp' can be the following functions: `dateIsBeforeFn`, `dateIsBeforeOrEqualFn`, `dateIsAfterFn`, `dateIsAfterOrEqualFn`. The comparison needs to be on the column that is the time dimension in the Druid Index (in our example the 'l_shipDate' column). The literal-date is an expression representing a date. It can be a literal date specified with `dateTime`, `dateTimeWithTZFn`, `dateTimeWithFormatFn`, `dateTimeWithFormatAndTZFn` optionally followed by (+/-) a *Period* specification. For example the following predicate is translated to the Interval ("1992-12-01", "1997-09-02") :

```
dateIsBeforeOrEqual(  
  dateTime('l_shipdate'),  
  dateMinus(  
    dateTime("1997-12-01"),  
    period("P90D")  
  )  
)
```

It is much easier to read when specified using spark-dateTime dsl

```
dateTime('l_shipdate') <= (dateTime("1997-12-01") - 90.day)
```

Currently we only translate the SQL predicates into a single interval. The QueryIntervals class is setup to handle multiple intervals. In the future we plan to handle a disjunction of date Predicates in each conjunct.

Rewrite 2.2: Dimension Filter rewrite Predicates of the form `dimCol compOp Literal` or `Literal compOp dimCol` are converted into Filter Specifications on the Druid Query. The column being compared must be a dimension column in the Druid Index. The comparator operator needs to be `<`, `>`, `<=`, `>=`, `=`. Comparison predicates can be combined with logical `and`, `or` operators.

Rewrite 3: Grouping Expressions

A Group-By expression can be on a Druid index dimension or a `dateTime` expression on a regular or time dimension in the Druid index. The `dateTime` expression must be of the form `dateElem(dateTimeFn(col))`. The 'dateTimeFn'

form must be `dateTime`, `withZone(dateTime...)`, that is a `dateTime` expression or a `dateTime` with `Timezone` application. The column must be a dimension or the time column of the Druid Index. The element being extracted can be any of:

```
era, century, yearOfEra, yearOfCentury, year, weekyear,
monthOfYear, monthOfYearName, weekOfWeekyear,
dayOfYear, dayOfMonth, dayOfWeek, dayOfWeekName,
hourOfDay, secondOfMinute
```

An expression on a dimension is expressed as a `DefaultDimension Specification` the `DruidQuery`. While a time element expression is converted to a `TimeFormatExtraction Specification`.

Rewrite 4: Aggregation Expressions

From the aggregation list we extract the `AggregateFunction` invocations, and attempt to translate them to `Druid Aggregation` and `PostAggregation Specifications` on the `Druid Query`. On the translated Plan a `Project` operator is placed on top of the `Druid Relation` to compute any expressions that the `Aggregate Function` invocations were part of. So for the expression `sum(p_retailprice) - 5`: the `sum(p_retailprice)` is pushed to the `Druid Query`; the subtraction on the sum is handled in the `Project Operator` on top.

The following rules are used to translate `Aggregate functions`

Count `Count(1)` is translated to a `Cardinality Aggregation Specification`.

Sum, Min, Max The aggregation must be on a `Druid Metric` column. The `dataType` of the expression must be convertible from the `Druid metric dataType` without loss of precision. The expression is translated to a `Function Aggregation Specification` on the `Druid Query`.

Avg This has the same constraints as `Sum/Min/Max`. It is converted to a `Post Aggregation Specification` of dividing the `Sum` by the `Count`.

CountDistinct Is converted to `Cardinality Aggregation Specification`. `Druid` uses `HyperLogLog` to estimate this. So in the future we will add a parameter to the `DataSource`, so users can control if this rewrite should be allowed.

Rewrite 5: Having predicates (TBD)

Predicates on the `Aggregation expressions` will be pushed down as `Having Specifications` in the `Druid Query`.

Rewrite 6: Sort Operator (TBD)

A `Sort Operator` on top of `Aggregation` will be pushed down as a `Limit Specification` in the `Druid Query`.

Rewrite 7: Limit Operator (TBD)

A Limit Operator on top of a Sort will be pushed down as a limit value on the Limit Specification in the Druid Query.

Rewrite 8: Enhanced Time Granularity and Interval Handling

We currently assume that the Druid Index has the same Time Granularity and Range as the **raw** data. This is obviously not necessary, and in practice an uncommon way to setup the Index. More likely, the Index is on a Grain(hourly, daily) higher than the raw events. Also index for old data maybe removed for space reasons.

Shorter Time Range for Druid Index

It is likely that the DruidIndex is maintained for a smaller Time window like the last year; whereas the raw dataset is for much longer time window. In such cases the original Plan should be converted into a **union all Plan**. The component queries being a Druid Query on the Time Window that is in the Druid Index(and intersects with the Query predicate) and a Spark Query on the raw event DataSource for the remaining Time Window.

Druid Index on a higher Time Grain.

It is likely that the Druid Index doesn't hold raw data, but is aggregated up to a minimum time grain such as an hour or a day. In this the original Plan can only be rewritten if the Query has a Time Aggregation that is at a higher grain than the granularity in the Druid Index.

Benchmark

The Benchmark was run on a 4 node cluster. Each node is a 2 core,16GB memory, 256GB hard drive machine running centos 6.4. The output of the **lscpu** and **hdparm** are listed below:

Listing 5: Machine Details

```
1
2 lscpu
3
4 Architecture:          x86_64
5 CPU op-mode(s):        32-bit , 64-bit
6 Byte Order:            Little Endian
7 CPU(s):                 2
8 On-line CPU(s) list:   0,1
9 Thread(s) per core:    1
10 Core(s) per socket:    1
11 Socket(s):              2
12 NUMA node(s):          1
13 Vendor ID:              GenuineIntel
14 CPU family:             6
15 Model:                  42
16 Stepping:               1
17 CPU MHz:                1999.999
18 BogoMIPS:               3999.99
19 Virtualization:         VT-x
```

```

20 Hypervisor vendor:      KVM
21 Virtualization type:    full
22 L1d cache:             32K
23 L1i cache:             32K
24 L2 cache:              4096K
25 NUMA node0 CPU(s):     0,1
26
27 sudo hdparm -tT /dev/vdb
28
29 /dev/vdb:
30   Timing cached reads:   12798 MB in  2.00 seconds = 6408.97 MB/sec
31   Timing buffered disk reads: 540 MB in  3.00 seconds = 179.98 MB/sec

```

The machines are setup with HDP 2.3 using Ambari. Also installed Druid 0.8 on the machines. The cluster is configured to use Yarn; we installed and setup Spark 1.4.1 to run using the Yarn Resource Manager.

For the benchmark we used the TPC-H benchmark dataset, datascale 10G. We converted the 10G star schema into a flattened(denormalized) transaction dataset using a tool we wrote TpchGenFlattenedData, for example we ran it like this:

```

spark/bin/spark-submit -num-executors 7 -properties-file spark-druid/spark.properties \
-packages com.databricks:spark-csv2.10:1.1.0 \
-jars spark-druid/spark-datetime-assembly-0.0.1.jar,spark-druid/spark-druid-olap-assembly-
-class org.sparklinedata.tpch.hadoop.TpchGenFlattenedData \
spark-druid/tpchdata-assembly-0.0.1.jar tpchflatorc10 tpchflattened

```

For spark we further processed the data to setup a Partitioned table, stored in Parquet format; the table is partitioned by day. We use the TpchBuildParquetPartitioned to do this.

The Druid Index was created using the HadoopDruidIndexer with the following command:

```

java -Xmx256m -Dhdp.version=2.3.0.0-2557 -Duser.timezone=UTC \
-Dfile.encoding=UTF-8 -classpath \
$DIR/config/_common:$HADOOP_CONF_DIR:$DIR/lib/* \
io.druid.cli.Main index hadoop <spec_file>

```

See Druid TPC-H Index Specification for detailed specification of the TPC-H index in Druid.

DataSource setup

The raw event DataSource and Druid datasource are defined in the following way:

Listing 6: Raw Event DataSource

```

1
2 // parquet based partitioned table
3 val df = sqlCtx.read.parquet(cfg.tpchFlatDir)
4 df.cache()

```

```

5 df.registerTempTable("orderLineItemPartSupplier")
6
7 // Druid Datasource
8 CREATE TEMPORARY TABLE orderLineItemPartSupplier
9   USING org.sparklinedata.druid
10  OPTIONS (sourceDataframe "$baseFlatTableName",
11          timeDimensionColumn "l_shipdate",
12          druidDatasource "tpch",
13          druidHost "${cfg.druidBroker}",
14          druidPort "8082");

```

Queries

The Queries we ran have the following form:

- aggregation on the entire dataset
- aggregation on a time slice
- aggregation on a time slice with Dimension Filters applied.

Basic Aggregation

Listing 7: Basic Aggregation Query

```

1 select l_returnflag, l_linestatus, count(*),
2       sum(l_extendedprice) as s, max(ps_supplycost) as m,
3       avg(ps_availqty) as a, count(distinct o_orderkey)
4       from orderLineItemPartSupplier
5       group by l_returnflag, l_linestatus

```

Interval and Dimension Filters

Listing 8: Interval and Dimension Filters Query

```

1
2 val shipDtPredicateA =
3   dateTime('l_shipdate') <= (dateTime("1997-12-01") - 90.day)
4 sqlCtx.sql(
5   date"""
6   select f, s, count(*) as count_order
7   from
8   (
9     select l_returnflag as f, l_linestatus as s,
10      l_shipdate, s_region, s_nation, c_nation
11     from orderLineItemPartSupplier
12   ) t
13   where $shipDtPredicateA and
14     ((s_nation = 'FRANCE' and c_nation = 'GERMANY') or
15      (c_nation = 'FRANCE' and s_nation = 'GERMANY'))
16   )
17   group by f, s

```

```

18         order by f,s
19     """)

```

Ship Date Range

Listing 9: Ship Date Range Query

```

1
2 val shipDtPredicate =
3     dateTime('l_shipdate') <= (dateTime("1997-12-01") - 90.day)
4 val shipDtPredicate2 =
5     dateTime('l_shipdate') > (dateTime("1995-12-01"))
6
7 sqlCtx.sql(
8     date""
9     select f, s, count(*) as count_order
10    from
11    (
12        select l_returnflag as f, l_linestatus as s,
13              l_shipdate, s_region, s_nation, c_nation
14        from orderLineItemPartSupplier
15    ) t
16    where $shipDtPredicate and $shipDtPredicate2
17    group by f,s
18    order by f,s""
19 )

```

SubQuery + nation,Type predicates + ShipDate Range

Listing 10: Nation,Part type predicates + ShipDate Range Query

```

1
2 val shipDtPredicateL =
3     dateTime('l_shipdate') <= (dateTime("1997-12-01") - 90.day)
4 val shipDtPredicateH =
5     dateTime('l_shipdate') > (dateTime("1995-12-01"))
6
7 sqlCtx.sql(
8     date""
9     select s_nation,
10          count(*) as count_order,
11          sum(l_extendedprice) as s,
12          max(ps_supplycost) as m,
13          avg(ps_availqty) as a,
14          count(distinct o_orderkey)
15    from
16    (
17        select l_returnflag as f, l_linestatus as s, l_shipdate,
18              s_region, s_nation, c_nation, p_type,
19              l_extendedprice, ps_supplycost, ps_availqty, o_orderkey
20        from orderLineItemPartSupplier
21        where p_type = 'ECONOMY ANODIZED STEEL'

```



```

22         ) t
23     where $shipDtPredicateL and
24           $shipDtPredicateH and
25           ((s_nation = 'FRANCE' and c_nation = 'GERMANY') or
26            (c_nation = 'FRANCE' and s_nation = 'GERMANY')
27           )
28     group by s_nation
29     order by s_nation
30 """)

```

TPCH Q1

Listing 11: TPCH Q1

```

1 sqlCtx.sql("""select l_returnflag, l_linestatus, count(*),
2 sum(l_extendedprice) as s, max(ps_supplycost) as m,
3 avg(ps_availqty) as a, count(distinct o_orderkey)
4 from orderLineItemPartSupplier
5 group by l_returnflag, l_linestatus""")
6
7 )

```

Running the Benchmark

Druid Rewrites

For the Druid experiment the queries are run on spark using the Druid Tpch-BenchMark tool. It is run using the following command:

Listing 12: Running Tpchbenchmark on Druid Datasource

```

1
2 ~/spark-1.4.1-bin-hadoop2.6/bin/spark-submit \
3 --properties-file spark.properties \
4 --packages com.databricks:spark-csv_2.10:1.1.0 \
5 --jars sparkjars/spark-datetime-assembly-0.0.1.jar \
6 --class org.sparklinedata.druid.tools.TpchBenchMark \
7 sparkjars/spark-druid-olap-assembly-0.0.1.jar \
8 -n hb-1.openstacklocal \
9 -t tpchFlattenedData_10/orderLineItemPartSupplierCustomer \
10 -d hb-1.openstacklocal

```

The cluster is setup to run a historical server on each node. Each historical server is configure with 8GB of memory:

```

JAVA_HISTORICAL_OPTIONS="-server \
-Xmx8g \
-Xms8g \
-XX:NewSize=1g \
-XX:MaxNewSize=1g \
-XX:MaxDirectMemorySize=10g \
-XX:+UseConcMarkSweepGC \

```

```
-XX:+PrintGCDetails \
-XX:+PrintGCTimeStamps \
-XX:+HeapDumpOnOutOfMemoryError \
-Duser.timezone=UTC \
-Dfile.encoding=UTF-8"
```

The spark shell is run in local mode on one of the nodes, so that Spark uses as little cluster resources as possible.

Test against native Spark

For the queries goin against Spark we used the Spark TpchBenchmark tool. It is run with the following command:

Listing 13: Running the Benchmark, on the Raw Event DataFrame

```
1 ~/spark-1.4.1-bin-hadoop2.6/bin/spark-submit \
2 --properties-file spark.properties \
3 --packages com.databricks:spark-csv_2.10:1.1.0 \
4 --jars sparkjars/spark-datetime-assembly-0.0.1.jar,\
5       sparkjars/spark-druid-olap-assembly-0.0.1.jar,\
6       sparkjars/tpchdata-assembly-0.0.1.jar \
7 --num-executors 4 --master yarn-client \
8 --class org.sparklinedata.tpch.hadoop.TpchParquetBenchmark \
9 sparkjars/tpchdata-assembly-0.0.1.jar \
10 -t tpchFlattenedData_10/orderLineItemPartSupplierCustomer.parquet.partitioned
```

In this case we give the Spark executors as much of the Yarn cluster as possible. The Spark configuration is:

```
spark.serializer=org.apache.spark.serializer.KryoSerializer
#spark.sql.autoBroadcastJoinThreshold=100000000
spark.sql.autoBroadcastJoinThreshold=-1
spark.sql.planner.externalSort=true

spark.executor.memory=9g
spark.driver.memory=2g
#spark.executor.cores=2
```

As part of the initialization, the orderLineItemPartSupplier DataFrame is cached in memory.

Future work

Appendix

Druid TPCP Index Specification

```
{
  "dataSchema": {
```

```

        "dataSource": "tpch",
        "parser": {
            "type": "string",
            "parseSpec": {
                "format": "tsv",
                "timestampSpec": {
                    "column": "l_shipdate",
                    "format": "iso"
                }
            },
            "columns": [
                "o_orderkey",
                "o_custkey",
                "o_orderstatus",
                "o_totalprice",
                "o_orderdate",
                "o_orderpriority",
                "o_clerk",
                "o_shippriority",
                "o_comment",
                "l_partkey",
                "l_suppkey",
                "l_linenumber",
                "l_quantity",
                "l_extendedprice",
                "l_discount",
                "l_tax",
                "l_returnflag",
                "l_linestatus",
                "l_shipdate",
                "l_commitdate",
                "l_receiptdate",
                "l_shipinstruct",
                "l_shipmode",
                "l_comment",
                "order_year",
                "ps_partkey",
                "ps_suppkey",
                "ps_availqty",
                "ps_supplycost",
                "ps_comment",
                "s_name",
                "s_address",
                "s_phone",
                "s_acctbal",
                "s_comment",
                "s_nation",
                "s_region",
                "p_name",
                "p_mfgr",
                "p_brand",

```

```

    "p_type",
    "p_size",
    "p_container",
    "p_retailprice",
    "p_comment",
    "c_name",
    "c_address",
    "c_phone",
    "c_acctbal",
    "c_mktsegment",
    "c_comment",
    "c_nation",
    "c_region"
  ],
  "delimiter": "|",
  "dimensionsSpec": {
    "dimension": [
      "o_orderkey",
      "o_orderdate",
      "o_orderstatus",
      "o_orderpriority",
      "o_clerk",
      "o_shippriority",
      "o_comment",
      "l_returnflag",
      "l_linestatus",
      "l_commitdate",
      "l_receiptdate",
      "l_shipinstruct",
      "l_shipmode",
      "l_comment",
      "ps_comment",
      "s_name",
      "s_address",
      "s_phone",
      "s_comment",
      "s_nation",
      "s_region",
      "p_name",
      "p_mfgr",
      "p_brand",
      "p_type",
      "p_size",
      "p_container",
      "p_retailprice",
      "p_comment",
      "c_name",
      "c_address",
      "c_phone",
      "c_mktsegment",

```

```

        "c_comment",
        "c_nation",
        "c_region"
    ],
    "dimensionExclusions": [],
    "spatialDimensions": []
}

    },
    "metricsSpec": [
        {
            "type": "count",
            "name": "count"
        },
        {
            "type": "doubleSum",
            "name": "o_totalprice",
            "fieldName": "o_totalprice"
        },
        {
            "type": "longSum",
            "name": "l_quantity",
            "fieldName": "l_quantity"
        },
        {
            "type": "doubleSum",
            "name": "l_extendedprice",
            "fieldName": "l_extendedprice"
        },
        {
            "type": "javascript",
            "name": "l_tax",
            "fieldNames": [
                "l_extendedprice",
                "l_discount",
                "l_tax"
            ],
            "fnAggregate": "function(current, l_extendedprice, l_discount, l_tax) { return current + (",
            "fnCombine": "function(partialA, partialB) { return partialA + partialB; }",
            "fnReset": "function() { return 0; }"
        },
        {
            "type": "javascript",
            "name": "l_discount",
            "fieldNames": [
                "l_extendedprice",
                "l_discount"
            ],
            "fnAggregate": "function(current, l_extendedprice, l_discount) { return current + (l_exten",
            "fnCombine": "function(partialA, partialB) { return partialA + partialB; }",

```

```

"fnReset": "function()                                { return 0; }"
    },
    {
      "type": "longSum",
      "name": "ps_availqty",
      "fieldName": "ps_availqty"
    },
    {
      "type": "doubleSum",
      "name": "ps_supplycost",
      "fieldName": "ps_supplycost"
    },
    {
      "type": "doubleSum",
      "name": "c_acctbal",
      "fieldName": "c_acctbal"
    }
  ],
  "granularitySpec": {
    "type": "uniform",
    "segmentGranularity": "MONTH",
    "queryGranularity": "NONE",
    "intervals": [
      "1993-01-01/1997-12-31"
    ]
  },
  "ioConfig": {
    "type": "hadoop",
    "inputSpec": {
      "type": "static",
      "paths": "hdfs://hb-1.openstacklocal/user/hive/tpchFlattenedData_10/orderLineItemPar
    },
    "metadataUpdateSpec": {
      "type": "mysql",
      "connectURI": "jdbc:mysql://hb-2.openstacklocal:3306/druid",
      "password": "diurd",
      "segmentTable": "druid_segments",
      "user": "druid"
    },
    "segmentOutputPath": "hdfs://hb-1.openstacklocal/user/hive/druidStorage"
  },
  "tuningConfig": {
    "type": "hadoop",
    "workingPath": "/tmp",
    "partitionsSpec": {
      "type": "hashed",
      "targetPartitionSize": 10000000
    },
    "leaveIntermediate": false,

```

```
    "cleanupOnFailure": true,  
    "overwriteFiles": false,  
    "ignoreInvalidRows": false  
  }  
}
```

References

- [DRUID01] : A Real-time Analytical Data Store