

C-253

APPENDIX C

APPENDIX C

TABLE C.5.1-M.1. M.1/M.81/M.11D to Link 16 Message Translation Tree (Sheet
2 of 4)

NOTES

1. The locations of all units in the Link 11/11B interface must be reported either in the M.1 Data Reference Position message or the M.5 Special Points Position message. However, systems may, in the same Link 11 transmit opportunity, report unit location in M.1's having R/P = 0 followed by a report of the SCC location in M.1's having R/P = 1, in which case, an M.5 message will not normally be received.
2. The FJU shall check to determine if M.11D message(s) having IFF/SIF data for the unit follow the M.1 or M.1/M.81 sequence. This check will terminate after three Link 11/11B message frame times.

MIL-STD-6016B

APPENDIX C

TABLE C.5.1-M.1. M.1/M.81/M.11D to Link 16 Message Translation Tree (Sheet
3 of 4)

RELATED MESSAGES

RECEIVED LINK 11/11B
MESSAGE

M.1/M.81
M.11D

ALL POSSIBLE LINK 16 MESSAGES
THAT MAY BE REQUIRED

J2.0
J7.5

APPENDIX C

TABLE C.5.1-M.1. M.1/M.81/M.11D to Link 16 Message Translation Tree (Sheet
4 of 4)

FORWARDING TRANSMIT REQUIREMENTS

1. A single J2.0 message shall be transmitted for each M.1 message sequence received on Link 11. In cases where two separate M.1 message sequences are received during a single transmit opportunity, the FJU may transmit a single J2.0 or a separate J2.0 for each M.1 sequence.
2. J2.0 messages shall be redundantly transmitted for all active units received from Link 11B.
3. The J2.0C1 shall be transmitted by the FJU with the next periodic update of the J2.0B message when IFF/SIF data are received.

DATA RETENTION RULES

1. The FJU shall retain track and IFF/SIF data on all active PUs and RUs for whom data are being forwarded.
2. Timers shall be maintained on each active PU and RU being forwarded for proper initiation of update PPLI messages or Drop Track messages.