

C-297

APPENDIX C

MIL-STD-6016B

TABLE C.5.1-M.6D. M.6D or M.6D/M.86D to Link 16 Message Translation Tree (Sheet 2 of 5)

C-298

TEST NODE DIAGRAM	TEST NODE CONDITION	NOTES
<pre>graph TD 10[10] -- N --> 13[13] 10 -- Y --> 11[11] 11 -- N --> 13 11 -- Y --> 12[12] 12 -- N --> 13 12 -- Y --> 14[14] 13 -- N --> 14 13 -- Y --> 14 14 -- N --> 13 14 -- Y --> 14</pre>	10. CONTROL = 5. 11. FREQUENCY/FREQUENCY RANGE = 0. 12. EMITTER FUNCTION AND EMITTER NUMBER = 0. 13. CONTROL = 7, 12, OR 13 AND REFERENCED/ CANCELLED CONTROL VALUE IS OTHER THAN 5 THROUGH 13. 14. CONTROL = 14 OR 15.	
	REQUIRED ACTION	
A C G H I J Z	A. DISCARD MESSAGE. C. FWD J14.2I/J14.2E0. G. FWD J14.2I/J14.2E0/J14.2C1. H. FWD J14.2I/J14.2E0/J14.2C1/J14.2C3. I. FWD J14.2I/J14.2E0/J14.2C1/J14.2C3/ J14.2C4. J. FWD J14.2I/J14.2E0/J14.2C1/J14.2C4. Z. END TRANSLATION.	

APPENDIX C

TABLE C.5.1-M.6D. M.6D or M.6D/M.86D to Link 16 Message Translation Tree
(Sheet 3 of 5)

NOTES

1. The FJU shall discard all identical M.6D EW Control/Coordination (Addressee = 177 (octal) or no Addressee) messages received within 90 seconds after the initial message is received and forwarded.
2. The collective address of 177 (octal) is included as one for which data are being forwarded.

MIL-STD-6016B

APPENDIX C

TABLE C.5.1-M.6D. M.6D or M.6D/M.86D to Link 16 Message Translation Tree
(Sheet 4 of 5)

RELATED MESSAGES

RECEIVED LINK 11/11B
MESSAGE

M.6D
M.86D

ALL POSSIBLE LINK 16 MESSAGES
THAT MAY BE REQUIRED

J14.2

APPENDIX C

TABLE C.5.1-M.6D. M.6D or M.6D/M.86D to Link 16 Message Translation Tree
(Sheet 5 of 5)

FORWARDING TRANSMIT REQUIREMENTS

1. The J14.2 message with other than R/C = 1 shall be redundantly forwarded until a Machine Receipt, or other appropriate reply, is received or until redundancy requirements are met. When redundancy requirements are met and a reply has been received for an Original (R/C = 0) EW Coordination and Control message, the FJU shall reply on Link 11 with an automatic CANTCO (R/C = 3).
2. The J14.2 message with R/C = 1 shall be forwarded three times on Link 16. The redundant M.6D(R/C=1) messages received will be discarded.

DATA RETENTION RULES

There are no Data Retention Rules associated with this message translation.