

C-305

APPENDIX C

MIL-STD-6016B

APPENDIX C

TABLE C.5.1-M.9A. M.9A to Link 16 Message Translation Tree (Sheet 4 of 8)

NOTES

1. The following messages or message sequences constitute valid track reports which follow the M.9A(AC=0) message. When the amplifying message as specified below is not received, the M.9A(AC=0) message shall be discarded.

- o M.2 (valid only on Link 11)
- o M.2/M.82
- o M.3 (valid only on Link 11)
- o M.3/M.83
- o M.4A
- o M.4A/M.84A
- o M.4C/M.84C
- o M.4D/M.84D
- o M.5
- o M.5/M.85
- o M.6A
- o M.6B/M.86B
- o M.9F/M.89F

The following messages or message sequences constitute valid track reports which follow the M.9A(AC=5) message. When the amplifying message as specified below is not received, the M.9A(AC=5) message shall be discarded. The M.9A (AC=5, STI=0) Emergency Alert shall also be discarded whenever an M.5, M.4A or M.4C translates to a J3.0 Reference Point message (i.e., M.5 Point Type = 2,4,5,6,8,9 or 10, M.4A Data Report Type = 3, or M.4C Switch = 2 or 3). The M.9A (AC=5) Alert shall also be discarded whenever an M.5 translates to a J3.1 Emergency Point message (i.e., M.5 Point Type = 7).

- o M.2/M.82
- o M.3/M.83
- o M.4A
- o M.4A/M.84A
- o M.4C/M.84C

APPENDIX C

TABLE C.5.1-M.9A. M.9A to Link 16 Message Translation Tree (Sheet 5 of 8)

NOTES (Continued)

- o M.4D/M.84D
- o M.5
- o M.6A
- o M.6B/M.86B
- o M.9A(AC=0, SI=1)

2. Refer to the specific Link 11/11B message to Link 16 message translation tree to determine the appropriate J series message to be forwarded.

3. When the addressed unit is the FJU, it shall, when appropriate, respond with M.5(PT=13) messages in an initial report sequence for all active interface units for which data are being forwarded.

4. The source, SPI, and Simulation Indicator data in the M.9A(AC=0) message from Link 11B and the track alert status data in the M.9A(AC=5 or 7) message must be retained in the FJU database for utilization in track reports. The controlling unit address in the M.9A(AC=6) message must also be retained for identity difference and change data order processing.

5. Receipt of a change to the M.9A(AC=1) CI value shall be retained in the FJU database for transmission of the appropriate J3.x message.

6. If the FJU is retaining ID data received in a previous M.9A(AC=1, CI=0) or J7.0(ACT = 1) message for the same TN, discard this message.

APPENDIX C

TABLE C.5.1-M.9A. M.9A to Link 16 Message Translation Tree (Sheet 6 of 8)

RELATED MESSAGES

RECEIVED LINK 11/11B
MESSAGE

M.9A

ALL POSSIBLE LINK 16 MESSAGES
THAT MAY BE REQUIRED

J7.0(ACT = 0, 1, 2, 3, or 4)
J7.1
J7.5
J10.5

APPENDIX C

TABLE C.5.1-M.9A. M.9A to Link 16 Message Translation Tree (Sheet 7 of 8)

FORWARDING TRANSMIT REQUIREMENTS

1. A single J7.0 message shall be forwarded for the first M.9A(AC=1, CI=0) or M.9A(AC=7) message received. The FJU shall discard all identical messages received within 30 seconds after the initial message is received and forwarded.
2. A single J7.0 message shall be forwarded for each M.9A(AC=2) message received.
3. A single J7.1 message shall be forwarded for each M.9A(AC=3) message received.
4. A single J7.0 message shall be forwarded on the Surveillance NPG for each M.9A(AC=4) message received. If the TN in the M.9A(AC=4) message is being reported in M.6 or M.9F (Source = 1) messages, the J7.0 message may be transmitted on both the Surveillance and EW NPGs. The FJU shall discard all identical messages received within 30 seconds after the initial message is received and forwarded.
5. A single J7.0 message shall be forwarded for the first M.9A(AC=5) message received from a nonR² unit. When the first M.9A(AC=5) message is received from the R² unit, the appropriate alert indication in the Link 16 series message will be set. This alert indication will be retained until terminated by any unit. The FJU shall discard all identical messages received within 30 seconds after the initial message is received and forwarded.
6. A single J10.5 message shall be forwarded for each M.9A(AC=6) message received. The M.9A(AC=6) message identity data will not be used when forwarding surveillance data.
7. A single J7.5 message shall be forwarded for the first M.9A(AC=9) message received. The FJU shall discard all identical messages received within 30 seconds after the initial message is received and forwarded.

APPENDIX C

TABLE C.5.1-M.9A. M.9A to Link 16 Message Translation Tree (Sheet 8 of 8)

DATA RETENTION RULES

1. The SPI, Simulation Indicator, and Source data from the Link 11B M.9A(AC=0) message shall be retained in the FJU database for utilization in track reports.
2. The FJU shall retain the latest reported status of the Emergency and Force Tell Indicators for all tracks being forwarded.
3. The current controlling unit address received in an M.9A(AC=6, STI=0) shall be retained in the FJU database until control is terminated.
4. The FJU shall retain and update IFF/SIF information received in an M.9A(AC=9, ISAC=0) IFF/SIF Clear message received from any source.
5. The FJU shall retain ID data received in an M.9A(AC=1, CI=0) message from a nonR² unit for the track until the conflict has been resolved by the R² unit or an R² shift occurs.