

[HOME](#) [TOP](#) [CATALOG](#) [CONTESTS](#) [GYM](#) [PROBLEMSET](#) [GROUPS](#) [RATING](#) [EDU](#) [API](#) [CALENDAR](#) [HELP](#)
[PROBLEMS](#) [SUBMIT CODE](#) [MY SUBMISSIONS](#) [STATUS](#) [HACKS](#) [ROOM](#) [STANDINGS](#) [CUSTOM INVOCATION](#)

C. Sasha and the Casino

time limit per test: 2 seconds
 memory limit per test: 256 megabytes
 input: standard input
 output: standard output

Sasha decided to give his girlfriend the best handbag, but unfortunately for Sasha, it is very expensive. Therefore, Sasha wants to earn it. After looking at earning tips on the internet, he decided to go to the casino.

Sasha knows that the casino operates under the following rules. If Sasha places a bet of y coins (where y is a positive integer), then in case of winning, he will receive $y \cdot k$ coins (i.e., his number of coins will increase by $y \cdot (k - 1)$). And in case of losing, he will lose the entire bet amount (i.e., his number of coins will decrease by y).

Note that the bet amount must always be a positive (> 0) integer and cannot exceed Sasha's current number of coins.

Sasha also knows that there is a promotion at the casino: he cannot lose more than x times in a row.

Initially, Sasha has a coins. He wonders whether he can place bets such that he is guaranteed to win any number of coins. In other words, is it true that for any integer n , Sasha can make bets so that for any outcome that does not contradict the rules described above, at some moment of time he will have at least n coins.

Input

Each test consists of multiple test cases. The first line contains a single integer t ($1 \leq t \leq 1000$) — the number of test cases. The description of the test cases follows.

The single line of each test case contains three integers k , x and a ($2 \leq k \leq 30$, $1 \leq x \leq 100$, $1 \leq a \leq 10^9$) — the number of times the bet is increased in case of a win, the maximum number of consecutive losses, and the initial number of coins Sasha has.

Output

For each test case, output "YES" (without quotes) if Sasha can achieve it and "NO" (without quotes) otherwise.

You can output "YES" and "NO" in any case (for example, the strings "yEs", "yes" and "Yes" will be recognized as a positive answer).

Example

input	Copy
9 2 1 7 2 1 1 2 3 15 3 3 6 4 4 5 5 4 7 4 88 1000000000 25 69 231 13 97 18806	
output	Copy
YES NO YES NO NO YES NO NO NO	

Codeforces Round 926 (Div. 2)

Finished

Practice


[→ Virtual participation](#)
[→ Clone Contest to Mashup](#)

You can clone this contest to a mashup.

[Clone Contest](#)
[→ Submit?](#)

 Language: Python 3.8.10
 Almost always, if you send a solution on PyPy, it works much faster

 Choose file: [Choose File](#) No file chosen

[Submit](#)
[→ Problem tags](#)
binary search brute force
constructive algorithms games greedy
math *1400

No tag edit access

[→ Contest materials](#)

- Announcement
- Tutorial (en)

Note

In the first test case, Sasha can proceed as follows:

- If Sasha places a bet for the first time or if he won the previous bet, then he places 1 coin.
- If Sasha lost the previous bet, then he places 2 coins.

Note that Sasha cannot lose more than once in a row.

It can be proven that with this strategy, Sasha can obtain as many coins as he wants.

In the second test case, Sasha can only place 1 coin for the first time. But in case of a loss, he will not be able to place any more bets, so he will not be able to guarantee having as many coins as he wants.

[Codeforces](#) (c) Copyright 2010-2024 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: Jun/15/2024 20:51:01^{UTC+5.5} (h1).
Desktop version, switch to [mobile version](#).
[Privacy Policy](#)

Supported by



ITMO UNIVERSITY