

1.4 日历系统阶段 3_物联网 / 嵌入式工程师 - 慕课网

“ 慕课网慕课教程 1.4 日历系统阶段 3 涵盖海量编程基础技术教程，以图文图表的形式，把晦涩难懂的编程专业用语，以通俗易懂的方式呈现给用户。

$$W = (d + 2m + 3(m+1) / 5 + y + y / 4 - y / 100 + y / 400 + 1) \% 7$$

<1> d 表示天数，m 表示月数，y 表示年数，W 表示星期几

<2> 若是，输入的月数是 1 月或者 2 月的话，则要转换成上

输入 2004-1-10，则应该换成 2003-13-10 来计算

输入 2006-2-5，则应换算成 2005-14-5 来计算

```
#include <stdio.h>

#define LE_YEAR 1

int Isleap(int y)
{
    if(((y % 4 == 0) && (y % 100 != 0)) || (y % 400 == 0))
    {
        return 1;
    }else{
        return 0;
    }
}

int max_day(int y,int m)
{
    int month[12] = {31,28,31,30,31,30,31,31,30,31,30,31};
    int ret = 0;

    ret = Isleap(y);

    if(ret == LE_YEAR)
    {
        month[1] = 29;
    }

    return month[m - 1];
}

int Total_day(int y,int m,int d)
{
    int sum = 0;
    int i = 0;
    int ret = 0;

    #if 0

    ret = max_day(y,1);
```

```

    printf("ret : %d\n",ret);
#endif

    for(i = 1;i < m;i++)
    {
        sum = sum + max_day(y,i);
    }

    sum = sum + d;
    return sum;
}

int weekday(int y,int m,int d)
{
    int count = 0;

    if(m == 1 || m == 2)
    {
        m = m + 12;
        y = y - 1;
    }

    count = (d + 2 * m + 3 * (m + 1) / 5 + y + y / 4 - y / 100 + y / 400 + 1) % 7;

    return count;
}

void display_week(int y,int m,int d)
{
    int count = 0;

    count = weekday(y,m,d);

    switch(count)
    {
    case 0:
        printf("%d-%d-%d is Sunday\n",y,m,d);
        break;
    case 1:
        printf("%d-%d-%d is Monday\n",y,m,d);
        break;
    case 2:
        printf("%d-%d-%d is Tuesday\n",y,m,d);
        break;
    case 3:
        printf("%d-%d-%d is Wednesday\n",y,m,d);
        break;
    case 4:
        printf("%d-%d-%d is Thursday\n",y,m,d);
        break;
    case 5:
        printf("%d-%d-%d is Friday\n",y,m,d);
        break;
    case 6:
        printf("%d-%d-%d is Saturday\n",y,m,d);
        break;
    }
}

int main()
{
    int year = 0,month = 0, day = 0;
    int ret = 0;
    printf("please input [year month day] : ");
    scanf("%d%d%d",&year,&month,&day);

    if(month < 1 || month > 12 || day < 1 || day > 31)
    {
        printf("Input date is error!\n");
        return -1;
    }
    ret = Isleap(year);

    if(ret == LE_YEAR)
    {
        printf("%d-%d-%d is leap yar\n",year,month,day);
    }else{
        printf("%d-%d-%d is not leap yar\n",year,month,day);
    }
    ret = Total_day(year,month,day);
}

```

```
1.4 日历系统阶段3_物联网/嵌入式工程师-慕课网
printf("%d-%d-%d is %d day of the year\n",year,month,day,ret);

display_week(year,month,day);
}
```

全文完

本文由 简悦 SimpRead 优化，用以提升阅读体验

使用了 全新的简悦词法分析引擎 beta，[点击查看详细说明](#)

