

written by Sam Rawlins
with extensive quoting from the GMP Manual

This manual describes how to use the gmp Ruby gem, which provides bindings to the GNU multiple precision arithmetic library, version 4.3.x.

Copyright 2009 Sam Rawlins.
No license yet.

Contents

1	Introduction to GNU MP	4
2	Introduction to the gmp gem	5
3	Installing the gmp gem	5
3.1	Prerequisites	5
3.2	Installing	5
4	GMP and gmp gem basics	6
4.1	Classes	6
5	Integer Functions	7
5.1	Initializing, Assigning Integers	7
5.2	Converting Integers	7
5.3	Integer Arithmetic	8
5.4	Integer Division	9
5.5	Integer Roots	10
5.6	Integer Exponentiation	11

1 Introduction to GNU MP

This entire page is copied verbatim from the GMP Manual.

GNU MP is a portable library written in C for arbitrary precision arithmetic on integers, rational numbers, and floating-point numbers. It aims to provide the fastest possible arithmetic for all applications that need higher precision than is directly supported by the basic C types.

Many applications use just a few hundred bits of precision; but some applications may need thousands or even millions of bits. GMP is designed to give good performance for both, by choosing algorithms based on the sizes of the operands, and by carefully keeping the overhead at a minimum.

The speed of GMP is achieved by using fullwords as the basic arithmetic type, by using sophisticated algorithms, by including carefully optimized assembly code for the most common inner loops for many different CPUs, and by a general emphasis on speed (as opposed to simplicity or elegance).

There is assembly code for these CPUs: ARM, DEC Alpha 21064, 21164, and 21264, AMD 29000, AMD K6, K6-2, Athlon, and Athlon64, Hitachi SuperH and SH-2, HPPA 1.0, 1.1, and 2.0, Intel Pentium, Pentium Pro/II/III, Pentium 4, generic x86, Intel IA-64, i960, Motorola MC68000, MC68020, MC88100, and MC88110, Motorola/IBM PowerPC 32 and 64, National NS32000, IBM POWER, MIPS R3000, R4000, SPARCv7, SuperSPARC, generic SPARCv8, UltraSPARC, DEC VAX, and Zilog Z8000. Some optimizations also for Cray vector systems, Clipper, IBM ROMP (RT), and Pyramid AP/XP.

For up-to-date information on GMP, please see the GMP web pages at <http://gmplib.org/>

The latest version of the library is available at <ftp://ftp.gnu.org/gnu/gmp/>

Many sites around the world mirror '[ftp.gnu.org](ftp://ftp.gnu.org)', please use a mirror near you, see <http://www.gnu.org/organization> for a full list.

There are three public mailing lists of interest. One for release announcements, one for general questions and discussions about usage of the GMP library, and one for bug reports. For more information, see

<http://gmplib.org/mailman/listinfo/>.

The proper place for bug reports is gmp-bugs@gmplib.org. See Chapter 4 [Reporting Bugs], page 28 for information about reporting bugs.

2 Introduction to the gmp gem

The gmp Ruby gem is a Ruby library that provides bindings to GMP. The gem is incomplete, and will likely only include a subset of the GMP functions. It is built as a C extension for ruby, interacting with gmp.h. The gmp gem is not endorsed or supported by GNU or the GMP team. The gmp gem also does not ship with GMP, so GMP must be compiled separately.

3 Installing the gmp gem

3.1 Prerequisites

OK. First, we've got a few requirements. To install the gmp gem, you need one of the following versions of Ruby:

- (MRI) Ruby 1.8.6 - tested lightly.
- (MRI) Ruby 1.8.7 - tested seriously.
- (MRI) Ruby 1.9.1 - more of a "release candidate" state. Please report bugs.

As you can see only Matz's Ruby Interpreter (MRI) is supported. I haven't even put a thought into trying other interpreters/VMs. I intend to look into FFI, which supposedly will allow me to load this extension into JRuby and Rubinius, not sure about others...

Next is the platform, the combination of the architecture (processor) and OS. As far as I can tell, if you can compile GMP and Ruby on a given platform, you can use the gmp gem there too. Please report problems with that hypothesis.

Lastly, GMP. GMP must be compiled and working. "and working" means you ran "make check" while installing GMP. The following versions of GMP have been tested:

- GMP 4.3.1

That's all. I don't intend to test any older versions, maybe 4.3.0 for completeness.

Here is a table of the exact environments I have tested the gmp gem on:

Platform	Ruby	GMP
Cygwin on x86	(MRI) Ruby 1.8.7	GMP 4.3.1
Linux (LinuxMint 7) on x86	(MRI) Ruby 1.8.7	GMP 4.3.1
Mac OS X 10.5.7 on x86 (32-bit)	(MRI) Ruby 1.8.6	GMP 4.3.1
Mac OS X 10.5.7 on x86 (32-bit)	(MRI) Ruby 1.9.1	GMP 4.3.1

3.2 Installing

You may clone the gmp gem's git repository with:

```
git clone git://github.com/srawlins/gmp.git
```

Or you may install the gem from github:

```
gem install srawlins-gmp
```

At this time, the gem does not self-compile (how does that work?). To compile the C extensions, do the following:

```
cd <srawlins-gmp gem directory>/ext
ruby extconf.rb
make
```

There shouldn't be any errors, or warnings.

4 GMP and gmp gem basics

4.1 Classes

The gmp gem includes the namespace **GMP** and three classes within **GMP**:

- **GMP::Z** - Methods for signed integer arithmetic. There are at least 35 methods here (still accounting).
- **GMP::Q** - Methods for rational number arithmetic. There are at least 6 methods here (still accounting).
- **GMP::F** - Methods for floating-point arithmetic. There are at least 0 methods here (still accounting).

In addition to the above three classes, there is also one constant within **GMP**:

- **GMP::GMP_VERSION** - The version of GMP compiled into the gmp gem.

5 Integer Functions

5.1 Initializing, Assigning Integers

new

$GMP::Z.new \rightarrow integer$
 $GMP::Z.new(numeric = 0) \rightarrow integer$
 $GMP::Z.new(str) \rightarrow integer$

This method creates a new *GMP::Z* integer. It takes one optional argument for the value of the integer. This argument can be one of several classes. Here are some examples:

```
GMP::Z.new          #=> 0 (default)
GMP::Z.new(1)       #=> 1 (Ruby Fixnum)
GMP::Z.new("127")   #=> 127 (Ruby String)
GMP::Z.new(4294967296) #=> 4294967296 (Ruby Bignum)
GMP::Z.new(GMP::Z.new(31)) #=> 31 (GMP Integer)
```

There is also a convenience method available, *GMP::Z()*.

5.2 Converting Integers

to_d

$integer.to_d \rightarrow float$

Returns *integer* as an Float if *integer* fits in a Float.

Otherwise returns the least significant part of *integer*, with the same sign as *integer*.

If *integer* is too big to fit in a Float, the returned result is probably not very useful. To find out if the value will fit, use the function *mpz_fits_slong_p* (**Unimplemented**).

to_i

$integer.to_i \rightarrow fixnum$

Returns *integer* as a Fixnum if *integer* fits in a Fixnum.

Otherwise returns the least significant part of *integer*, with the same sign as *integer*.

If *integer* is too big to fit in a Fixnum, the returned result is probably not very useful. To find out if the value will fit, use the function *mpz_fits_slong_p* (**Unimplemented**).

to_s	<i>integer.to_s(base = 10) → str</i>
-------------	--------------------------------------

Converts *integer* to a string of digits in base *base*. The *base* argument may vary from 2 to 62 or from -2 to -36, or be a symbol, one of *:bin*, *:oct*, *:dec*, or *:hex*.

For *base* in the range 2..36, digits and lower-case letters are used; for -2..-36 (and *:bin*, *:oct*, *:dec*, and *:hex*), digits and upper-case letters are used; for 37..62, digits, upper-case letters, and lower-case letters (in that significance order) are used. Here are some examples:

```
GMP::Z(1).to_s      #=> "1"
GMP::Z(32).to_s(2)   #=> "100000"
GMP::Z(32).to_s(4)   #=> "200"
GMP::Z(10).to_s(16)  #=> "a"
GMP::Z(10).to_s(-16) #=> "A"
GMP::Z(255).to_s(:bin) #=> "11111111"
GMP::Z(255).to_s(:oct) #=> "377"
GMP::Z(255).to_s(:dec) #=> "255"
GMP::Z(255).to_s(:hex) #=> "ff"
```

5.3 Integer Arithmetic

+	<i>integer + numeric → numeric</i>
---	------------------------------------

Returns the sum of *integer* and *numeric*. *numeric* can be a member of *GMP::Z*, *Fixnum*, *GMP::Q*, *GMP::F*, or *Bignum*.

add	<i>integer.add(numeric) → numeric</i>
------------	---------------------------------------

Returns the sum of *integer* and *numeric*. *numeric* can be a member of *GMP::Z*, *Fixnum*, *GMP::Q*, *GMP::F*, or *Bignum*.

add!	<i>integer.add!(numeric) → numeric</i>
-------------	--

Sums *integer* and *numeric*, in place. *numeric* can be a member of *GMP::Z*, *Fixnum*, *GMP::Q*, *GMP::F*, or *Bignum*.

-	<i>integer</i> - <i>numeric</i> → <i>numeric</i> <i>integer.sub(numeric)</i> → <i>numeric</i> <i>integer.sub!(numeric)</i> → <i>numeric</i>
---	---

Returns the difference of *integer* and *numeric*. The destructive method calculates the difference in place. *numeric* can be a member of *GMP::Z*, *Fixnum*, *GMP::Q*, *GMP::F*, or *Bignum*. Here are some examples:

```
seven = GMP::Z(7)
nine  = GMP::Z(9)
half  = GMP::Q(1,2)
pi     = GMP::F("3.14")
nine - 5      #=> 4 (GMP Integer)
nine - seven  #=> 2 (GMP Integer)
nine - (2**32) #=> -4294967287 (GMP Integer)
nine - nine   #=> 0 (GMP Integer)
nine - half   #=> 8.5 (GMP Rational)
nine - pi     #=> 5.86 (GMP Float)
```

*	<i>integer</i> * <i>numeric</i> → <i>numeric</i> <i>integer.mul(numeric)</i> → <i>numeric</i> <i>integer.mul!(numeric)</i> → <i>numeric</i>
---	---

Returns the product of *integer* and *numeric*. The destructive method calculates the product in place. *numeric* can be a member of *GMP::Z*, *Fixnum*, *GMP::Q*, *GMP::F*, or *Bignum*.

-@	- <i>integer</i> <i>integer.neg</i> <i>integer.neg!</i>
----	---

Returns the negation, the additive inverse, of *integer*. The destructive method negates in place.

abs	<i>integer.abs</i> <i>integer.abs!</i>
-----	---

Returns the absolute value of *integer*. The destructive method calculates the absolute value in place.

5.4 Integer Division

tdiv	<i>integer.tdiv(numeric)</i> → <i>integer</i>
------	---

Returns the division of *integer* by *numeric*, truncated. *numeric* can be a member of *GMP::Z*, *Fixnum*, *Bignum*. The return object's class is always *GMP::Z*.

fdiv	$integer.fdiv(numeric) \rightarrow integer$
Returns the division of <i>integer</i> by <i>numeric</i> , floored. <i>numeric</i> can be a member of <i>GMP::Z</i> , <i>Fixnum</i> , <i>Bignum</i> . The return object's class is always <i>GMP::Z</i> .	
cdiv	$integer.cdiv(numeric) \rightarrow integer$
Returns the ceiling division of <i>integer</i> by <i>numeric</i> . <i>numeric</i> can be a member of <i>GMP::Z</i> , <i>Fixnum</i> , <i>Bignum</i> . The return object's class is always <i>GMP::Z</i> .	
tmod	$integer.tmod(numeric) \rightarrow integer$
Returns the remainder after truncated division of <i>integer</i> by <i>numeric</i> . <i>numeric</i> can be a member of <i>GMP::Z</i> , <i>Fixnum</i> , <i>Bignum</i> . The return object's class is always <i>GMP::Z</i> .	
fmod	$integer.fmod(numeric) \rightarrow integer$
Returns the remainder after floored division of <i>integer</i> by <i>numeric</i> . <i>numeric</i> can be a member of <i>GMP::Z</i> , <i>Fixnum</i> , <i>Bignum</i> . The return object's class is always <i>GMP::Z</i> .	
cmod	$integer.cmod(numeric) \rightarrow integer$
Returns the remainder after ceiling division of <i>integer</i> by <i>numeric</i> . <i>numeric</i> can be a member of <i>GMP::Z</i> , <i>Fixnum</i> , <i>Bignum</i> . The return object's class is always <i>GMP::Z</i> .	
5.5 Integer Roots	
root	$integer.root(numeric) \rightarrow numeric$
Returns the integer part of the <i>numeric</i> 'th root of <i>integer</i> .	
sqrt	$integer.sqrt \rightarrow numeric$ $integer.sqrt!(numeric) \rightarrow numeric$
Returns the truncated integer part of the square root of <i>integer</i> .	
sqrtrem	$integer.sqrtrem \rightarrow sqrt, rem$
Returns the truncated integer part of the square root of <i>integer</i> as <i>sqrt</i> and the remainder, <i>integer</i> - <i>sqrt</i> * <i>sqrt</i> , as <i>rem</i> , which will be zero if <i>integer</i> is a perfect square.	

5.6 Integer Exponentiation

integer ** *numeric* → *numeric*
integer.pow(numeric) → *numeric*

Returns *integer* raised to the *numeric* power.