



INTERNATIONAL® 9900i

## Product Specifications

Model Configurations	9900i SFA 6x4	Standard	Maximum
	Front GAW	12,000 lbs	14,000 lbs
	Rear GAW	34,000 lbs	46,000 lbs
	<b>Total GVW</b>	46,000 lbs	60,000 lbs
	<b>Total GCW</b>	90,000 lbs	140,000 lbs

	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius	
Wheelbase (in.)	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance
181	8090	7094	15184	91	144	53	263.7	26ft. 7in.	27ft. 6in.
185	8095	7098	15193	95	148	53	267.7	27ft. 1in.	28ft. 0in.
193	8107	7109	15216	103	156	53	275.7	28ft. 2in.	29ft. 1in.
205	8126	7125	15251	115	168	53	287.7	29ft. 8in.	30ft. 7in.
217	8153	7153	15306	127	180	53	299.7	31ft. 3in.	32ft. 2in.
240	8188	7185	15373	150	203	53	322.7	34ft. 2in.	35ft. 2in.

<b>Frame Rails</b>	110,000 PSI	10.125" (5/16 in) 10.250" (3/8 in)
--------------------	-------------	---------------------------------------

<b>Frame Reinforcement</b>	80,000; 110,000 PSI Inner "C" Channel	8.625", 9.500"
----------------------------	--	----------------

<b>Front Axle</b>	Meritor	12,000; 13,200; 14,000 lb Capacity Wide Track and Standard Track
	Dana Spicer	12,000; 14,000 lb Capacity Wide Track and Standard Track

<b>Front Suspension</b>	Parabolic Taper Leaf w/ Shocks	12,000; 14,000 lb Capacity
-------------------------	-----------------------------------	----------------------------

<b>Brakes</b>	Bendix	Air ABS (4-Channel) Available w/ Traction Control
	Meritor-Wabco	Air ABS (4-Channel) Available w/ Traction Control

<b>Steering</b>	Ross, Sheppard
-----------------	----------------

<b>Exhaust System</b>	Daycab – Frame
-----------------------	----------------



INTERNATIONAL® 9900i

## Product Specifications

	<p>mounted right side vertical aftertreatment device.</p> <p>Sleeper – Horizontal aftertreatment device w/Vertical tailpipe and guard frame mounted right side.</p> <p>Sleeper – Horizontal aftertreatment device w/Dual Vertical tailpipes cab mounted</p>
--	---

<b>Electrical System</b>	Leece-Neville	110, 135, 140, 145, 160 Amp Alternators
	Delco-Remy America Inc.	110, 130, 135 Amp Alternators
	International	1850, 2250, 2600, 2775, 3000 CCA Battery System
	Exide	2250, 2800, 2850, 3000 CCA Battery System
	Long Life Halogen Headlights	
	Qualcomm	Pre-wire Satellite Communications System

<b>Entertainment System</b>	Panasonic	Premium-Quality Stereo System – w/CD player, weather band, multiple coaxial speakers and Satellite radio from Sirius or XM
		Optional DVD Player
		Optional Monsoon Premium sound system

<b>Fifth Wheel</b>	Fontaine	Air Slide or Stationary
--------------------	----------	-------------------------

<b>Front End</b>	Tilting Composite Hood
------------------	------------------------

<b>Paint</b>	Base Coat / Clear Coat
--------------	------------------------

<b>Clutch</b>	Eaton Fuller, Meritor
---------------	-----------------------



INTERNATIONAL® 9900i

## Product Specifications

<b>Engine &amp; Equipment</b>	Cummins ISX	425 HP/1450 lb-ft to 600 HP/1850 lb-ft
	Caterpillar C13/C15	380 HP/1450 lb-ft to 550 HP/1850 lb-ft
	Air Cleaner	Dual Element Internal Dual External Cans
<b>Transmissions</b>	Eaton Fuller	10, 13, 15, 18 Speed Manual
	Eaton Fuller	10, 13, 18 Speed Automated Manual Ultrashift or Autoshift Series
<b>Rear Axle (Tandem)</b>	Meritor	40,000; 46,000 lb Capacity Available w/ Driver Controlled Locking Diff
	Dana Spicer	40,000; 46,000 lb Capacity Available w/ Driver Controlled Locking Diff
<b>Rear Suspension (Tandem)</b>	International Air Suspension	40,000 lb Capacity w/ 9.25" Ride Height; 52", 55", 60" Axle Spacing
	Hendrickson Air Suspension	40,000; 46,000 lb Capacity w/ 9.5" Ride Height; 55", 60" Axle Spacing
	International Multileaf 4-Spring Type	34,000; 36,000; 40,000 lb Capacity w/ 52" Axle Spacing
<b>Fuel Tank</b>	100 – 300 U.S. Gallons Total Capacity, Polished and Non-Polished Aluminum	Mounted Under Cab, Right or Left, Right and Left Side; Mounted Back of Cab, Right and Left Side
<b>Cab</b>	Conventional Aluminum Cab	120.0" BBC
	Sleeper Cab	Hi-Rise 51", 72" Low-Roof 51" Sky-Rise 72"
	Cabinets	Dresser, Footlocker, Refrigerator, Tower Wardrobe, Utility



INTERNATIONAL® 9900i

## Product Specifications

Interior Trim	Premium Eagle® American Eagle® Eagle® “Black and Tan” Tuck and Roll
Mirrors	(02) Rectangular w/ Breakaway Type Brackets
Driver Seats	A wide variety of seats including: <ul style="list-style-type: none"><li>• Air-Suspension</li><li>• High or Intermediate Back</li><li>• Swivel</li><li>• Air Lumbar Support</li></ul>
Passenger Seats	A wide variety of seats including: <ul style="list-style-type: none"><li>• Air-Suspension or Non-Suspension</li><li>• High or Intermediate Back</li><li>• Swivel</li><li>• Air Lumbar Support</li></ul>
Front Wheels	Painted Steel, Polished Aluminum, Non-Polished Aluminum22.5”, 24.5”; 10 Stud
Rear Wheels	Painted Steel, Polished Aluminum, Non-Polished Aluminum22.5”, 24.5”; 10 Stud
Tires	Michelin, Hankook, Double Coin, Continental
Optional	<ul style="list-style-type: none"><li>• Factory Installed Auxiliary Power Unit</li><li>• Factory Installed Silver or Platinum Chrome Accessory Packages</li><li>• Auxiliary Wiring Packages for Aftermarket Bumper and Air Cleaner Lights</li><li>• Alcoa Dura Bright Wheels</li></ul>