

# JAX-RS: Java™ API for RESTful Web Services

*Editors Draft*  
*March 7, 2008*

Editors:  
Marc Hadley  
Paul Sandoz

Comments to: [users@jsr311.dev.java.net](mailto:users@jsr311.dev.java.net)

*Sun Microsystems, Inc.*  
*4150 Network Circle*  
*Santa Clara, CA 95054 USA*



**Specification: JAX-RS - Java™ API for RESTful Web Services (“Specification”)**

**Version: 1.0-editors-draft**

**Status: Pre-FCS Public Release**

**Release: March 7, 2008**

**Copyright 2007 Sun Microsystems, Inc.**

**4150 Network Circle, Santa Clara, California 95054, U.S.A**

**180, Avenue de L'Europe, 38330 Montbonnot Saint Martin, France**

**All rights reserved.**

**NOTICE**

The Specification is protected by copyright and the information described therein may be protected by one or more U.S. patents, foreign patents, or pending applications. Except as provided under the following license, no part of the Specification may be reproduced in any form by any means without the prior written authorization of Sun Microsystems, Inc. (“Sun”) and its licensors, if any. Any use of the Specification and the information described therein will be governed by the terms and conditions of this Agreement.

Subject to the terms and conditions of this license, including your compliance with Paragraphs 1 and 2 below, Sun hereby grants you a fully-paid, non-exclusive, non-transferable, limited license (without the right to sublicense) under Sun’s intellectual property rights to:

1. Review the Specification for the purposes of evaluation. This includes: (i) developing implementations of the Specification for your internal, non-commercial use; (ii) discussing the Specification with any third party; and (iii) excerpting brief portions of the Specification in oral or written communications which discuss the Specification provided that such excerpts do not in the aggregate constitute a significant portion of the Technology.
2. Distribute implementations of the Specification to third parties for their testing and evaluation use, provided that any such implementation: (i) does not modify, subset, superset or otherwise extend the Licensor Name Space, or include any public or protected packages, classes, Java interfaces, fields or methods within the Licensor Name Space other than those required/authorized by the Specification or Specifications being implemented; (ii) is clearly and prominently marked with the word “UNTESTED” or “EARLY ACCESS” or “INCOMPATIBLE” or “UNSTABLE” or “BETA” in any list of available builds and in proximity to every link initiating its download, where the list or link is under Licensees control; and (iii) includes the following notice: “This is an implementation of an early-draft specification developed under the Java Community Process (JCP) and is made available for testing and evaluation purposes only. The code is not compatible with any specification of the JCP.”

The grant set forth above concerning your distribution of implementations of the specification is contingent upon your agreement to terminate development and distribution of your early draft implementation as soon as feasible following final completion of the specification. If you fail to do so, the foregoing grant shall be considered null and void.

No provision of this Agreement shall be understood to restrict your ability to make and distribute to third parties applications written to the Specification. Other than this limited license, you acquire no right, title or interest in or to the Specification or any other Sun intellectual property, and the Specification may only be used in accordance with the license terms set forth herein. This license will expire on the earlier of: (a) two (2) years from the date of Release listed above; (b) the date on which the final version of the Specification is publicly released; or (c) the date on which the Java Specification Request (JSR) to which the Specification corresponds is withdrawn. In addition, this license will terminate immediately without notice from Sun if you fail to comply with any provision of this license. Upon termination, you must cease use of or destroy the Specification.

“Licensor Name Space” means the public class or interface declarations whose names begin with “java” , “javax” , “com.sun” or their equivalents in any subsequent naming convention adopted by Sun through the Java Community Process, or any recognized successors or replacements thereof

**TRADEMARKS**

No right, title, or interest in or to any trademarks, service marks, or trade names of Sun or Sun’s licensors is granted hereunder. Sun, Sun Microsystems, the Sun logo, Java, are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

## **DISCLAIMER OF WARRANTIES**

THE SPECIFICATION IS PROVIDED "AS IS" AND IS EXPERIMENTAL AND MAY CONTAIN DEFECTS OR DEFICIENCIES WHICH CANNOT OR WILL NOT BE CORRECTED BY SUN. SUN MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT THAT THE CONTENTS OF THE SPECIFICATION ARE SUITABLE FOR ANY PURPOSE OR THAT ANY PRACTICE OR IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADE SECRETS OR OTHER RIGHTS. This document does not represent any commitment to release or implement any portion of the Specification in any product.

THE SPECIFICATION COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION THEREIN; THESE CHANGES WILL BE INCORPORATED INTO NEW VERSIONS OF THE SPECIFICATION, IF ANY. SUN MAY MAKE IMPROVEMENTS AND/OR CHANGES TO THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THE SPECIFICATION AT ANY TIME. Any use of such changes in the Specification will be governed by the then-current license for the applicable version of the Specification.

## **LIMITATION OF LIABILITY**

TO THE EXTENT NOT PROHIBITED BY LAW, IN NO EVENT WILL SUN OR ITS LICENSORS BE LIABLE FOR ANY DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUE, PROFITS OR DATA, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF OR RELATED TO ANY FURNISHING, PRACTICING, MODIFYING OR ANY USE OF THE SPECIFICATION, EVEN IF SUN AND/OR ITS LICENSORS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

You will hold Sun (and its licensors) harmless from any claims based on your use of the Specification for any purposes other than the limited right of evaluation as described above, and from any claims that later versions or releases of any Specification furnished to you are incompatible with the Specification provided to you under this license.

## **RESTRICTED RIGHTS LEGEND**

If this Software is being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), then the Government's rights in the Software and accompanying documentation shall be only as set forth in this license; this is in accordance with 48 C.F.R. 227.7201 through 227.7202-4 (for Department of Defense (DoD) acquisitions) and with 48 C.F.R. 2.101 and 12.212 (for non-DoD acquisitions).

## **REPORT**

You may wish to report any ambiguities, inconsistencies or inaccuracies you may find in connection with your evaluation of the Specification ("Feedback"). To the extent that you provide Sun with any Feedback, you hereby: (i) agree that such Feedback is provided on a non-proprietary and non-confidential basis, and (ii) grant Sun a perpetual, non-exclusive, worldwide, fully paid-up, irrevocable license, with the right to sublicense through multiple levels of sublicensees, to incorporate, disclose, and use without limitation the Feedback for any purpose related to the Specification and future versions, implementations, and test suites thereof.

## **GENERAL TERMS**

Any action related to this Agreement will be governed by California law and controlling U.S. federal law. The U.N. Convention for the International Sale of Goods and the choice of law rules of any jurisdiction will not apply.

The Specification is subject to U.S. export control laws and may be subject to export or import regulations in other countries. Licensee agrees to comply strictly with all such laws and regulations and acknowledges that it has the responsibility to obtain such licenses to export, re-export or import as may be required after delivery to Licensee.

This Agreement is the parties' entire agreement relating to its subject matter. It supersedes all prior or contemporaneous oral or written communications, proposals, conditions, representations and warranties and prevails over any conflicting or additional terms of any quote, order, acknowledgment, or other communication between the parties relating to its subject matter during the term of this Agreement. No modification to this Agreement will be binding, unless in writing and signed by an authorized representative of each party.

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Status . . . . .	1
1.2	Goals . . . . .	2
1.3	Non-Goals . . . . .	2
1.4	Conventions . . . . .	3
1.5	Terminology . . . . .	3
1.6	Expert Group Members . . . . .	3
1.7	Acknowledgements . . . . .	4
<b>2</b>	<b>Applications</b>	<b>5</b>
2.1	Configuration . . . . .	5
2.2	Publication . . . . .	5
2.2.1	Java SE . . . . .	5
2.2.2	Servlet . . . . .	6
2.2.3	Other Container . . . . .	6
<b>3</b>	<b>Resources</b>	<b>7</b>
3.1	Resource Classes . . . . .	7
3.1.1	Lifecycle and Environment . . . . .	7
3.1.2	Constructors . . . . .	7
3.2	Resource Methods . . . . .	7
3.2.1	Visibility . . . . .	8
3.2.2	Parameters . . . . .	8
3.2.3	Return Type . . . . .	8
3.2.4	Exceptions . . . . .	9
3.2.5	HEAD and OPTIONS . . . . .	9
3.3	URI Templates . . . . .	9

3.3.1	Sub Resources . . . . .	10
3.4	Declaring Media Type Capabilities . . . . .	11
3.5	Annotation Inheritance . . . . .	12
3.6	Matching Requests to Resource Methods . . . . .	12
3.6.1	Converting URI Templates to Regular Expressions . . . . .	14
3.7	Determining the MediaType of Responses . . . . .	14
<b>4</b>	<b>Providers</b>	<b>17</b>
4.1	Lifecycle and Environment . . . . .	17
4.2	Constructors . . . . .	17
4.3	Entity Providers . . . . .	17
4.3.1	Message Body Reader . . . . .	17
4.3.2	Message Body Writer . . . . .	18
4.3.3	Declaring Media Type Capabilities . . . . .	19
4.3.4	Standard Entity Providers . . . . .	19
4.3.5	Transfer Encoding . . . . .	19
4.3.6	Content Encoding . . . . .	20
4.4	Context Providers . . . . .	20
<b>5</b>	<b>Context</b>	<b>21</b>
5.1	Context Types . . . . .	21
5.1.1	URIs and URI Templates . . . . .	21
5.1.2	Headers . . . . .	21
5.1.3	Content Negotiation and Preconditions . . . . .	22
5.1.4	Security Context . . . . .	22
5.1.5	Message Body Workers . . . . .	22
5.1.6	Context Resolver . . . . .	23
5.2	Injection Scope . . . . .	23
<b>6</b>	<b>Environment</b>	<b>25</b>
6.1	Servlet Container . . . . .	25
6.2	Java EE Container . . . . .	25
6.3	Other . . . . .	25
<b>7</b>	<b>Runtime Delegate</b>	<b>27</b>
7.1	Configuration . . . . .	27

<b>A Summary of Annotations</b>	<b>29</b>
<b>Bibliography</b>	<b>31</b>





# Chapter 1 1

## Introduction 2

This specification defines a set of Java APIs for the development of Web services built according to the Representational State Transfer[1] (REST) architectural style. Readers are assumed to be familiar with REST; for more information about the REST architectural style and RESTful Web services, see: 3 4 5

- Architectural Styles and the Design of Network-based Software Architectures[1] 6
- The REST Wiki[2] 7
- Representational State Transfer on Wikipedia[3] 8

### 1.1 Status 9

This is an editors draft; this specification is not yet complete. A list of open issues can be found at: 10

<https://jsr311.dev.java.net/servlets/ProjectIssues> 11

Javadocs can be found online at: 12

<https://jsr311.dev.java.net/nonav/javadoc/index.html> 13

The reference implementation can be obtained at: 14

<https://jersey.dev.java.net/> 15

The expert group seeks feedback from the community on any aspect of this specification, please send comments to: 16 17

[users@jsr311.dev.java.net](mailto:users@jsr311.dev.java.net) 18

## 1.2 Goals

The following are the goals of the API:

**POJO-based** The API will provide a set of annotations and associated classes/interfaces that may be used with POJOs in order to expose them as Web resources. The specification will define object lifecycle and scope.

**HTTP-centric** The specification will assume HTTP[4] is the underlying network protocol and will provide a clear mapping between HTTP and URI[5] elements and the corresponding API classes and annotations. The API will provide high level support for common HTTP usage patterns and will be sufficiently flexible to support a variety of HTTP applications including WebDAV[6] and the Atom Publishing Protocol[7].

**Format independence** The API will be applicable to a wide variety of HTTP entity body content types. It will provide the necessary pluggability to allow additional types to be added by an application in a standard manner.

**Container independence** Artifacts using the API will be deployable in a variety of Web-tier containers. The specification will define how artifacts are deployed in a Servlet[8] container and as a JAX-WS[9] Provider.

**Inclusion in Java EE** The specification will define the environment for a Web resource class hosted in a Java EE container and will specify how to use Java EE features and components within a Web resource class.

## 1.3 Non-Goals

The following are non-goals:

**Support for Java versions prior to J2SE 5.0** The API will make extensive use of annotations and will require J2SE 5.0 or later.

**Description, registration and discovery** The specification will neither define nor require any service description, registration or discovery capability.

**Client APIs** The specification will not define client-side APIs. Other specifications are expected to provide such functionality.

**HTTP Stack** The specification will not define a new HTTP stack. HTTP protocol support is provided by a container that hosts artifacts developed using the API.

**Data model/format classes** The API will not define classes that support manipulation of entity body content, rather it will provide pluggability to allow such classes to be used by artifacts developed using the API.

## 1.4 Conventions

The keywords ‘MUST’, ‘MUST NOT’, ‘REQUIRED’, ‘SHALL’, ‘SHALL NOT’, ‘SHOULD’, ‘SHOULD NOT’, ‘RECOMMENDED’, ‘MAY’, and ‘OPTIONAL’ in this document are to be interpreted as described in RFC 2119[10].

Java code and sample data fragments are formatted as shown in figure 1.1:

Figure 1.1: Example Java Code

```

1 package com.example.hello;
2
3 public class Hello {
4     public static void main(String args[]) {
5         System.out.println("Hello World");
6     }
7 }

```

URIs of the general form ‘http://example.org/...’ and ‘http://example.com/...’ represent application or context-dependent URIs.

All parts of this specification are normative, with the exception of examples, notes and sections explicitly marked as ‘Non-Normative’. Non-normative notes are formatted as shown below.

**Note:** *This is a note.*

## 1.5 Terminology

**Resource class** A Java class that uses JAX-RS annotations to implement a corresponding Web resource, see chapter 3.

**Root resource class** A *resource class* annotated with `@Path`. Root resource classes provide the roots of the resource class tree and provide access to sub-resources, see chapter 3.

**Request method designator** A runtime annotation annotated with `@HttpMethod`. Used to identify the HTTP request method to be handled by a *resource method*.

**Resource method** A method of a *resource class* annotated with a *request method designator* that is used to handle requests on the corresponding resource, see section 3.2.

**Sub-resource locator** A method of a *resource class* that is used to locate sub-resources of the corresponding resource, see section 3.3.1.

**Sub-resource method** A method of a *resource class* that is used to handle requests on a sub-resource of the corresponding resource, see section 3.3.1.

## 1.6 Expert Group Members

This specification is being developed as part of JSR 311 under the Java Community Process. This specification is the result of the collaborative work of the members of the JSR 311 Expert Group. The following are the present and former expert group members:

Jan Algermissen (Individual Member)	1
Heiko Braun (Red Hat Middleware LLC)	2
Larry Cable (BEA Systems)	3
Bill De Hora (Individual Member)	4
Roy Fielding (Day Software, Inc.)	5
Harpreet Geekee (Nortel)	6
Nickolas Grabovas (Individual Member)	7
Mark Hansen (Individual Member)	8
John Harby (Individual Member)	9
Hao He (Individual Member)	10
Ryan Heaton (Individual Member)	11
David Hensley (Individual Member)	12
Changshin Lee (NCsoft Corporation)	13
Francois Leygues (Alcatel-Lucent)	14
Jerome Louvel (Individual Member)	15
Hamid Ben Malek (Fujitsu Limited)	16
Ryan J. McDonough (Individual Member)	17
Felix Meschberger (Day Software, Inc.)	18
David Orchard (BEA Systems)	19
Dhanji R. Prasanna (Individual Member)	20
Julian Reschke (Individual Member)	21
Jan Schulz-Hofen (Individual Member)	22
Joel Smith (IBM)	23
Stefan Tilkov (innoQ Deutschland GmbH)	24

## 1.7 Acknowledgements 25

**Editors Note 1.1** *TBD.* 26

## Chapter 2 1

# Applications 2

A JAX-RS application consists of one or more resources (see chapter 3) and zero or more providers (see chapter 4). This chapter describes aspects of JAX-RS that apply to an application as a whole, subsequent chapters describe particular aspects of a JAX-RS application and requirements on JAX-RS implementations. 3  
4  
5

## 2.1 Configuration 6

The resources and providers that make up a JAX-RS application are configured via an application-supplied subclass of `ApplicationConfig`. An implementation MAY provide alternate mechanisms for locating resource classes and providers (e.g. runtime class scanning) but use of `ApplicationConfig` is the only portable means of configuration. 7  
8  
9  
10

## 2.2 Publication 11

Applications are published in different ways depending on whether the application is run in a Java SE environment or within a container. This section describes the alternate means of publication. 12  
13

### 2.2.1 Java SE 14

In a Java SE environment a configured instance of an endpoint class can be obtained using the `createEndpoint` method of `RuntimeDelegate`. The application supplies an instance of `ApplicationConfig` and the type of endpoint required. An implementation MAY support zero or more endpoint types of any desired type. 15  
16  
17  
18

How the resulting endpoint class instance is used to publish the application is outside the scope of this specification. 19  
20

#### 2.2.1.1 JAX-WS 21

An implementation that supports publication via JAX-WS MUST support `createEndpoint` with an endpoint type of `javax.xml.ws.Provider`. JAX-WS describes how a `Provider` based endpoint can be published in an SE environment. 22  
23  
24

## 2.2.2 Servlet

A JAX-RS application is packaged as a Servlet in a `.war` file. The `ApplicationConfig` subclass (see 2.1, resource classes, and providers are packaged in `WEB-INF/classes`, required libraries are packaged in `WEB-INF/lib`. Included libraries MAY also contain resource classes and providers as desired. See the Servlet specification for full details on packaging of web applications.

When using a JAX-RS aware servlet container, the `servlet-class` element of the `web.xml` descriptor SHOULD name the application-supplied subclass of `ApplicationConfig`.

When using a non-JAX-RS aware servlet container, the `servlet-class` element of the `web.xml` descriptor SHOULD name the JAX-RS implementation-supplied Servlet class. The application-supplied subclass of `ApplicationConfig` is identified using an `init-param` with a `param-name` of `javax.ws.rs-ApplicationConfig`.

## 2.2.3 Other Container

An implementation MAY provides facilities to host a JAX-RS application in other types of container, such facilities are outside the scope of this specification.

# Chapter 3

## Resources

Using JAX-RS a Web resource is implemented as a resource class and requests are handled by resource methods. This chapter describes resource classes and resource methods in detail.

### 3.1 Resource Classes

A resource class is a Java class that uses JAX-RS annotations to implement a corresponding Web resource. Resource classes are POJOs that have at least one method annotated with `@Path` or a request method designator.

#### 3.1.1 Lifecycle and Environment

A new resource class instance is created for each request to that resource. First the constructor (see section 3.1.2) is called, then any requested dependencies are injected (see chapter 5), then the appropriate method (see section 3.2) is invoked and finally the object is made available for garbage collection.

#### 3.1.2 Constructors

Root resource classes are instantiated by the JAX-RS runtime and **MUST** have a constructor with one of the following annotations on every parameter: `@Context`, `@HeaderParam`, `@CookieParam`, `@MatrixParam`, `@QueryParam` or `@PathParam`. Note that a zero argument constructor is permissible under this rule. Section 3.2.2 defines the parameter types permitted for each annotation. If more than one constructor that matches the above pattern is available then an implementation **MUST** use the one with the most parameters. Choosing amongst constructors with the same number of parameters is implementation specific.

Non-root resource classes are instantiated by an application and do not require the above-described constructor.

### 3.2 Resource Methods

Resource methods are methods of a resource class annotated with a request method designator. They are used to handle requests and **MUST** conform to certain restrictions described in this section.

A request method designator is a runtime annotation that is annotated with the `@HttpMethod` annotation. JAX-RS defines a set of request method designators for the common HTTP methods: `@GET`, `@POST`, `@PUT`, `@DELETE`, `@HEAD`. Users may define their own custom request method designators including alternate designators for the common HTTP methods.

### 3.2.1 Visibility

Only `public` methods may be exposed as resource methods. An implementation SHOULD warn users if a non-`public` method carries a method designator or `@Path` annotation.

### 3.2.2 Parameters

When a resource method is invoked, annotated parameter values are mapped from the request according to the semantics of the annotation. The following describes the permitted types for an annotated parameter.

**@MatrixParam, @QueryParam or @PathParam** Either a primitive type, a class with a constructor that accepts a single `String` argument, or a class with a static method named `valueOf` that accepts a single `String` argument. By default, parameter values are automatically decoded; automatic decoding can be disabled using the `@Encoded` annotation.

**@Context** The class of the annotated parameter MUST be one of the types defined in chapter 5 or 6.

**@CookieParam** Either `Cookie`, a primitive type, a class with a constructor that accepts a single `String` argument, or a class with a static method named `valueOf` that accepts a single `String` argument.

**@HeaderParam** Either a primitive type, a class with a constructor that accepts a single `String` argument, or a class with a static method named `valueOf` that accepts a single `String` argument.

The value of an non-annotated parameter is mapped from the request entity body. Resource methods MUST NOT have more than one parameter that is not annotated with one of the above-listed annotations. Conversion between an entity body and a Java type is the responsibility of an entity provider, see section 4.3.

### 3.2.3 Return Type

Resource methods MAY return `void`, `Response` or another Java type, these return types are mapped to a response entity body as follows:

**void** Results in an empty entity body with a 204 status code.

**Response** Results in an entity body mapped from the `Entity` property of the `Response` with the status code specified by the status property of the `Response`. A `null` return value results in a 204 status code.

**Other** Results in an entity body mapped from the return type. If the return value is not `null` a 200 status code is used, a `null` return value results in a 204 status code.

Conversion between a Java types and an entity body is the responsibility of an entity provider, see section 4.3.



Methods that need to provide additional metadata with a response should return an instance of `Response`, the `ResponseBuilder` class provides a convenient way to create a `Response` instance using a builder pattern.

### 3.2.4 Exceptions

An implementation **MUST** catch `WebApplicationException` and map it to a response. If the response property of the exception is not `null` then it **MUST** be used to create the response. If the response property of the exception is `null` an implementation **MUST** generate a server error response.

An implementation **MUST** allow other runtime exceptions to propagate to the underlying container. This allows existing container facilities (e.g. a Servlet filter) to be used to handle the error if desired.

**Editors Note 3.1** *What to do about checked exceptions ? If we allow them on resource methods then do we need some standard runtime exception that can be used to wrap the checked exception so it can be propagated to the container in a standard way ?*

### 3.2.5 HEAD and OPTIONS

`HEAD` and `OPTIONS` requests receive additional automated support. On receipt of a `HEAD` request an implementation **MUST** either:

1. Call a method annotated with a request method designator for `HEAD` or, if none present,
2. Call a method annotated with a request method designator for `GET` and discard any returned entity.

Note that option 2 may result in reduced performance where entity creation is significant.

On receipt of an `OPTIONS` request an implementation **MUST** either:

1. Call a method annotated with a request method designator for `OPTIONS` or, if none present,
2. Generate an automatic response from the declared metadata of the matching class.

## 3.3 URI Templates

A resource class is anchored in URI space using the `@Path` annotation. The value of the annotation is a relative URI path template whose base URI is provided by the deployment context. Root resource classes are anchored directly using a `@Path` annotation on the class.

**Editors Note 3.2** *Add reference to URI Templates ID when available.*

A URI path template is a string with zero or more embedded parameters that, when values are substituted for all the parameters, is a valid URI[5] path. A template parameter is represented as `{'name'}` where *name* is the name of the parameter. E.g.:

```
1  @Path("widgets/{id}")
2  public class Widget {
3      ...
4  }
```

In the above example the `Widget` resource class is identified by the relative URI path `widgets/xxx` where `xxx` is the value of the `id` parameter.

**Note:** Because ‘{’ and ‘}’ are not part of either the reserved or unreserved productions of `URI[5]` they will not appear in a valid URI.

The `encode` property of `@Path` controls whether the value of the annotation is automatically encoded (the default) or not. E.g. the following two lines are equivalent:

```
1  @Path("widget list/{id}")
2  @Path(value="widget%20list/{id}" encode=false)
```

When automatic encoding is disabled, care must be taken to ensure that the value of the URI template is valid.

The `limited` property of `@Path` controls whether a trailing template variable matches a single path segment or multiple. Setting the property to `false` allows a single template variable to match a path and can be used, e.g., when a template represents a path prefix followed by a path consisting of arbitrarily many path segments. E.g.:

```
1  @Path(value="widgets/{path}", limited=false)
2  public class Widget {
3      ...
4  }
```

In the above example the `Widget` resource class can be used for any request whose path starts with the `widgets`; the value of the `path` parameter will be the request path following `widgets`. E.g. given the request path `widgets/small/a` the value of `path` would be `small/a`.

### 3.3.1 Sub Resources

Methods of a resource class that are annotated with `@Path` are either sub-resource methods or sub-resource locators. The differentiator is the presence or absence of request method designator:

**Present** Such methods, known as *sub-resource methods*, are treated like a normal resource method (see section 3.2) except the method is only invoked for request URIs that match a URI template created by concatenating the URI template of the resource class with the URI template of the method<sup>1</sup>.

**Absent** Such methods, known as *sub-resource locators*, are used to further resolve the object that will handle the request. Any returned object is treated as a resource class and used to either handle the request or to further resolve the object that will handle the request, see 3.6 for further details.

The following example illustrates the difference:

```
1  @Path("widgets")
2  public class WidgetsResource {
3      @GET
4      @Path("offers")
```

<sup>1</sup>If the resource class URI template does not end with a ‘/’ character then one is added during the concatenation.

```

5    public WidgetList getDiscounted() {...}           1
6                                           2
7    @Path("{id}")                                   3
8    public WidgetResource findWidget(@UriParam("id") String id) {           4
9        return lookupWidget(id);                     5
10   }                                                6
11 }                                                  7

```

In the above a GET request for the `widgets/offers` resource is handled directly by the `getDiscounted` sub-resource method of the resource class `WidgetsResource` whereas a GET request for `widgets/xxx` is handled by whatever resource class instance is returned by the `findWidget` sub-resource locator (a `WidgetResource`). 8 9 10 11

**Note:** A set of sub-resource methods annotated with the same URI template value are functionally equivalent to a similarly annotated sub-resource locator that returns an instance of a resource class with the same set of resource methods. 12 13 14

## 3.4 Declaring Media Type Capabilities 15

Application classes can declare the supported request and response media types using the `@ProduceMime` and `@ConsumeMime` annotations. These annotations MAY be applied to a resource method, a resource class, or to an entity provider (see section 4.3.3). Use of these annotations on a resource method overrides any on the resource class or on an entity provider for a method argument or return type. In the absence of either of these annotations, support for any media type (“\*/”) is assumed. 16 17 18 19 20

The following example illustrates the `@ProduceMime` annotation: 21

```

1  @Path("widgets")                                22
2  @ProduceMime("application/xml")                  23
3  public class WidgetsResource {                    24
4                                           25
5      @GET                                          26
6      public String getAll() {...}                  27
7                                           28
8      @GET                                          29
9      @Path("{id}")                                30
10     public Widget getWidget(@UriParam("id") String id) {...} 31
11                                           32
12     @GET                                          33
13     @Path("{id}/description")                     34
14     @ProduceMime("text/html")                     35
15     public String getDescription(@UriParam("id") String id) {...} 36
16 }                                                  37
17                                           38
18 @Provider                                         39
19 @ProduceMime({"application/xml", "application/json"}) 40
20 public class WidgetProvider implements MessageBodyWriter<Widget> {...} 41

```

In the above: 42

- The `getAll` resource method returns a `String` in the `application/xml` format, 43

- The `getDescription` sub-resource method returns a `String` as `text/html`, and
- The `getWidget` sub-resource method returns a `Widget` entity instance that can be mapped to either `application/xml` or `application/json` using the `WidgetProvider` class (see section 4.3 for more information on `MessageBodyWriter`).

An implementation **MUST NOT** invoke a method whose effective value of `@ProduceMime` does not match the request `Accept` header. An implementation **MUST NOT** invoke a method whose effective value of `@ConsumeMime` does not match the request `Content-Type` header.

### 3.5 Annotation Inheritance

JAX-RS annotations **MAY** be used on the methods of a super-class or an implemented interface. Such annotations are inherited by a corresponding sub-class or implementation class method provided that method does not have any of its own JAX-RS annotations. If a subclass or implementation method has any JAX-RS annotations then *all* of the annotations on the super class or interface method are ignored. E.g.:

```
1 public interface ReadOnlyAtomFeed {
2     @GET @ProduceMime("application/atom+xml")
3     Feed getFeed();
4 }
5
6 @Path("feed")
7 public class ActivityLog implements ReadOnlyAtomFeed {
8     public Feed getFeed() {...}
9 }
```

In the above, `ActivityLog.getFeed` inherits the `@GET` and `@ProduceMime` annotations from the interface. Conversely:

```
1 @Path("feed")
2 public class ActivityLog implements ReadOnlyAtomFeed {
3     @ProduceMime("application/atom+xml")
4     public Feed getFeed() {...}
5 }
```

In the above, the `@GET` annotation on `ReadOnlyAtomFeed.getFeed` is not inherited by `Activity-Log.getFeed` and it would require its own request method designator since it redefines the `@ProduceMime` annotation.

### 3.6 Matching Requests to Resource Methods

A request is matched to the corresponding resource method or sub-resource method by comparing the request URI, the media type of any request entity, and the requested response entity format to the metadata annotations on the resource classes and their methods. If no matching resource method or sub-resource method can be found then an appropriate error response is returned. Matching of requests to resource methods proceeds in three stages as follows:

1. Identify the root resource class: 1
  - (a) Set  $U$  = request URI path,  $C = \{\text{root resource classes}\}$ ,  $E = \{\}$  2
  - (b) For each class in  $C$  add a regular expression (computed using the function  $R(A)$  described in section 3.6.1) to  $E$  as follows: 3
    - Add  $R(T_{\text{class}})$  where  $T_{\text{class}}$  is the URI path template specified for the class. 4
  - (c) Filter  $E$  by matching each member against  $U$  as follows: 5
    - Remove members that do not match  $U$ . 6
    - Remove members for which the final capturing group value is neither empty nor '/' and the class associated with  $R(T_{\text{class}})$  had no sub-resource methods or locators. 7
  - (d) If  $E$  is empty then no matching resource can be found, the algorithm terminates and an implementation MUST generate a not found response (HTTP 404 status). 8
  - (e) Sort  $E$  using the number of literal characters<sup>2</sup> in each member as the primary key (descending order) and the number of capturing groups as a secondary key (descending order). 9
  - (f) Set  $R_{\text{match}}$  to be the first member of  $E$ , set  $U$  to be the value of the final capturing group of  $R(T_{\text{match}})$  when matched against  $U$ , and instantiate an object  $O$  of the associated class. 10
2. Obtain the object that will handle the request: 11
  - (a) If  $U$  is null or '/' go to step 3 12
  - (b) Set  $C = \text{class of } O$ ,  $E = \{\}$  13
  - (c) For class  $C$  add regular expressions to  $E$  for each sub-resource method and locator as follows: 14
    - i. For each sub-resource method, add  $R(T_{\text{method}})$  where  $T_{\text{method}}$  is the URI path template of the sub-resource method. 15
    - ii. For each sub-resource locator, add  $R(T_{\text{locator}})$  where  $T_{\text{locator}}$  is the URI path template of the sub-resource locator. 16
  - (d) Filter  $E$  by matching each member against  $U$  as follows: 17
    - Remove members that do not match  $U$ . 18
    - Remove members derived from  $T_{\text{method}}$  (those added in step 2(c)i) for which the final capturing group value is neither empty nor '/'. 19
  - (e) If  $E$  is empty then no matching resource can be found, the algorithm terminates and an implementation MUST generate a not found response (HTTP 404 status). 20
  - (f) Sort  $E$  using the number of literal characters in each member as the primary key (descending order) and the number of capturing groups as a secondary key (descending order). 21
  - (g) Set  $R_{\text{match}}$  to be the first member of  $E$  22
  - (h) If  $R_{\text{match}}$  was derived from  $T_{\text{method}}$  then go to step 3. 23
  - (i) Set  $U$  to be the value of the final capturing group of  $R(T_{\text{match}})$  when matched against  $U$ , invoke the sub-resource locator method of  $O$  and set  $O$  to the value returned from that method. 24
  - (j) Go to step 2a. 25
3. Identify the method that will handle the request: 26
  - (a) Find the set of resource methods  $M$  of  $O$  that meet the following criteria: 27

<sup>2</sup>Here, literal characters means those not resulting from template variable substitution.

- If  $U$  is neither empty nor equal to  $'/'$ , the method must be annotated with a URI template that, when transformed into a regular expression using the process described in section 3.6.1, matches  $U$  with a final capturing group value that is either empty or equal to  $'/'$ .
  - The request method is supported. If no methods support the request method an implementation MUST generate a method not allowed response (HTTP 405 status). Note the additional support for HEAD and OPTIONS described in section 3.2.5.
  - The media type of the request entity body (if any) is a supported input data format (see section 3.4). If no methods support the media type of the request entity body an implementation MUST generate an unsupported media type response (HTTP 415 status).
  - At least one of the acceptable response entity body media types is a supported output data format (see section 3.4). If no methods support one of the acceptable response entity body media types an implementation MUST generate a not acceptable response (HTTP 406 status).
- (b) Sort  $M$  as follows:
- The primary key is the media type of input data. Methods whose @ConsumeMime value most closely match the media type of the request are sorted first.
  - The secondary key is the @ProduceMime value. Methods whose value of @ProduceMime most closely match the value of the request accept header are sorted first.
- Sorting of media types follows the general rule:  $x/y < x/* < */*$ , i.e. a method that explicitly lists one of the requested media types is sorted before a method that lists  $*/*$ . Quality parameter values are also used such that  $x/y;q=1.0 < x/y;q=0.7$ . See section 14.1 of [4] for more details.
- (c) If  $M$  is not empty then the request is dispatched to the first Java method in the set; otherwise no matching resource method can be found and the algorithm terminates.

### 3.6.1 Converting URI Templates to Regular Expressions

The function  $R(A)$  converts a URI path template annotation  $A$  into a regular expression as follows:

1. If  $A.encode = true$ , URI encode the template, ignoring URI template variable specifications.
2. Escape any regular expression characters in the URI template, again ignoring URI template variable specifications.
3. Replace the URI template variables<sup>3</sup> with the regular expression  $'(.*)'$ .
4. If the resulting string ends with  $'/'$  then remove the final character.
5. If  $A.limited = true$ , append  $'(/.*)?'$  to the result, else append  $'(/)'$  to the result.

Note that the above renders the name of template variables irrelevant for template matching purposes. However, implementations will need to retain template variable names in order to facilitate the extraction of template variable values via @PathParam or UriInfo.getTemplateParameters.

## 3.7 Determining the MediaType of Responses

In many cases it is not possible to statically determine the media type of a response. The following algorithm is used to determine the response media type,  $M_{selected}$ , at run time:

<sup>3</sup>The regular expression to match a URI path template variable is  $\backslash\{([w\backslash. \sim]+?)\}$ .

1. Gather the set of producible media types  $P$ : 1
  - If the method is annotated with `@ProduceMime`, set  $P = \{V(\text{method})\}$  where  $V(t)$  represents 2  
the values of `@ProduceMime` on the specified target  $t$ . 3
  - Else if the class is annotated with `@ProduceMime`, set  $P = \{V(\text{class})\}$ . 4
  - Else set  $P = \{V(\text{writers})\}$  where ‘writers’ is the set of `MessageBodyWriter` that support the 5  
class of the returned entity object. 6
2. If  $P = \{\}$ , set  $P = \{‘*/*’\}$  7
3. Obtain the acceptable media types  $A$ . If  $A = \{\}$ , set  $A = \{‘*/*’\}$  8
4. Sort  $A$  and  $P$  in descending order, each with a primary key of q-value and secondary key of specificity 9  
(‘n/m’ > ‘n/\*’ > ‘\*//\*’). 10
5. Set  $M = \{\}$ . For each member of  $A$ ,  $a$ : 11
  - For each member of  $P$ ,  $p$ : 12
    - If  $a$  is compatible with  $p$ , add  $S(a, p)$  to  $M$ , where the function  $S$  returns the most specific 13  
media type of the supplied list. 14
6. If  $M = \{\}$  then return a not acceptable response (HTTP 406 status), finish. 15
7. For each member of  $M$ ,  $m$ : 16
  - If  $m$  is a concrete type, set  $M_{\text{selected}} = m$ , finish. 17
8. If  $M$  contains ‘\*//\*’ or ‘application/\*’, set  $M_{\text{selected}} = \text{‘application/octet-stream’}$ , finish. 18
9. Return a not acceptable response (HTTP 406 status), finish. 19

Note that the above renders a response with a default media type of ‘application/octet-stream’ when a concrete type cannot be determined. It is RECOMMENDED that `MessageBodyWriter` implementations specify at least one concrete type via `@ProduceMime`. 20  
21  
22





# Chapter 4

## Providers

The JAX-RS runtime is extended using application-supplied provider classes. A provider is annotated with `@Provider` and implements one or more interfaces defined by JAX-RS.

### 4.1 Lifecycle and Environment

A single instance of each provider class is instantiated for each JAX-RS application. First the constructor (see section 4.2) is called, then any requested dependencies are injected (see chapter 5), then the appropriate provider methods may be called multiple times (simultaneously), and finally the object is made available for garbage collection.

### 4.2 Constructors

Provider classes are instantiated by the JAX-RS runtime and **MUST** have a constructor with `@Context` on every parameter. Note that a zero argument constructor is permissible under this rule. If more than one constructor that matches the above pattern is available then an implementation **MUST** use the one with the most parameters. Choosing amongst constructors with the same number of parameters is implementation specific.

Section 3.2.2 defines the parameter types permitted for `@Context`. Since providers may be created outside the scope of a particular request, only deployment-specific properties may be available from injected interfaces at construction time. Request-specific properties are available when a provider method is called.

### 4.3 Entity Providers

Entity providers supply mapping services between representations and their associated Java types. Entity providers come in two flavors: `MessageBodyReader` and `MessageBodyWriter` described below.

#### 4.3.1 Message Body Reader

The `MessageBodyReader` interface defines the contract between the JAX-RS runtime and components that provide mapping services from representations to a corresponding Java type. A class wishing to provide such

a service implements the `MessageBodyReader` interface and is annotated with `@Provider`.

The following describes the logical<sup>1</sup> steps taken by a JAX-RS implementation when mapping a request entity body to a Java method parameter:

1. Identify the Java type of the parameter whose value will be mapped from the entity body. Section 3.6 describes how the Java method is chosen.
2. Select the set of `MessageBodyReader` classes that support the media type of the request, see section 4.3.3.
3. Iterate through the selected `MessageBodyReader` classes and, utilizing the `isReadable` method of each, choose a `MessageBodyReader` provider that supports the desired Java type.
4. Use the `readFrom` method of the chosen `MessageBodyReader` to map the entity body to the desired Java type.

### 4.3.2 Message Body Writer

The `MessageBodyWriter` interface defines the contract between the JAX-RS runtime and components that provide mapping services from a Java type to a representation. A class wishing to provide such a service implements the `MessageBodyWriter` interface and is annotated with `@Provider`.

The following describes the logical steps taken by a JAX-RS implementation when mapping a return value to a response entity body:

1. Obtain the object that will be mapped to the response entity body. For a return type of `Response` or subclasses the object is the value of the `entity` property, for other return types it is the returned object.
2. Obtain the effective value of `@ProduceMime` (see section 3.4) and intersect that with the requested response formats to obtain set of permissible media types for the response entity body. Note that section 3.6 ensures that this set will not be empty.
3. Select the set of `MessageBodyWriter` providers that support (see section 4.3.3) one or more of the permissible media types for the response entity body.
4. Sort the selected `MessageBodyWriter` providers as described in section 4.3.3.
5. Iterate through the sorted `MessageBodyWriter` providers and, utilizing the `isWriteable` method of each, choose an `MessageBodyWriter` that supports the object that will be mapped to the entity body.
6. Use the `writeTo` method of the chosen `MessageBodyWriter` provider to map the object to the entity body.

---

<sup>1</sup>Implementations are free to optimize their processing provided the results are equivalent to those that would be obtained if these steps are followed.

### 4.3.3 Declaring Media Type Capabilities

Message body readers and writers MAY restrict the media types they support using the `@ConsumeMime` and `@ProduceMime` annotations respectively. The absence of these annotations is equivalent to their inclusion with media type (“\*/\*”), i.e. absence implies that any media type is supported. An implementation MUST NOT use an entity provider for a media type that is not supported by that provider.

When choosing an entity provider an implementation sorts the available providers according to the media types they declare support for. Sorting of media types follows the general rule:  $x/y < x/* < */*$ , i.e. a provider that explicitly lists a media types is sorted before a provider that lists `*/*`. Quality parameter values are also used such that  $x/y;q=1.0 < x/y;q=0.7$ .

### 4.3.4 Standard Entity Providers

An implementation MUST include pre-packaged `MessageBodyReader` and `MessageBodyWriter` implementations for the following Java and media type combinations:

**byte[]** All media types (`*/*`).

**java.lang.String** All text media types (`text/*`).

**java.io.InputStream** All media types (`*/*`).

**java.io.File** All media types (`*/*`).

**javax.activation.DataSource** All media types (`*/*`).

**javax.xml.transform.Source** XML types (`text/xml`, `application/xml` and `application/+-xml`).

**javax.xml.bind.JAXBElement and application-supplied JAXB classes** XML media types (`text/xml`, `application/xml` and `application/+-xml`).

**MultivaluedMap<String,String>** Form content (`application/x-www-form-urlencoded`).

An implementation MUST support application-provided entity providers and MUST use those in preference to its own pre-packaged providers when either could handle the same request.

### 4.3.5 Transfer Encoding

Transfer encoding for inbound data is handled by a component of the container or the JAX-RS runtime. `MessageBodyReader` providers always operate on the decoded HTTP entity body rather than directly on the HTTP message body.

**Editors Note 4.1** *Should JAX-RS require support for specific transfer encodings ?*

A JAX-RS runtime or container MAY transfer encode outbound data or this MAY be done by application code.

### 4.3.6 Content Encoding

Content encoding is the responsibility of the application. Application-supplied entity providers MAY perform such encoding and manipulate the HTTP headers accordingly.

## 4.4 Context Providers

Context providers supply context to resource classes and other providers. A context provider class implements the `ContextResolver<T>` interface and is annotated with `@Provider`. E.g. an application wishing to provide a customized `JAXBContext` to the default JAXB entity providers would supply a class implementing `ContextResolver<JAXBContext>`.

Context providers MAY return `null` from the `getContext` method if they do not wish to provide their context for a particular Java type. E.g. a JAXB context provider may wish to only provide the context for certain JAXB classes. Context providers MAY also manage multiple contexts of the same type keyed to different Java types.

Section 5.1.6 describes how to access a context provider from a resource class or provider.

# Chapter 5 1

## Context 2

JAX-RS provides facilities for obtaining and processing information about the application deployment context and the context of individual requests. Such information is available to both resource classes (see chapter 3) and providers (see chapter 4). This chapter describes these facilities. 3  
4  
5

### 5.1 Context Types 6

This section describes the types of context available to resource classes and providers. 7

#### 5.1.1 URIs and URI Templates 8

An instance of `UriInfo` can be injected into a class field or method parameter using the `@Context` annotation. `UriInfo` provides both static and dynamic, per-request information, about the components of a request URI. E.g. the following would return the names of any query parameters in a request: 9  
10  
11

```
1  @HttpMethod(GET) 12
2  @ProduceMime{"text/plain"} 13
3  public String listQueryParamNames(@Context UriInfo info) { 14
4      StringBuilder buf = new StringBuilder(); 15
5      for (String param: info.getQueryParameters().keySet()) { 16
6          buf.append(param); 17
7          buf.append("\n"); 18
8      } 19
9      return buf.toString(); 20
10 }
```

#### 5.1.2 Headers 22

An instance of `HttpHeaders` can be injected into a class field or method parameter using the `@Context` annotation. `HttpHeaders` provides access to request header information either in map form or via strongly typed convenience methods. E.g. the following would return the names of all the headers in a request: 23  
24  
25

```
1  @HttpMethod(GET) 26
2  @ProduceMime{"text/plain"} 27
```

```

3 public String listHeaderNames(@Context HttpHeaders headers) { 1
4     StringBuilder buf = new StringBuilder(); 2
5     for (String header: headers.getRequestHeaders().keySet()) { 3
6         buf.append(header); 4
7         buf.append("\n"); 5
8     } 6
9     return buf.toString(); 7
10 } 8

```

Note that response headers may be provided using the `Response` interface, see 3.2.3 for more details. 9

### 5.1.3 Content Negotiation and Preconditions 10

JAX-RS simplifies support for content negotiation and preconditions using the `Request` interface. An instance of `Request` can be injected into a class field or method parameter using the `@Context` annotation. The methods of `Request` allow a caller to determine the best matching representation variant and to evaluate whether the current state of the resource matches any preconditions in the request. Precondition support methods return a `ResponseBuilder` that can be returned to the client to inform it that the request preconditions were not met. E.g. the following checks if the current entity tag matches any preconditions in the request before updating the resource: 17

```

1 @HttpMethod(PUT) 18
2 public Response updateFoo(@Context Request request, Foo foo) { 19
3     EntityTag tag = getCurrentTag(); 20
4     ResponseBuilder responseBuilder = request.evaluate(tag, null); 21
5     if (responseBuilder != null) 22
6         return responseBuilder.build(); 23
7     else 24
8         return doUpdate(foo); 25
9 } 26

```

The application could also set the content location, expiry date and cache control information into the returned `ResponseBuilder` before building the response. 28

### 5.1.4 Security Context 29

The `SecurityContext` interface provides access to information about the security context of the current request. An instance of `SecurityContext` can be injected into a class field or method parameter using the `@Context` annotation. The methods of `SecurityContext` provide access to the current user principle, information about roles assumed by the requester, whether the request arrived over a secure channel and the authentication scheme used. 34

### 5.1.5 Message Body Workers 35

The `MessageBodyWorkers` interface allows for lookup of `MessageBodyReader` and `MessageBodyWriter` instances based on a set of search criteria including support media and Java type. An instance of `MessageBodyWorkers` can be injected into a class field or method parameter using the `@Context` annotation. 39

This interface is expected to be primarily of interest to entity provider authors wishing to use other entity providers to process a composite entity.

### 5.1.6 Context Resolver

Section 4.4 describes how an application can supply a `ContextResolver` for a particular context type. An instance of `ContextResolver` can be injected into a class field or method parameter using the `@Context` annotation.

The generic type of the annotation target is used select providers of the desired context type. The injected instance is not an instance of an application supplied context provider, rather it is a proxy that iterates through all the providers of the desired context type until one returns a non-`null` context for the type supplied in `getContext`. If no providers return a non-`null` context then the `getContext` method returns `null`.

## 5.2 Injection Scope

When the `@Context` annotation is applied to a class field, an implementation is only required to inject the applicable context into those class instances created by the implementation runtime. Objects returned by sub-resource locators (see section 3.3.1) are expected to be initialized by their creator and are not subject to resource injection by the implementation runtime.





# Chapter 6

## Environment

The container-managed resources available to a JAX-RS resource class or provider depend on the environment in which it is deployed. Section 5.1 describes the types of context available regardless of container. The following sections describe the additional container-managed resources available to a JAX-RS resource class deployed in a variety of environments.

### 6.1 Servlet Container

The `@Context` annotation can be used to indicate a dependency on a Servlet-defined resource. A Servlet-based implementation **MUST** support injection of the following Servlet-defined types: `ServletConfig`, `ServletContext`, `HttpServletRequest` and `HttpServletResponse`.

An injected `HttpServletRequest` allows a resource method to stream the contents of a request entity. If the resource method has a parameter whose value is derived from the request entity then the stream will have already been consumed and an attempt to access it **MAY** result in an exception.

An injected `HttpServletResponse` allows a resource method to commit the HTTP response prior to returning. An implementation **MUST** check the committed status and only process the return value if the response is not yet committed.

### 6.2 Java EE Container

**Editors Note 6.1** *TBD. We anticipate offering the same resource injection capabilities as are provided for a Servlet instance running in a Java EE Web container. In particular we anticipate supporting dependency injection using the following annotations: `@Resource`, `@Resources`, `@EJB`, `@EJBs`, `@WebServiceRef`, `@WebServiceRefs`, `@PersistenceContext`, `@PersistenceContexts`, `@PersistenceUnit` and `@PersistenceUnits`. We also anticipate supporting the following JSR 250 lifecycle management and security annotations: `@PostConstruct`, `@PreDestroy`, `@RunAs`, `@RolesAllowed`, `@PermitAll`, `@DenyAll` and `@DeclareRoles`.*

### 6.3 Other

Other container technologies **MAY** specify their own set of injectable resources but **MUST**, at a minimum, support access to the types of context listed in section 5.1.



# Chapter 7

## Runtime Delegate

`RuntimeDelegate` is an abstract factory class that provides various methods for the creation of objects that implement JAX-RS APIs. These methods are designed for use by other JAX-RS API classes and are not intended to be called directly by applications. `RuntimeDelegate` allows the standard JAX-RS API classes to use different JAX-RS implementations without any code changes.

An implementation of JAX-RS MUST provide a concrete subclass of `RuntimeDelegate`, this can be provided to JAX-RS in one of two ways:

1. An instance of `RuntimeDelegate` can be instantiated and injected using its static method `setInstance`. In this case the implementation is responsible for creating the instance; this option is intended for use with implementations based on IoC frameworks.
2. The class to be used can be configured, see section 7.1. In this case JAX-RS is responsible for instantiating an instance of the class and the configured class MUST have a public constructor which takes no arguments.

A JAX-RS implementation may rely on a particular implementation of `RuntimeDelegate` being used – overriding the supplied `RuntimeDelegate` instance with an application-supplied alternative is not recommended and may cause unexpected problems.

### 7.1 Configuration

If not supplied by injection, the `RuntimeDelegate` implementation class is determined using the following algorithm. The steps listed below are performed in sequence and, at each step, at most one candidate implementation class name will be produced. The implementation will then attempt to load the class with the given class name using the current context class loader or, missing one, the `java.lang.Class.forName(String)` method. As soon as a step results in an implementation class being successfully loaded, the algorithm terminates.

1. If a resource with the name of `META-INF/services/javax.ws.rs.ext.RuntimeDelegate` exists, then its first line, if present, is used as the UTF-8 encoded name of the implementation class.
2. If the `${java.home}/lib/jaxrs.properties` file exists and it is readable by the `java.util.Properties.load(InputStream)` method and it contains an entry whose key is `javax.ws.rs.ext.RuntimeDelegate`, then the value of that entry is used as the name of the implementation class.

3. If a system property with the name `javax.xml.ws.spi.Provider` is defined, then its value is used as the name of the implementation class. 1  
2
4. Finally, a default implementation class name is used. 3

## Summary of Annotations

Annotation	Target	Description
ConsumeMime	Type or method	Specifies a list of media types that can be consumed.
ProduceMime	Type or method	Specifies a list of media types that can be consumed.
GET	Method	Specifies that the annotated method handles HTTP GET requests.
POST	Method	Specifies that the annotated method handles HTTP POST requests.
PUT	Method	Specifies that the annotated method handles HTTP PUT requests.
DELETE	Method	Specifies that the annotated method handles HTTP DELETE requests.
HEAD	Method	Specifies that the annotated method handles HTTP HEAD requests. Note that HEAD may be automatically handled, see section 3.2.5.
Path	Type or method	Specifies a relative path for a resource. When used on a class this annotation identifies that class as a root resource. When used on a method this annotation identifies a sub-resource method or locator.
PathParam	Parameter	Specifies that the value of a method parameter is to be extracted from the request URI path. The value of the annotation identifies the name of a URI template parameter.
QueryParam	Parameter	Specifies that the value of a method parameter is to be extracted from a URI query parameter. The value of the annotation identifies the name of a query parameter.
MatrixParam	Parameter	Specifies that the value of a method parameter is to be extracted from a URI matrix parameter. The value of the annotation identifies the name of a matrix parameter.
CookieParam	Parameter	Specifies that the value of a method parameter is to be extracted from a HTTP cookie. The value of the annotation identifies the name of a the cookie.
HeaderParam	Parameter	Specifies that the value of a method parameter is to be extracted from a HTTP header. The value of the annotation identifies the name of a HTTP header.

Annotation	Target	Description
Encoded	Type, constructor, method or parameter	Disables automatic URI decoding for path, query and matrix parameters.
DefaultValue	Parameter	Specifies a default value for a method parameter annotated with <code>@QueryParam</code> , <code>@MatrixParam</code> , <code>@CookieParam</code> or <code>@HeaderParam</code> . The specified value will be used if the corresponding query or matrix parameter is not present in the request URI, or if the corresponding HTTP header is not included in the request.
Context	Field or parameter	Identifies an injection target for one of the types listed in section 5.1 or the applicable section of chapter 6.
HttpMethod	Annotation	Specifies the HTTP method for a request method designator annotation.
Provider	Type	Specifies that the annotated class implements a JAX-RS extension interface.

# Bibliography

- [1] R. Fielding. Architectural Styles and the Design of Network-based Software Architectures. Ph.d dissertation, University of California, Irvine, 2000. See <http://roy.gbiv.com/pubs/dissertation/top.htm>.
- [2] REST Wiki. Web site. See <http://rest.blueoxen.net/cgi-bin/wiki.pl>.
- [3] Representational State Transfer. Web site, Wikipedia. See [http://en.wikipedia.org/wiki/Representational\\_State\\_Transfer](http://en.wikipedia.org/wiki/Representational_State_Transfer).
- [4] R. Fielding, J. Gettys, J. C. Mogul, H. Frystyk, and T. Berners-Lee. RFC 2616: Hypertext Transfer Protocol – HTTP/1.1. RFC, IETF, January 1997. See <http://www.ietf.org/rfc/rfc2616.txt>.
- [5] T. Berners-Lee, R. Fielding, and L. Masinter. RFC 3986: Uniform Resource Identifier (URI): Generic Syntax. RFC, IETF, January 2005. See <http://www.ietf.org/rfc/rfc3986.txt>.
- [6] L. Dusseault. RFC 4918: HTTP Extensions for Web Distributed Authoring and Versioning (WebDAV). RFC, IETF, June 2007. See <http://www.ietf.org/rfc/rfc4918.txt>.
- [7] J.C. Gregorio and B. de hOra. The Atom Publishing Protocol. Internet Draft, IETF, March 2007. See <http://bitworking.org/projects/atom/draft-ietf-atompub-protocol-14.html>.
- [8] G. Murray. Java Servlet Specification Version 2.5. JSR, JCP, October 2006. See <http://java.sun.com/products/servlet>.
- [9] R. Chinnici, M. Hadley, and R. Mordani. Java API for XML Web Services. JSR, JCP, August 2005. See <http://jcp.org/en/jsr/detail?id=224>.
- [10] S. Bradner. RFC 2119: Keywords for use in RFCs to Indicate Requirement Levels. RFC, IETF, March 1997. See <http://www.ietf.org/rfc/rfc2119.txt>.